11/25/24, 11:14 AM Check Answers

12.3.7 Lab: Configure a Captive Portal

Candidate: Richard Habib ()
Time Spent: 00:24

Score: 0%

Task Summary

Required Actions

- X Add a Captive Portal zone Show Details
- X Enable and configure the Captive Portal Show Details
- × Allow a MAC address to pass through the portal
- X Allow an IP address to pass through the portal Show Details

Explanation



Complete this lab as follows:

- 1. Sign in to the pfSense management console.
 - a. In the Username field, enter admin.
 - b. In the Password field, enter P@ssw0rd (zero).
 - c. Select **SIGN IN** or press **Enter**.
- 2. Add a Captive Portal zone.
 - a. From the pfSense menu bar, select **Services** > **Captive Portal**.
 - b. Select **Add**.
 - c. For Zone name, enter Guest_WiFi.
 - d. For Zone description, enter Zone used for the guest Wi-Fi.
 - e. Select Save & Continue.
- 3. Enable and configure the Captive Portal.
 - a. Under Captive Portal Configuration, select Enable.
 - b. For Interfaces, select GuestWi-Fi.
 - c. For Maximum concurrent connections, select 100.
 - d. For Idle timeout, enter 30.
 - e. For Hard timeout, enter **120**.
 - f. Scroll down and select Per-user bandwidth restriction.
 - g. For Default download (Kbit/s), enter 8000.
 - h. For Default upload (Kbit/s), enter **2500**.
 - i. Under Authentication, use the drop-down menu to select None, don't authenticate users.
 - j. Scroll to the bottom and select **Save**.
- 4. Allow a MAC address to pass through the portal.

11/25/24, 11:14 AM Check Answers

a. From the Captive Portal page, select the *Edit Zone* icon (pencil).

- b. Under the Services breadcrumb, select MACs.
- c. Select **Add**.
- d. Make sure the *Action* field is set to **Pass**.
- e. For Mac Address, enter 00:00:1B:12:34:56.
- f. Select **Save**.
- 5. Allow an IP address to pass through the portal.
 - a. Under the Services breadcrumb, select Allowed IP Addresses.
 - b. Select **Add**.
 - c. For IP Address, enter **198.28.1.100**.
 - d. Use the IP address drop-down menu to select 16. This sets the subnet mask to 255.255.0.0.
 - e. For the Description field, enter Admin's Laptop.
 - f. Make sure *Direction* is set to **Both**.
 - g. Select **Save**.