

```

WITH HitterGameLog AS (
    SELECT
        hteamdate,
        batter,
        SUM(CASE WHEN ab=1 THEN 1 ELSE 0 END) AS AtBats,
        SUM(CASE WHEN hitvalue>0 THEN 1 ELSE 0 END) AS Hits,
        SUM(CASE WHEN hitvalue=2 THEN 1 ELSE 0 END) AS Dbls,
        SUM(CASE WHEN hitvalue=3 THEN 1 ELSE 0 END) AS Tpls,
        SUM(CASE WHEN hitvalue=4 THEN 1 ELSE 0 END) AS HRs,
        SUM(rbi) AS RBIs,
        SUM(CASE WHEN CHARINDEX('K', RESULT) >0 THEN 1 ELSE 0 END) AS strikeouts,
        SUM(CASE WHEN e_type=14 THEN 1 ELSE 0 END) AS walks,
        SUM(CASE WHEN outs=2 AND ab=1 THEN 1 ELSE 0 END) AS AB2outs,
        SUM(CASE WHEN outs=2 AND hitvalue>0 THEN 1 ELSE 0 END) AS Hits2outs
    FROM tblEventLog2025
    GROUP BY hteamdate, visitors, batter
),
BATTERTOTALS AS (
    SELECT
        Batter,
        SUM(AtBats) AS TotAb,
        SUM(Hits) AS TotH,
        SUM(Dbls) AS Tot2b,
        SUM(Tpls) AS Tot3b,
        SUM(HRs) AS TotHR,
        SUM(RBIs) AS TotRBIs,
        SUM(Strikeouts) AS TotKs,
        SUM(Walks) AS TotBBs,
        SUM(AB2outs) AS Tot2OutAb,
        SUM(Hits2outs) AS Tot2outHits
    FROM HitterGameLog
    GROUP BY Batter
),
RUNSTOTALS AS (
    SELECT
        stack.player_id,
        COUNT(*) AS TotRuns
    FROM tblEventLog2025
    CROSS APPLY (
        VALUES
            (batter, batdest),
            (on1st, on1_dest),
            (on2nd, on2_dest),
            (on3rd, on3_dest)
        ) AS stack(player_id, destination)
    WHERE stack.destination > 3
        AND stack.player_id IS NOT NULL
    GROUP BY stack.player_id
),
UniqueRoster AS (
    SELECT DISTINCT ID, (Fname+' '+Lname) as PlayerName
    FROM tblRosters2025
)
-- Final Join: Fixed by using standard explicit JOIN syntax throughout
SELECT
    U.PlayerName,
    BT.Batter,
    BT.TotAb,

```

```

BT.TotH,
BT.Tot2b,
BT.Tot3b,
BT.TotHR,
BT.TotRBIs,
BT.TotKs,
BT.TotBBs,
BT.Tot2OutAb,
BT.Tot2outHits,
COALESCE(RT.TotRuns, 0) AS TotRuns
FROM BATTERTOTALS BT
JOIN UniqueRoster U ON BT.Batter = U.ID
LEFT JOIN RUNSTOTALS RT ON BT.Batter = RT.player_id -- Left Join ensures players
with 0 runs aren't excluded
ORDER BY TotRuns DESC;

```