mapping_id	source_ontology_id	source_entity_type	source_iri	source_prefix	source_label	target_ontology_id	target_entity_type	target_iri	target_prefix	target_label	alignment_relation	direction	mapping_notes & justification
Stable mapping identifier, e.g., DPP_DPPO_0001	*DPP|DPPO|CEON*	*Class|ObjectProperty|DataProperty|AnnotationProperty|Individual*	*Absolute IRI*		*Human-readable label*	*DPP|DPPO|CEON*	*Class|ObjectProperty|DataProperty|AnnotationProperty|Individual*	*Absolute IRI*		*Human-readable label*	*Controlled vocabulary (see README)*	*source_to_target|target_to_source|bidirectional*	*rationale, ignored by generator for logic*
DPP_DPPO_0001	DPP	Class	http://w3id.org/dpp#Product	dpp	Product	DPPO	Class	http://w3id.org/dppo/ontology/dpp-odp/Product	dpp-odp	Product	subclass_of	source_to_target	DPP is stricter: product≠material; DPPO keeps them possibly overlapping. Subclass mapping preserves DPPO's sector-agnostic stance without breaking DPP's disjointness.
DPP_DPPO_0002	DPP	Class	http://w3id.org/dpp#Component	dpp	Component	DPPO	Class	http://w3id.org/dppo/ontology/dpp-core/Component	dpp-core	Component	equivalent_class	bidirectional	Both represent part-whole relationships. Structural correspondence: both as subclasses of Product with part-of links. Modular alignment allows complex product breakdowns in DPP (e.g., building elements into sub-components) to map into DPPO's composition pattern.
DPP_DPPO_0003	DPP	Class	http://w3id.org/dpp#Material	dpp	Material	DPPO	Class	http://w3id.org/dppo/ontology/dpp-core/Material	dpp-core	Material	subclass_of	source_to_target	Semantically equivalent: both capture the matter constituting products/parts. Subclass mapping (dppo:Material ⊑ dppo:Product) reflects DPPO's flexibility; DPP's modular placement preserves structure. Alignment preserves CE relevance (resource loops, recyclability).
DPP_DPPO_0004	DPP	Class	http://w3id.org/dpp#MaterialComposition	dpp	MaterialComposition	DPPO	Class	http://w3id.org/dppo/ontology/dpp-info/CompositionInformation	dpp-info	CompositionInformation	subclass_of	source_to_target	Both model partonomy as first-class nodes; quantitative details remain attached to the reified link.
DPP_DPPO_0005	DPP	Class	http://w3id.org/dpp#Agent	dpp	Agent	DPPO	Class	http://w3id.org/dppo/ontology/dpp-prov/Actor	dpp-prov	Actor	equivalent_class	bidirectional	For product-level roles, keep DPP's AgentRole on dpp:Product; additionally mint DPPO responsibleActor on each DPPInformation item to meet DPPO's auditability.
DPP_DPPO_0006	DPP	ObjectProperty	http://w3id.org/dpp#hasComponent	dpp	hasComponent	DPPO	ObjectProperty	http://w3id.org/dppo/ontology/dpp-odp/hasPart	dpp-odp	hasPart	subproperty_of	source_to_target	DPP asserts partonomy directly at the product level through dpp:hasComponent (domain dpp:Product, range dpp:Component), whereas DPPO uses the generic dpp-odp:hasPart. The DPP property is therefore a specialisation of the DPPO one. Stated in the Product Component and Partonomy Alignment section of the accompanying paper.
DPP_DPPO_0007	DPP	Class	http://w3id.org/dpp#Manufacturer	dpp	Manufacturer	DPPO	Class	http://w3id.org/dppo/ontology/dpp-prov/ValueChainActor	dpp-prov	ValueChainActor	subclass_of	source_to_target	DPPO defines ValueChainActor as an actor that is an active participant of the value chain of a product, explicitly exemplified by a manufacturer. dpp:Manufacturer, an entity responsible for producing products, components or materials, is therefore a specialisation. Additional mapping, not discussed in the paper.