



COMPUTER SCIENCE

0478/22

Paper 2

October/November 2018

MARK SCHEME

Maximum Mark: 50

Published

This mark scheme is published as an aid to teachers and candidates, to indicate the requirements of the examination. It shows the basis on which Examiners were instructed to award marks. It does not indicate the details of the discussions that took place at an Examiners' meeting before marking began, which would have considered the acceptability of alternative answers.

Mark schemes should be read in conjunction with the question paper and the Principal Examiner Report for Teachers.

Cambridge International will not enter into discussions about these mark schemes.

Cambridge International is publishing the mark schemes for the October/November 2018 series for most Cambridge IGCSE™, Cambridge International A and AS Level components and some Cambridge O Level components.

PUBLISHED**Generic Marking Principles**

These general marking principles must be applied by all examiners when marking candidate answers. They should be applied alongside the specific content of the mark scheme or generic level descriptors for a question. Each question paper and mark scheme will also comply with these marking principles.

GENERIC MARKING PRINCIPLE 1:

Marks must be awarded in line with:

- the specific content of the mark scheme or the generic level descriptors for the question
- the specific skills defined in the mark scheme or in the generic level descriptors for the question
- the standard of response required by a candidate as exemplified by the standardisation scripts.

GENERIC MARKING PRINCIPLE 2:

Marks awarded are always **whole marks** (not half marks, or other fractions).

GENERIC MARKING PRINCIPLE 3:

Marks must be awarded **positively**:

- marks are awarded for correct/valid answers, as defined in the mark scheme. However, credit is given for valid answers which go beyond the scope of the syllabus and mark scheme, referring to your Team Leader as appropriate
- marks are awarded when candidates clearly demonstrate what they know and can do
- marks are not deducted for errors
- marks are not deducted for omissions
- answers should only be judged on the quality of spelling, punctuation and grammar when these features are specifically assessed by the question as indicated by the mark scheme. The meaning, however, should be unambiguous.

GENERIC MARKING PRINCIPLE 4:

Rules must be applied consistently e.g. in situations where candidates have not followed instructions or in the application of generic level descriptors.

GENERIC MARKING PRINCIPLE 5:

Marks should be awarded using the full range of marks defined in the mark scheme for the question (however; the use of the full mark range may be limited according to the quality of the candidate responses seen).

GENERIC MARKING PRINCIPLE 6:

Marks awarded are based solely on the requirements as defined in the mark scheme. Marks should not be awarded with grade thresholds or grade descriptors in mind.

Question	Answer	Marks																		
	Section A																			
1(a)(i)	Many correct answers, they must be meaningful. The name is an example only. 1 mark per bullet point Variable name Winner4to6 Data type string Use storing the unique id of the runner age 4 to 6 with the fastest time	3																		
1(a)(ii)	Many correct answers, they must be meaningful. The names are examples only. 1 mark per bullet point 5 arrays seen At least one suitable name e.g. IdNumber At least one suitable datatype e.g. string At least one suitable use e.g. to store the unique identification number All 5 names, datatypes and uses correct Array examples <table> <thead> <tr> <th>Array name</th><th>datatype</th><th>Use</th></tr> </thead> <tbody> <tr> <td>IdNumber</td><td>integer</td><td>unique identification number</td></tr> <tr> <td>Name</td><td>string</td><td>name of child</td></tr> <tr> <td>Age</td><td>integer</td><td>age of child in years</td></tr> <tr> <td>NumRuns</td><td>integer</td><td>number of 2 kilometre runs completed</td></tr> <tr> <td>PB</td><td>real</td><td>fastest time run</td></tr> </tbody> </table>	Array name	datatype	Use	IdNumber	integer	unique identification number	Name	string	name of child	Age	integer	age of child in years	NumRuns	integer	number of 2 kilometre runs completed	PB	real	fastest time run	5
Array name	datatype	Use																		
IdNumber	integer	unique identification number																		
Name	string	name of child																		
Age	integer	age of child in years																		
NumRuns	integer	number of 2 kilometre runs completed																		
PB	real	fastest time run																		

Question	Answer	Marks
1(b)	Many correct answers. 1 mark for each correct point (max 4). Ensuring uniqueness e.g. Search list of previously stored identification numbers (1) To check it has not already been used. (1) Calculation and addition of check digit Attempt at calculation of check digit from the first three digits // calculation from all four digits to obtain zero remainder (1) Adding the calculated check digit as a fourth digit // confirming the check digit is valid. (1)	4
1(c)	Any four from: 1 Initialisation//Setting up array for race times for this race 2 Loop for all runners 3 Input ID 4 Check for valid ID number 5 Input start time and finish time 6 Calculate run time 7 Store run time in suitable array//Use ID index to store run time in appropriate position 8 Store ID in suitable array//Find index for runner	4

Question	Answer	Marks
1(c)	Sample answer: <pre> Counter ← 1 Found ← FALSE WHILE NOT Found = TRUE OUTPUT "Please enter ID number use 9999 to finish " INPUT ParkrunID Search ← 1 REPEAT IF ParkrunID = IdNumber[search] THEN Found ← TRUE Search ← Search + 1 UNTIL Search = 21 OR Found = TRUE ENDWHILE RunnerID[Counter] ← ParkRunID WHILE ParkRunID <> 9999 INPUT StartTime INPUT FinishTime RunnerTime[Counter] ← FinishTime - StartTime Counter ← Counter + 1 Found ← FALSE WHILE NOT Found = TRUE OUTPUT "Please enter ID number (use 9999 to finish) " INPUT ParkrunID Search ← 1 REPEAT IF ParkrunID = IdNumber[Search] THEN Found ← TRUE Search ← Search + 1 UNTIL Search = 21 OR Found = TRUE ENDWHILE RunnerID[Counter] ← ParkRunID ENDWHILE </pre>	

Question	Answer	Marks
1(d)	1 mark for each correct point (max 4). Explanation: 1 Search the results for this park run 2 Separate check for each age range 3 If time recorded is faster 4 ... store new fastest time 5 ... store the ID/Name for the runner 6 Use ID number/Index to look up name after all runners have been searched 7 Output name and fastest time Programming statements may be used but must be fully explained.	4

Question	Answer	Marks
	Section B	
2(a)	Any five from: 1 Use of correct variables 2 Input 3 numbers 3 Check all 3 input numbers are different 4 Attempt to find the largest two numbers input 5 Correctly finding the largest two numbers 6 Multiply their two largest numbers together and assign to variable 7 Output the result of the multiplication Sample answer: <pre> REPEAT OUTPUT "Enter three different numbers" INPUT Number1, Number2, Number3 UNTIL Number1 <> Number2 AND Number2 <> Number3 AND Number3 <> Number1 IF Number3 < Number2 AND Number3 < Number1 THEN Answer ← Number1 * Number2 ENDIF IF Number2 < Number3 AND Number2 < Number1 THEN Answer ← Number1 * Number3 ENDIF IF Number1 < Number2 AND Number1 < Number3 THEN Answer ← Number2 * Number3 ENDIF OUTPUT "Answer = ", Answer </pre>	5
2(b)	There are many correct answers. E.g.: 7, 7, 7 (1 mark) ... should be rejected as numbers are equal (1 mark) 7, 8, 9 (1 mark) ... normal data answer should be 72 (1 mark)	4

Question	Answer	Marks
3	1 mark for each correct line (max 3) Each box must have only one connection. Programming concept Library routine Structure diagram Procedure Function Description A subroutine that does not have to return a value. A standard subroutine that is available for immediate use. A subroutine that always returns a value. An overview of a program or subroutine.	3

Question	Answer	Marks
4	Answers must be given in context. There are many possible answers. E.g.: Selection use of IF statement to check the values of the meter readings (1 mark) IF Reading > 400 and Reading < 900 THEN ... (1 mark) Repetition use of FOR loop to check all 2000 meter readings (1 mark) FOR Meter = 1 TO 2000 ... NEXT (1 mark)	4

Question	Answer					Marks																			
5(a)	<table><tr><th>Height</th><th>Depth</th><th>Chlorine</th><th>OK</th><th>OUTPUT</th></tr><tr><td>6</td><td>2.5</td><td>2</td><td>True</td><td>Pool OK to use</td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr></table>					Height	Depth	Chlorine	OK	OUTPUT	6	2.5	2	True	Pool OK to use										
						Height	Depth	Chlorine	OK	OUTPUT															
						6	2.5	2	True	Pool OK to use															
						<table><tr><th>Height</th><th>Depth</th><th>Chlorine</th><th>OK</th><th>OUTPUT</th></tr><tr><td>4</td><td>3</td><td>1.5</td><td>True</td><td>Water too deep</td></tr><tr><td></td><td></td><td></td><td>False</td><td></td></tr></table>					Height	Depth	Chlorine	OK	OUTPUT	4	3	1.5	True	Water too deep				False	
											Height	Depth	Chlorine	OK	OUTPUT										
											4	3	1.5	True	Water too deep										
									False																
						<table><tr><th>Height</th><th>Depth</th><th>Chlorine</th><th>OK</th><th>OUTPUT</th></tr><tr><td>6</td><td>3.5</td><td>4</td><td>True</td><td>Water too deep</td></tr><tr><td></td><td></td><td></td><td>False</td><td>Too much chlorine add more water</td></tr></table>					Height	Depth	Chlorine	OK	OUTPUT	6	3.5	4	True	Water too deep				False	Too much chlorine add more water
	Height	Depth	Chlorine	OK	OUTPUT																				
	6	3.5	4	True	Water too deep																				
				False	Too much chlorine add more water																				
	1 mark for first 4 columns in each trace table (max 3)																								
	1 mark for the output in each trace table (max 3)																								
	5(b)	Any one from:																							
Cannot add more water if the water is too deep																									
No validation e.g. allows a negative height/depth/amount of chlorine																									
Tells you to add chlorine when there is no water																									
Runs only once																									

Question	Answer	Marks										
6(a)	Many correct answers, an example is given. 1 mark for each correct row (max 4). <table><tr><th>Field</th><th>Data type</th></tr><tr><td>Reference Number</td><td>Text</td></tr><tr><td>Size</td><td>Text</td></tr><tr><td>Type</td><td>Text/Boolean</td></tr><tr><td>Price in \$</td><td>Number/Currency</td></tr></table>	Field	Data type	Reference Number	Text	Size	Text	Type	Text/Boolean	Price in \$	Number/Currency	4
Field	Data type											
Reference Number	Text											
Size	Text											
Type	Text/Boolean											
Price in \$	Number/Currency											
6(b)	1 mark per bullet: Incorrect field name for Reference Number Incorrect criteria for Price in \$ should be < Type not checked	3										