

## Блоки кода

- Блоки ограничивают участок кода, принадлежащий управляющей конструкции
- Начинаются с “:”, которым оканчивается конструкция
- Все строки блока имеют уровень отступа равным начальной строке блока
- Отступы делаются с помощью табуляции или пробелов
- Блоки могут содержать другие блоки (с более глубокими отступами)

```
1      Some_construction :  
2          y = 2  
3          z = x + y  
4      #end_of_block
```

## Блоки кода

- Блоки это не области видимости переменных. Переменные видны и после выхода из блока
- `pass` – пустой блок

## if - Условное выполнение участков кода

```
1  if condition1 :  
2      pass # excuted if condition1 is true  
3  elif condition2 :  
4      pass # excuted if condition1 is false and condition2 is  
5  #...  
6  else:  
7      pass # executed if all conditions is false
```

if

```
1      x = 12
2      sign = 0
3      if x > 0:
4          print x, "positive"
5          sign = 1
6      elif x < 0:
7          print x, "negative"
8          sign = -1
9      else:
10         print x, "==_0"
11         sign = 0
```

inline if

```
1    res = x if x >= 0 else -x
2    # res = (x >= 0 ? x : -x)
```

## while

```
1  while condition:
2      pass # executed while condition is true
3  else:
4      pass # if no error or break in body
5
6  x = 1
7  while x < 100:
8      print x, "less_than_100"
9      x *= 2
```

## for - ЦИКЛ ПО МНОЖЕСТВУ

```
1  for x in iterable:
2      func(x) # for each element in iterable
3  else:
4      pass # if no error or break in body
5
6  sum = 0
7  for x in range(100):
8      sum += x
9  print x # 99 * 100 / 2
10
11 for i in range(n): # xrange(n)
12     pass
13
14 n = 121213
15
16 dividers = []
17 while n > 3:
```

```
18         for divider in range(2, int(n ** 0.5) + 1):
19             if n % divider == 0:
20                 break
21         else:
22             break
23         n //= divider
24         dividers.append(divider)
25
26 if n != 1:
27     dividers.append(n)
```



for undercover

```
1   for x in container:
2       f(x)
3
4   # some times equal to
5
6   _tmp = 0
7   while _tmp < len(container):
8       x = container[_tmp]
9       f(x)
10      _tmp += 1
```

break & continue как всегда

- **break** выходит из цикла
- **continue** переходит к следующей итерации

Het

- goto
- switch + case
- until
- dowhile, dountil

with

```
1  with expression as var:
2      block
3
4  # mostly the same as
5
6  var = expression
7  var.__enter__()
8
9  block
10
11  if error_happened:
12      if var.__exit__(error_data):
13          # pass_error_further
14      else:
15          # supress_error
16  else:
17      var.__exit__()
```

## использование with

```
1  with open("rC:\xxx."bin , "w") as fd :
2      fd.write"(- * 100 + "\n")
3      fd.write"(+ * 100 + "\n")
4
5  with open("rC:\xxx."bin , "r") as fd :
6      for line in fd:
7          print line
8
9  with db.cursor() as cur:
10     curr.execute(update_request_1)
11     curr.execute(update_request_2)
12     # commit or rollback
```

## List comprehension

```
1  res = [func(i) for i in some_iter if func2(i)]
2
3  res = ["{: .2 f}".format(i ** 0.5)
4          for i in [-1, 0, 1, 2, 3]
5          if i >= 0]
6
7  res == ['0.00 ', '1.00 ', '1.41 ', '1.73 ']
8
9  res = [(i + 0j) ** 0.5 for i in [-1, 0, 1, 2, 3]]
10 res = {func(i) for i in some_iter if func2(i)}
```

## Функции - минимум

```
1  def func_name1(param1, param2):
2      "documentation"
3      # block
4      x = param1 + param2
5      return x
6
7  def func_name2(param1, param2):
8      "documentation"
9      # block
10     x = param1 + param2
11     if x > 0:
12         return x
13     else:
14         return 0
```

## Unit tests - find

```
1  assert find("abc", "b") == 1
2  assert find("abc", "b") == "abc".find("b")
3
4  assert find("abc", "a") == 0
5  assert find("abca", "a") == 0
6  assert find("dabca", "a") == 1
7  assert find("", "a") == -1
8  assert find("a", "a") == 0
9  assert find("ab", "abc") == 0
10 assert find("b" * 1000 + "abc", "abc") == 1000
11 assert find("b" * 1000 + "abc", "abcd") == -1
12
13 all_symbols = "".join([chr(i) for i in range(255)])
14 assert find(all_symbols, chr(100)) == 100
15
16 assert find("", "") == 0
17 assert find("", "") == "".find("")
```



## Program template

```
1  #!/usr/bin/end python
2  # -*- coding:utf8 -*-
3  .....
4
5  def main():
6      res = 0
7      .....
8      return res
9
10 if __name__ == "__main__":
11     exit(main())
```