Native baseline correspondence: ring circumference $C = 2L$

Measured ring / interval ratio	Mirror expectation	Wave-pinning (4 pairs)	Goryachev (4 pairs)	Holmes 3 (5 pairs)
Full half-contrast width	2	1.999904–2.000004	1.997945–2.004584	1.999984–2.000002
Full excess-active core amount	2	1.999887–2.000054	1.995859–2.002976	1.999913–2.000015
Absolute primary peak	1	1.000000–1.000049	1.000931–1.001986	1.000000–1.000001
Matched cue-weighted input gain	1	1.000000–1.000000	0.999519–1.002375	1.000000–1.000001
Opposing-point gain (support)	1	1.000000–1.000000	0.999519–1.002375	1.000000–1.000001

WP/G: L = 5, 15, 25, 35 ↔ C = 10, 30, 50, 70
Holmes: L = 10, 15, 20, 25, 30 ↔ C = 20, 30, 40, 50, 60

Matched cue: endpoint support 3 ↔ ring full support 6.
Point gain remains a distinct supporting readout.

Independently prepared native basals; all 26 checkpoint hashes verified. Ring h = 0.05; interval uses 201 cells.
A support-3 endpoint cue reflects to full ring support 6; the retained ring challenges use support 3. Finite cues are not mirror-equivalent.