


S11 · Goryachev · size label 40 · f=0.02 · noise
context common · σ=1 · horizon=32000 · n=12 independent noisy realizations






Native concentrations and every retained field frame are plotted without spatial resampling. First half shaded: excluded from summary selection.
Spring mesh-face interpolation applies only to boundary geometry; snapshots use their actual saved C(t). P uses basal M₁ normalization, not instantaneous coherence.
Selection and controls are supplemental; no main example is chosen. Native NPZ/status links remain local/HPC data.


S11 · Goryachev · size label 40 · f=0.03 · mean
context common · σ=0 · horizon=32000 · 1 deterministic control





Native concentrations and every retained field frame are plotted without spatial resampling.
First half shaded: excluded from summary selection.
Spring mesh-face interpolation changes only boundary geometry; snapshots use actual saved C(t).
P uses basal M_1 normalization, distinct from instantaneous coherence.
Supplemental selection and controls; no main example is chosen.
Native NPZ/status links remain local/HPC data.

S11 · Goryachev · size label 40 · f=0.03 · noise
context common · σ=1 · horizon=32000 · n=12 independent noisy realizations











Native concentrations and every retained field frame are plotted without spatial resampling. First half shaded: excluded from summary selection.
Spring mesh-face interpolation applies only to boundary geometry; snapshots use their actual saved C(t). P uses basal M_1 normalization, not instantaneous coherence.
Selection and controls are supplemental; no main example is chosen. Native NPZ/status links remain local/HPC data.


S11 · Goryachev · size label 40 · f=0.05 · mean
context common · σ=0 · horizon=32000 · 1 deterministic control





Native concentrations and every retained field frame are plotted without spatial resampling.
First half shaded: excluded from summary selection.
Spring mesh-face interpolation changes only boundary geometry; snapshots use actual saved C(t).
P uses basal M_1 normalization, distinct from instantaneous coherence.
Supplemental selection and controls; no main example is chosen.
Native NPZ/status links remain local/HPC data.

S11 · Goryachev · size label 40 · f=0.05 · noise
context common · σ=1 · horizon=32000 · n=12 independent noisy realizations












Native concentrations and every retained field frame are plotted without spatial resampling. First half shaded: excluded from summary selection.
Spring mesh-face interpolation applies only to boundary geometry; snapshots use their actual saved C(t). P uses basal M_1 normalization, not instantaneous coherence.
Selection and controls are supplemental; no main example is chosen. Native NPZ/status links remain local/HPC data.

S11 · Goryachev · size label 40 · f=0.1 · mean
context common · σ=0 · horizon=32000 · 1 deterministic control









Native concentrations and every retained field frame are plotted without spatial resampling.
First half shaded: excluded from summary selection.
Spring mesh-face interpolation changes only boundary geometry; snapshots use actual saved C(t).
P uses basal M_1 normalization, distinct from instantaneous coherence.
Supplemental selection and controls; no main example is chosen.
Native NPZ/status links remain local/HPC data.


S11 · Goryachev · size label 40 · f=0.1 · noise
context common · σ=1 · horizon=32000 · n=12 independent noisy realizations







Native concentrations and every retained field frame are plotted without spatial resampling. First half shaded: excluded from summary selection.
Spring mesh-face interpolation applies only to boundary geometry; snapshots use their actual saved C(t). P uses basal M_1 normalization, not instantaneous coherence.
Selection and controls are supplemental; no main example is chosen. Native NPZ/status links remain local/HPC data.

S11 · Goryachev · size label 40 · f=0.3 · mean
context common · σ=0 · horizon=32000 · 1 deterministic control











Native concentrations and every retained field frame are plotted without spatial resampling.
First half shaded: excluded from summary selection.
Spring mesh-face interpolation changes only boundary geometry; snapshots use actual saved C(t).
P uses basal M_1 normalization, distinct from instantaneous coherence.
Supplemental selection and controls; no main example is chosen.
Native NPZ/status links remain local/HPC data.

S11 · Goryachev · size label 40 · f=0.3 · noise
context common · σ=1 · horizon=32000 · n=2 independent noisy realizations











Native concentrations and every retained field frame are plotted without spatial resampling. First half shaded: excluded from summary selection.
Spring mesh-face interpolation applies only to boundary geometry; snapshots use their actual saved C(t). P uses basal M_1 normalization, not instantaneous coherence.
Selection and controls are supplemental; no main example is chosen. Native NPZ/status links remain local/HPC data.


S11 · Goryachev · size label 40 · f=1 · mean
context common · σ=0 · horizon=32000 · 1 deterministic control



Native concentrations and every retained field frame are plotted without spatial resampling.
First half shaded: excluded from summary selection.
Spring mesh-face interpolation changes only boundary geometry; snapshots use actual saved C(t).
P uses basal M_1 normalization, distinct from instantaneous coherence.
Supplemental selection and controls; no main example is chosen.
Native NPZ/status links remain local/HPC data.


S11 · Goryachev · size label 40 · f=1 · noise
context common · σ=1 · horizon=32000 · n=2 independent noisy realizations







Native concentrations and every retained field frame are plotted without spatial resampling. First half shaded: excluded from summary selection.
Spring mesh-face interpolation applies only to boundary geometry; snapshots use their actual saved C(t). P uses basal M₁ normalization, not instantaneous coherence.
Selection and controls are supplemental; no main example is chosen. Native NPZ/status links remain local/HPC data.

S11 · Goryachev · size label 50 · f=0 · zero
context common · σ=0 · horizon=32000 · 1 deterministic control










Native concentrations and every retained field frame are plotted without spatial resampling.
First half shaded: excluded from summary selection.
Spring mesh-face interpolation changes only boundary geometry; snapshots use actual saved C(t).
P uses basal M_1 normalization, distinct from instantaneous coherence.
Supplemental selection and controls; no main example is chosen.
Native NPZ/status links remain local/HPC data.

S11 · Goryachev · size label 50 · f=0.001 · mean
context common · σ=0 · horizon=32000 · 1 deterministic control









Native concentrations and every retained field frame are plotted without spatial resampling.
First half shaded: excluded from summary selection.
Spring mesh-face interpolation changes only boundary geometry; snapshots use actual saved C(t).
P uses basal M_1 normalization, distinct from instantaneous coherence.
Supplemental selection and controls; no main example is chosen.
Native NPZ/status links remain local/HPC data.


S11 · Goryachev · size label 50 · f=0.001 · noise
context common · σ=1 · horizon=32000 · n=12 independent noisy realizations







Native concentrations and every retained field frame are plotted without spatial resampling. First half shaded: excluded from summary selection.
Spring mesh-face interpolation applies only to boundary geometry; snapshots use their actual saved C(t). P uses basal M_1 normalization, not instantaneous coherence.
Selection and controls are supplemental; no main example is chosen. Native NPZ/status links remain local/HPC data.

S11 · Goryachev · size label 50 · f=0.003 · mean
context common · σ=0 · horizon=32000 · 1 deterministic control









Native concentrations and every retained field frame are plotted without spatial resampling.
First half shaded: excluded from summary selection.
Spring mesh-face interpolation changes only boundary geometry; snapshots use actual saved C(t).
P uses basal M_1 normalization, distinct from instantaneous coherence.
Supplemental selection and controls; no main example is chosen.
Native NPZ/status links remain local/HPC data.


S11 · Goryachev · size label 50 · f=0.003 · noise
context common · σ=1 · horizon=32000 · n=12 independent noisy realizations







Native concentrations and every retained field frame are plotted without spatial resampling. First half shaded: excluded from summary selection.
Spring mesh-face interpolation applies only to boundary geometry; snapshots use their actual saved C(t). P uses basal M₁ normalization, not instantaneous coherence.
Selection and controls are supplemental; no main example is chosen. Native NPZ/status links remain local/HPC data.

S11 · Goryachev · size label 50 · f=0.01 · mean
context common · σ=0 · horizon=32000 · 1 deterministic control









Native concentrations and every retained field frame are plotted without spatial resampling.
First half shaded: excluded from summary selection.
Spring mesh-face interpolation changes only boundary geometry; snapshots use actual saved C(t).
P uses basal M_1 normalization, distinct from instantaneous coherence.
Supplemental selection and controls; no main example is chosen.
Native NPZ/status links remain local/HPC data.


S11 · Goryachev · size label 50 · f=0.01 · noise
context common · σ=1 · horizon=32000 · n=12 independent noisy realizations







Native concentrations and every retained field frame are plotted without spatial resampling. First half shaded: excluded from summary selection.
Spring mesh-face interpolation applies only to boundary geometry; snapshots use their actual saved C(t). P uses basal M₁ normalization, not instantaneous coherence.
Selection and controls are supplemental; no main example is chosen. Native NPZ/status links remain local/HPC data.

S11 · Goryachev · size label 50 · f=0.03 · mean
context common · σ=0 · horizon=32000 · 1 deterministic control









Native concentrations and every retained field frame are plotted without spatial resampling.
First half shaded: excluded from summary selection.
Spring mesh-face interpolation changes only boundary geometry; snapshots use actual saved C(t).
P uses basal M_1 normalization, distinct from instantaneous coherence.
Supplemental selection and controls; no main example is chosen.
Native NPZ/status links remain local/HPC data.


S11 · Goryachev · size label 50 · f=0.03 · noise
context common · σ=1 · horizon=32000 · n=12 independent noisy realizations







Native concentrations and every retained field frame are plotted without spatial resampling. First half shaded: excluded from summary selection.
Spring mesh-face interpolation applies only to boundary geometry; snapshots use their actual saved C(t). P uses basal M_1 normalization, not instantaneous coherence.
Selection and controls are supplemental; no main example is chosen. Native NPZ/status links remain local/HPC data.

S11 · Goryachev · size label 50 · f=0.1 · mean
context common · σ=0 · horizon=32000 · 1 deterministic control









Native concentrations and every retained field frame are plotted without spatial resampling.
First half shaded: excluded from summary selection.
Spring mesh-face interpolation changes only boundary geometry; snapshots use actual saved C(t).
P uses basal M_1 normalization, distinct from instantaneous coherence.
Supplemental selection and controls; no main example is chosen.
Native NPZ/status links remain local/HPC data.


S11 · Goryachev · size label 50 · f=0.1 · noise
context common · σ=1 · horizon=32000 · n=12 independent noisy realizations







Native concentrations and every retained field frame are plotted without spatial resampling. First half shaded: excluded from summary selection.
Spring mesh-face interpolation applies only to boundary geometry; snapshots use their actual saved C(t). P uses basal M₁ normalization, not instantaneous coherence.
Selection and controls are supplemental; no main example is chosen. Native NPZ/status links remain local/HPC data.

S11 · Goryachev · size label 60 · f=0 · zero
context common · σ=0 · horizon=32000 · 1 deterministic control









Native concentrations and every retained field frame are plotted without spatial resampling.
First half shaded: excluded from summary selection.
Spring mesh-face interpolation changes only boundary geometry; snapshots use actual saved C(t).
P uses basal M_1 normalization, distinct from instantaneous coherence.
Supplemental selection and controls; no main example is chosen.
Native NPZ/status links remain local/HPC data.

S11 · Goryachev · size label 60 · f=0.0001 · mean
context common · σ=0 · horizon=32000 · 1 deterministic control




Native concentrations and every retained field frame are plotted without spatial resampling.
First half shaded: excluded from summary selection.
Spring mesh-face interpolation changes only boundary geometry; snapshots use actual saved C(t).
P uses basal M_1 normalization, distinct from instantaneous coherence.
Supplemental selection and controls; no main example is chosen.
Native NPZ/status links remain local/HPC data.

S11 · Goryachev · size label 60 · f=0.0001 · noise
context common · σ=1 · horizon=32000 · n=2 independent noisy realizations




Native concentrations and every retained field frame are plotted without spatial resampling. First half shaded: excluded from summary selection.
Spring mesh-face interpolation applies only to boundary geometry; snapshots use their actual saved C(t). P uses basal M_1 normalization, not instantaneous coherence.
Selection and controls are supplemental; no main example is chosen. Native NPZ/status links remain local/HPC data.


S11 · Goryachev · size label 60 · f=0.0003 · mean
context common · σ=0 · horizon=32000 · 1 deterministic control



Native concentrations and every retained field frame are plotted without spatial resampling.
First half shaded: excluded from summary selection.
Spring mesh-face interpolation changes only boundary geometry; snapshots use actual saved C(t).
P uses basal M_1 normalization, distinct from instantaneous coherence.
Supplemental selection and controls; no main example is chosen.
Native NPZ/status links remain local/HPC data.


S11 · Goryachev · size label 60 · f=0.0003 · noise
context common · σ=1 · horizon=32000 · n=2 independent noisy realizations







Native concentrations and every retained field frame are plotted without spatial resampling. First half shaded: excluded from summary selection.
Spring mesh-face interpolation applies only to boundary geometry; snapshots use their actual saved C(t). P uses basal M₁ normalization, not instantaneous coherence.
Selection and controls are supplemental; no main example is chosen. Native NPZ/status links remain local/HPC data.

S11 · Goryachev · size label 60 · f=0.001 · mean
context common · σ=0 · horizon=32000 · 1 deterministic control









Native concentrations and every retained field frame are plotted without spatial resampling.
First half shaded: excluded from summary selection.
Spring mesh-face interpolation changes only boundary geometry; snapshots use actual saved C(t).
P uses basal M_1 normalization, distinct from instantaneous coherence.
Supplemental selection and controls; no main example is chosen.
Native NPZ/status links remain local/HPC data.


S11 · Goryachev · size label 60 · f=0.001 · noise
context common · σ=1 · horizon=32000 · n=12 independent noisy realizations







Native concentrations and every retained field frame are plotted without spatial resampling. First half shaded: excluded from summary selection.
Spring mesh-face interpolation applies only to boundary geometry; snapshots use their actual saved C(t). P uses basal M₁ normalization, not instantaneous coherence.
Selection and controls are supplemental; no main example is chosen. Native NPZ/status links remain local/HPC data.

S11 · Goryachev · size label 60 · f=0.003 · mean
context common · σ=0 · horizon=32000 · 1 deterministic control









Native concentrations and every retained field frame are plotted without spatial resampling.
First half shaded: excluded from summary selection.
Spring mesh-face interpolation changes only boundary geometry; snapshots use actual saved C(t).
P uses basal M_1 normalization, distinct from instantaneous coherence.
Supplemental selection and controls; no main example is chosen.
Native NPZ/status links remain local/HPC data.


S11 · Goryachev · size label 60 · f=0.003 · noise
context common · σ=1 · horizon=32000 · n=12 independent noisy realizations






Native concentrations and every retained field frame are plotted without spatial resampling. First half shaded: excluded from summary selection.
Spring mesh-face interpolation applies only to boundary geometry; snapshots use their actual saved C(t). P uses basal M₁ normalization, not instantaneous coherence.
Selection and controls are supplemental; no main example is chosen. Native NPZ/status links remain local/HPC data.


S11 · Goryachev · size label 60 · f=0.005 · mean
context common · σ=0 · horizon=32000 · 1 deterministic control



Native concentrations and every retained field frame are plotted without spatial resampling.
First half shaded: excluded from summary selection.
Spring mesh-face interpolation changes only boundary geometry; snapshots use actual saved C(t).
P uses basal M_1 normalization, distinct from instantaneous coherence.
Supplemental selection and controls; no main example is chosen.
Native NPZ/status links remain local/HPC data.


S11 · Goryachev · size label 60 · f=0.005 · noise
context common · σ=1 · horizon=32000 · n=12 independent noisy realizations






Native concentrations and every retained field frame are plotted without spatial resampling. First half shaded: excluded from summary selection.
Spring mesh-face interpolation applies only to boundary geometry; snapshots use their actual saved C(t). P uses basal M₁ normalization, not instantaneous coherence.
Selection and controls are supplemental; no main example is chosen. Native NPZ/status links remain local/HPC data.


S11 · Goryachev · size label 60 · f=0.01 · mean
context common · σ=0 · horizon=32000 · 1 deterministic control



Native concentrations and every retained field frame are plotted without spatial resampling.
First half shaded: excluded from summary selection.
Spring mesh-face interpolation changes only boundary geometry; snapshots use actual saved C(t).
P uses basal M_1 normalization, distinct from instantaneous coherence.
Supplemental selection and controls; no main example is chosen.
Native NPZ/status links remain local/HPC data.


S11 · Goryachev · size label 60 · f=0.01 · noise
context common · σ=1 · horizon=32000 · n=12 independent noisy realizations







Native concentrations and every retained field frame are plotted without spatial resampling. First half shaded: excluded from summary selection.
Spring mesh-face interpolation applies only to boundary geometry; snapshots use their actual saved C(t). P uses basal M₁ normalization, not instantaneous coherence.
Selection and controls are supplemental; no main example is chosen. Native NPZ/status links remain local/HPC data.

S11 · Goryachev · size label 60 · f=0.015 · mean
context common · σ=0 · horizon=32000 · 1 deterministic control









Native concentrations and every retained field frame are plotted without spatial resampling.
First half shaded: excluded from summary selection.
Spring mesh-face interpolation changes only boundary geometry; snapshots use actual saved C(t).
P uses basal M_1 normalization, distinct from instantaneous coherence.
Supplemental selection and controls; no main example is chosen.
Native NPZ/status links remain local/HPC data.


S11 · Goryachev · size label 60 · f=0.015 · noise
context common · σ=1 · horizon=32000 · n=12 independent noisy realizations







Native concentrations and every retained field frame are plotted without spatial resampling. First half shaded: excluded from summary selection.
Spring mesh-face interpolation applies only to boundary geometry; snapshots use their actual saved C(t). P uses basal M₁ normalization, not instantaneous coherence.
Selection and controls are supplemental; no main example is chosen. Native NPZ/status links remain local/HPC data.

S11 · Goryachev · size label 60 · f=0.02 · mean
context common · σ=0 · horizon=32000 · 1 deterministic control











Native concentrations and every retained field frame are plotted without spatial resampling.
First half shaded: excluded from summary selection.
Spring mesh-face interpolation changes only boundary geometry; snapshots use actual saved C(t).
P uses basal M_1 normalization, distinct from instantaneous coherence.
Supplemental selection and controls; no main example is chosen.
Native NPZ/status links remain local/HPC data.

S11 · Goryachev · size label 60 · f=0.02 · noise
context common · σ=1 · horizon=32000 · n=12 independent noisy realizations












Native concentrations and every retained field frame are plotted without spatial resampling. First half shaded: excluded from summary selection.
Spring mesh-face interpolation applies only to boundary geometry; snapshots use their actual saved C(t). P uses basal M_1 normalization, not instantaneous coherence.
Selection and controls are supplemental; no main example is chosen. Native NPZ/status links remain local/HPC data.

S11 · Goryachev · size label 60 · f=0.03 · mean
context common · σ=0 · horizon=32000 · 1 deterministic control










Native concentrations and every retained field frame are plotted without spatial resampling.
First half shaded: excluded from summary selection.
Spring mesh-face interpolation changes only boundary geometry; snapshots use actual saved C(t).
P uses basal M_1 normalization, distinct from instantaneous coherence.
Supplemental selection and controls; no main example is chosen.
Native NPZ/status links remain local/HPC data.

S11 · Goryachev · size label 60 · f=0.03 · noise
context common · σ=1 · horizon=32000 · n=12 independent noisy realizations








Native concentrations and every retained field frame are plotted without spatial resampling. First half shaded: excluded from summary selection.
Spring mesh-face interpolation applies only to boundary geometry; snapshots use their actual saved C(t). P uses basal M_1 normalization, not instantaneous coherence.
Selection and controls are supplemental; no main example is chosen. Native NPZ/status links remain local/HPC data.



S11 · Goryachev · size label 60 · f=0.05 · mean
context common · σ=0 · horizon=32000 · 1 deterministic control
Summary-feature medoid · seed 0
deterministic control · profile cadence 5
Native time
Physical arc from fixed material origin
Native active concentration
t=0, C=60
t=16000, C=60
t=24000, C=60
t=32000, C=60
Native active concentration
Actual physical arc at each saved snapshot
|P| (basal M₁ normalized)
Native spatial mean input
Native time
Native concentrations and every retained field frame are plotted without spatial resampling.
First half shaded: excluded from summary selection.
Spring mesh-face interpolation changes only boundary geometry; snapshots use actual saved C(t).
P uses basal M₁ normalization, distinct from instantaneous coherence.
Supplemental selection and controls; no main example is chosen.
Native NPZ/status links remain local/HPC data.

S11 · Goryachev · size label 60 · f=0.05 · noise
context common · σ=1 · horizon=32000 · n=12 independent noisy realizations












Native concentrations and every retained field frame are plotted without spatial resampling. First half shaded: excluded from summary selection.
Spring mesh-face interpolation applies only to boundary geometry; snapshots use their actual saved C(t). P uses basal M_1 normalization, not instantaneous coherence.
Selection and controls are supplemental; no main example is chosen. Native NPZ/status links remain local/HPC data.

S11 · Goryachev · size label 60 · f=0.1 · mean
context common · σ=0 · horizon=32000 · 1 deterministic control











Native concentrations and every retained field frame are plotted without spatial resampling.
First half shaded: excluded from summary selection.
Spring mesh-face interpolation changes only boundary geometry; snapshots use actual saved C(t).
P uses basal M_1 normalization, distinct from instantaneous coherence.
Supplemental selection and controls; no main example is chosen.
Native NPZ/status links remain local/HPC data.

S11 · Goryachev · size label 60 · f=0.1 · noise
context common · σ=1 · horizon=32000 · n=12 independent noisy realizations












Native concentrations and every retained field frame are plotted without spatial resampling. First half shaded: excluded from summary selection.
Spring mesh-face interpolation applies only to boundary geometry; snapshots use their actual saved C(t). P uses basal M_1 normalization, not instantaneous coherence.
Selection and controls are supplemental; no main example is chosen. Native NPZ/status links remain local/HPC data.

S11 · Goryachev · size label 60 · f=0.3 · mean
context common · σ=0 · horizon=32000 · 1 deterministic control









Native concentrations and every retained field frame are plotted without spatial resampling.
First half shaded: excluded from summary selection.
Spring mesh-face interpolation changes only boundary geometry; snapshots use actual saved C(t).
P uses basal M_1 normalization, distinct from instantaneous coherence.
Supplemental selection and controls; no main example is chosen.
Native NPZ/status links remain local/HPC data.


S11 · Goryachev · size label 60 · f=0.3 · noise
context common · σ=1 · horizon=32000 · n=2 independent noisy realizations






Native concentrations and every retained field frame are plotted without spatial resampling. First half shaded: excluded from summary selection.
Spring mesh-face interpolation applies only to boundary geometry; snapshots use their actual saved C(t). P uses basal M₁ normalization, not instantaneous coherence.
Selection and controls are supplemental; no main example is chosen. Native NPZ/status links remain local/HPC data.


S11 · Goryachev · size label 60 · f=1 · mean
context common · σ=0 · horizon=32000 · 1 deterministic control





Native concentrations and every retained field frame are plotted without spatial resampling.
First half shaded: excluded from summary selection.
Spring mesh-face interpolation changes only boundary geometry; snapshots use actual saved C(t).
P uses basal M_1 normalization, distinct from instantaneous coherence.
Supplemental selection and controls; no main example is chosen.
Native NPZ/status links remain local/HPC data.

S11 · Goryachev · size label 60 · f=1 · noise
context common · σ=1 · horizon=32000 · n=2 independent noisy realizations












Native concentrations and every retained field frame are plotted without spatial resampling. First half shaded: excluded from summary selection.
Spring mesh-face interpolation applies only to boundary geometry; snapshots use their actual saved C(t). P uses basal M_1 normalization, not instantaneous coherence.
Selection and controls are supplemental; no main example is chosen. Native NPZ/status links remain local/HPC data.

S11 · Holmes 3 · size label 20 · f=0 · zero
context common · σ=0 · horizon=32000 · 1 deterministic control







Native concentrations and every retained field frame are plotted without spatial resampling.
First half shaded: excluded from summary selection.
Spring mesh-face interpolation changes only boundary geometry; snapshots use actual saved C(t).
P uses basal M_1 normalization, distinct from instantaneous coherence.
Supplemental selection and controls; no main example is chosen.
Native NPZ/status links remain local/HPC data.