



## Applied Deep Learning

Dr. Philippe Blaettchen  
Bayes Business School (formerly Cass)

[www.bayes.city.ac.uk](http://www.bayes.city.ac.uk)

## Learning objectives of today

### **Goals:**

- Understand some of the key tools to run computer vision algorithms in practice

### **How will we do this?**


- We start with discussing the Functional API and the added flexibility it enables use
- We then take a look at architectural typical for CNNs and specific tips and tricks of modifying them
- Finally, we introduce transfer learning, a key tool to create powerful algorithms from little data





# From Sequential to Functional

# TensorFlow: the right complexity for everyone



Source: Chollet





**BAYES**  
BUSINESS SCHOOL  
CITY, UNIVERSITY OF LONDON

Try it out – Code Parts 1.1-1.3!



- What key differences do you observe between the Sequential API and the Functional API?
- For which types of applications is the Sequential API insufficient?

## A typical application: object localization and detection





Source: Géron



**Some architectural ideas specific to CNNs**


# GoogLeNet



Source: Szegedy



# U-Net




Source: Ronneberge



**BAYES**  
BUSINESS SCHOOL  
CITY, UNIVERSITY OF LONDON

# VGG16



Source: Chollet



**BAYES**  
BUSINESS SCHOOL  
CITY, UNIVERSITY OF LONDON

## Architectural tips and tricks around CNNs

- Create modules, organize them into hierarchies, and reuse the same modules
- Create deep stacks of narrow layers (rather than shallow stacks of large layers)

## The problem with deep stacks




## Architectural tips and tricks around CNNs

- Create modules, organize them into hierarchies, and reuse the same modules
- Create deep stacks of narrow layers (rather than shallow stacks of large layers)
- To avoid vanishing gradients in deep networks, retain noiseless versions of information from previous input (“residual connections”)



## A residual connection



→ Watch out for dimensions!


Source: Chollet

## Architectural tips and tricks around CNNs

- Create modules, organize them into hierarchies, and reuse the same modules
- Create deep stacks of narrow layers (rather than shallow stacks of large layers)
- To avoid vanishing gradients in deep networks, retain noiseless versions of information from previous input (“residual connections”)
- Use data augmentation
- Use batch normalization (even more so than in other types of networks)
- Use advanced layers that make efficient use of the information structure of your data

## Depthwise separable convolutions

- Convolute channels independently
- Assumes information is spatially highly correlated but largely independent across channels → this is usually the case for representations of images
- Key benefit: much fewer parameters and computations



Source: Chollet



**BAYES**  
BUSINESS SCHOOL  
CITY, UNIVERSITY OF LONDON



## Try it out – Code Part 2!



- Which architectural features do you notice? Do they make sense to you?
- What do we have to do to make the residual dimensions stack up?





**Transfer learning: creating powerful computer vision algorithms  
with little data**


## Transfer learning: using pre-trained models

- If a CNN is trained on a large number of images, the spatial feature hierarchy can act as a generic model of the visual world
- For example, take a model trained on the ImageNet dataset (1.4 million labeled images of 1,000 different classes, such as animals and everyday objects)
  - What type of classification tasks might this be useful for?




## Repurposing a neural network

- Naïve approach: take the existing (trained) neural network
- Adjust the output layer
- Train some more with your data set




## Difference between low-level and high-level features

- Problem with the previous approach: training may be very slow. Because the added training is on less data (usually), we might also be adding overfitting issues
- But: early layers capture low-level features that are unlikely to be different
- Deeper layers capture high-level features that are likely to be different



## Option 1: Feature extraction




## Try it out – Code Part 3!



- In 3.1, you use the outputs from a pre-trained model
- In 3.2, you build a model including the pre-trained layers, but freeze training for these



## Option 2: Fine-tuning





## Transfer learning for computer vision

- In deep learning for computer vision, the visual input is broken down into generic patterns, which are then combined in a hierarchy to derive the ultimate prediction
- The deeper we go in the network, the more we move from representing the visual content to representing its meaning
- If we are not too deep, the representations are quite independent of the specific task but are (good) representations of a visual input

Time permitting – Apply what you learned in Code Part 4



**BAYES**  
BUSINESS SCHOOL  
CITY, UNIVERSITY OF LONDON

Please fill out the module evaluation



<https://city.surveys.evasysplus.co.uk/>



**BAYES**  
BUSINESS SCHOOL  
CITY, UNIVERSITY OF LONDON



See you next week!

## Sources

- Amini et al., 2019, Uncovering and Mitigating Algorithmic Bias through Learned Latent Structure: [http://introtodeeplearning.com/AAAI\\_MitigatingAlgorithmicBias.pdf](http://introtodeeplearning.com/AAAI_MitigatingAlgorithmicBias.pdf)
- Chollet, 2021, Deep Learning with Python (2<sup>nd</sup> edition)
- Géron, 2022, Hands-On Machine Learning with Scikit-Learn, Keras, and TensorFlow (3<sup>rd</sup> edition)
- Goodfellow, Bengio, Courville, 2016, The Deep Learning Book: <http://www.deeplearningbook.org>
- Google, 2017, Machine Learning and Human Bias: <https://www.youtube.com/watch?v=59bMh59JQDo>
- Manyika et al., 2019, What Do We Do About the Biases in AI? <https://hbr.org/2019/10/what-do-we-do-about-the-biases-in-ai>
- Ronneberger et al., 2015, U-Net: Convolutional Networks for Biomedical Image Segmentation: [https://link.springer.com/content/pdf/10.1007/978-3-319-24574-4\\_28.pdf](https://link.springer.com/content/pdf/10.1007/978-3-319-24574-4_28.pdf)
- Szegedy et al., 2015, Going Deeper with Convolutions: [https://www.cv-foundation.org/openaccess/content\\_cvpr\\_2015/papers/Szegedy\\_Going\\_Deeper\\_With\\_CVPR\\_paper.pdf](https://www.cv-foundation.org/openaccess/content_cvpr_2015/papers/Szegedy_Going_Deeper_With_CVPR_paper.pdf)

