

sol2_implementer_agent_sdk

Take-home **configuration port**. It does not run the eight-step loop.

This is the role graph. The live harness is `sol2_implementer_deep_agents`.

`task run prints ClaudeAgentOptions`. It does not implement T001.

Read `HOW_TO_RUN.md`, `DESIGN_DOC.md`, `TEST_PLAN.md`, **and** `E2E_PLAN.md`.

Spillwave Solutions | spillwave.com

Cast, not the driver

DRIVER VERSUS CAST

LIVE DRIVER

 sol2 implementer deep agents

 eight-step loop

 task run implements T001

 red gate plus rubric plus exits

CONFIG PORT

 sol2 implementer agent sdk

 role table only

 task run prints options

 does not implement T001

 Same table. Different enforcement knob.

Do not demo T001 from the cast folder.

`task run prints ClaudeAgentOptions.` It does not implement T001.

Spillwave Solutions | spillwave.com

2

What it proves

The role table survived the runtime swap.

role	writes	scope	
orchestrator	no	nothing	
planner	yes	steps.jsonl	
test_implementer	yes	tests/**	
code_implementer	yes	app/**, src/**	denied tests/**
judge	no	nothing	

Missing on purpose: `implementer.py`, `gates.py`, `rubric.py`, `doers.py`.

Do not copy this folder into `labs/lab2_implementer/harness.py`. Saturday wants `red_gate / score_attempt / run_loop`.

Setup. Folder-local venv

```
cd solutions/sol2_implementer_agent_sdk
echo 'ANTHROPIC_API_KEY=sk-ant-...' >> ../../.env
task setup          # .venv + claude-agent-sdk. PEP 668.
task clone          # only if you want live options against a real repo
```

Do not `pip install` into Homebrew Python.

Scripts with no model

```
task table      # judge writes must print no
task test      # pytest. No key, no SDK, no clone.
```

If judge prints `yes`, stop. The port is wrong.

Architecture



`task run --` prints options with `dontAsk` and one `PreToolUse` hook. No call to `implementer.run`.

Scope. Two places, both required

`tools=[...]` decides whether a role can write at all.

One `PreToolUse` hook reads `agent_type` and looks up that role's scope.

A write with no agent is denied. The parent has no business writing anything.

Deny envelope:

```
hookSpecificOutput.hookEventName = PreToolUse
hookSpecificOutput.permissionDecision = deny
```

A typo fails **open**. The field is `maxTurns`, camelCase.

`task run` is configuration

```
task run --
```

Needs `task setup`. Prints options. Stops.

That is not a ticket run. A test that expects `task run -- --ticket T001` to implement a ticket is testing a product this folder refused to be.

Live T001. Glue, not a second loop

`e2e_t001.py` hands `AgentSdkBackend` to the Deep Agents driver.

Both folders ship `adapter.py` and `roles.py`. Putting both on `sys.path` shadows one of them. The glue loads each folder in an isolated import scope.

Do not invent a shared `loops/` package. Do not copy `implementer.py` into this folder.

Read `E2E_PLAN.md` before spending a token.

Testing skill

```
.agents/skills/test-ticket-implementer/
```

Track A is `sol2_implementer_deep_agents`. Track B is this backend plugged into that driver.

Run `task test` here first. Do not spend a token to diagnose a failing offline suite.

Spillwave Solutions | spillwave.com

Plugin files vs Python

```
plugin/agents/...  
plugin/skills/...
```

The plugin is the readable specification. Python owns the options. When an agent markdown file and the role table disagree, `options_for` raises.

Troubleshooting

SYMPTOM	FIX
Thought this ran T001	config port. Use Deep Agents task run
Judge writes yes	strip Write from judge tools
Fail-open writes	full hookSpecificOutput deny
externally-managed-environment	task setup, not system pip
Copied into lab2 stub	Saturday wants three functions

Recap

Config port, not a filled loop. Same table, different enforcement knob.

The eight steps live in `sol2_implementer_deep_agents`. This folder proves the table survived.

`task setup`, `task table`, `task test`, `task run`. Read `HOW_TO_RUN.md`.