

Containers & Orchestration

CSC 410/510

Richard Kelley

Last Time

- Overview of Containers
 - Container concept
 - Docker
 - Dockerfile
 - Mentioned idea of orchestration

Today

- Installing Docker on EC2
- Some web stuff
 - curl
 - reverse proxies
- Docker commands
- Assignment 2

Installing Docker on EC2

Update system and install prerequisites

```
$ sudo apt update
```

```
$ sudo apt install -y ca-certificates curl gnupg
```

Add Docker's official GPG key

```
$ sudo install -m 0755 -d /etc/apt/keyrings
```

```
$ curl -fsSL https://download.docker.com/linux/ubuntu/gpg | \
  sudo gpg --dearmor -o /etc/apt/keyrings/docker.gpg
```

```
$ sudo chmod a+r /etc/apt/keyrings/docker.gpg
```

Add the Docker apt repository

```
$ echo \  
  "deb [arch=$(dpkg --print-architecture) \  
    signed-by=/etc/apt/keyrings/docker.gpg] \  
    https://download.docker.com/linux/ubuntu \  
    $(. /etc/os-release && echo "$VERSION_CODENAME") stable" | \  
    sudo tee /etc/apt/sources.list.d/docker.list > /dev/null  
  
$ sudo apt update
```

Install Docker Engine + CLI

```
$ sudo apt install -y docker-ce docker-ce-cli containerd.io
```


Verify it works

```
$ sudo docker run hello-world
```

(Optional) Allow your user to run docker without sudo

```
$ sudo usermod -aG docker $USER
```

After this command, you have to log out and then log back in for the command to take effect!!

curl

HTTP

HTTP Request Methods

- **GET**
- PUT
- **POST**
- DELETE

HTTP GET

HTTP POST

Curl: Testing HTTP Interfaces

Curl for GET requests

```
curl -i http://localhost/api/health
```

Curl for POST requests

```
curl -i -X POST http://localhost/api/items \  
  -H "Content-Type: application/json" \  
  -d '{"name": "alpha"}'
```

Reverse Proxies

Reverse Proxy — Core Concept

- A **reverse proxy** is a server that sits **in front of one or more backend servers**
- It receives client requests on behalf of those servers
- It forwards the request to an internal server
- It returns the backend server's response to the client
- To the client, it appears as though it *is* the origin server

Forward Proxy vs Reverse Proxy (Clarification)

- **Forward proxy**

- Sits between client and internet
- Clients explicitly connect to it
- Often used for filtering, caching, anonymity

- **Reverse proxy**

- Sits between internet and servers
- Clients are unaware it exists
- Used for infrastructure control and scaling

Basic Request Flow

- Client sends HTTP request to example.com
- DNS resolves to reverse proxy IP
- Reverse proxy receives request
- Reverse proxy forwards request to backend server
- Backend responds to reverse proxy
- Reverse proxy returns response to client

Why Use a Reverse Proxy?

- **1. Load Balancing**
- Distributes traffic across multiple backend servers
- Enables horizontal scaling
- Can use:
 - Round-robin
 - Least connections
 - Weighted routing
 - Health checks

Why Use a Reverse Proxy?

- **TLS Termination**

- Reverse proxy handles HTTPS encryption/decryption
- Backend servers can communicate over plain HTTP internally
- Centralizes certificate management
- Reduces cryptographic overhead on app servers

Why Use a Reverse Proxy?

- **Security Isolation**

- Backend servers are not directly exposed to the internet
- Internal IP addresses remain hidden
- Can enforce:
 - IP allow/deny lists
 - Rate limiting
 - Web Application Firewall (WAF) rules

Why Use a Reverse Proxy?

- **Caching**
 - Frequently requested content can be cached at proxy
 - Reduces load on backend
 - Improves latency

Why Use a Reverse Proxy?

- **URL Routing / Path-Based Routing**
 - Route different paths to different services:
 - /api → API server
 - /app → Web frontend
 - /static → CDN or static server
 - Enables microservice architectures

- **Centralized Logging & Observability**


- All traffic passes through one point
- Easier to monitor:
 - Request rates
 - Errors
 - Latency
- Supports distributed tracing headers

Common Reverse Proxy Software

- Nginx
- Apache HTTP Server
- HAProxy
- Traefik
- Envoy
- Caddy

Architectural Placement

- Cloud deployment



Conceptual Summary

- Reverse proxy = **traffic controller in front of your servers**
- Hides backend servers
- Improves scalability
- Improves security
- Centralizes TLS and routing
- Essential building block in modern cloud architectures

Dockerfile Commands

FROM

- **FROM specifies the base image for the build**
 - Every Docker image starts from an existing image layer.
- Example
 - FROM python:3.12-slim

ENV

- **ENV sets environment variables inside the container image**
 - These values apply at runtime to all processes in the container.
- example
 - ENV PYTHONDONTWRITEBYTECODE=1 \ PYTHONUNBUFFERED=1
- PYTHONDONTWRITEBYTECODE=1
 - Prevents Python from creating .pyc bytecode files (keeps container filesystem cleaner).
- PYTHONUNBUFFERED=1
 - Forces stdout/stderr to flush immediately (logs appear in real time in docker logs).

RUN

- **RUN executes a command at build time**
 - Modifies the image filesystem and creates a new layer.
- example:
 - RUN useradd --create-home --shell /usr/sbin/nologin appuser
 -

WORKDIR

- **WORKDIR sets the working directory for subsequent instructions**
 - All following COPY, RUN, and CMD commands execute relative to this path.
- example:
 - WORKDIR /app
 - Creates (if necessary) and switches into /app inside the container filesystem.

COPY

- **COPY copies files from the build context into the image**
 - Source is on the host; destination is inside the container filesystem.

USER

- **USER sets the user for subsequent instructions and at container runtime**
 - The container will no longer run as root.
- example
 - USER appuser

EXPOSE

- **EXPOSE documents which port the container listens on**
 - Indicates the intended network port for the application.
- example
 - EXPOSE 8000
 - FastAPI (via uvicorn) listens on port 8000 inside the container.

Assignment 2

- https://github.com/RichardKelley-CUA/DA510_assignment_2