

Learning to Love the Lambda in the Stream

Introduction to Java 8 Lambda and Functional Interfaces

Speaker Introduction

- ▶ Richard Roda
- ▶ Sr. Technical Lead at DXC Technology
- ▶ Over 15 years of Java development experience
- ▶ OCA Java and Security+ certifications
- ▶ Linked In: <https://www.linkedin.com/in/richardroda>
- ▶ Twitter: @Richard_Roda
- ▶ These slides (pdf): <https://tinyurl.com/love-lambda>

What is a Lambda Expression?

- ▶ In Java, it is an unnamed function that may be bound to an interface as an object.
- ▶ Similar to a closure, *effectively final* arguments, local variables and class members are available to it.
- ▶ Lambdas may only exist when assigned to a Functional Interface, including being passed in as a parameter.

Lambda Examples

► Example 1a

```
Predicate<Integer> isFive = n -> n == 5;  
System.out.println(isFive.test(4)); // false
```

► Example 1b

```
Predicate<Integer> mkTestFunc(int value)  
    { return n -> n == value; }  
  
Predicate<Integer> isFour = mkTestFunc(4);  
System.out.println(isFour.test(4)); // true
```

► Lambda expressions must be assigned to a functional interface

► `(n -> 5).test();` // Does not compile

Functional Interface (FI) in Java 8

- ▶ “A functional interface is any interface that contains only one abstract method.” -- [Oracle Java Tutorial](#)
- ▶ Example 2- Valid Functional Interface

```
@FunctionalInterface // Optional
public interface Example2 {

    int myMethod() ; // Abstract.

    boolean equals(Object other); // In Object
    int hashCode(); // In Object
    default int myMethod2() {return myMethod();}
    static int myMethod3() {return 0;}
}
```

Binding Lambda to Example2 FI vs Anonymous Inner class

- ▶ Both of these implement myMethod defined in Example2.
- ▶ Since there is exactly one abstract method, method types and return values are inferred from the FI.

```
public class Example3 {  
    static public void main(String[] args) {  
        Example2 lambda = () -> 3; // 8 chars  
        Example2 innerClass = new Example2() {  
            @Override public int myMethod() {  
                return 3;  
            }  
        }; // 5 lines of code  
        System.out.println(lambda.myMethod()); // 3  
        System.out.println(innerClass.myMethod()); // 3  
    }  
}
```

Functional Interface Conventions

- ▶ The abstract method is called the *functional method*
- ▶ The following conventions apply for type variables used by Java 8 FIs:
- ▶ T - First argument
- ▶ U - Second argument
- ▶ R - Return Value
- ▶ Any of the above are omitted if not used.
- ▶ If an FI lacks an argument, T is sometimes used for the return value instead of R.

The background features abstract, overlapping green geometric shapes, primarily triangles and polygons, in various shades of green, creating a modern and dynamic visual effect.

Key Functional Interfaces

Predicate<T>

- ▶ Accepts an argument, returns a `boolean`.
- ▶ Commonly used to select matching elements, or filter for matching elements.
- ▶ Functional method: `boolean test (T t)`
- ▶ 2 argument FI: `BiPredicate<T,U>`
- ▶ Related Primitive FIs: `DoublePredicate`, `IntPredicate`, `LongPredicate`

Consumer<T>

- ▶ Accepts an argument. Returns no value (void).
- ▶ Commonly used to perform an operation, such as printing.
- ▶ Functional Method: `void accept (T t)`
- ▶ 2 Argument FI: `BiConsumer<T,U>`
- ▶ Related Primitive FIs: `DoubleConsumer`, `IntConsumer`, and `Long Consumer`

Supplier<R>

- ▶ Accepts no arguments, returns a result
- ▶ Commonly used to provide an origin value to an algorithm. Also a good interface to use for the Factory Object pattern.
- ▶ Functional Method: `R get()`
- ▶ Related Primitive FIs: `DoubleSupplier`, `IntSupplier`, `LongSupplier`

Function<T,R>

- ▶ Accepts an argument, returns a result.
- ▶ Commonly used to compute a result, or to map one value to another value.
- ▶ Functional Method:
- ▶ 2 Argument FI: BiFunction
- ▶ Related Primitive FIs: [Double,Int,Long]Function, [Double,Int,Long]To[Double,Int,Long]Function, To[Double,Int,Long]Function, To[Double,Int,Long]BiFunction

UnaryOperator<T>

- ▶ Accepts an argument, returns the same type of result as its argument.
- ▶ Used to compute a result or map a value to the same type as the input.
- ▶ Functional Method
- ▶ 2 Argument FI: BinaryOperator<T>
- ▶ Related Primitive FIs: [Double,Int,Long]UnaryOperator, [Double,Int,Long]BinaryOperator
- ▶ UnaryOperator<T> extends Function<T,T> and BinaryOperator<T> extends BiFunction<T,T,T>

Streams

- ▶ Abstraction for computation of elements. Is not a data structure, but rather a computation structure.
- ▶ A stream consists of
 1. A data source, such as a collection, file, or computation. May be infinite, such as the set of numbers starting at 0. A data source is *lazy*.
 2. Zero or more intermediate operations.
 - ▶ Accepts a stream and returns a new stream with the operation appended to it
 - ▶ *Lazy*: Only executed when a terminal operation processed the stream.
 3. A terminal operation
 - ▶ Returns a result, such as a number or a collection.
 - ▶ *Eager*: Applying a terminal operation to a stream begins the process of pulling data from the data source, and applying the intermediate operations.
- ▶ Example:

```
System.out.print(IntStream.iterate(0, i -> i+1)
    .limit(12).sum()); // 66
```