

It comes back on Tailscale and Commander reaches it.

SURFACE

CLOSED

Only reply: no listed issues 0

The closure map is empty until release evidence names verified issues.

One dot, one closed issue. 0 issue-bearing surfaces.

Read the map data ↓

Release at a glance

01 / 06

0

Issues closed

Named, verified closed issues in this report

0

Features added

Top-level Added entries in the CHANGELOG section

0

Changed entries

Top-level Changed entries in the CHANGELOG section

1

Fix entries

Top-level Fixed entries in the CHANGELOG section

34m 27s

Green to published

gate.green.epoch to the published receipt, when available

▼ Change map · data and reading guide

One filled dot represents one closed issue. Dots have equal weight: this is a count of closures, not a measured impact score.

Change map data · closed issues by surface

SURFACE	ISSUES CLOSED	ISSUE NUMBERS
Only reply:	0	No listed issues
Total	0	0 issue-bearing themes

Source: CHANGELOG /Users/pippenz/Petrastella/cas-src/.cas/release-3.29.1/CHANGELOG.md, release-notes /Users/pippenz/Petrastella/cas-src/.cas/release-3.29.1/docs/release-notes/2026-09-24-v3.29.1-slack.md; retrieved 2026-09-24T16:05:04Z.

What you can do now

02 / 06

Only reply (user)

Mac hub on Tailscale

WAS after `cas` update, a Mac hub could come back without its Tailscale address, and Commander showed the host as unreachable. →

NOW the hub republishes its Tailscale address every time, whether Tailscale came from Homebrew or the Mac app.

Hub service repair

WAS an older Mac hub service kept settings that hid the Tailscale command. →

NOW every restart repairs those settings, with no manual fix needed.

Under the hood

03 / 06

Only reply (dev)

Tailscale CLI mode

WAS detached and launchd hubs ran with `PATH=/usr/bin:/bin:/usr/sbin:/sbin` and no `TERM`, so they fell back to `/Applications/Tailscale.app/Contents/MacOS/Tailscale`. That binary chooses GUI mode without `TERM`, so `status --json` returned "The Tailscale GUI failed to start" and every restart stayed loopback-only. →

NOW every Tailscale child command sets `TERM=dumb` when `TERM` is unset (PR #1003).

CLI selection

WAS the app bundle was the only macOS fallback. →

NOW `/opt/homebrew/bin/tailscale` and `/usr/local/bin/tailscale` are tried before the app bundle, and an explicit `TAILSCALE` override survives the detached launcher's environment scrub (PR #1003).

launchd env

WAS `EnvironmentVariables` were only written at install. →

NOW `install` and `restart_supervised` always rewrite `PATH` (with Homebrew dirs) and `TERM`, so existing plists are repaired (PR #1003).

Proof

WAS n/a. →

NOW an isolated launchd test with the app-bundle CLI forced under a sparse `PATH` published and verified public HTTPS across restarts and updates. The real v3.27.8, v3.28.1 and v3.28.2 update matrix passes (PR #1003).

Issue register · 0 verified closures

ISSUE	STATE	CLOSED	THEME
-------	-------	--------	-------

Install



```
cas update # install v3.29.1 through the project's normal release channel
```

Change map data · closed issues by surface

ASSET	DIGEST	SIZE
No published assets	unavailable	unavailable

Evidence and scope

Retrieved: 2026-09-24T16:05:04Z.

Source: CHANGELOG /Users/pippenz/Petrastella/cas-src/.cas/release-3.29.1/CHANGELOG.md, release-notes /Users/pippenz/Petrastella/cas-src/.cas/release-3.29.1/docs/release-notes/2026-09-24-v3.29.1-slack.md; retrieved 2026-09-24T16:05:04Z.

GitHub issue theme assignment uses labels first, then the keyword table in the CLI. Any issue classified as Unclassified is shown in the map so a human can correct the Markdown before rendering.

Release-notes draft: docs/release-notes/2026-09-24-v3.29.1-slack.md.

CHANGELOG source: CHANGELOG.md.

GitHub release: unavailable.

Release receipt: /Users/pippenz/.cas/artifacts/release/v3.29.1-release-3.29.1/release-published.receipt.

Source warnings:

- GitHub sources: issues.repo is unset; remedy cas config set issues.repo owner/name