PUBLISHED 14 OCTOBER 2026 · 07:10 UTC

Cassy shows who is working on your project and helps you avoid taking the same task.

SURFACE		CLOSED
Working across machines	no listed issues	0
Release	no listed issues	0
Smaller fixes	no listed issues	0
Repository peers and task ownership		1
Factory	no listed issues	0
Delivery and smaller fixes		1

Delivery and smaller fixes leads the closure map with 1 issue.

One dot, one closed issue. 2 issue-bearing surfaces.

Read the map data ↓

Release at a glance

01 / 06

2
Issues closed
Named, verified closed issues in this report

0
Features added
Top-level Added entries in the CHANGELOG section

0
Changed entries
Top-level Changed entries in the CHANGELOG section

0
Fix entries
Top-level Fixed entries in the CHANGELOG section

44m 44s
Green to published
gate.green.epoch to the published receipt, when available

3m 33s — within budget (10m 0s budget)
Tag to published
First tag workflow to publication; measured budget result

3
Manual interventions
Distinct rescued stages plus recorded hand fixes; receipt INTERVENTIONS

▼ Change map · data and reading guide

One filled dot represents one closed issue. Dots have equal weight: this is a count of closures, not a measured impact score.

Change map data · closed issues by surface

SURFACE	ISSUES CLOSED	ISSUE NUMBERS
Working across machines	0	No listed issues
Release	0	No listed issues
Smaller fixes	0	No listed issues
Repository peers and task ownership	1	#155
Factory	0	No listed issues
Delivery and smaller fixes	1	#1186
Total	2	2 issue-bearing themes

Source: CHANGELOG `/mnt/rewind/cas/scratch/release-3.51.0/CHANGELOG.md`, release-notes `/mnt/rewind/cas/scratch/release-3.51.0/docs/release-notes/2026-10-14-v3.51.0-slack.md`, GitHub `Richards-LLC/cassy` release v3.51.0; retrieved 2026-10-14T07:11:28Z.

What you can do now

02 / 06

Working across machines

See the other work

WAS another copy of your project was out of sight. →

NOW Cassy shows the other sessions, their machines, current work and recent activity, including a closer view of tasks and branches.

Current, visible connections

WAS a failed connection could stay broken and the work shown could stay out of date. →

NOW Cassy retries, refreshes the view and tells you when it cannot connect. Turning off cloud sharing keeps your session details on your machine.

Messages reach the other machine

WAS a message could stay on your machine instead of reaching its destination. →

NOW it goes through Cassy Cloud, with replies and delivery status you can check.

Clear send results

WAS a message could promise later delivery to a name that did not exist. →

NOW unknown names and destinations that cannot receive fail at once, connection errors explain the cause, and acceptance by the other mailbox is distinguished from confirmed delivery.

Avoid taking the same task

WAS two machines could start the same task. →

NOW a task held elsewhere on your account is refused before more work starts, with the holder and expiry shown. An explicit takeover is identified.

Agree on a division of work

WAS dividing a larger job depended on remembering who took each part. →

NOW both sides can agree on their shares, and Cassy refuses starts on the other side's parts until the agreement ends.

Know the account limit

WAS an empty task list could look like no work was taken. →

NOW Cassy says when another account's claims are hidden. Automatic claim protection is per account today. Across accounts, agree by message and record the division of work.

Receive after logging in

WAS starting Cassy before login could leave incoming messages stuck until a restart. →

NOW receiving starts after login without restarting, and the status view says whether messages are being received or why they are not.

Retries without extra copies

WAS retrying a send could deliver the same message twice. →

NOW a temporary failure is reported and kept for automatic retry for up to 15 minutes, with one delivery per send. Sending the same words again still counts as a new message.

One useful cleanup notice

WAS a message that never arrived could disappear without warning. →

NOW the sender gets its ID and reason, with one combined notice when several messages are cleared together.

Smaller fixes

Readable terminal output

WAS connection details could run past the terminal edge and section rules could render badly in a basic text locale. →

NOW lines fit or wrap, and the rules use plain ASCII where needed.

Safety settings stay yours

WAS settings that relax safety checks could be changed from a working session. →

NOW those changes require you at a terminal, and protected connections cannot be removed or replaced from a working session.

Under the hood

Repository peers and task ownership

Project-scoped discovery

WAS sessions had no view of repository peers. →

NOW discovery uses `?project=<canonical_id>`, excludes locally registered sessions, honours stale status and lists machine, focus and heartbeat age.

Presence recovery

WAS initial failure stayed failed and focus froze at startup. →

NOW presence retries with bounded backoff, re-registers after 401/404, and heartbeats refresh project, focus, branch and hostname. Status opens with the local presence state. `cloud.auto_sync=false` disables publishing session details while discovery remains one-way.

Cloud mailbox routing

WAS remote messages could remain in the local queue. →

NOW name or name@machine routes through the peer mailbox, `in_reply_to` replies to the sender and `message_status` reads delivery. Peer messages carry no operator authority and cannot be urgent.

Honest send failures

WAS unknown targets could return a misleading pending receipt. →

NOW only pending local starts qualify for that fallback, unknown names and peers without a receiving mailbox fail immediately, and cloud refusals preserve the recipient and cause. Status 404 says the message is not visible to this account or does not exist.

Task claims

WAS local leases allowed duplicate starts across machines. →

NOW starts and claims acquire a repository-scoped cloud claim, renew it while held and release it on terminal or ownership transitions. A conflict preserves the holder and reports expiry. Cloud outages explicitly fall back to the local lease with peers unchecked.

Refuse before starting more work

WAS a peer-held assignment could queue new work before warning. →

NOW the peer check refuses it before queueing unless forced. Clearing or moving focus releases its claim, and losing a claim reports the loss instead of silently continuing.

Detailed peer view

WAS only startup focus was visible. →

NOW `cas peers --detail` and `--peer` show claims, live work and branches in bounded-width groups. JSON preserves structured details, split state and separate mailbox health.

Per-account claim boundary

WAS hidden claims could look like an idle peer. →

NOW a different account is labelled as having claims not visible. Claims are still per account, while discovery and messaging span team members. Team-wide claims remain open in petra-stella-cloud#155: https://github.com/Richards-LLC/petra-stella-cloud/issues/155

Explicit task partitions

WAS no durable agreement divided a larger task's children. →

NOW `epic_split` proposes shares, claims only the caller's share and accepts, rejects, cancels or expires the agreement. Local start and spawn checks enforce the other side's share even offline. Cancellation releases only the caller's claims.

Delivery and smaller fixes

Inbound recovery and health

WAS startup before login disabled receiving until restart and receive errors went quiet. →

NOW receiving recovers after login, retries failures with backoff and exposes receiving or the current cause in peers and both status views.

Durable logical sends

WAS retry identity could change and duplicate delivery. →

NOW each persisted send has one stable key, automatic retries with leases and backoff, a 15-minute TTL, and pending/retrying/sent/abandoned status. Identical deliberate sends get separate rows. Missing-token and 401 failures are not queued for retry.

Abandonment notices

WAS expired delivery could disappear silently or generate a burst of notices during cleanup. →

NOW abandonment notifies the sender atomically, and bulk sweeps aggregate per sender. A notice survives a removed sender through a fallback destination. GH #1186.

Terminal fit

WAS presence lines exceeded 80 columns and `cas status --verbose` always used Unicode rules. →

NOW peer rows wrap, details fit 72 columns, and `LC_ALL=C` uses ASCII rules.

Restart regression fixture

WAS force restart raced the test's recordless/stopping precondition. →

NOW SIGTERM and the existing barrier establish that state before force restart, preserving the assertions. Thirty consecutive loaded runs passed. Test-only, with no runtime behavior change.

Operator-only safety controls

WAS guard-relaxing config and protected MCP connections could be changed from a working session. →

NOW config changes require a terminal operator, hooks refuse direct config edits and guarded shell commands, and CLI/MCP protect restricted connections. Ordinary settings and project write roots retain their existing rules.

Fixes ledger

04 / 06

Issue register · 2 verified closures

ISSUE	STATE	CLOSED	THEME
#1186 (https://github.com/Richards-LLC/cassy/issues/1186)	CLOSED	2026-10-14T05:00:14Z	Factory
#155 (https://github.com/Richards-LLC/cassy/issues/155)	CLOSED	2026-08-07T20:49:07Z	Factory

Install

05 / 06

```
cas update  # install v3.51.0 through the proje
ct's normal release channel
```

Change map data · closed issues by surface

ASSET	DIGEST	SIZE
cas-aarch64-apple-darwin.tar.gz	sha256:b340b56ed70519737ec2a3df96dd338275a8d48e096264ea99fdb0cb1c51968f	31519114
cas-x86_64-unknown-linux-gnu.tar.gz	sha256:02ff253b3c115b2c46407b0ed57864e75af8d44ebb6de1b339a21e8b1c7572e3	36663483

Evidence and scope

06 / 06

Retrieved: 2026-10-14T07:11:28Z.

Source: CHANGELOG `/mnt/rewind/cas/scratch/release-3.51.0/CHANGELOG.md`, release-notes `/mnt/rewind/cas/scratch/release-3.51.0/docs/release-notes/2026-10-14-v3.51.0-slack.md`, GitHub `Richards-LLC/cassy` release v3.51.0; retrieved 2026-10-14T07:11:28Z.

GitHub issue theme assignment uses labels first, then the keyword table in the CLI. Any issue classified as `Unclassified` is shown in the map so a human can correct the Markdown before rendering.

Release-notes draft: `docs/release-notes/2026-10-14-v3.51.0-slack.md`.

CHANGELOG source: `CHANGELOG.md`.

GitHub release: <https://github.com/Richards-LLC/cassy/releases/tag/v3.51.0> (published or unknown).

Release receipt: `/home/pippenz/.cas/artifacts/release/v3.51.0-release-3.51.0/release-published.receipt`.

No source warnings.