cas-src v3.71.0

RELEASE REPORT · PUBLISHED 21 OCTOBER 2026 · 7:40 PM CT

Checks follow your changes and recovery is clearer.

AREA	CHANGES
Commander	1
Tasks	6
Releases	4
Slack and Cloud	1
Other	3

15 changes shipped across 5 areas; Tasks has the most, 6.

One dot, one shipped change. No GitHub issues are counted in this report's fixes ledger.

See every change ↓

01 / 06

Release at a glance

▼ What shipped, by area

One dot is one change listed in the v3.71.0 CHANGELOG. Dots count changes, not their size or importance.

AREA	CHANGES	WHAT CHANGED
Commander	1	Hub commands and services explain their outcomes
Tasks	6	QA checks describe what good looks like; QA warnings and evidence stay trustworthy; Inspect documentation drift before enforcing it; Documentation follows the active checkout; Work resumes and hands over without losing its history; Portable verifier artifacts
Releases	4	Concurrent changes publish safely; Disk space recovers before builds are refused; Release tooling uses verified inputs; Project maps and published records
Slack and Cloud	1	Split-state reconciliation
Other	3	Configuration edits preserve the surrounding file; Account checks keep their real cause; Codex command workdir
Total	15	5 areas

Source: CHANGELOG `CHANGELOG.md`, release-notes draft `docs/release-notes/2026-10-21-v3.71.0-slack.md`, GitHub `Richards-LLC/cassy` release v3.71.0; retrieved 21 October 2026 · 7:52 PM CT.

15

Changes shipped

2 added, 9 fixed, 4 internal; tests and docs not counted

6m 31s

Green to published

Within budget (10m 0s budget); merge-queue CI completion to publication

about 2h 20m

Release commit queued to main

Approximate event timeline; target ≤30m (over by about 1h 50m)

6m 23s

Main to published

Main merge to publication; target ≤20m

Changes and GitHub issues are counted separately. A change is one titled entry in the v3.71.0 CHANGELOG section; tests and documentation entries are listed under the hood but not counted. A GitHub issue counts when PR #1329 or the CHANGELOG references it and it closed between PR opening (5:13 PM CT) and 15 minutes after merge (7:49 PM CT). No issues closed in that window. The commit-to-main value is approximate: it uses the supplied queue-entry and merge event times, not a stage measurement in the latency receipt. The receipt records no blocked stages and zero manual interventions. Request-to-published, cut-to-published and lesson recurrence were not measured.

Release timeline

All times are Central Time on 21 October 2026. Queue event times are approximate; merge and publication times come from GitHub.

MILESTONE	TIME	DETAIL
Release commit queued	about 5:14 PM	Start of the release queue interval
First queue ejection	about 5:30 PM	14 Rust tests failed; repairs A–D followed
Second queue ejection	about 6:49 PM	A pre-existing hub setup race was fixed before retry
Merged to main	7:34:29 PM	PR #1329 landed on main
Published	7:40:52 PM	Both release assets were available

Commit queued to main took about 2h 20m against a 30m target. Main to publication took 6m 23s against a 20m target. Merge-queue green to publication took 391s (6m 31s), within its 600s budget.

02 / 06

What you can do now

QA checks describe what good looks like

Focused re-checks

WAS

a shared change could miss a part of the product that needed checking.

NOW

checks follow the affected journeys, including changes shared by several journeys.

Checks with an owner

WAS

a check that had not been written could stay on the list without a deadline.

NOW

unfinished checks name an owner and due date, and overdue checks are flagged.

Clear examples

WAS
different people could judge the same example differently.

NOW
checks can define their meaning and require a label on each example, with missing labels shown as gaps.

Measurable limits

WAS
a numeric check could not say how much change was acceptable.

NOW
check definitions can state an exact result or an acceptable change from an earlier measurement.

QA warnings and evidence stay trustworthy

Visible check gaps

WAS
unfinished checks were hard to distinguish or compare over time.

NOW
status names the kinds of gaps and shows how counts changed since the previous check.

Reliable safeguards

WAS
a change could accidentally weaken the checks meant to review it.

NOW
existing safeguards remain in force and a failed check calculation cannot silently remove a known problem.

Readable check errors

WAS
one malformed comparison could hide the rest of the check list.

NOW
the bad entry is named while the remaining checks stay readable.

Complete comparisons

WAS
a before-and-after review could lose its before image or demand a comparison that was never requested.

NOW
requested comparisons retain their before images, and optional comparisons stay optional.

Readable reports

WAS
a report label could appear apart from its heading.

NOW
each label stays with the heading it describes.

Inspect documentation drift before enforcing it

Warnings before enforcement

WAS
outdated project guidance could become a surprise when stricter checks were switched on.

NOW
status shows what is out of date, and switching on enforcement warns about known gaps first.

Documentation follows the active checkout

The right project guidance

WAS
freshness warnings could refer to another checkout or to queued work.

NOW
warnings describe the work currently open and explain how to bring it up to date.

Overview coverage

WAS
the product overview could quietly stop tracking the folders that mattered.

NOW
its watched folders are declared and a missing coverage scope produces a warning.

Work resumes and hands over without losing its history

Resume your work

WAS
returning from review could reject changes that already belonged to the work in progress.

NOW
the existing work is recognized across review pauses and updates, while unrelated edits remain protected.

Keep work recognizable

WAS
bringing two sets of edits together could make your own change look unrelated.

NOW
Cassy still recognizes your change after you resolve the conflict, so handover can continue.

Stable change receipts

WAS
later updates could change what an earlier handover receipt appeared to cover.

NOW
each receipt stays tied to the change it originally recorded.

Current check results

WAS
an old success notice could appear to approve a newer change.

NOW
check notices are revalidated against the exact change they describe.

Trustworthy proof

WAS
a partial note could be mistaken for proof of a different change.

NOW
proof keeps its full origin and must match the complete recorded note.

Safe settings changes

WAS
changing settings from an internal data folder could alter machine settings, and reset saved a fixed default.

NOW
settings edits there report that no project is initialized. Reset removes the saved setting so the normal default applies.

Review repairs first

WAS
an automatic repair could be recorded before you reviewed it.

NOW
on shared branches, the repair is left for you to review before it is recorded.

Hub commands and services explain their outcomes

Clear restart results

WAS
a restart could give conflicting machine-readable results or lose the successful stop step when starting failed.

NOW
one result records what stopped and what failed to start.

A useful connection remedy

WAS
a connection refusal could leave you without a usable next step.

NOW
the cause and the supported retry choices appear together.

Readable service status

WAS
service status could wrap badly and leave the repair step unclear.

NOW
compact status rows put a repair command beneath the result and explain failed readiness checks.

Configuration edits preserve the surrounding file

Small settings edits

WAS
changing one setting could rewrite unrelated settings and formatting.

NOW
only the named setting changes, including supported aliases and inline tables.

Concurrent changes publish safely

Concurrent updates

WAS

two simultaneous updates could leave one change saved only locally while a retry claimed it was complete.

NOW

publication checks the remote result and safely retries a competing update once.

Useful launch errors

WAS

startup errors could lose their cause or point at a log that did not exist.

NOW

errors retain the cause and point at the actual diagnostic log.

Disk space recovers before builds are refused

Disk space recovery

WAS

old build files could fill the disk and stop new work until someone cleaned up.

NOW

unused managed build files are reclaimed automatically, while active files, recent caches and unrelated folders stay protected.

Account checks keep their real cause

Accurate sign-in diagnosis

WAS

a locked Mac keychain during an SSH session could look like a signed-out account.

NOW

the message identifies the keychain problem and explains how to unlock it locally.

Honest sign-in status

WAS

a broken cache could hide whether you were signed in.

NOW

the real sign-in check still runs and its result stays visible.

Release tooling uses verified inputs

Fewer interrupted releases

WAS

a brief failure to find a prepared release download could stop the release.

NOW

the lookup retries within its time limit and retains a useful failure cause if it still fails.

Under the hood

QA checks describe what good looks like

Selected journeys

WAS

QA could depend on a legacy catalog or miss a shared pipeline change.

NOW

Commander uses its tracked journey registry and semantic path selection, including shared-pipeline fan-out, while preserving catalog parity.

Pending checkers

WAS

an unwritten automated check had no accountable owner or deadline.

NOW

criteria can name a pending checker with an owner and due date. Overdue checkers fail validation, and manual checks distinguish human judgment from automation still to be written.

Labeled criteria

WAS

example fixtures had no shared labels for judging a criterion.

NOW

criteria can declare a definition and require per-fixture labels. Missing labels become debt and unknown or contradictory labels are rejected.

Numeric comparisons

WAS

numeric criteria could not declare exact equality or an allowed change from a baseline.

NOW

criteria accept exact or banded comparisons with a minimum ratio or maximum delta. Invalid bands and misspelled or contradictory criterion fields are diagnosed.

QA warnings and evidence stay trustworthy

Debt and history

WAS

QA status hid types of unfinished checks and had no previous count for comparison.

NOW

status separates curation, manual-check, pending-checker and unlabeled-fixture debt, retaining previous check counts to show the change.

Enforcement cannot weaken itself

WAS

a delivery could relax its own upkeep policy, or impact errors could erase an established refusal.

NOW

the stricter base or delivered policy remains authoritative, proven registry findings survive impact failures, and malformed base policy sets a conservative floor without upgrading a warning-only delivered policy.

Malformed comparisons

WAS

one malformed numeric comparison could make the whole journey registry unreadable.

NOW

validation reports the bad comparison as one actionable registry problem so the remaining entries can still be inspected.

Before-and-after evidence

WAS

declared visual comparisons could drop before-capture cells, while optional pair rules could apply even when no comparison was declared.

NOW

declared before cells must survive comparison planning, optional coverage is enforced only when declared, shared pairs and diagnostic findings are preserved, and recorded waivers can recover.

Report section labels

WAS

release-report labels could separate from their headings.

NOW

labels stay with their section headings in report layouts.

Inspect documentation drift before enforcing it

Upkeep status and warnings

WAS

turning on enforcement could reveal documentation drift only after it started blocking work.

NOW

`cas qa journeys --status` reports registry, CODEMAP and overview drift against a pinned integration commit. A real transition to enforcement warns about known positive drift after saving the setting, while zero and unknown remain distinct.

Documentation follows the active checkout

Current documentation reference

WAS

freshness checks could inspect the main checkout, a queued assignment or the wrong integration branch.

NOW

checks use the current checkout and active task target, preserve existing ledger stores, show the measured reference and update time, and name the target-sync command when a stale checkout blocks editing.

Overview watch paths

WAS

overview upkeep could fall back to nonexistent default directories and watch nothing silently.

NOW

watch paths come from tracked overview declarations or configured existing paths, with an explicit warning when no product scope can be determined.

Work resumes and hands over without losing its history

Resume after review

WAS

resuming a review hold could reject the same task's own accepted commits.

NOW

owned delivery commits remain attributable across review holds, anchored target merges and dirty edits. A fresh task still refuses unrelated uncommitted work.

Rebased delivery ownership

WAS

rebasing after a conflict could make a valid delivery look unrelated or let a foreign subject pass through a body reference.

NOW

fresh parking binds to the task-owned rebased delivery and checks the commit subject independently of references in its body.

Squash receipt range

WAS

later documentation merges could distort the change range proved by a squash receipt.

NOW

a first-parent squash receipt is measured against its own parent instead of a later target position.

Released CI evidence

WAS

a queued success notice could outlive the exact delivery it had checked.

NOW

release revalidates the immutable delivery and current CI evidence, marks superseded signals explicitly, and preserves relabeled prompts through native and batch handoff.

Proof provenance

WAS

trusted notes could be partially matched, truncated or reused outside their original provenance block.

NOW

whole provenance blocks are preserved and trusted notes match exactly from the start of a complete note.

Store discovery and config reset

WAS

discovery inside a `.cas` folder could adopt its enclosing store, and reset saved a default override.

NOW

discovery stops at `.cas`, so `cas config set` there reports not initialized. `cas config reset <key>` removes the stored key instead of writing a default.

Staged managed repairs

WAS

reconciling managed files could create an unexpected commit on an integration branch.

NOW

integration-branch repairs remain staged for review, using the full HEAD reference to classify the branch.

Hub commands and services explain their outcomes

Restart JSON receipt

WAS

`cas hub restart --json` could emit more than one value or lose the completed stop step when starting failed.

NOW

restart emits one JSON receipt, preserves stop evidence across start failures and raced stops, and fits its help text to terminal width.

Transport refusal remedy

WAS

required-transport errors could omit the explicit loopback remedy or obscure the connection cause.

NOW

the refusal names the cause and the supported loopback or socket-selection retry.

Service readiness

WAS

service status could wrap badly or omit a repair action, probe failure cause or manual reboot remedy.

NOW

readiness rows and custom profile labels fit narrow terminals, the repair command sits beneath the verdict, and failed probes retain their causes and recovery guidance.

Configuration edits preserve the surrounding file

In-place config changes

WAS

`cas config set` could rewrite the whole TOML document, reorder tables and materialize defaults.

NOW

only the named value is edited in place, including supported aliases, dotted keys and inline tables, while unrelated formatting and values stay intact.

Concurrent changes publish safely

Concurrent merge publication

WAS

a peer advancing origin between fetch and push could leave a local-only merge and a retry could falsely say already contained.

NOW

per-target locking covers merge paths, containment uses a fresh explicit origin ref, and an ordinary non-fast-forward push gets one fetch/merge/non-force retry without widening transactional review pins.

Safe spawn references

WAS

a divergent or unverifiable spawn base could be accepted or a refusal could name the wrong checkout.

NOW

configured origin evidence is verified, unsafe divergence is refused, and diagnostics name the unpublished branch and actual checkout.

Launch diagnostics

WAS

preflight causes and runtime-log locations could be lost, or speculative log paths could appear before a launch decision.

NOW

refusals retain their causes and actual log pointers, announce logs only after the decision, and keep pre-initialization logs in the host directory.

Disk space recovers before builds are refused

Managed scratch cleanup

WAS

relocated build targets were omitted from cache cleanup and a full disk required manual intervention.

NOW

GC inventories verified scratch targets on the admission filesystem, preserves live and warm targets, and admission attempts guarded cleanup once before remeasuring free space. Safe shutdown and replacement retire their target after preserving proof.

Account checks keep their real cause

SSH keychain diagnostics

WAS

a locked macOS login keychain over SSH could look like a signed-out Claude account.

NOW

checks identify the unavailable keychain and provide a local unlock remedy. Repeated account probes reuse bounded evidence without refreshing its age.

Optional auth cache failure

WAS

a broken optional cache could hide the account's actual login state.

NOW

cache failures fall back to the real authentication probe and preserve its evidence, including a genuine logout.

Release tooling uses verified inputs

Exact-revision QA candidate

WAS

building a QA binary required hand-written scratch commands and could miss Zig, use an unverified revision or grow a shared target without bound.

NOW

`cas qa candidate build --task <id> --rev <full-sha>` resolves the release environment, checks binary version and revision, publishes the canonical manifest, and removes its private bounded target after artifact publication.

Prebuild lookup retries

WAS

a transient artifact lookup failure could abort an otherwise valid release wait.

NOW

prebuild lookups retry within the wait bound and preserve a sanitized failure cause if the lookup still cannot complete.

Release help width

WAS

release-report help could run beyond a normal terminal width.

NOW

report help wraps to the terminal width without dropping the latency options.

Internal

Codex command workdir

WAS

command admission could interpret a Codex exec call in the wrong directory or lose the source of a redirected write.

NOW

the native hook reads the explicit workdir, retains each write's source and preserves safe relative-log admission while explaining refused omitted-workdir redirects.

Split-state reconciliation

WAS

old shipped split bindings or repair/cleanup passes could strand or overwrite surviving child bindings.

NOW

stale shipped splits stop binding children and cloud repair/cleanup preserve the surviving split state.

Portable verifier artifacts

WAS

verifier permissions differed across supported instruction flavors.

NOW

all shipped verifier flavors can fetch the task artifacts needed to inspect portable proof.

Project maps and published records

WAS

the carried-forward project map, overview and release artifacts did not reflect the assembled changes.

NOW

the structural map and product overview are refreshed, the previous release report and publication receipts are retained, and shared builtin reference history stays synchronized.

04 / 06

Fixes ledger

GitHub issues closed with this release · 0

ISSUE	TITLE	CLOSED	AREA

No GitHub issues are counted in this report's fixes ledger.

05 / 06

Install



```
cas update --yes --version 3.71.0
```

PUBLISHED ASSET	SHA-256
cas-aarch64-apple-darwin.tar.gz · 34,326,734 bytes	`1a087716384357be92571acc88a80e231485facd491b1522ecd77b1cbc078a4b`
cas-x86_64-unknown-linux-gnu.tar.gz · 38,743,732 bytes	`e74336799f5e4882a479c3f14b2503f16774940ca1baaacc0019d7ce719fc81b`

- Linux x86_64 SHA-256: `e74336799f5e4882a479c3f14b2503f16774940ca1baaacc0019d7ce719fc81b`
- macOS ARM64 SHA-256: `1a087716384357be92571acc88a80e231485facd491b1522ecd77b1cbc078a4b`

Evidence and scope

Retrieved: 21 October 2026 · 7:52 PM CT.

Source: CHANGELOG `CHANGELOG.md`, release-notes draft `docs/release-notes/2026-10-21-v3.71.0-slack.md`, GitHub `Richards-LLC/cassy` release v3.71.0; retrieved 21 October 2026 · 7:52 PM CT.

Each change is placed in a product area by the words in its title, then its text; a change that matches no area is listed under Other. Correct an area in the Change map table before rendering.

Release PR: https://github.com/Richards-LLC/cassy/pull/1329 (https://github.com/Richards-LLC/cassy/pull/1329) (merged 21 October 2026 · 7:34 PM CT).

Release-notes draft: `docs/release-notes/2026-10-21-v3.71.0-slack.md`.

CHANGELOG source: `CHANGELOG.md`.

GitHub release: https://github.com/Richards-LLC/cassy/releases/tag/v3.71.0 (https://github.com/Richards-LLC/cassy/releases/tag/v3.71.0) (published 21 October 2026 · 7:40:52 PM CT).

Release latency receipt: `docs/release-reports/v3.71.0-latency.receipt`.

Publication and install evidence

The release workflow https://github.com/Richards-LLC/cassy/actions/runs/39700510040 (https://github.com/Richards-LLC/cassy/actions/runs/39700510040) completed successfully: Linux and macOS assets passed their package checks and the release was created at 7:40:52 PM CT. The hosted install-path proof https://github.com/Richards-LLC/cassy/actions/runs/39701135235 (https://github.com/Richards-LLC/cassy/actions/runs/39701135235) passed on a clean Linux container and macOS Apple Silicon. Both transcripts are retained with the task proof. Hosted checks do not cover a consumer Mac's manual Gatekeeper and SIP checklist.

No source warnings.
