SPECIFICATIONS BRAKE (FRONT) TORQUE SPECIFICATIONS

Front Brake

Part Tightened	N*m	kgf*cm	ft.*lbf
Bleeder plug	10.75	110	8
Front flexible hose x Disc brake cylinder assembly	30.4	310	22
Disc brake cylinder assembly x Knuckle	123	1254	91
Front disc x Front axle hub	95	969	70

Front Brake Flexible Hose (w/ ABS)

Part Tightened		N*m	kgf*cm	ft.*lbf
Flexible hose x Brake brake cylinder assembly		30.4	310	22
Front flexible hose LH x Brake tube	without union nut wrench	15.2	155	11
	with union nut wrench	13.4	137	10
Front flexible hose x Brake tube	without union nut wrench	15.2	155	11
	with union nut wrench	13.4	137	10

Front Brake Flexible Hose (w/o ABS)

Part Tightened		N*m	kgf*cm	ft.*lbf
Flexible hose x Brake brake cylinder assembly		30.4	310	22
Front flexible hose LH x Brake tube	without union nut wrench	15.2	155	11
	with union nut wrench	13.4	137	10
Front flexible hose x Brake tube	without union nut wrench	15.2	155	11
	with union nut wrench	13.4	137	10
Front flexible hose x 3-way		23	235	17

^{© 2012} TOYOTA MOTOR CORPORATION. All Rights Reserved.