Exit

SPECIFICATIONS BRAKE (REAR) TORQUE SPECIFICATIONS

Rear Brake (for Rear Disc Brake)

Part Tightened	N*m	kgf*cm	ft.*lbf	in.*lbf
Dust boot protector x Rear disc brake cylinder assembly	7.85	80		69
Rear disc brake cylinder assembly x Rear disc brake cylinder mounting	88.3	900	65	
Rear disc brake bleeder plug	10.75	110	8	
Rear flexible hose x Rear disc brake cylinder assembly	30	306	22	
Rear disc brake mounting x Carrier	103	1050	76	

Rear Brake (for Rear Drum Brake)

Part Tightened		N*m	kgf*cm	ft.*lbf	in.*lbf
Rear brake drum bleeder plug		11	112	8	
Rear wheel brake cylinder assembly x Brake tube	without union nut wrench	15.2	155	11	
	with union nut wrench	13.4	137	10	
Rear wheel brake cylinder assembly		9.5	97		84
Parking brake bell crank x Rear brake backing plate		12.5	127	9	
Adjust bolt lock nut		5.0	51		44
Rear brake drum x Rear axle hub		12.74	130	9	

Rear Disc Brake Pad

Part Tightened	N*m	kgf*cm	ft.*lbf
Rear disc brake cylinder assembly x Rear disc brake cylinder mounting	88.3	900	65
Dust boot protector x Rear disc brake cylinder assembly	7.85	80	6

Rear Brake Flexible Hose (for Rear Disc Brake)

Part Tightened		N*m	kgf*cm	ft.*lbf
Rear flexible hose LH x Rear disc brake cylinder assembly		30	306	22
Rear flexible hose LH x Brake tube	without union nut wrench	15.2	155	11
	with union nut wrench	13.4	137	10
Rear flexible hose x 3-way		23	235	17
Rear flexible hose x Brake tube	without union nut wrench	15.2	155	11
	with union nut wrench	13.4	137	10

Rear Brake Flexible Hose (for Rear Drum Brake)

Part Tightened		N*m	kgf*cm	ft.*lbf
Rear flexible hose LH x 3-way		23	235	17
Rear flexible hose LH x Brake tube	without union nut wrench	15.2	155	11
	with union nut wrench	13.4	137	10

^{© 2012} TOYOTA MOTOR CORPORATION. All Rights Reserved.