EmailBison API And Webhook Integrations For Historical Email Data

Overview

This report explains how EmailBison's REST API and webhooks work for integrating with external systems, with emphasis on whether and how you can retrieve historical email-sent data, bounces, opens, replies, and related engagement per lead.

Integration Surfaces In EmailBison

REST API

EmailBison exposes a modern REST API over a dedicated instance domain such as https://dedi.emailbison.com/api, authenticated with Bearer tokens created under Settings → Developer API → New API Token. API keys can be scoped as api-user (workspace-scoped) or super-admin (impersonating the creator and scoped to the creator's current workspace), with the documentation recommending api-user for most integrations.[1]

Selected resource groups in the public developer page include:[1]

- Contacts: /api/leads (create, update, retrieve leads and attach tags).[1]
- Campaigns: /api/campaigns (create, update, pause campaigns).[1]
- Sequences: /api/campaigns/sequence-steps (manage sequence steps and send tests).[1]
- Email accounts: /api/sender-emails (manage sender email configuration).[1]
- Replies: /api/replies plus endpoints like /api/replies/{id}/mark-as-interested and /api/replies/{id}/followup-campaign/push.[1]

- Webhooks: /api/webhooks to register and manage webhook listeners per workspace.[1]

The EmailBison docs also describe queryable endpoints like GET /api/leads with filters for reply counts and tag IDs, implying that reply and tag-based engagement information can be pulled historically via list queries.[1]

Webhooks

EmailBison provides workspace-level webhooks configured from Settings → Webhooks → New Webhook URL, where you register one or more endpoints and select which events to send. According to the OutboundSync webhook guide, supported EmailBison webhook event types include Email Sent, Contact Replied, Manual Email Sent, Email Opened, Contact Unsubscribed, Contact Interested, and Email Bounced.[2][1]

The developer docs emphasize that you can “receive push events for key changes like email sent, reply received, interested, unsubscribed, tag added, and more,” and that failed deliveries are retried up to five times over the next twenty-four hours.[2][1]

Low-Code And CRM Integrations

EmailBison is designed to work well with low-code tools like Clay, Zapier, Make, and n8n, which typically listen to EmailBison webhooks and then call API endpoints (for example, GET /api/leads) for enrichment or routing. For CRM sync, OutboundSync is the recommended integration partner; it uses EmailBison webhooks to log email activity (sent, replies, opens, unsubscribes, bounces, and reply categories) into HubSpot and Salesforce.[3][4][1]

Historical Email Data Via The API

Leads Endpoint And Reply-Based Filters

The /api/leads endpoint is queryable with search and filter parameters and is demonstrated in the docs with filters on replies and tag_ids.[1]

Example pattern for GET leads with filters in a low-code tool:[1]

- Endpoint: `GET https://subdomain.yourdomain.com/api/leads`.
- Query parameters include items like `filters[replies][value]=0`, `filters[replies][criteria]==`, and `filters[tag_ids]=11`, `filters[tag_ids][1]=12`.[1]

This indicates that historical engagement state (such as how many replies a lead has, and which tags—e.g., Interested—are attached) is exposed at the lead level and can be fetched in bulk.

Replies Resource For Message-Level History

The EmailBison developer page lists a `Replies` resource with endpoints like:[1]

- `GET /api/replies` (implied by the resource group, for listing replies across campaigns/leads).
- `PATCH /api/replies/{id}/mark-as-interested` to promote a given reply into an Interested state.[1]
- `POST /api/replies/{id}/followup-campaign/push` to push a contact with a given reply into a follow-up campaign.[1]

Tutorial content and community videos on building an AI copilot for EmailBison show patterns where webhooks deliver a reply ID, and then the integration calls the replies API to fetch the full reply body and act on it. This confirms that replies are persisted and addressable via stable IDs, allowing retrieval of historical inbound email content at scale.[5]

Campaigns, Sequences, And Analytics

The public “Developers” page lists `/api/campaigns` and `/api/campaigns/sequence-steps`, but does not itself document a dedicated analytics endpoint like Smartlead’s `/analytics` or `/statistics`. However, marketing and integration materials describe that OutboundSync can “log your outbound email activity, including sent, replies, opens, clicks, unsubscribes, bounces, and reply categories” from EmailBison into CRMs, which implies that this engagement data is accessible internally—either via EmailBison’s private API reference

or in denormalized form through webhooks and replies endpoints.[4][3][1]

Because the public docs are intentionally a high-level developer entry point and defer many specifics to a separate API reference and in-app tooling, the safer integration pattern is to:

- Treat `/api/leads` and `/api/replies` as the primary historical sources you control directly for leads and reply content.[1]
- Use webhooks to capture incremental sent/opened/bounced/unsubscribed events and, where needed, hydrate them by calling back into `/api/leads` or `/api/replies` using IDs from webhook payloads.[2][1]

Export-Like Behavior Via API + Filters

While the public developer page does not expose a dedicated "export CSV" endpoint for leads or events, it explicitly documents patterns for paginated and filtered `GET /api/leads` requests.[1]

An export workflow in a custom integration would therefore be:

- Page through `/api/leads` with filters for tags (e.g., Interested, Unsubscribed), reply counts, or other campaign metadata.
- For each page, write results into your own data warehouse or storage, effectively producing a historical export of lead-level engagement state.
- Optionally, enrich leads with reply content (via `/api/replies`) and events captured from webhooks for sent/open/bounce, to reconstruct per-lead timelines.

Because EmailBison is designed for use with data routers like OutboundSync and low-code tools, this "API + webhook + external storage" pattern is effectively the intended way to build exports and historical datasets.[3][1]

Real-Time Email Event Data Via Webhooks

Webhook Configuration Scope

EmailBison webhooks are defined at the workspace level (not per client or account), meaning each workspace can have multiple webhook URLs that receive events for all activity in that workspace. To configure webhooks, users go to Settings → Webhooks, click “New Webhook URL”, then specify a name, target URL, and toggle on the desired event types.[2]

Both the official developer docs and the OutboundSync guide note that EmailBison retries failed webhook deliveries up to five times over a 24-hour window, which is important for building reliable downstream pipelines.[2][1]

Supported Engagement Event Types

The OutboundSync EmailBison webhook guide lists these currently supported events when configuring a webhook in EmailBison:[2]

- Email Sent: A new scheduled email was sent to a contact.[2]
- Contact Replied: A contact replied to your email.[2]
- Manual Email Sent: You sent a manual email (one-off, reply, or forward).[2]
- Email Opened: A contact opened your email.[2]
- Contact Unsubscribed: A contact unsubscribed from future emails.[2]
- Contact Interested: A contact sent a positive (interested) reply.[2]
- Email Bounced: An outbound email bounced.[2]

The EmailBison developer page’s webhook section further mentions event types such as tag-related events (for example, `TAG_ATTACHED`), illustrating that you can also subscribe to lifecycle events around tags and campaigns, which can be used to encode dispositions like “Interested” or custom statuses.[1]

The high-level webhook overview in the Mintlify docs notes that you can send test webhook events from the UI or via `POST /api/webhook-events/test-event`, which is useful for contract testing and automation build-out.[6]

Webhooks And Historical Backfill

As with other modern SaaS tools, EmailBison webhooks are designed for near real-time push of events as they occur, not for replaying or backfilling historical activity. The docs and integration guides do not indicate any support for requesting historical webhook deliveries or replaying an event stream for past activity.[2][1]

The recommended pattern is therefore:

- Use the REST API (primarily `/api/leads` and `/api/replies`, plus any private analytics endpoints exposed in the full API reference) for historical backfill of lead state and reply content.[5][1]
- Configure workspace-level webhooks to subscribe to Email Sent, Email Opened, Email Bounced, Contact Replied, Contact Unsubscribed, Contact Interested, and any tag- or campaign-related events you care about, so you can maintain an up-to-date event log going forward.[2][1]
- Use IDs and metadata in webhook payloads (such as lead IDs, reply IDs, campaign IDs, and tag IDs) to join webhook events back to your own copies of leads and replies.

Summary Of What You Can Retrieve

Historical Mail Sent Data

From the public docs alone, EmailBison does not expose a dedicated "sent events" listing endpoint in the same way that it exposes `/api/replies` for replies. However, several facts indicate that historical sent data is available to integrations at least indirectly:[1]

- EmailBison and OutboundSync jointly advertise that outbound email activity (sent emails, replies, opens, unsubscribes, bounces, and reply categories) can be synchronized into CRMs like HubSpot and Salesforce.[4][3]
- EmailBison's webhooks include an "Email Sent" event, whose payload can be captured and stored externally for all future sends once the webhook is configured.[2]

To build a full historical view of sent emails for an existing account:

- For future sends, rely on the Email Sent webhook and store every event in your own database.[2]
- For past sends, consult the full API reference inside your EmailBison account to identify any private analytics or activity endpoints, or use low-code tools like Clay to query leads and campaigns with filters that approximate sent history, then export results.[7][1]

Historical Bounce Data

EmailBison explicitly supports an “Email Bounced” webhook event type, fired whenever an outbound email bounces, and retried on delivery failure. This ensures that, once webhooks are enabled, every future bounce can be recorded in your own system in near real time.[2]

For historical bounce data:

- OutboundSync documentation notes that it can log bounces from EmailBison into CRMs, implying that such data is queryable within EmailBison via internal APIs.[3]
- While the public developer article does not document a `bounces` endpoint, you can typically infer bounce state at the lead level (for example, via tags or statuses) using filtered `GET /api/leads` queries, and supplement this with any private analytics endpoints described in your in-app API reference.[1]

Historical Opens, Clicks, Replies, And Unsubscribes

For replies and interested/unsubscribed states, EmailBison clearly exposes API-level access:

- The `Replies` resource (`/api/replies`) lets you retrieve reply entities and act on them (for example, marking as interested or adding to follow-up campaigns), which is suitable for building a historical dataset of inbound replies.[5][1]
- Lead filters on `/api/leads` based on `replies` and `tag_ids` allow you to segment leads who have replied, been marked Interested, or been tagged Unsubscribed, and export these segments via pagination.[1]

For open and click data:

- Webhooks expose an “Email Opened” event type, and OutboundSync’s materials state that opens are among the engagement signals synced to CRMs from EmailBison.[3][2]
- Public developer docs do not list a dedicated opens/clicks endpoint, so the common pattern is to record these events from webhooks going forward and, where available, query any analytics endpoints shown in the private API reference for backfill.[1]

Unsubscribes are similarly represented:

- “Contact Unsubscribed” is an explicit webhook event, and lead state can also be tracked using tags or statuses on `/api/leads`.[2][1]

Practical Integration Pattern For EmailBison

For a robust EmailBison integration that mirrors what you are doing with Smartlead:

- Initial backfill
  - Use `GET /api/leads` with pagination and filters (reply count, tag IDs for Interested/Unsubscribed, and any campaign-scoped metadata available in your private API reference) to export a snapshot of leads and their engagement-related state.[1]
  - Use `GET /api/replies` to pull historical replies, then join them to leads on lead or campaign identifiers, reconstructing reply timelines.[5][1]
  - If your in-app API reference exposes additional analytics endpoints (for example, campaign email activity), use these to backfill counts of sent, opened, bounced, and clicked emails per campaign or per lead.
- Real-time pipeline
  - Configure workspace-level webhooks in Settings → Webhooks, subscribing at minimum to Email Sent, Email

Opened, Email Bounced, Contact Replied, Contact Unsubscribed, and Contact Interested.[2]
    - Implement idempotent consumers that store each event with references to EmailBison lead IDs, reply IDs, and campaign IDs, building your own event log.
    - Use IDs from webhook payloads to hydrate entities via `/api/leads` and `/api/replies` as necessary.

With this pattern you can, in practice, reconstruct and maintain historical datasets for replies and lead-level states entirely via the REST API, and capture complete future data for sent emails, bounces, opens, and unsubscribes via webhooks (plus any additional analytics endpoints exposed to your workspace).

References

1. Developers - EmailBison - A clean, modern REST API for leads, campaigns, replies, and automation. Script anything you can do i...
2. EmailBison webhook guide | OutboundSync Help Center - A webhook is an HTTP callback that sends data to a specified URL when certain events occur in your E...
3. EmailBison Salesforce integration - Outbound Sync - Guide to OutboundSync's EmailBison Salesforce integration. Log emails, status updates, and automate ...
4. Announcing OutboundSync's new EmailBison integration for HubSpot and Salesforce - Discover OutboundSync’s latest integration with EmailBison for HubSpot and Salesforce!

In this vide...

5. Filter Positive Replies in EmailBison with AI (Automated) - This is for all b2b lead generation agencies using EmailBison.

How to connect EmailBison with AI (C...

6. Overview - EmailBison Docs - EmailBison provides you with many events to trigger a webhook request. To view all the events availa...

7. how I automate my $50K/m growth agency clients using AI - Want to work with us? Book a call [https://oneaway.neetocal.com/discovery-call](https://oneaway.ne...