Smartlead API And Webhook Integrations For Historical Email Data

Overview

This report explains how Smartlead's REST API and webhooks work from an integration perspective, with a focus on whether and how you can pull historical data on emails sent, bounces, opens, clicks, and replies for leads.

Integration Surfaces In Smartlead

REST API

Smartlead exposes a versioned REST API at `https://server.smartlead.ai/api/v1`, authenticated via an API key passed as a query parameter `?api_key=YOUR_KEY` and rate-limited to 10 requests every 2 seconds. The public documentation makes it clear that "almost everything you can do using the interface" can be automated via this API, including campaigns, leads, statistics, and webhooks.[1]

Webhooks

Smartlead supports campaign-level webhooks via API endpoints under `/campaigns/{campaign_id}/webhooks`, with event types such as `EMAIL_SENT`, `EMAIL_OPEN`, `EMAIL_LINK_CLICK`, `EMAIL_REPLY`, `LEAD_UNSUBSCRIBED`, and `LEAD_CATEGORY_UPDATED`. Third-party guides also describe user-, client-, and campaign-level webhooks configurable from the UI, used to push Smartlead events into external systems like CRMs or analytics tools.[2][3][1]

Manual CSV Export (UI)

From the Smartlead app, you can export lead and inbox data to CSV, including metrics such as sent email, sent time, opened time, clicked time, replied time, open count, click count, and reply message content. These UI exports are useful to understand what data Smartlead tracks, and they broadly line up with the fields exposed through API endpoints like `leads-export` and campaign statistics.[4][1]

Historical Email Data Via The API

Campaign-Level Analytics And Stats

Smartlead offers multiple analytics endpoints that expose historical aggregates for each campaign.

- `/campaigns/{campaign_id}/analytics` returns top-level campaign metrics such as `sent_count`, `open_count`, `click_count`, `reply_count`, `bounce_count`, and `unsubscribed_count`, plus unique counts (e.g., `unique_open_count`, `unique_click_count`, `unique_sent_count`) and a `campaign_lead_stats` breakdown by lead status.[1]
- `/campaigns/{campaign_id}/analytics-by-date?start_date=YYYY-MM-DD&end_date=YYYY-MM-DD` returns date-bucketed stats for a campaign, including `sent_count`, `open_count`, `click_count`, `reply_count`, `bounce_count`, and `unsubscribed_count` over a specified window (up to 30 days per request).[1]

These endpoints let you reconstruct historical performance over time at an aggregate level (per campaign or per day), including bounces, opens, clicks, and replies.

Per-Email Event Statistics (Including Bounces)

For detailed event-level tracking, Smartlead exposes a statistics endpoint scoped to a campaign:

- `GET /campaigns/{campaign_id}/statistics?offset=&limit=&email_sequence_number=&email_status=` returns a list of stats rows per email sent to each lead in the campaign.[1]

- Each row includes lead_name, lead_email, lead_category, sequence_number, email_subject, email_message, sent_time, open_time, click_time, reply_time, open_count, click_count, is_unsubscribed, and is_bounced.[1]
- The email_status filter supports values like opened, clicked, replied, unsubscribed, and bounced, allowing you to query specifically for bounced emails or other statuses.[1]

This endpoint effectively provides a historical log of engagement events for each email, including whether it bounced, was opened, clicked, or replied to, with associated timestamps where applicable.[1]

Per-Lead Message History (Thread-Level)

Smartlead also exposes a message-history endpoint for an individual lead within a campaign:

- GET /campaigns/{campaign_id}/leads/{lead_id}/message-history returns an array history that contains items with type (SENT or REPLY), message_id, stats_id, time, email_body, and subject, as well as top-level from and to fields.[1]
- This is effectively the same data as seen in the Master Inbox UI, giving you a full historic thread of outbound and inbound messages for that lead in that campaign.[1]

By combining message-history (for content and threading) with the statistics endpoint (for engagement events like opens, clicks, and bounces keyed via stats_id), you can reconstruct detailed historical interaction timelines per lead.[1]

Lead Exports With Engagement Counters

Smartlead provides a dedicated API endpoint to export all leads for a campaign as a CSV, including engagement counters:

- GET /campaigns/{campaign_id}/leads-export returns a CSV with columns such as id, campaign_lead_map_id, status, created_at, first_name, last_name, email, phone_number, company_name, website, location, custom_fields, linkedin_profile, company_url, is_unsubscribed, last_email_sequence_sent, is_interested, open_count, click_count, and reply_count.[1]

This gives a campaign-wide snapshot of per-lead engagement metrics (open, click, reply counts and subscription status), which you can use as a historical export or to seed another system.

Other Lead And Campaign Endpoints Relevant To History

- GET /campaigns/{campaign_id}/leads returns all leads in a campaign with metadata such as status (e.g., SENT, INPROGRESS, COMPLETED, BLOCKED), basic profile fields, and whether a lead is unsubscribed.[1]
- GET /leads/{lead_id}/campaigns returns all campaigns a particular lead belongs to, which you can use to iterate over campaigns and then pull stats or message history per campaign for that lead.[1]

Together, these endpoints support building a full historical view per lead across campaigns by traversing from lead → campaigns → statistics/message-history.

Real-Time Email Event Data Via Webhooks

Webhook Configuration And Scopes

The Smartlead API documentation exposes campaign-level webhook management via:

- GET /campaigns/{campaign_id}/webhooks to list webhooks attached to a campaign, returning fields like id, name, webhook_url, email_campaign_id, event_types, and categories.[1]
- POST /campaigns/{campaign_id}/webhooks to create or update a webhook by specifying name, webhook_url, event_types, and optional categories.[1]
- DELETE /campaigns/{campaign_id}/webhooks to remove a webhook by id.[1]

External integration guides further explain that from the Smartlead UI you can define webhooks at user, client, or campaign level, with user-level webhooks having the highest priority, and that these are

used to push Smartlead events to downstream systems like OutboundSync or Outreach Magic.[3][2]

Supported Webhook Event Types

The official API documentation lists the following `WEBHOOK_EVENT_TYPE` values:[1]

```
EMAIL_SENT
EMAIL_OPEN
EMAIL_LINK_CLICK
EMAIL_REPLY
LEAD_UNSUBSCRIBED
LEAD_CATEGORY_UPDATED
```

Third-party documentation for specific integrations shows additional selectable events in the UI, such as `Email Sent`, `Email Open`, `Email Link Click`, `Email Reply`, `Lead Unsubscribed`, `Lead Category Updated`, `Email Bounce`, `Campaign Status Changed`, and others like `First Email Sent` or `Untracked Replies`. This suggests the actual event catalog in the Smartlead app may be slightly richer than the core list currently documented in the API reference, especially around bounce and campaign-status notifications.[2][3]

In practice, for email engagement you can receive near real-time notifications whenever an email is sent, opened, clicked, or replied to, and when a lead unsubscribes or changes category; for bounces, you should verify whether your Smartlead account's webhook UI exposes a dedicated bounce event, even if it is not yet explicitly documented in the API docs.[2][1]

Webhooks And Historical Data

Webhooks in Smartlead behave like standard webhooks in other systems: they push events to your endpoint when the event occurs (e.g., when an email is sent, opened, clicked, replied, or when a lead unsubscribes). There is no indication in the documentation that webhooks can be used to replay or backfill historical events; you typically start receiving events only after the webhook is configured.[3][1]

Because of this, the recommended pattern for building a complete dataset is:

- Use the REST API (analytics, statistics, leads-export, and message-history endpoints) to perform an initial historical backfill of email activity and engagement.[1]
- Configure webhooks (at user, client, or campaign level) to capture incremental events going forward, ensuring you subscribe to all relevant event types (EMAIL_SENT, EMAIL_OPEN, EMAIL_LINK_CLICK, EMAIL_REPLY, LEAD_UNSUBSCRIBED, and any available bounce or campaign-status events) in your webhook settings.[3][2][1]

Summary Of What You Can Retrieve

Historical Mail Sent Data

- Aggregated sent counts per campaign and per date range via `/campaigns/{campaign_id}/analytics` and `/analytics-by-date`.[1]
- Per-email sent records (with timestamps, subjects, and body) via `/campaigns/{campaign_id}/statistics` and `/campaigns/{campaign_id}/leads/{lead_id}/message-history`.[1]
- Per-lead sent history summarized via `/campaigns/{campaign_id}/leads-export` (open/click/reply counts and last sequence sent).[1]

Historical Bounce Data

- Bounce counts per campaign and per date range via `/campaigns/{campaign_id}/analytics` and `/analytics-by-date`, which expose `bounce_count`.[1]
- Per-email bounce status via `/campaigns/{campaign_id}/statistics` using the `email_status=bounced` filter and the `is_bounced` boolean field in each stats row.[1]

Historical Opens, Clicks, And Replies

- Aggregated open, click, and reply counts via `/campaigns/{campaign_id}/analytics` and `/analytics-by-date`.[1]
- Per-email events with exact `open_time`, `click_time`, `reply_time`, `open_count`, and `click_count` via

/campaigns/{campaign_id}/statistics.[1]
- Per-lead engagement counters (open_count, click_count, reply_count) and subscription status via /campaigns/{campaign_id}/leads-export.[1]
- Full message content and timing for sent and reply emails via /campaigns/{campaign_id}/leads/{lead_id}/message-history.[1]

Real-Time Events (For Ongoing Activity)

- Near real-time notifications of sends, opens, clicks, replies, lead unsubscribes, and category changes via webhooks with event types like EMAIL_SENT, EMAIL_OPEN, EMAIL_LINK_CLICK, EMAIL_REPLY, LEAD_UNSUBSCRIBED, and LEAD_CATEGORY_UPDATED, plus any additional bounce or campaign-status events exposed in the UI.[2][3][1]

Practical Integration Pattern

For a robust integration that needs both historical and real-time data on Smartlead email performance:

- Perform an initial backfill using:
  - /campaigns?api_key=... to enumerate campaigns.[1]
  - For each campaign, call /campaigns/{campaign_id}/analytics, /analytics-by-date, /statistics, and /leads-export to collect aggregates, per-email events, and per-lead counters (including bounces, opens, clicks, and replies).[1]
  - Optionally, for high-value leads, call /campaigns/{campaign_id}/leads/{lead_id}/message-history to mirror the inbox-level thread history.[1]
- Configure webhooks at the most appropriate scope (user or client for full account coverage, campaign for surgical control) and subscribe to all relevant engagement event types in your Smartlead settings.[3][2][1]
- In your own system, treat API-sourced data as the historical truth and webhook-sourced events as the incremental stream to keep that truth up to date.

Following this pattern, you can reliably retrieve and maintain complete historical datasets for sent emails, bounce outcomes, opens, clicks, replies, and lead status changes originating from Smartlead.

References

1. Smartlead API, Webhooks and Automation - Smartlead's API lets you control campaign sends, manage inboxes, update lead statuses, and automate ...
2. Setup Smartlead Webhook - Outreach Magic Documentation - Outreach Magic is the intelligence platform for B2B teams, unifying tools like Smartlead, Instantly ...
3. Smartlead webhook guide - OutboundSync Help Center - Knowledge base of OutboundSync Help Center
4. Data export options in Smartlead - Smartlead allows you to export lead data from the Campaign > Lead list > Filter > Download as CSV. H...