

Manual:IPv6/Firewall/Filter

From MikroTik Wiki
< Manual:IPv6 | Firewall

Contents

- 1 Summary
- 2 Properties

Applies
to
RouterOS: v5



Summary

Sub-menu: /ipv6 firewall filter

Properties

Property	Description
action (<i>accept</i> <i>add-dst-to-address-list</i> ...; Default: accept)	Action to take if packet is matched by the rule: <ul style="list-style-type: none">■ accept - Accept the packet. It is not passed to the next firewall rule.■ add-dst-to-address-list - Add destination address to address list specified by address-list parameter■ add-src-to-address-list - Add source address to address list specified by address-list parameter■ drop - Silently drop the packet.■ jump - Jump to the user defined chain specified by the value of jump-target parameter

- **log** - Add a message to the system log containing following data: in-interface, out-interface, src-mac, protocol, src-ip:port->dst-ip:port and length of the packet. After packet is matched it is passed to the next rule in the list, similar as passthrough
- **passthrough** - Ignore this rule and go to next one (useful for statistics).
- **reject** - Drop the packet and send an ICMP reject message
- **return** - Passes control back to the chain from where the jump took place.

address-list (; Default:)

time (; Default:)

[Top | Back to Content]

Retrieved from "https://wiki.mikrotik.com/index.php?title=Manual:IPv6/Firewall/Filter&oldid=23201"

Categories: Manual | Firewall | IPv6

- This page was last edited on 24 February 2012, at 16:46.