

localhost

 Servers

Servers 1

 localhost

localhost

Databases 1



Properties

Name	Value
Product	MySQL
Version	8.0.42
Version Comment	MySQL Community Server - GPL
Version Compile Machine	x86_64
Version Compile Os	Win64
Collation	utf8mb4_0900_ai_ci
Hostname	localhost
Port	3306
Base Directory	C:\Program Files\MySQL\MySQL Server 8.0\

 Databases

Databases 1



 serviziogas

Properties

Name	Value
Collation	utf8mb4_0900_ai_ci

Object Types 1

 Tables

 Tables

Objects 5

Name	Description
departamentos	
inquilinos	
lecturas	
pagos	
proveedores	

departamentos

Description

Properties

Name	Value
Engine	InnoDB
Auto Increment	0
Average Row Length	0
Charset	utf8mb4
Collation	utf8mb4_0900_ai_ci
Row Format	Default
Min Rows	0
Max Rows	0
Checksum	False
Page Checksum	True
Pack Keys	False
Delay Key Write	False
Is Partitioned	False
Encryption	False
Persistent Statistics	DEFAULT
Auto Recalculate Statistics	DEFAULT
Sample Pages	0
Created	23/07/2025 03:48:03 p. m.
Last Modified	01/01/0001 12:00:00 a. m.

Columns

Key	Name	Data Type	Length	Precision	Scale	Unsigned	Zerofill	Binary	Not Null	Auto Increment	Default	Virtual	Invisible	Description
	id_departamento	INT		11		True	False	False	True	True		False	False	
	numero_departamento	VARCHAR	10			False	False	False	True	False		False	False	
	id_inquilino_responsable	INT		11		True	False	False	False	False	NULL	False	False	
	estado	ENUM	0			False	False	False	True	False	'Ocupado'	False	False	
	servicio_suspendido	TINYINT		1		False	False	False	True	False	'0'	False	False	

Indexes

Key	Name	Columns	Unique	Type	Key Lengths
		id_departamento	True	None	0
	numero_departamento	numero_departamento	True	None	0
	id_inquilino_responsable	id_inquilino_responsable	False	None	0

Foreign Keys

Name	Columns	Delete Rule	Update Rule
departamentos_ibfk_1	id_inquilino	N/S	N/S

SQL Script

```
CREATE TABLE departamentos (  
  id_departamento INT UNSIGNED NOT NULL AUTO_INCREMENT,  
  numero_departamento VARCHAR(10) NOT NULL,  
  id_inquilino_responsable INT UNSIGNED DEFAULT NULL,  
  estado ENUM('Ocupado','Vacio') NOT NULL DEFAULT 'Ocupado',  
  servicio_suspendido TINYINT(1) NOT NULL DEFAULT 0,  
  PRIMARY KEY (id_departamento)  
)  
  
ENGINE = INNODB,  
CHARACTER SET utf8mb4,  
COLLATE utf8mb4_0900_ai_ci;  
  
ALTER TABLE departamentos  
  ADD UNIQUE INDEX numero_departamento(numero_departamento);  
  
ALTER TABLE departamentos  
  ADD CONSTRAINT departamentos_ibfk_1 FOREIGN KEY (id_inquilino_responsable)  
    REFERENCES inquilinos(id_inquilino);
```

Depends On ¹

 inquilinos

Used By ¹

 lecturas

inquilinos

Description

Properties

Name	Value
Engine	InnoDB
Auto Increment	0
Average Row Length	0
Charset	utf8mb4
Collation	utf8mb4_0900_ai_ci
Row Format	Default
Min Rows	0
Max Rows	0
Checksum	False
Page Checksum	True
Pack Keys	False
Delay Key Write	False
Is Partitioned	False
Encryption	False
Persistent Statistics	DEFAULT
Auto Recalculate Statistics	DEFAULT
Sample Pages	0
Created	23/07/2025 03:48:03 p. m.
Last Modified	01/01/0001 12:00:00 a. m.

Columns

Key	Name	Data Type	Length	Precision	Scale	Unsigned	Zerofill	Binary	Not Null	Auto Increment	Default	Virtual	Invisible	Description
	id_inquilino	INT		11		True	False	False	True	True		False	False	
	nombre_completo	VARCHAR	150			False	False	False	True	False		False	False	

Indexes

Key	Name	Columns	Unique	Type	Key Lengths
		id_inquilino	True	None	0

SQL Script

```
CREATE TABLE inquilinos (  
  id_inquilino INT UNSIGNED NOT NULL AUTO_INCREMENT,  
  nombre_completo VARCHAR(150) NOT NULL,  
  PRIMARY KEY (id_inquilino)  
)
```

```
ENGINE = INNODB,  
CHARACTER SET utf8mb4,  
COLLATE utf8mb4_0900_ai_ci;
```

Depends On

No items found

Used By 2



departamentos



pagos

lecturas

Description

Properties

Name	Value
Engine	InnoDB
Auto Increment	0
Average Row Length	0
Charset	utf8mb4
Collation	utf8mb4_0900_ai_ci
Row Format	Default
Min Rows	0
Max Rows	0
Checksum	False
Page Checksum	True
Pack Keys	False
Delay Key Write	False
Is Partitioned	False
Encryption	False
Persistent Statistics	DEFAULT
Auto Recalculate Statistics	DEFAULT
Sample Pages	0
Created	23/07/2025 03:48:04 p. m.
Last Modified	01/01/0001 12:00:00 a. m.

Columns

Key	Name	Data Type	Length	Precision	Scale	Unsigned	Zerofill	Binary	Not Null	Auto Increment	Default	Virtual	Invisible	Description
	id_lectura	INT		11		True	False	False	True	True		False	False	
	id_departamento	INT		11		True	False	False	True	False		False	False	
	fecha_lectura	DATE		0		False	False	False	True	False		False	False	
	lectura_medidor	DECIMAL		10	2	False	False	False	True	False		False	False	
	consumo_mes_actual	DECIMAL		10	2	False	False	False	True	False		False	False	
	precio_litro_gas	DECIMAL		10	2	False	False	False	True	False		False	False	
	monto_a_pagar	DECIMAL		10	2	False	False	False	True	False		False	False	

Indexes

Key	Name	Columns	Unique	Type	Key Lengths
-----	------	---------	--------	------	-------------

		id_lectura	True	None	0
	id_departamento	id_departamento	False	None	0

Foreign Keys

Name	Columns	Delete Rule	Update Rule
lecturas_ibfk_1	id_departamento	N/S	N/S

SQL Script

```
CREATE TABLE lecturas (  
  id_lectura INT UNSIGNED NOT NULL AUTO_INCREMENT,  
  id_departamento INT UNSIGNED NOT NULL,  
  fecha_lectura DATE NOT NULL,  
  lectura_medidor DECIMAL(10, 2) NOT NULL,  
  consumo_mes_actual DECIMAL(10, 2) NOT NULL,  
  precio_litro_gas DECIMAL(10, 2) NOT NULL,  
  monto_a_pagar DECIMAL(10, 2) NOT NULL,  
  PRIMARY KEY (id_lectura)  
)  
ENGINE = INNODB,  
CHARACTER SET utf8mb4,  
COLLATE utf8mb4_0900_ai_ci;  
  
ALTER TABLE lecturas  
  ADD CONSTRAINT lecturas_ibfk_1 FOREIGN KEY (id_departamento)  
    REFERENCES departamentos(id_departamento);
```

Depends On 1

 departamentos

Used By 1

 pagos



Description

Properties

Name	Value
Engine	InnoDB
Auto Increment	0
Average Row Length	0
Charset	utf8mb4
Collation	utf8mb4_0900_ai_ci
Row Format	Default
Min Rows	0
Max Rows	0
Checksum	False
Page Checksum	True
Pack Keys	False
Delay Key Write	False
Is Partitioned	False
Encryption	False
Persistent Statistics	DEFAULT
Auto Recalculate Statistics	DEFAULT
Sample Pages	0
Created	23/07/2025 03:48:04 p. m.
Last Modified	01/01/0001 12:00:00 a. m.

Columns

Key	Name	Data Type	Length	Precision	Scale	Unsigned	Zerofill	Binary	Not Null	Auto Increment	Default	Virtual	Invisible	Description
	id_pago	INT		11		True	False	False	True	True		False	False	
	id_lectura	INT		11		True	False	False	True	False		False	False	
	id_inquilino_pago	INT		11		True	False	False	False	False	NULL	False	False	
	fecha_pago	DATE		0		False	False	False	False	False	NULL	False	False	
	fecha_limite_pago	DATE		0		False	False	False	True	False		False	False	
	monto_pagado	DECIMAL		10	2	False	False	False	False	False	NULL	False	False	
	metodo_pago	ENUM	0			False	False	False	False	False	NULL	False	False	
	estado_pago	ENUM	0			False	False	False	True	False	'Pendiente'	False	False	

Indexes

Key	Name	Columns	Unique	Type	Key Lengths
		id_pago	True	None	0
	id_lectura	id_lectura	False	None	0
	id_inquilino_paga	id_inquilino_paga	False	None	0

Foreign Keys

Name	Columns	Delete Rule	Update Rule
pagos_ibfk_1	id_lectura	N/S	N/S
pagos_ibfk_2	id_inquilino	N/S	N/S

SQL Script

```
CREATE TABLE pagos (  
  id_pago INT UNSIGNED NOT NULL AUTO_INCREMENT,  
  id_lectura INT UNSIGNED NOT NULL,  
  id_inquilino_paga INT UNSIGNED DEFAULT NULL,  
  fecha_pago DATE DEFAULT NULL,  
  fecha_limite_pago DATE NOT NULL,  
  monto_pagado DECIMAL(10, 2) DEFAULT NULL,  
  metodo_pago ENUM('Efectivo','Transferencia','Cheque') DEFAULT NULL,  
  estado_pago ENUM('Pagado','Pendiente','Demora','Retraso Severo') NOT NULL DEFAULT 'Pendiente',  
  PRIMARY KEY (id_pago)  
)  
ENGINE = INNODB,  
CHARACTER SET utf8mb4,  
COLLATE utf8mb4_0900_ai_ci;  
  
ALTER TABLE pagos  
  ADD CONSTRAINT pagos_ibfk_1 FOREIGN KEY (id_lectura)  
    REFERENCES lecturas(id_lectura);  
  
ALTER TABLE pagos  
  ADD CONSTRAINT pagos_ibfk_2 FOREIGN KEY (id_inquilino_paga)  
    REFERENCES inquilinos(id_inquilino);
```

Depends On 2

-  inquilinos
-  lecturas

Used By

No items found

proveedores

Description

Properties

Name	Value
Engine	InnoDB
Auto Increment	0
Average Row Length	0
Charset	utf8mb4
Collation	utf8mb4_0900_ai_ci
Row Format	Default
Min Rows	0
Max Rows	0
Checksum	False
Page Checksum	True
Pack Keys	False
Delay Key Write	False
Is Partitioned	False
Encryption	False
Persistent Statistics	DEFAULT
Auto Recalculate Statistics	DEFAULT
Sample Pages	0
Created	23/07/2025 03:48:03 p. m.
Last Modified	01/01/0001 12:00:00 a. m.

Columns

Key	Name	Data Type	Length	Precision	Scale	Unsigned	Zerofill	Binary	Not Null	Auto Increment	Default	Virtual	Invisible	Description
	id_proveedor	INT		11		True	False	False	True	True		False	False	
	nombre_comercial	VARCHAR	100			False	False	False	True	False		False	False	
	nombre_contacto	VARCHAR	150			False	False	False	False	False	NULL	False	False	
	telefono	VARCHAR	20			False	False	False	False	False	NULL	False	False	
	plataformas_comunicacion	VARCHAR	255			False	False	False	False	False	NULL	False	False	

Indexes

Key	Name	Columns	Unique	Type	Key Lengths
		id_proveedor	True	None	0

SQL Script

```
CREATE TABLE proveedores (  
  id_proveedor INT UNSIGNED NOT NULL AUTO_INCREMENT,  
  nombre_comercial VARCHAR(100) NOT NULL,  
  nombre_contacto VARCHAR(150) DEFAULT NULL,
```

```
telefono VARCHAR(20) DEFAULT NULL,  
plataformas_comunicacion VARCHAR(255) DEFAULT NULL,  
PRIMARY KEY (id_proveedor)  
)  
ENGINE = INNODB,  
CHARACTER SET utf8mb4,  
COLLATE utf8mb4_0900_ai_ci;
```

Depends On

No items found

Used By

No items found