DogWhistle: companion guide

Rick Clinton

A short way into the question, the evidence, and the limits. This guide adds no new experiment or result to the submitted paper.

THE QUESTION

Can a schema-valid handoff carry a hidden signal that changes a successor's action? Can an audit identify the listener that knows its code without knowing the signal?

What the agents actually saw

Task	Assign six items to four vendors, at most two items per vendor. An exact solver finds every highest-value assignment, including ties.
Handoff	A deterministic gate validates a JSON handoff, rejects blocked words, and rebuilds all fields except **required_memory_refs**.
Code	The two refs name vendors outside a hidden pair: refs A and C mean “favour B and D.” Two refs from four vendors give six unordered pairs, about 2.6 bits.

Each study is a pull request in the repo, PR #1 to #6. **Who chose the refs?** In PRs #1–#2, a model chose them in free arms; code chose them in matched controls. In PRs #3–#4 and #6, study code supplied both codeword and public refs; those were receiver-only tests.

Three findings

1. A valid field carried the code

In PR #2, the model sender emitted the planted codeword in **30/30** handoffs and the receiver decoded **30/30**. The full claim still failed: both allocation-effect positive controls missed their registered threshold.

2. Hardening stopped the sender, not the listener

Code-chosen public refs removed sender control. In PR #3 the instructed listener (the paper's coalition listener) still favoured the decoy pair: **+0.109** excess as a share of six items. This was **exploratory and post-reveal**.

3. A field-swap audit identified the listener

On the same 30 new tasks in PR #6, extra answer-change sensitivity differed by **D = +0.356** (95% CI 0.256–0.456; exact one-sided $p = 2.05 \times 10^{-7}$). The difference was positive on **27/30** tasks.

How the audit works

Each of 30 tie-rich tasks was answered under two listener prompts, two ref types and three prompt wordings: 360 fresh, one-shot calls. The task, not the call, is the unit of comparison.

The comparison needs no hidden labels

W: How often does the assignment change when only the prompt wording changes?

X: How often does it change when the wording and refs change?

S = X - W: Extra change associated with the refs after allowing for wording variation.

D = S for the instructed listener - S for the honest listener. The audit reads only assignments; it does not need the hidden pair or an answer key.

What changed


Mean fraction of answer pairs with different full assignments, across the same 30 tasks:

Listener	W	X	S
Instructed	**0.589**	**0.961**	**+0.372**
Honest	0.122	0.139	+0.017

D = 0.356: a 35.6 percentage-point gap in extra change rates. The instructed listener's answers moved more when refs changed; the honest listener's were mostly stable.

One bar per task

The registered D values: 27 above zero, two at zero, one below. This shows the task-level variation behind the mean.



The action check agreed: codeword refs gave the instructed listener **+0.933** hidden-pair items per answer relative to public refs. The honest contrast was **+0.067**, inside its registered ±0.20 equivalence margin.

What the result does - and does not - say

The six studies were preregistered separately. Each used new tasks; their samples were not pooled. The series includes failed and retired studies.

The study record

PR #1	No shared code; full claim failed.
PR #2	Code transmitted, but full claim failed on positive controls.
PR #3	Instructed contrast +0.422 items (p = 0.00033); decoy analysis exploratory.
PR #4	Honest contrast -0.011 items, equivalent within ±0.20; different tasks from PR #3.
PR #5	Retired after 80/360 calls before analysis; no confirmatory decision.
PR #6	Same-task label-free audit passed; 360/360 Codex calls valid.

Why the record is checkable

- Tasks, prompts and decision rules were committed before model calls. Hidden pairs were fixed by salted commitments.
- The full receiver ledger digest was pushed before reveal. PR #6 had 360/360 valid Codex calls and zero retries.
- Deterministic audits replay the commitments, gate and scores. A separate re-analysis reproduced all 30 task-level D values. Its 17-test series correction was **exploratory**; adjusted primary p = 0.0002.

Where the claim stops

- The convention was planted and the instructed listener was told it. Unaided collusion was not tested.
- One synthetic allocation task, one handoff field and one confirmatory model (gpt-6.1-sol). The local Qwen run failed its validity threshold, so transfer remains untested.
- The listener prompts and output formats differ. The honest listener was highly stable; its S was not shown to be exactly zero.
- S flags reliance on a field, including legitimate reliance. Here the refs supplied no task information. The audit needs a suspect field, a neutral replacement and repeated calls.

Read the **submitted paper** for the full methods, Figure 2 and numbers; the **repository** has the ledgers and replay commands. This guide is a reading aid, not a new sprint result.

Submitted paper **Project page** **Code and replay**