

# **BOOTSTRAP**

- Bootstrap is a most popular HTML,CSS and JavaScript opensource framework developed by Twitter for creating web application.
- It is absolutely free to download and use.
- Bootstrap is a front-End framework used for easier and faster web application development.
- It includes HTML and css based design templates for typography(arranging the text),forms,buttons , tables ,navigations and etc.
- It can also have JavaScript Plug-In's.
- Bootstrap is developed by Mark Otto and Jacob Thornton at Twitter.
- It was release an open source product in August 2011 on GitHUB.
- Bootstrap 4 version was introduced in 2015 by Mark Otto.
- Bootstrap 5 the latest version was officially released on May 5, 2021.

## **Advantages of Bootstrap**

### **1)It supports Responsive web design**

- Responsive web design is about using HTML and CSS to automatically resize,hide,shrink or enlarge a website to make it look good on all devices like pc, desktop,phone,tab and etc.

### **2)It saves lot of development time**

- In bootstrap we are not responsible to write the code from the scratch.
- Bootstrap provides readymade classes to customized our application requirement.

### **<html>**

**<p>**

**<font color="red">**

**This is Paragraph**

</font>

</p>

## CSS

<p style="color:red">This is Paragraph</p>

## bootstrap

<p class="text-primary">This is paragraph</p>

### 3)consistent Framework

- It supports major all browsers and css compatability fixes.

### 4)Customizable

- Bootstrap is higly customizable based on the requirement we download and use.

ex:

<http://getbootstrap.com/docs/3.4/customize>

### 5)Good Documentation and Community support

- Documentation is a specification having set of rules and guidelines to use bootstrap.

ex:

<http://getbootstrap.com/docs/4.5/getting-started/introduction/>

### 6)It supports great Grid System

- Grid system builds layouts of all shapes and sizes in a web page.

### 7)Supports serveral javascript plugins using the jquery.

- Both "bootstrap.min.js" and "bootstrap.js" contains all javascript plugins.

In Bootstrap program we need to add following plugins to work online

link : <https://getbootstrap.com/docs/5.0/getting-started/introduction/>

ex:

```
<!DOCTYPE html>

<html>

<head>

    <title>MyPage!</title>


    <!-- Add bootstrap -->

<meta charset="utf-8">


<meta name="viewport" content="width=device-width, initial-
scale=1">


<!-- Bootstrap CSS -->

<link
href="https://cdn.jsdelivr.net/npm/bootstrap@5.0.2/dist/css/bootstra
p.min.css" rel="stylesheet" integrity="sha384-
EVSTQN3/azprG1Anm3QDgpJLIm9Nao0Yz1ztcQTwFspd3yD65Vohhpuu
COmLASjC" crossorigin="anonymous">

<!-- Option 1: Bootstrap Bundle with Popper -->

<script
src="https://cdn.jsdelivr.net/npm/bootstrap@5.0.2/dist/js/bootstrap.
bundle.min.js" integrity="sha384-
MrcW6ZMFYlzcLA8Nl+NtUVF0sA7MsXsP1UyJoMp4YLEuNSfAP+JcXn/t
WtlaxVXM" crossorigin="anonymous"></script>

</head>

<body>

</body>

</html>
```

## Bootstrap colors

- By using utility classes change the color of a text.

### ex:1:

```
<!DOCTYPE html>
```

```
<html>
```

```
<head>
```

```
    <title>MyPage!</title>
```

```
    <!-- Add bootstrap -->
```

```
<meta charset="utf-8">
```

```
<meta name="viewport" content="width=device-width, initial-  
scale=1">
```

```
<!-- Bootstrap CSS -->
```

```
<link
```

```
href="https://cdn.jsdelivr.net/npm/bootstrap@5.0.2/dist/css/bootstra  
p.min.css" rel="stylesheet" integrity="sha384-  
EVSTQN3/azprG1Anm3QDgPJLIm9Nao0Yz1ztcQTwFspd3yD65Vohhpuu  
COMLASjC" crossorigin="anonymous">
```

```
<!-- Option 1: Bootstrap Bundle with Popper -->
```

```
<script
```

```
src="https://cdn.jsdelivr.net/npm/bootstrap@5.0.2/dist/js/bootstrap.  
bundle.min.js" integrity="sha384-  
MrcW6ZMFYlzcLA8Nl+NtUVF0sA7MsXsP1UyJoMp4YLEuNSfAP+JcXn/t  
WtlaxVXM" crossorigin="anonymous"></script>
```

**</head>**

**<body>**

**<p class="text-primary"> primary text</p>**

**<p class="text-secondary"> Secondary text</p>**

**<p class="text-info">Info text</p>**

**<p class="text-warning">Warning text </p>**

**<p class="text-success">success text</p>**

**<p class="text-danger">danger text</p>**

**<p class="text-white">white text</p>**

**<p class="text-dark">dark text</p>**

**</body>**

**</html>**

**ex:2**

**<!DOCTYPE html>**

**<html>**

**<head>**

**<title>MyPage!</title>**

**<!-- Add bootstrap -->**

**<meta charset="utf-8">**

**<meta name="viewport" content="width=device-width, initial-scale=1">**

**<!-- Bootstrap CSS -->**

**<link**

**href="https://cdn.jsdelivr.net/npm/bootstrap@5.0.2/dist/css/bootstrap.min.css" rel="stylesheet" integrity="sha384-**

EVSTQN3/azprG1Anm3QDgpJLIm9Nao0Yz1ztcQTwFspd3yD65Vohhpuu  
COmLASjC" crossorigin="anonymous">

<!-- Option 1: Bootstrap Bundle with Popper -->

<script  
src="https://cdn.jsdelivr.net/npm/bootstrap@5.0.2/dist/js/bootstrap.  
bundle.min.js" integrity="sha384-  
MrcW6ZMFYlzcLA8Nl+NtUVF0sA7MsXsP1UyJoMp4YLEuNSfAP+JcXn/t  
WtlaxVXM" crossorigin="anonymous"></script>

<style>

.text-violet

{

color:#8e44ad;

}

</style>

</head>

<body>

<p class="text-primary">primary text</p>

<p class="text-secondary"> Secondary text</p>

<p class="text-info">Info text</p>

<p class="text-warning">Warning text </p>

<p class="text-success">success text</p>

<p class="text-danger">danger text</p>

<p class="text-white">white text</p>

<p class="text-dark">dark text</p>

<p class="text-violet">violet text</p>

</body>

</html>

## Bootstrap background colors

- In bootstrap background color can be applied to any element/tag.

### ex:1

```
<!DOCTYPE html>
```

```
<html>
```

```
<head>
```

```
    <title>MyPage!</title>
```

```
    <!-- Add bootstrap -->
```

```
<meta charset="utf-8">
```

```
<meta name="viewport" content="width=device-width, initial-  
scale=1">
```

```
<!-- Bootstrap CSS -->
```

```
<link
```

```
href="https://cdn.jsdelivr.net/npm/bootstrap@5.0.2/dist/css/bootstra  
p.min.css" rel="stylesheet" integrity="sha384-  
EVSTQN3/azprG1Anm3QDgpJLIm9Nao0Yz1ztcQTWfspd3yD65Vohhpuu  
COMLASjC" crossorigin="anonymous">
```

```
<!-- Option 1: Bootstrap Bundle with Popper -->
```

```
<script
```

```
src="https://cdn.jsdelivr.net/npm/bootstrap@5.0.2/dist/js/bootstrap.  
bundle.min.js" integrity="sha384-
```

MrcW6ZMFYlzcLA8NI+NtUVF0sA7MsXsP1UyJoMp4YLEuNSfAP+JcXn/t  
WtlaxVXM" crossorigin="anonymous"></script>

</head>

<body>

<p class="bg-info text-primary">primary text</p>

<p class="bg-danger text-secondary"> Secondary text</p>

<p class="bg-primary text-info">Info text</p>

<p class="bg-secondary text-warning">Warning text </p>

<p class="bg-warning text-success">success text</p>

<p class="bg-success text-danger">danger text</p>

<p class="bg-dark text-white">white text</p>

<p class="bg-white text-dark">dark text</p>

</body>

</html>

ex:2

<!DOCTYPE html>

<html>

<head>

<title>MyPage!</title>

<!-- Add bootstrap -->

<meta charset="utf-8">



```
<meta name="viewport" content="width=device-width, initial-scale=1">
```

```
<!-- Bootstrap CSS -->
```

```
<link  
href="https://cdn.jsdelivr.net/npm/bootstrap@5.0.2/dist/css/bootstrap.min.css" rel="stylesheet" integrity="sha384-EVSTQN3/azprG1Anm3QDgpJLIm9Nao0Yz1ztcQTwFspd3yD65VohhpuuCOMmLASjC" crossorigin="anonymous">
```

```
<!-- Option 1: Bootstrap Bundle with Popper -->
```

```
<script  
src="https://cdn.jsdelivr.net/npm/bootstrap@5.0.2/dist/js/bootstrap.bundle.min.js" integrity="sha384-MrcW6ZMFYlzcLA8Nl+NtUVF0sA7MsXsP1UyJoMp4YLEuNSfAP+JcXn/tWtIaxVXM" crossorigin="anonymous"></script>
```

```
<style>
```

```
  .bg-violet
```

```
  {
```

```
    background-color:#8e44ad;
```

```
  }
```

```
</style>
```

```
</head>
```

```
<body>
```

```
  <p class="bg-info text-primary">primary text</p>
```

```
  <p class="bg-danger text-secondary"> Secondary text</p>
```

```
  <p class="bg-primary text-info">Info text</p>
```

```
<p class="bg-secondary text-warning">Warning text </p>
<p class="bg-warning text-success">success text</p>
<p class="bg-success text-danger">danger text</p>
<p class="bg-dark text-white">white text</p>
<p class="bg-white text-dark">dark text</p>
<p class="bg-violet">This is violet text</p>

</body>
</html>
```

### Bootstrap borders

- Border utility is used to change quickly the border-style and border-radius of an element.
- It is mainly used for images, buttons and etc.
- we can use border classes to an element to remove all borders or add some borders.

#### ex:1

```
<!DOCTYPE html>

<html>

<head>

    <title>MyPage!</title>

    <!-- Add bootstrap -->

    <meta charset="utf-8">

    <meta name="viewport" content="width=device-width, initial-
scale=1">
```

<!-- Bootstrap CSS -->

<link

href="https://cdn.jsdelivr.net/npm/bootstrap@5.0.2/dist/css/bootstrap.min.css" rel="stylesheet" integrity="sha384-

EVSTQN3/azprG1Anm3QDgpJLIm9Nao0Yz1ztcQTwFspd3yD65VohhpuuCOMLASjC" crossorigin="anonymous">

<!-- Option 1: Bootstrap Bundle with Popper -->

<script

src="https://cdn.jsdelivr.net/npm/bootstrap@5.0.2/dist/js/bootstrap.bundle.min.js" integrity="sha384-

MrcW6ZMFYlzcLA8Nl+NtUVF0sA7MsXsP1UyJoMp4YLEuNSfAP+JcXn/tWtIaxVXM" crossorigin="anonymous"></script>

</head>

<body>

<span class="border"> All Borders</span>

<span class="border-top"> Top Border</span>

<span class="border-start"> start Border</span>

<span class="border-bottom"> bottom Border</span>

<span class="border-end"> end Border</span>

</body>

</html>

ex:2

<!DOCTYPE html>

<html>

```
<head>

  <title>MyPage!</title>

  <!-- Add bootstrap -->

<meta charset="utf-8">

<meta name="viewport" content="width=device-width, initial-
scale=1">

<!-- Bootstrap CSS -->

<link
href="https://cdn.jsdelivr.net/npm/bootstrap@5.0.2/dist/css/bootstra
p.min.css" rel="stylesheet" integrity="sha384-
EVSTQN3/azprG1Anm3QDgpJLIm9Nao0Yz1ztcQTwFspd3yD65Vohhpuu
COmLASjC" crossorigin="anonymous">

<!-- Option 1: Bootstrap Bundle with Popper -->

<script
src="https://cdn.jsdelivr.net/npm/bootstrap@5.0.2/dist/js/bootstrap.
bundle.min.js" integrity="sha384-
MrcW6ZMFYlzcLA8Nl+NtUVF0sA7MsXsP1UyJoMp4YLEuNSfAP+JcXn/t
WtlaxVXM" crossorigin="anonymous"></script>

</head>

<body>

  <br>

  <span class="border border-primary"> All Borders</span>
```

```
<span class="border-top border-secondary"> Top  
Border</span>
```

```
<span class="border-start border-danger"> start  
Border</span>
```

```
<span class="border-bottom border-info"> bottom  
Border</span>
```

```
<span class="border-end border-warning"> end  
Border</span>
```

```
</body>
```

```
</html>
```

### Bootstrap border radius

- Add classes to an element to easily rounds its corners.

ex:

```
<!DOCTYPE html>
```

```
<html>
```

```
<head>
```

```
<title>MyPage!</title>
```

```
<!-- Add bootstrap -->
```

```
<meta charset="utf-8">
```

```
<meta name="viewport" content="width=device-width, initial-  
scale=1">
```

```
<!-- Bootstrap CSS -->
```

```
<link
```

```
href="https://cdn.jsdelivr.net/npm/bootstrap@5.0.2/dist/css/bootstra
```

```
p.min.css" rel="stylesheet" integrity="sha384-
EVSTQN3/azprG1Anm3QDgpJLIm9Nao0Yz1ztcQTwFspd3yD65Vohhpuu
COmLASjC" crossorigin="anonymous">
```

```
<!-- Option 1: Bootstrap Bundle with Popper -->
```

```
<script
src="https://cdn.jsdelivr.net/npm/bootstrap@5.0.2/dist/js/bootstrap.
bundle.min.js" integrity="sha384-
MrcW6ZMFYlzcLA8Nl+NtUVF0sA7MsXsP1UyJoMp4YLEuNSfAP+JcXn/t
WtlaxVXM" crossorigin="anonymous"></script>
```

```
</head>
```

```
<body>
```

```
    <br>
```

```
    
```

```
    
```

```
    
```

```
    
```

```
    
```

**</body>**

**</html>**

**ex:2**

**<!DOCTYPE html>**

**<html>**

**<head>**

**<title>MyPage!</title>**

**<!-- Add bootstrap -->**

**<meta charset="utf-8">**

**<meta name="viewport" content="width=device-width, initial-scale=1">**

**<!-- Bootstrap CSS -->**

**<link**

**href="https://cdn.jsdelivr.net/npm/bootstrap@5.0.2/dist/css/bootstrap.min.css" rel="stylesheet" integrity="sha384-EVSTQN3/azprG1Anm3QDgpJLIm9Nao0Yz1ztcQTwFspd3yD65VohhpuuCOMmLASjC" crossorigin="anonymous">**

**<!-- Option 1: Bootstrap Bundle with Popper -->**

**<script**

**src="https://cdn.jsdelivr.net/npm/bootstrap@5.0.2/dist/js/bootstrap.bundle.min.js" integrity="sha384-MrcW6ZMFYlzcLA8Nl+NtUVF0sA7MsXsP1UyJoMp4YLEuNSfAP+JcXn/tWtIaxVXM" crossorigin="anonymous"></script>**

```
<style type="text/css">
    .myrounded
    {
        border-radius: 50px;
    }
</style>
</head>
<body>
    <br>

    

</body>
</html>
```

### Bootstrap sizing

- IT is used to size the element by using sizing utility classes.
- we can easily make an element wide or a tall with our width and height utility.
- It supports for 25%,50%,75% and 100% by default.

#### ex:1

```
<!DOCTYPE html>
<html>
<head>
```



**<title>MyPage!</title>**

**<!-- Add bootstrap -->**

**<meta charset="utf-8">**

**<meta name="viewport" content="width=device-width, initial-scale=1">**

**<!-- Bootstrap CSS -->**

**<link  
href="https://cdn.jsdelivr.net/npm/bootstrap@5.0.2/dist/css/bootstrap.min.css" rel="stylesheet" integrity="sha384-EVSTQN3/azprG1Anm3QDgpJLIm9Nao0Yz1ztcQTwFspd3yD65VohhpuuCOMmLASjC" crossorigin="anonymous">**

**<!-- Option 1: Bootstrap Bundle with Popper -->**

**<script  
src="https://cdn.jsdelivr.net/npm/bootstrap@5.0.2/dist/js/bootstrap.bundle.min.js" integrity="sha384-MrcW6ZMFYlzcLA8Nl+NtUVF0sA7MsXsP1UyJoMp4YLEuNSfAP+JcXn/tWtIaxVXM" crossorigin="anonymous"></script>**

**</head>**

**<body>**

**<br>**

**<div class="border border-primary w-25">This is div</div>**

```
<div class="border border-primary w-50">This is div</div>
```

```
<div class="border border-primary w-75">This is div</div>
```

```
<div class="border border-primary w-100">This is div</div>
```

```
</body>
```

```
</html>
```

**ex:2**

```
<!DOCTYPE html>
```

```
<html>
```

```
<head>
```

```
  <title>MyPage!</title>
```

```
  <!-- Add bootstrap -->
```

```
<meta charset="utf-8">
```

```
<meta name="viewport" content="width=device-width, initial-  
scale=1">
```

```
<!-- Bootstrap CSS -->
```

```
<link
```

```
  href="https://cdn.jsdelivr.net/npm/bootstrap@5.0.2/dist/css/bootstra  
p.min.css" rel="stylesheet" integrity="sha384-
```

```
EVSTQN3/azprG1Anm3QDgpJLIm9Nao0Yz1ztcQTWfSpd3yD65Vohhpuu  
COMLASjC" crossorigin="anonymous">
```

**<!-- Option 1: Bootstrap Bundle with Popper -->**

```
<script  
src="https://cdn.jsdelivr.net/npm/bootstrap@5.0.2/dist/js/bootstrap.  
bundle.min.js" integrity="sha384-  
MrcW6ZMFYlzcLA8Nl+NtUVF0sA7MsXsP1UyJoMp4YLEuNSfAP+JcXn/t  
WtlaxVXM" crossorigin="anonymous"></script>
```

```
<style type="text/css">
```

```
.w-60
```

```
{
```

```
width:60%;
```

```
}
```

```
</style>
```

```
</head>
```

```
<body>
```

```
<br>
```

```
<div class="border border-primary w-25">This is div</div>
```

```
<div class="border border-primary w-50">This is div</div>
```

```
<div class="border border-primary w-75">This is div</div>
```

```
<div class="border border-primary w-100">This is div</div>
```

```
<div class="border border-primary w-60">This is div</div>
```

```
</body>
```

```
</html>
```

### ex:3

**<!DOCTYPE html>**

**<html>**

**<head>**

**<title>MyPage!</title>**

**<!-- Add bootstrap -->**

**<meta charset="utf-8">**

**<meta name="viewport" content="width=device-width, initial-scale=1">**

**<!-- Bootstrap CSS -->**

**<link**

**href="https://cdn.jsdelivr.net/npm/bootstrap@5.0.2/dist/css/bootstrap.min.css" rel="stylesheet" integrity="sha384-EVSTQN3/azprG1Anm3QDgpJLIm9Nao0Yz1ztcQTwFspd3yD65VohhpuuCOmLASjC" crossorigin="anonymous">**

**<!-- Option 1: Bootstrap Bundle with Popper -->**

**<script**

**src="https://cdn.jsdelivr.net/npm/bootstrap@5.0.2/dist/js/bootstrap.bundle.min.js" integrity="sha384-MrcW6ZMFYlzcLA8Nl+NtUVF0sA7MsXsP1UyJoMp4YLEuNSfAP+JcXn/tWtIaxVXM" crossorigin="anonymous"></script>**

**<style type="text/css">**

**.w-60**

```
        {
            width:60%;
        }
    </style>
</head>
<body>
    
    <br>
    
    <br>
    
    <br>
    

</body>
</html>
```

### Bootstrap Containers

- Containers are used to pad the content inside of them.
- In bootstrap there are two containers classes available.

1)container-fluid

2)container

ex:1

```
<!DOCTYPE html>
<html>
```

```
<head>

  <title>MyPage!</title>

  <!-- Add bootstrap -->

<meta charset="utf-8">

<meta name="viewport" content="width=device-width, initial-
scale=1">

<!-- Bootstrap CSS -->

<link
href="https://cdn.jsdelivr.net/npm/bootstrap@5.0.2/dist/css/bootstra
p.min.css" rel="stylesheet" integrity="sha384-
EVSTQN3/azprG1Anm3QDgpJLIm9Nao0Yz1ztcQTwFspd3yD65Vohhpuu
COmLASjC" crossorigin="anonymous">

<!-- Option 1: Bootstrap Bundle with Popper -->

<script
src="https://cdn.jsdelivr.net/npm/bootstrap@5.0.2/dist/js/bootstrap.
bundle.min.js" integrity="sha384-
MrcW6ZMFYlzcLA8Nl+NtUVF0sA7MsXsP1UyJoMp4YLEuNSfAP+JcXn/t
WtlaxVXM" crossorigin="anonymous"></script>

</head>

<body>

  <div class="container-fluid bg-primary">

    <h1>This is Bootstrap</h1>

    <p>This is Website designing classes</p>
```

**</div>**

**</body>**

**</html>**

**ex:2**

**<!DOCTYPE html>**

**<html>**

**<head>**

**<title>MyPage!</title>**

**<!-- Add bootstrap -->**

**<meta charset="utf-8">**

**<meta name="viewport" content="width=device-width, initial-scale=1">**

**<!-- Bootstrap CSS -->**

**<link**

**href="https://cdn.jsdelivr.net/npm/bootstrap@5.0.2/dist/css/bootstrap.min.css" rel="stylesheet" integrity="sha384-EVSTQN3/azprG1Anm3QDgpJLIm9Nao0Yz1ztcQTwFspd3yD65VohhpuuCOMmLASjC" crossorigin="anonymous">**

**<!-- Option 1: Bootstrap Bundle with Popper -->**

**<script**

**src="https://cdn.jsdelivr.net/npm/bootstrap@5.0.2/dist/js/bootstrap.bundle.min.js" integrity="sha384-MrcW6ZMFYlzcLA8Nl+NtUVF0sA7MsXsP1UyJoMp4YLEuNSfAP+JcXn/tWtIaxVXM" crossorigin="anonymous"></script>**

```
</head>
<body>
  <div class="container bg-primary">
    <h1>This is Bootstrap</h1>
    <p>This is Website designing classes</p>
  </div>
</body>
</html>
```

## Bootstrap Display

### d-none

```
<!DOCTYPE html>
<html>
<head>
  <title>IHUB TALENT</title>

  <!-- add bootstrap 5 plugins -->
  <meta charset="utf-8">

  <meta name="viewport" content="width=device-width, initial-
scale=1">

  <link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-
alpha3/dist/css/bootstrap.min.css" rel="stylesheet" >
```



```
<script src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/js/bootstrap.bundle.min.js" ></script>
```

```
</head>
```

```
<body>
```

```
  <div class="container">
```

```
    <h1 class="d-none">This is Heading Tag</h1>
```

```
    <p>This is Paragraph Tag</p>
```

```
  </div>
```

```
</body>
```

```
</html>
```

d-inline

```
<!DOCTYPE html>
```

```
<html>
```

```
<head>
```

```
  <title>IHUB TALENT</title>
```

```
  <!-- add bootstrap 5 plugins -->
```

```
  <meta charset="utf-8">
```

```
  <meta name="viewport" content="width=device-width, initial-scale=1">
```

```
  <link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/css/bootstrap.min.css" rel="stylesheet" >
```

```
<script src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/js/bootstrap.bundle.min.js" ></script>
```

```
</head>
```

```
<body>
```

```
  <div class="container">
```

```
    <div class="d-inline">This is Div1</div>
```

```
    <div class="d-inline">This is Div2</div>
```

```
    <div class="d-inline">This is Div3</div>
```

```
  </div>
```

```
</body>
```

```
</html>
```

d-block

```
<!DOCTYPE html>
```

```
<html>
```

```
<head>
```

```
  <title>IHUB TALENT</title>
```

```
  <!-- add bootstrap 5 plugins -->
```

```
  <meta charset="utf-8">
```

```
  <meta name="viewport" content="width=device-width, initial-scale=1">
```

```
<link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/css/bootstrap.min.css" rel="stylesheet" >
```

```
<script src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/js/bootstrap.bundle.min.js" ></script>
```

```
</head>
```

```
<body>
```

```
  <div class="container">
```

```
    <span class="d-block">This is Span1 </span>
```

```
    <span class="d-block">This is Span2 </span>
```

```
    <span class="d-block">This is Span3 </span>
```

```
  </div>
```

```
</body>
```

```
</html>
```

### d-inline-block

```
<!DOCTYPE html>
```

```
<html>
```

```
<head>
```

```
  <title>IHUB TALENT</title>
```

```
  <!-- add bootstrap 5 plugins -->
```

```
  <meta charset="utf-8">
```

```
<meta name="viewport" content="width=device-width, initial-scale=1">
```

```
<link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/css/bootstrap.min.css" rel="stylesheet" >
```

```
<script src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/js/bootstrap.bundle.min.js" ></script>
```

```
</head>
```

```
<body>
```

```
    <div class="container">
```

```
        <span class="d-inline-block border border-primary w-25">This is Span1 </span>
```

```
        <span class="d-inline-block border border-info w-25">This is Span2 </span>
```

```
        <span class="d-inline-block border border-secondary w-25">This is Span3 </span>
```

```
    </div>
```

```
</body>
```

```
</html>
```

### Bootstrap spacing

- Spacing utility is used to assign the responsive friendly margin or padding values to an element or a subset of its sides with shorthand classes.
- It includes individual properties , all properties ,vertical properties and horizontal properties.

## Bootstrap margin

<b>m</b>	<b>for classes that set margin</b>
<u>Where sides is one of:</u>	
<b>t</b>	for classes that set margin-top or padding-top
<b>b</b>	for classes that set margin-bottom or padding-bottom.
<b>s</b>	(start) for classes that set margin-left or padding-left in LTR, margin-right or padding-right in RTL.
<b>e</b>	(end) for classes that set margin-right or padding-right in LTR, margin-left or padding-left in RTL.
<b>x</b>	for classes that set both *-left and *-right.
<b>y</b>	for classes that set both *-top and *-bottom blank - for classes that set a margin or padding on all 4 sides of the element.

### Where size is one of:

<b>0</b>	for classes that eliminate the margin or padding by setting it to 0.
<b>1</b>	(by default) for classes that set the margin or padding to \$spacer * .25
<b>2</b>	(by default) for classes that set the margin or padding to \$spacer * .5
<b>3</b>	(by default) for classes that set the margin or padding to \$spacer.
<b>4</b>	(by default) for classes that set the margin or padding to \$spacer * 1.5

5

(by default) for classes that set  
the margin or padding to \$spacer  
\* 3  
auto - for classes that set the  
margin to auto

**ex:1**

```
<!DOCTYPE html>
```

```
<html>
```

```
<head>
```

```
  <title>IHUB TALENT</title>
```

```
  <!-- add bootstrap 5 plugins -->
```

```
  <meta charset="utf-8">
```

```
  <meta name="viewport" content="width=device-width, initial-  
scale=1">
```

```
  <link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-  
alpha3/dist/css/bootstrap.min.css" rel="stylesheet" >
```

```
  <script src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-  
alpha3/dist/js/bootstrap.bundle.min.js" ></script>
```

```
</head>
```

```
<body>
```

```
  <div class="container-fluid">
```

```
    <h1 class="border border-primary m-0">This is  
heading1 tag</h1>
```

```
    <h1 class="border border-primary m-1">This is  
heading2 tag</h1>
```

```
    <h1 class="border border-primary m-2">This is  
heading3 tag</h1>
```

```
    <h1 class="border border-primary m-3">This is  
heading4 tag</h1>
```

```
    <h1 class="border border-primary m-4">This is  
heading5 tag</h1>
```

```
    <h1 class="border border-primary m-5">This is  
heading6 tag</h1>
```

```
  </div>
```

```
</body>
```

```
</html>
```

## ex:2

```
<!DOCTYPE html>
```

```
<html>
```

```
<head>
```

```
  <title>IHUB TALENT</title>
```

```
  <!-- add bootstrap 5 plugins -->
```

```
  <meta charset="utf-8">
```

```
  <meta name="viewport" content="width=device-width, initial-  
scale=1">
```

```
<link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/css/bootstrap.min.css" rel="stylesheet" >
```

```
<script src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/js/bootstrap.bundle.min.js" ></script>
```

```
</head>
```

```
<body>
```

```
  <div class="container-fluid">
```

```
    <h1 class="border border-primary mt-5">This is  
heading1 tag</h1>
```

```
    <h1 class="border border-primary ms-5">This is  
heading2 tag</h1>
```

```
    <h1 class="border border-primary mb-5">This is  
heading3 tag</h1>
```

```
    <h1 class="border border-primary me-5">This is  
heading4 tag</h1>
```

```
    <h1 class="border border-primary mx-5">This is  
heading5 tag</h1>
```

```
    <h1 class="border border-primary my-5">This is  
heading6 tag</h1>
```

```
  </div>
```

```
</body>
```

```
</html>
```



## Bootstrap padding

**p**

for classes that set padding

### Where sides is one of:

<b>t</b>	for classes that set margin-top or padding-top.
<b>b</b>	for classes that set margin-bottom or padding-bottom.
<b>s</b>	(start) for classes that set margin-left or padding-left in LTR, margin-right or padding-right in RTL
<b>e</b>	(end) for classes that set margin-right or padding-right in LTR, margin-left or padding-left in RTL.
<b>x</b>	for classes that set both *-left and *-right.
<b>y</b>	for classes that set both *-top and *-bottom blank - for classes that set a margin or padding on all 4 sides of the element.

### Where size is one of:

<b>0</b>	for classes that eliminate the margin or padding by setting it to 0.
<b>1</b>	(by default) for classes that set the margin or padding to \$spacer * .25
<b>2</b>	(by default) for classes that set the margin or padding to \$spacer * .5

3	(by default) for classes that set the margin or padding to \$spacer
4	(by default) for classes that set the margin or padding to \$spacer * 1.5
5	(by default) for classes that set the margin or padding to \$spacer * 3 auto - for classes that set the margin to auto.

### ex:1

```
<!DOCTYPE html>
```

```
<html>
```

```
<head>
```

```
  <title>IHUB TALENT</title>
```

```
  <!-- add bootstrap 5 plugins -->
```

```
  <meta charset="utf-8">
```

```
  <meta name="viewport" content="width=device-width, initial-scale=1">
```

```
  <link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/css/bootstrap.min.css" rel="stylesheet" >
```

```
  <script src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/js/bootstrap.bundle.min.js" ></script>
```

**</head>**

**<body>**

**<div class="container-fluid">**

**<h1 class="border border-primary p-0">This is  
heading1 tag</h1>**

**<h1 class="border border-primary p-1">This is  
heading2 tag</h1>**

**<h1 class="border border-primary p-2">This is  
heading3 tag</h1>**

**<h1 class="border border-primary p-3">This is  
heading4 tag</h1>**

**<h1 class="border border-primary p-4">This is  
heading5 tag</h1>**

**<h1 class="border border-primary p-5">This is  
heading6 tag</h1>**

**</div>**

**</body>**

**</html>**

**ex:2**

**<!DOCTYPE html>**

**<html>**

**<head>**

**<title>IHUB TALENT</title>**

**<!-- add bootstrap 5 plugins -->**

**<meta charset="utf-8">**

```
<meta name="viewport" content="width=device-width, initial-scale=1">
```

```
<link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/css/bootstrap.min.css" rel="stylesheet" >
```

```
<script src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/js/bootstrap.bundle.min.js" ></script>
```

```
</head>
```

```
<body>
```

```
  <div class="container-fluid">
```

```
    <h1 class="border border-primary pt-5">This is  
heading1 tag</h1>
```

```
    <h1 class="border border-primary ps-5">This is  
heading2 tag</h1>
```

```
    <h1 class="border border-primary pe-5">This is  
heading3 tag</h1>
```

```
    <h1 class="border border-primary pb-5">This is  
heading4 tag</h1>
```

```
    <h1 class="border border-primary px-5">This is  
heading5 tag</h1>
```

```
    <h1 class="border border-primary py-5">This is  
heading6 tag</h1>
```

```
  </div>
```

```
</body>
```

</html>

## Bootstrap 5 Grid System

- Bootstrap's grid system is built with flexboxes.
- To create a row in a grid system we need to use "row" class.
- It allows to create 12 columns in a single row and It is not required that we must use all 12 columns.
- The Grid system is responsive and the column will rearrange automatically dependent upon the screen size.

## Grid class

- According Bootstrap5 ,A grid system contains 6 classes.

col-	extra small device
col-sm-	small devices
col-md-	medium devices
col-lg-	large devices
col-xl-	xlarge devices.
col-xxl-	too xlarge device

### ex:1

```
<!DOCTYPE html>
```

```
<html>
```

```
<head>
```

```
  <title>IHUB TALENT</title>
```

```
  <!-- add bootstrap 5 plugins -->
```

```
  <meta charset="utf-8">
```

```
<meta name="viewport" content="width=device-width, initial-scale=1">
```

```
<link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/css/bootstrap.min.css" rel="stylesheet" >
```

```
<script src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/js/bootstrap.bundle.min.js" ></script>
```

```
</head>
```

```
<body>
```

```
  <div class="container-fluid mt-5">
```

```
    <div class="row">
```

```
      <!-- 1 column occupies 12 column space -->
```

```
      <div class="col bg-primary">column1</div>
```

```
    </div>
```

```
  </div>
```

```
</body>
```

```
</html>
```

ex:2

```
<!DOCTYPE html>
```

```
<html>
```

```
<head>
```

```
  <title>IHUB TALENT</title>
```

```
<!-- add bootstrap 5 plugins -->
```

```
<meta charset="utf-8">
```

```
<meta name="viewport" content="width=device-width, initial-scale=1">
```

```
<link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/css/bootstrap.min.css" rel="stylesheet" >
```

```
<script src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/js/bootstrap.bundle.min.js" ></script>
```

```
</head>
```

```
<body>
```

```
  <div class="container-fluid mt-5">
```

```
    <div class="row">
```

```
      <!-- 2 columns occupies 6 column space -->
```

```
      <div class="col bg-primary">column1</div>
```

```
      <div class="col bg-info">column2</div>
```

```
    </div>
```

```
  </div>
```

```
</body>
```

**</html>**

**ex:3**

**<!DOCTYPE html>**

**<html>**

**<head>**

**<title>IHUB TALENT</title>**

**<!-- add bootstrap 5 plugins -->**

**<meta charset="utf-8">**

**<meta name="viewport" content="width=device-width, initial-scale=1">**

**<link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/css/bootstrap.min.css" rel="stylesheet" >**

**<script src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/js/bootstrap.bundle.min.js" ></script>**

**</head>**

**<body>**

**<div class="container-fluid mt-5">**

**<div class="row">**

**<!-- 3 columns occupies 4 column space -->**

**<div class="col bg-primary">column1</div>**



```
<div class="col bg-info">column2</div>
```

```
<div class="col bg-warning">column3</div>
```

```
</div>
```

```
</div>
```

```
</body>
```

```
</html>
```

**ex:4**

```
<!DOCTYPE html>
```

```
<html>
```

```
<head>
```

```
  <title>IHUB TALENT</title>
```

```
  <!-- add bootstrap 5 plugins -->
```

```
  <meta charset="utf-8">
```

```
  <meta name="viewport" content="width=device-width, initial-  
scale=1">
```

```
  <link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-  
alpha3/dist/css/bootstrap.min.css" rel="stylesheet" >
```

```
  <script src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-  
alpha3/dist/js/bootstrap.bundle.min.js" ></script>
```

**</head>**

**<body>**

**<div class="container-fluid mt-5">**

**<div class="row">**

**<!-- 4 columns occupies 3 column space -->**

**<div class="col bg-primary">column1</div>**

**<div class="col bg-info">column2</div>**

**<div class="col bg-warning">column3</div>**

**<div class="col bg-success">column4</div>**

**</div>**

**</div>**

**</body>**

**</html>**

**ex:5**

**<!DOCTYPE html>**

**<html>**

**<head>**

**<title>IHUB TALENT</title>**

**<!-- add bootstrap 5 plugins -->**

**<meta charset="utf-8">**

**<meta name="viewport" content="width=device-width, initial-scale=1">**

**<link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/css/bootstrap.min.css" rel="stylesheet" >**

**<script src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/js/bootstrap.bundle.min.js" ></script>**

**</head>**

**<body>**

**<div class="container-fluid mt-5">**

**<div class="row">**

**<!-- 5 columns occupies 3 column space -->**

**<div class="col bg-primary">column1</div>**

**<div class="col bg-info">column2</div>**

**<div class="col bg-warning">column3</div>**

**<div class="col bg-success">column4</div>**

```
        <div class="col bg-danger">column5</div>
    </div>
```

```
</div>
```

```
</body>
```

```
</html>
```

ex:6

```
<!DOCTYPE html>
```

```
<html>
```

```
<head>
```

```
    <title>IHUB TALENT</title>
```

```
    <!-- add bootstrap 5 plugins -->
```

```
    <meta charset="utf-8">
```

```
    <meta name="viewport" content="width=device-width, initial-
scale=1">
```

```
    <link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-
alpha3/dist/css/bootstrap.min.css" rel="stylesheet" >
```

```
    <script src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-
alpha3/dist/js/bootstrap.bundle.min.js" ></script>
```

```
</head>
```

```
<body>
```

```
<div class="container-fluid mt-5">
```

```
<div class="row">
```

```
<div class="col-2 bg-primary">column1</div>
```

```
<div class="col-4 bg-info">column2</div>
```

```
<div class="col-6 bg-warning">column3</div>
```

```
</div>
```

```
</div>
```

```
</body>
```

```
</html>
```

ex:7

```
<!DOCTYPE html>
```

```
<html>
```

```
<head>
```

```
<title>IHUB TALENT</title>
```

```
<!-- add bootstrap 5 plugins -->
```

```
<meta charset="utf-8">
```

```
<meta name="viewport" content="width=device-width, initial-scale=1">
```

```
<link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/css/bootstrap.min.css" rel="stylesheet" >
```

```
<script src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/js/bootstrap.bundle.min.js" ></script>
```

```
</head>
```

```
<body>
```

```
  <div class="container-fluid mt-5">
```

```
    <div class="row">
```

```
      <div class="col-lg-4 bg-primary">column1</div>
```

```
      <div class="col-lg-4 bg-info">column2</div>
```

```
      <div class="col-lg-4 bg-warning">column3</div>
```

```
    </div>
```

```
    <br><br>
```

```
    <div class="row">
```

```
      <div class="col-lg-4 col-md-4 bg-primary">column1</div>
```

```
      <div class="col-lg-4 col-md-4 bg-info">column2</div>
```

```
      <div class="col-lg-4 col-md-4 bg-warning">column3</div>
```

```
    </div>
```

```
<br><br>
```

```
<div class="row">
```

```
    <div class="col-lg-4 col-md-4 col-sm-4 bg-  
primary">column1</div>
```

```
    <div class="col-lg-4 col-md-4 col-sm-4 bg-  
info">column2</div>
```

```
    <div class="col-lg-4 col-md-4 col-sm-4 bg-  
warning">column3</div>
```

```
</div>
```

```
<br><br>
```

```
<div class="row">
```

```
    <div class="col-lg-4 col-md-4 col-sm-4 col-12 bg-  
primary">column1</div>
```

```
    <div class="col-lg-4 col-md-4 col-sm-4 col-12 bg-  
info">column2</div>
```

```
    <div class="col-lg-4 col-md-4 col-sm-4 col-12 bg-  
warning">column3</div>
```

```
</div>
```

```
</div>
```

```
</body>
```

```
</html>
```

## Bootstrap images

➤ 3 classes to display the images.

1)rounded image (rounded)

2)circle image (rounded-circle)

3)thumbnail (img-thumbnail)

### 1)rounded image

```
<!DOCTYPE html>
```

```
<html>
```

```
<head>
```

```
  <title>IHUB TALENT</title>
```

```
  <!-- add bootstrap 5 plugins -->
```

```
  <meta charset="utf-8">
```

```
  <meta name="viewport" content="width=device-width, initial-  
scale=1">
```

```
  <link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-  
alpha3/dist/css/bootstrap.min.css" rel="stylesheet" >
```

```
  <script src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-  
alpha3/dist/js/bootstrap.bundle.min.js" ></script>
```

```
</head>
```

```
<body>
```



```
<div class="container-fluid mt-5">
    
</div>
</body>
</html>
```

## 2)circle image

```
<!DOCTYPE html>
<html>
<head>
    <title>IHUB TALENT</title>

    <!-- add bootstrap 5 plugins -->
    <meta charset="utf-8">

    <meta name="viewport" content="width=device-width, initial-
scale=1">

    <link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-
alpha3/dist/css/bootstrap.min.css" rel="stylesheet" >

    <script src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-
alpha3/dist/js/bootstrap.bundle.min.js" ></script>

</head>
```

```
<body>
    <div class="container-fluid mt-5">
        
    </div>
</body>
</html>
```

### 3)thumbnail image

```
<!DOCTYPE html>
<html>
<head>
    <title>IHUB TALENT</title>

    <!-- add bootstrap 5 plugins -->
    <meta charset="utf-8">

    <meta name="viewport" content="width=device-width, initial-
scale=1">

    <link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-
alpha3/dist/css/bootstrap.min.css" rel="stylesheet" >

    <script src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-
alpha3/dist/js/bootstrap.bundle.min.js" ></script>

</head>
```

```
<body>

    <div class="container-fluid mt-5">

        

    </div>

</body>
</html>
```

### Bootstrap float

- Bootstrap float is used for alignment of an element.

#### ex:1

```
<!DOCTYPE html>

<html>

<head>

    <title>IHUB TALENT</title>

    <!-- add bootstrap 5 plugins -->

    <meta charset="utf-8">

    <meta name="viewport" content="width=device-width, initial-
scale=1">

    <link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-
alpha3/dist/css/bootstrap.min.css" rel="stylesheet" >

    <script src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-
alpha3/dist/js/bootstrap.bundle.min.js" ></script>
```

```
</head>
<body>
    <div class="container-fluid mt-5">
        
        
    </div>
</body>
</html>
```

### ex:2

```
<!DOCTYPE html>
<html>
<head>
    <title>IHUB TALENT</title>

    <!-- add bootstrap 5 plugins -->
    <meta charset="utf-8">

    <meta name="viewport" content="width=device-width, initial-
scale=1">

    <link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-
alpha3/dist/css/bootstrap.min.css" rel="stylesheet" >
```

```
<script src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/js/bootstrap.bundle.min.js" ></script>
```

```
</head>
```

```
<body>
```

```
    <div class="container-fluid mt-5">
```

```
        
```

```
    </div>
```

```
</body>
```

```
</html>
```

## Bootstrap Design

```
<!DOCTYPE html>
```

```
<html>
```

```
<head>
```

```
    <title>IHUB TALENT</title>
```

```
    <!-- add bootstrap 5 plugins -->
```

```
    <meta charset="utf-8">
```

```
    <meta name="viewport" content="width=device-width, initial-scale=1">
```

```
    <link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/css/bootstrap.min.css" rel="stylesheet" >
```

```
<script src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/js/bootstrap.bundle.min.js" ></script>
```

```
</head>
```

```
<body>
```

```
  <div class="container-fluid mt-5">
```

```
    <div class="row">
```

```
      <div class="col-lg-4 col-md-4 col-sm-6 col-12">
```

```
        
```

```
      </div>
```

```
      <div class="col-lg-4 col-md-4 col-sm-6 col-12">
```

```
        
```

```
      </div>
```

```
      <div class="col-lg-4 col-md-4 col-sm-6 col-12">
```

```
        
```

```
      </div>
```

```
    </div>
```

```
  </div>
```

```
</body>
```

</html>

## Bootstrap tables

- Tables are used to represent the data in the form of rows and columns.

### ex:1

```
<!DOCTYPE html>
```

```
<html>
```

```
<head>
```

```
  <title>IHUB TALENT</title>
```

```
  <!-- add bootstrap 5 plugins -->
```

```
  <meta charset="utf-8">
```

```
  <meta name="viewport" content="width=device-width, initial-  
scale=1">
```

```
  <link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-  
alpha3/dist/css/bootstrap.min.css" rel="stylesheet" >
```

```
  <script src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-  
alpha3/dist/js/bootstrap.bundle.min.js" ></script>
```

```
</head>
```

```
<body>
```

```
  <div class="container-fluid mt-5">
```

```
<table class="table">
  <tr>
    <th>ID</th>
    <th>NAME</th>
    <th>ADD</th>
  </tr>
  <tr>
    <td>101</td>
    <td>Alan</td>
    <td>Texas</td>
  </tr>
  <tr>
    <td>102</td>
    <td>Jessi</td>
    <td>Florida</td>
  </tr>
  <tr>
    <td>103</td>
    <td>Mark</td>
    <td>Chicago</td>
  </tr>
  <tr>
    <td>104</td>
    <td>Lisa</td>
```



```
        <td>California</td>
    </tr>
</table>
```

```
    </div>
</body>
</html>
```

### ex:2

```
<!DOCTYPE html>
<html>
<head>
    <title>IHUB TALENT</title>

    <!-- add bootstrap 5 plugins -->
    <meta charset="utf-8">

    <meta name="viewport" content="width=device-width, initial-
scale=1">

    <link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-
alpha3/dist/css/bootstrap.min.css" rel="stylesheet" >

    <script src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-
alpha3/dist/js/bootstrap.bundle.min.js" ></script>

</head>
```

```
<body>
```

```
<div class="container-fluid mt-5">
```

```
<table class="table table-bordered">
```

```
<tr>
```

```
<th>ID</th>
```

```
<th>NAME</th>
```

```
<th>ADD</th>
```

```
</tr>
```

```
<tr>
```

```
<td>101</td>
```

```
<td>Alan</td>
```

```
<td>Texas</td>
```

```
</tr>
```

```
<tr>
```

```
<td>102</td>
```

```
<td>Jessi</td>
```

```
<td>Florida</td>
```

```
</tr>
```

```
<tr>
```

```
<td>103</td>
```

```
<td>Mark</td>
```

```
<td>Chicago</td>
```

```
</tr>
```

```
<tr>
```

```
        <td>104</td>
        <td>Lisa</td>
        <td>California</td>
    </tr>
</table>
```

```
</div>
</body>
</html>
```

### ex:3

```
<!DOCTYPE html>
<html>
<head>
    <title>IHUB TALENT</title>

    <!-- add bootstrap 5 plugins -->
    <meta charset="utf-8">

    <meta name="viewport" content="width=device-width, initial-
scale=1">

    <link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-
alpha3/dist/css/bootstrap.min.css" rel="stylesheet" >

    <script src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-
alpha3/dist/js/bootstrap.bundle.min.js" ></script>
```

```
</head>
```

```
<body>
```

```
  <div class="container-fluid mt-5">
```

```
    <table class="table table-borderless">
```

```
      <tr>
```

```
        <th>ID</th>
```

```
        <th>NAME</th>
```

```
        <th>ADD</th>
```

```
      </tr>
```

```
      <tr>
```

```
        <td>101</td>
```

```
        <td>Alan</td>
```

```
        <td>Texas</td>
```

```
      </tr>
```

```
      <tr>
```

```
        <td>102</td>
```

```
        <td>Jessi</td>
```

```
        <td>Florida</td>
```

```
      </tr>
```

```
      <tr>
```

```
        <td>103</td>
```

```
        <td>Mark</td>
```

```
        <td>Chicago</td>
```

```
        </tr>
        <tr>
            <td>104</td>
            <td>Lisa</td>
            <td>California</td>
        </tr>
    </table>
```

```
</div>
```

```
</body>
```

```
</html>
```

**ex:4**

```
<!DOCTYPE html>
```

```
<html>
```

```
<head>
```

```
    <title>IHUB TALENT</title>
```

```
    <!-- add bootstrap 5 plugins -->
```

```
    <meta charset="utf-8">
```

```
    <meta name="viewport" content="width=device-width, initial-
scale=1">
```

```
    <link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-
alpha3/dist/css/bootstrap.min.css" rel="stylesheet" >
```

```
<script src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/js/bootstrap.bundle.min.js" ></script>
```

```
</head>
```

```
<body>
```

```
<div class="container-fluid mt-5">
```

```
<table class="table table-bordered table-hover">
```

```
<tr>
```

```
<th>ID</th>
```

```
<th>NAME</th>
```

```
<th>ADD</th>
```

```
</tr>
```

```
<tr>
```

```
<td>101</td>
```

```
<td>Alan</td>
```

```
<td>Texas</td>
```

```
</tr>
```

```
<tr>
```

```
<td>102</td>
```

```
<td>Jessi</td>
```

```
<td>Florida</td>
```

```
</tr>
```

```
<tr>
```

```
<td>103</td>
```

```
        <td>Mark</td>
        <td>Chicago</td>
    </tr>
    <tr>
        <td>104</td>
        <td>Lisa</td>
        <td>California</td>
    </tr>
</table>
```

```
</div>
```

```
</body>
```

```
</html>
```

ex:5

```
<!DOCTYPE html>
```

```
<html>
```

```
<head>
```

```
    <title>IHUB TALENT</title>
```

```
    <!-- add bootstrap 5 plugins -->
```

```
    <meta charset="utf-8">
```

```
    <meta name="viewport" content="width=device-width, initial-
scale=1">
```

```
<link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/css/bootstrap.min.css" rel="stylesheet" >
```

```
<script src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/js/bootstrap.bundle.min.js" ></script>
```

```
</head>
```

```
<body>
```

```
<div class="container-fluid mt-5">
```

```
<table class="table table-bordered table-striped">
```

```
<tr>
```

```
<th>ID</th>
```

```
<th>NAME</th>
```

```
<th>ADD</th>
```

```
</tr>
```

```
<tr>
```

```
<td>101</td>
```

```
<td>Alan</td>
```

```
<td>Texas</td>
```

```
</tr>
```

```
<tr>
```

```
<td>102</td>
```

```
<td>Jessi</td>
```

```
<td>Florida</td>
```

```
</tr>
```



```
        <tr>
            <td>103</td>
            <td>Mark</td>
            <td>Chicago</td>
        </tr>
        <tr>
            <td>104</td>
            <td>Lisa</td>
            <td>California</td>
        </tr>
    </table>
```

```
</div>
```

```
</body>
```

```
</html>
```

ex:6

```
<!DOCTYPE html>
```

```
<html>
```

```
<head>
```

```
    <title>IHUB TALENT</title>
```

```
    <!-- add bootstrap 5 plugins -->
```

```
    <meta charset="utf-8">
```

```
<meta name="viewport" content="width=device-width, initial-scale=1">
```

```
<link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/css/bootstrap.min.css" rel="stylesheet" >
```

```
<script src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/js/bootstrap.bundle.min.js" ></script>
```

```
</head>
```

```
<body>
```

```
  <div class="container-fluid mt-5">
```

```
    <table class="table table-bordered table-dark">
```

```
      <tr>
```

```
        <th>ID</th>
```

```
        <th>NAME</th>
```

```
        <th>ADD</th>
```

```
      </tr>
```

```
      <tr>
```

```
        <td>101</td>
```

```
        <td>Alan</td>
```

```
        <td>Texas</td>
```

```
      </tr>
```

```
      <tr>
```

```
        <td>102</td>
```

```
        <td>Jessi</td>
        <td>Florida</td>
    </tr>
    <tr>
        <td>103</td>
        <td>Mark</td>
        <td>Chicago</td>
    </tr>
    <tr>
        <td>104</td>
        <td>Lisa</td>
        <td>California</td>
    </tr>
</table>
```

```
</div>
```

```
</body>
```

```
</html>
```

ex:7

```
<!DOCTYPE html>
```

```
<html>
```

```
<head>
```

```
    <title>IHUB TALENT</title>
```

```
    <!-- add bootstrap 5 plugins -->
```

**<meta charset="utf-8">**

**<meta name="viewport" content="width=device-width, initial-scale=1">**

**<link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/css/bootstrap.min.css" rel="stylesheet" >**

**<script src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/js/bootstrap.bundle.min.js" ></script>**

**</head>**

**<body>**

**<div class="container-fluid mt-5">**

**<table class="table table-bordered table-striped table-info">**

**<tr>**

**<th>ID</th>**

**<th>NAME</th>**

**<th>ADD</th>**

**</tr>**

**<tr>**

**<td>101</td>**

**<td>Alan</td>**

**<td>Texas</td>**

</tr>

<tr>

<td>102</td>

<td>Jessi</td>

<td>Florida</td>

</tr>

<tr>

<td>103</td>

<td>Mark</td>

<td>Chicago</td>

</tr>

<tr>

<td>104</td>

<td>Lisa</td>

<td>California</td>

</tr>

</table>

</div>

</body>

</html>

## Bootstrap alerts

- Bootstrap has given a simple way to create alerts by using "alert" class along with contextual state classes.

**We have following contextual state classes**

**ex:**

alert-success

alert-danger

alert-warning

alert-info

**ex:1**

```
<!DOCTYPE html>
```

```
<html>
```

```
<head>
```

```
  <title>IHUB TALENT</title>
```

```
  <!-- add bootstrap 5 plugins -->
```

```
  <meta charset="utf-8">
```

```
  <meta name="viewport" content="width=device-width, initial-  
scale=1">
```

```
  <link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-  
alpha3/dist/css/bootstrap.min.css" rel="stylesheet" >
```

```
<script src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/js/bootstrap.bundle.min.js" ></script>
```

```
</head>
```

```
<body>
```

```
  <div class="container mt-5">
```

```
    <div class="alert alert-warning">
```

```
      <strong>Warning!</strong>Please focus in class
```

```
    </div>
```

```
    <div class="alert alert-danger">
```

```
      <strong>Danger!</strong> Don't loose your hope
```

```
    </div>
```

```
    <div class="alert alert-info">
```

```
      <strong>INFO!</strong> React is going to start
```

next week

```
    </div>
```

```
    <div class="alert alert-success">
```

```
      <strong>Good!</strong> Project Done
```

successfully.

```
    </div>
```

```
  </div>
```

```
</body>
```

**</html>**

**ex:2**

**<!DOCTYPE html>**

**<html>**

**<head>**

**<title>IHUB TALENT</title>**

**<!-- add bootstrap 5 plugins -->**

**<meta charset="utf-8">**

**<meta name="viewport" content="width=device-width, initial-scale=1">**

**<link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/css/bootstrap.min.css" rel="stylesheet" >**

**<script src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/js/bootstrap.bundle.min.js" ></script>**

**</head>**

**<body>**

**<div class="container mt-5">**

**<div class="alert alert-warning collapse">**

**<strong>Warning!</strong>Please focus in class**

**</div>**

**</div>**



**</body>**

**</html>**

**ex:3**

**<!DOCTYPE html>**

**<html>**

**<head>**

**<title>IHUB TALENT</title>**

**<!-- add bootstrap 5 plugins -->**

**<meta charset="utf-8">**

**<meta name="viewport" content="width=device-width, initial-scale=1">**

**<link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/css/bootstrap.min.css" rel="stylesheet" >**

**<script src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/js/bootstrap.bundle.min.js" ></script>**

**</head>**

**<body>**

**<div class="container mt-5">**

**<div class="alert alert-warning alert-dismissible">**

**<strong>Warning!</strong>Please focus in class**

```
        <button class="btn-close" data-bs-  
dismiss="alert"></button>  
    </div>  
</div>  
</body>  
</html>
```

### Bootstrap buttons

- Bootstrap 5 has given "btn" class to declare a button along with contextual state classes.
- ✓ We have following contextual state classes.

ex:

btn-default  
btn-primary  
btn-secondary  
btn-info  
btn-warning  
btn-danger  
btn-success  
btn-light  
btn-link  
and etc.

ex:1

```
<!DOCTYPE html>  
<html>
```

**<head>**

**<title>IHUB TALENT</title>**

**<!-- add bootstrap 5 plugins -->**

**<meta charset="utf-8">**

**<meta name="viewport" content="width=device-width, initial-scale=1">**

**<link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/css/bootstrap.min.css" rel="stylesheet" >**

**<script src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/js/bootstrap.bundle.min.js" ></script>**

**</head>**

**<body>**

**<div class="container mt-5">**

**<button>Normal</button>**

**<button class="btn btn-primary">primary</button>**

**<button class="btn btn-secondary">secondary</button>**

**<button class="btn btn-warning">warning</button>**

**<button class="btn btn-info">info</button>**

**<button class="btn btn-danger">danger</button>**

**<button class="btn btn-success">success</button>**

**</div>**

**</body>**

**</html>**

**ex:2**

**<!DOCTYPE html>**

**<html>**

**<head>**

**<title>IHUB TALENT</title>**

**<!-- add bootstrap 5 plugins -->**

**<meta charset="utf-8">**

**<meta name="viewport" content="width=device-width, initial-scale=1">**

**<link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/css/bootstrap.min.css" rel="stylesheet" >**

**<script src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/js/bootstrap.bundle.min.js" ></script>**

**</head>**

**<body>**

**<div class="container mt-5">**

**<button>Normal</button>**

```
<button class="btn btn-outline-  
primary">primary</button>
```

```
<button class="btn btn-outline-  
secondary">secondary</button>
```

```
<button class="btn btn-outline-  
warning">warning</button>
```

```
<button class="btn btn-outline-info">info</button>
```

```
<button class="btn btn-outline-  
danger">danger</button>
```

```
<button class="btn btn-outline-  
success">success</button>
```

```
</div>
```

```
</body>
```

```
</html>
```

**ex:3**

```
<!DOCTYPE html>
```

```
<html>
```

```
<head>
```

```
<title>IHUB TALENT</title>
```

```
<!-- add bootstrap 5 plugins -->
```

```
<meta charset="utf-8">
```

```
<meta name="viewport" content="width=device-width, initial-  
scale=1">
```

```
<link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/css/bootstrap.min.css" rel="stylesheet" >
```

```
<script src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/js/bootstrap.bundle.min.js" ></script>
```

```
</head>
```

```
<body>
```

```
  <div class="container mt-5">
```

```
    <a href="" class="btn btn-primary"> ReadMe </a>
```

```
  </div>
```

```
</body>
```

```
</html>
```

ex:4

```
<!DOCTYPE html>
```

```
<html>
```

```
<head>
```

```
  <title>IHUB TALENT</title>
```

```
  <!-- add bootstrap 5 plugins -->
```

```
  <meta charset="utf-8">
```

```
  <meta name="viewport" content="width=device-width, initial-scale=1">
```

```
<link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/css/bootstrap.min.css" rel="stylesheet" >
```

```
<script src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/js/bootstrap.bundle.min.js" ></script>
```

```
</head>
```

```
<body>
```

```
  <div class="container mt-5">
```

```
    <button class="btn btn-link"> ReadMe </button>
```

```
  </div>
```

```
</body>
```

```
</html>
```

### Bootstrap button groups

- A "btn-group" class is used to group the buttons in bootstrap.

#### ex:1

```
<!DOCTYPE html>
```

```
<html>
```

```
<head>
```

```
  <title>IHUB TALENT</title>
```

```
  <!-- add bootstrap 5 plugins -->
```

```
  <meta charset="utf-8">
```

```
<meta name="viewport" content="width=device-width, initial-scale=1">
```

```
<link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/css/bootstrap.min.css" rel="stylesheet" >
```

```
<script src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/js/bootstrap.bundle.min.js" ></script>
```

```
</head>
```

```
<body>
```

```
    <div class="container mt-5">
```

```
        <div class="btn-group">
```

```
            <button class="btn btn-primary"> HOME
```

```
</button>
```

```
            <button class="btn btn-info"> ABOUT </button>
```

```
            <button class="btn btn-warning"> SERVICE
```

```
</button>
```

```
        </div>
```

```
    </div>
```

```
</body>
```

```
</html>
```

ex:2

```
<!DOCTYPE html>
```

```
<html>
```



**<head>**

**<title>IHUB TALENT</title>**

**<!-- add bootstrap 5 plugins -->**

**<meta charset="utf-8">**

**<meta name="viewport" content="width=device-width, initial-scale=1">**

**<link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/css/bootstrap.min.css" rel="stylesheet" >**

**<script src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/js/bootstrap.bundle.min.js" ></script>**

**</head>**

**<body>**

**<div class="container mt-5">**

**<div class="btn-group btn-group-sm">**

**<button class="btn btn-primary"> HOME**

**</button>**

**<button class="btn btn-info"> ABOUT </button>**

**<button class="btn btn-warning"> SERVICE**

**</button>**

```

        </div>
        <div class="btn-group">
            <button class="btn btn-primary"> HOME
        </button>
            <button class="btn btn-info"> ABOUT </button>
            <button class="btn btn-warning"> SERVICE
        </button>
        </div>
        <div class="btn-group btn-group-lg">
            <button class="btn btn-primary"> HOME
        </button>
            <button class="btn btn-info"> ABOUT </button>
            <button class="btn btn-warning"> SERVICE
        </button>
        </div>
    </div>
</body>
</html>

```

### Bootstrap Glyphicons

- Bootstrap icons are provided by Glyphicons.
- Bootstrap provide 260 Glyphicons.
- As Glyphicon are font based,their color and size automatically adjusts to the element color and size on which is being used.
- Glyphicons can be used in text,buttons,toolbars,navigation,forms and etc.

We can see list of Glyphicons using below url.

ex:

<http://getbootstrap.com/docs/3.3/components/>

To use Bootstrap icons in your code you'll require an `<i>` tag with an individual icon class `.bi-*` applied on it. The general syntax for using Bootstrap icons is:

```
<i class="bi-class-name"></i>
```

To work with bootstrap glyphicons we need to add below cdn link.

ex:

```
<!-- Bootstrap Font Icon CSS -->
```

```
<link rel="stylesheet" href="https://cdn.jsdelivr.net/npm/bootstrap-icons@1.5.0/font/bootstrap-icons.css">
```

ex:1

```
<!DOCTYPE html>
```

```
<html>
```

```
<head>
```

```
<title>IHUB TALENT</title>
```

```
<!-- add bootstrap 5 plugins -->
```

```
<meta charset="utf-8">
```

```
<meta name="viewport" content="width=device-width, initial-scale=1">
```

```
<link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/css/bootstrap.min.css" rel="stylesheet" >
```

```
<script src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/js/bootstrap.bundle.min.js" ></script>
```

```
<!-- Bootstrap Font Icon CSS -->
```

```
<link rel="stylesheet" href="https://cdn.jsdelivr.net/npm/bootstrap-icons@1.5.0/font/bootstrap-icons.css">
```

```
</head>
```

```
<body>
```

```
<div class="container mt-5">
```

```
<div class="bi-heart text-danger"></div>
```

```
</div>
```

```
</body>
```

```
</html>
```

ex:2

```
<!DOCTYPE html>
```

```
<html>
```

```
<head>
```

```
<title>IHUB TALENT</title>
```

```
<!-- add bootstrap 5 plugins -->
```

```
<meta charset="utf-8">
```

```
<meta name="viewport" content="width=device-width, initial-scale=1">
```

```
<link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/css/bootstrap.min.css" rel="stylesheet" >
```

```
<script src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/js/bootstrap.bundle.min.js" ></script>
```

```
<!-- Bootstrap Font Icon CSS -->
```

```
<link rel="stylesheet" href="https://cdn.jsdelivr.net/npm/bootstrap-icons@1.5.0/font/bootstrap-icons.css">
```

```
</head>
```

```
<body>
```

```
    <div class="container mt-5">
```

```
        <div class="bi-facebook"></div>
```

```
        <div class="bi-twitter"></div>
```

```
        <div class="bi-youtube"></div>
```

```
        <div class="bi-instagram"></div>
```

```
        <div class="bi-whatsapp"></div>
```

```
    </div>
```

```
</body>
```

```
</html>
```

**ex:3**

```
<!DOCTYPE html>
```

```
<html>
```

```
<head>
```

**<title>IHUB TALENT</title>**

**<!-- add bootstrap 5 plugins -->**

**<meta charset="utf-8">**

**<meta name="viewport" content="width=device-width, initial-scale=1">**

**<link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/css/bootstrap.min.css" rel="stylesheet" >**

**<script src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/js/bootstrap.bundle.min.js" ></script>**

**<!-- Bootstrap Font Icon CSS -->**

**<link rel="stylesheet" href="https://cdn.jsdelivr.net/npm/bootstrap-icons@1.5.0/font/bootstrap-icons.css">**

**</head>**

**<body>**

**<div class="container mt-5">**

**<button class="btn btn-primary">**

**Search <span class="bi-search"></span>**

**</button>**

```
<button class="btn btn-primary">
    <span class="bi-search"></span> Search
</button>
```

```
</div>

</body>
</html>
```

### Bootstrap Pagination

- If we have website with lot of pages ,you may wish to add some sort of pagination to each page.
- To create a basic pagination ,add the "pagination" class to an <ul> element.
- Add "page-item" class to each page item.

#### ex:1

```
<!DOCTYPE html>

<html>

<head>

    <title>IHUB TALENT</title>

    <!-- add bootstrap 5 plugins -->

    <meta charset="utf-8">


    <meta name="viewport" content="width=device-width, initial-
scale=1">
```

```
<link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/css/bootstrap.min.css" rel="stylesheet" >
```

```
<script src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/js/bootstrap.bundle.min.js" ></script>
```

```
<!-- Bootstrap Font Icon CSS -->
```

```
<link rel="stylesheet" href="https://cdn.jsdelivr.net/npm/bootstrap-icons@1.5.0/font/bootstrap-icons.css">
```

```
</head>
```

```
<body>
```

```
<div class="container mt-5">
```

```
<ul class="pagination">
```

```
<li class="page-item">
```

```
<a href="" class="page-link">Previous</a>
```

```
</li>
```

```
<li class="page-item">
```

```
<a href="" class="page-link">1</a>
```

```
</li>
```

```
<li class="page-item">
```

```
<a href="" class="page-link">2</a>
```

```
</li>
```

```
<li class="page-item">
```

```
<a href="" class="page-link">3</a>
```



```
        </li>
        <li class="page-item">
            <a href="" class="page-link">4</a>
        </li>
        <li class="page-item">
            <a href="" class="page-link">5</a>
        </li>
        <li class="page-item">
            <a href="" class="page-link">6</a>
        </li>
        <li class="page-item">
            <a href="" class="page-link">7</a>
        </li>
        <li class="page-item">
            <a href="" class="page-link">Next</a>
        </li>
    </ul>
```

```
</div>
```

```
</body>
```

```
</html>
```

ex:2

```
<!DOCTYPE html>
```

```
<html>
```

**<head>**

**<title>IHUB TALENT</title>**

**<!-- add bootstrap 5 plugins -->**

**<meta charset="utf-8">**

**<meta name="viewport" content="width=device-width, initial-scale=1">**

**<link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/css/bootstrap.min.css" rel="stylesheet" >**

**<script src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/js/bootstrap.bundle.min.js" ></script>**

**<!-- Bootstrap Font Icon CSS -->**

**<link rel="stylesheet" href="https://cdn.jsdelivr.net/npm/bootstrap-icons@1.5.0/font/bootstrap-icons.css">**

**</head>**

**<body>**

**<div class="container mt-5">**

**<ul class="pagination">**

**<li class="page-item">**

**<a href="" class="page-link">&laquo;</a>**

</li>

<li class="page-item">

<a href="" class="page-link">1</a>

</li>

<li class="page-item">

<a href="" class="page-link">2</a>

</li>

<li class="page-item">

<a href="" class="page-link">3</a>

</li>

<li class="page-item">

<a href="" class="page-link">4</a>

</li>

<li class="page-item">

<a href="" class="page-link">5</a>

</li>

<li class="page-item">

<a href="" class="page-link">6</a>

</li>

<li class="page-item">

<a href="" class="page-link">7</a>

</li>

<li class="page-item">

<a href="" class="page-link">&raquo;</a>

</li>

</ul>

</div>

</body>

</html>

ex:3

<!DOCTYPE html>

<html>

<head>

<title>IHUB TALENT</title>

<!-- add bootstrap 5 plugins -->

<meta charset="utf-8">

<meta name="viewport" content="width=device-width, initial-scale=1">

<link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/css/bootstrap.min.css" rel="stylesheet" >

<script src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/js/bootstrap.bundle.min.js" ></script>

<!-- Bootstrap Font Icon CSS -->

```
<link rel="stylesheet" href="https://cdn.jsdelivr.net/npm/bootstrap-icons@1.5.0/font/bootstrap-icons.css">
```

```
</head>
```

```
<body>
```

```
  <div class="container mt-5">
```

```
    <ul class="pagination">
```

```
      <li class="page-item disabled">
```

```
        <a href="" class="page-link">&laquo;</a>
```

```
      </li>
```

```
      <li class="page-item active">
```

```
        <a href="" class="page-link">1</a>
```

```
      </li>
```

```
      <li class="page-item">
```

```
        <a href="" class="page-link">2</a>
```

```
      </li>
```

```
      <li class="page-item">
```

```
        <a href="" class="page-link">3</a>
```

```
      </li>
```

```
      <li class="page-item">
```

```
        <a href="" class="page-link">4</a>
```

```
      </li>
```

```
      <li class="page-item">
```

```
        <a href="" class="page-link">5</a>
```

```

        </li>
        <li class="page-item">
            <a href="" class="page-link">6</a>
        </li>
        <li class="page-item">
            <a href="" class="page-link">7</a>
        </li>
        <li class="page-item">
            <a href="" class="page-link">&raquo;</a>
        </li>
    </ul>

```

```

    </div>
</body>
</html>

```

### Bootstrap Progress Bar

- A Progress bar is used for showing the progress of a task such as
- downloading a file ,software installation and etc.
- In general, A progress bar can be used to show a user how far along he/she is in a progress.
- To create progress bar we need to use "progress" class inside <div> tag.

#### ex:1

```
<!DOCTYPE html>
```

```
<html>

<head>

  <title>IHUB TALENT</title>

  <!-- add bootstrap 5 plugins -->

  <meta charset="utf-8">

  <meta name="viewport" content="width=device-width, initial-
scale=1">

  <link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-
alpha3/dist/css/bootstrap.min.css" rel="stylesheet" >

  <script src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-
alpha3/dist/js/bootstrap.bundle.min.js" ></script>

  <!-- Bootstrap Font Icon CSS -->

  <link rel="stylesheet" href="https://cdn.jsdelivr.net/npm/bootstrap-
icons@1.5.0/font/bootstrap-icons.css">

</head>

<body>

  <div class="container mt-5">

    <div class="progress">

      <div class="progress-bar" style="width:50%;">

        50%

      </div>

    </div>

  </div>

</body>

</html>
```

**</div>**

**</div>**

**</div>**

**</body>**

**</html>**

**ex:2**

**<!DOCTYPE html>**

**<html>**

**<head>**

**<title>IHUB TALENT</title>**

**<!-- add bootstrap 5 plugins -->**

**<meta charset="utf-8">**

**<meta name="viewport" content="width=device-width, initial-scale=1">**

**<link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/css/bootstrap.min.css" rel="stylesheet" >**

**<script src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/js/bootstrap.bundle.min.js" ></script>**

**<!-- Bootstrap Font Icon CSS -->**

**<link rel="stylesheet" href="https://cdn.jsdelivr.net/npm/bootstrap-icons@1.5.0/font/bootstrap-icons.css">**



```
</head>
<body>
  <div class="container mt-5">
    <div class="progress">
      <div class="progress-bar progress-bar-striped"
style="width:50%;">
        50%
      </div>
    </div>
  </div>
</body>
</html>
```

### ex:3

```
<!DOCTYPE html>
<html>
<head>
  <title>IHUB TALENT</title>

  <!-- add bootstrap 5 plugins -->
  <meta charset="utf-8">

  <meta name="viewport" content="width=device-width, initial-
scale=1">
```

```
<link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/css/bootstrap.min.css" rel="stylesheet" >
```

```
<script src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/js/bootstrap.bundle.min.js" ></script>
```

```
<!-- Bootstrap Font Icon CSS -->
```

```
<link rel="stylesheet" href="https://cdn.jsdelivr.net/npm/bootstrap-icons@1.5.0/font/bootstrap-icons.css">
```

```
</head>
```

```
<body>
```

```
    <div class="container mt-5">
```

```
        <div class="progress">
```

```
            <div class="progress-bar progress-bar-striped progress-bar-animated" style="width:50%;">
```

```
                50%
```

```
            </div>
```

```
        </div>
```

```
    </div>
```

```
</body>
```

```
</html>
```

ex:4

```
<!DOCTYPE html>
```

```
<html>
```

```
<head>
```

**<title>IHUB TALENT</title>**

**<!-- add bootstrap 5 plugins -->**

**<meta charset="utf-8">**

**<meta name="viewport" content="width=device-width, initial-scale=1">**

**<link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/css/bootstrap.min.css" rel="stylesheet" >**

**<script src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/js/bootstrap.bundle.min.js" ></script>**

**<!-- Bootstrap Font Icon CSS -->**

**<link rel="stylesheet" href="https://cdn.jsdelivr.net/npm/bootstrap-icons@1.5.0/font/bootstrap-icons.css">**

**</head>**

**<body>**

**<div class="container mt-5">**

**<div class="progress">**

**<div class="progress-bar progress-bar-striped progress-bar-animated bg-info" style="width:50%;">**

**50%**

**</div>**

```
</div>
```

```
<br>
```

```
<div class="progress">
```

```
    <div class="progress-bar progress-bar-striped  
progress-bar-animated bg-danger" style="width:25%;">
```

```
        25%
```

```
    </div>
```

```
</div>
```

```
<br>
```

```
<div class="progress">
```

```
    <div class="progress-bar progress-bar-striped  
progress-bar-animated bg-success" style="width:75%;">
```

```
        75%
```

```
    </div>
```

```
</div>
```

```
</div>
```

```
</body>
```

```
</html>
```

ex:5

```
<!DOCTYPE html>
```

```
<html>
```

```
<head>
```

**<title>IHUB TALENT</title>**

**<!-- add bootstrap 5 plugins -->**

**<meta charset="utf-8">**

**<meta name="viewport" content="width=device-width, initial-scale=1">**

**<link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/css/bootstrap.min.css" rel="stylesheet" >**

**<script src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/js/bootstrap.bundle.min.js" ></script>**

**<!-- Bootstrap Font Icon CSS -->**

**<link rel="stylesheet" href="https://cdn.jsdelivr.net/npm/bootstrap-icons@1.5.0/font/bootstrap-icons.css">**

**</head>**

**<body>**

**<div class="container mt-5">**

**<div class="progress">**

**<div class="progress-bar progress-bar-striped progress-bar-animated bg-warning"**

**style="width:2%;min-width:20px;">**

**2%**

```
        </div>
    </div>

</div>

</body>
</html>
```

## Bootstrap Cards

- A card in Bootstrap 5 is a bordered box with some padding around its content. It includes options for headers, footers, content, colors, etc.
- A basic card is created with the .card class, and content inside the card has a .card-body class:
- The .card-header class adds a heading to the card and the .card-footer class adds a footer to the card.
- Use .card-title to add card titles to any heading element.
- The .card-text class is used to remove bottom margins for a <p> element if it is the last child (or the only one) inside .card-body.
- Add .card-img-top to an <img> to place the image at the top inside the card.
- Note that we have added the image outside of the .card-body to span the entire width:

### ex:1

```
<!DOCTYPE html>

<html>

<head>

    <title>IHUB TALENT</title>


    <!-- add bootstrap 5 plugins -->
```

**<meta charset="utf-8">**

**<meta name="viewport" content="width=device-width, initial-scale=1">**

**<link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/css/bootstrap.min.css" rel="stylesheet" >**

**<script src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/js/bootstrap.bundle.min.js" ></script>**

**<!-- Bootstrap Font Icon CSS -->**

**<link rel="stylesheet" href="https://cdn.jsdelivr.net/npm/bootstrap-icons@1.5.0/font/bootstrap-icons.css">**

**</head>**

**<body>**

**<div class="container mt-5">**

**<div class="card">**

**<div class="card-header">**

**Heading**

**</div>**

**<div class="card-body">**

**Body**

**</div>**

```
<div class="card-footer">
```

```
    Footing
```

```
</div>
```

```
</div>
```

```
</div>
```

```
</body>
```

```
</html>
```

**ex:2**

```
<!DOCTYPE html>
```

```
<html>
```

```
<head>
```

```
    <title>IHUB TALENT</title>
```

```
    <!-- add bootstrap 5 plugins -->
```

```
    <meta charset="utf-8">
```

```
    <meta name="viewport" content="width=device-width, initial-  
scale=1">
```

```
    <link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-  
alpha3/dist/css/bootstrap.min.css" rel="stylesheet" >
```

```
    <script src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-  
alpha3/dist/js/bootstrap.bundle.min.js" ></script>
```



**<!-- Bootstrap Font Icon CSS -->**

**<link rel="stylesheet" href="https://cdn.jsdelivr.net/npm/bootstrap-icons@1.5.0/font/bootstrap-icons.css">**

**</head>**

**<body>**

**<div class="container mt-5">**

**<div class="card">**

**<div class="card-header">**

**Heading**

**</div>**

**<div class="card-body">**

**<div class="card-title">Bootstrap</div>**

**<div class="card-text">Bootstrap is a css  
framework</div>**

**</div>**

**<div class="card-footer">**

**Footing**

**</div>**

**</div>**

**</div>**

**</body>**

**</html>**

### ex:3

```
<!DOCTYPE html>
```

```
<html>
```

```
  <head>
```

```
    <title>MyPage!</title>
```

```
    <!-- add bootstrap plugins -->
```

```
    <meta charset="utf-8">
```

```
    <meta name="viewport" content="width=device-width,  
initial-scale=1">
```

```
    <link  
href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0/dist/css/bootstrap.min.css" rel="stylesheet" >
```

```
    <script  
src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0/dist/js/bootstrap.bundle.min.js" ></script>
```

```
    <!-- Bootstrap Font Icon CSS -->
```

```
    <link rel="stylesheet"  
href="https://cdn.jsdelivr.net/npm/bootstrap-icons@1.5.0/font/bootstrap-icons.css">
```

**</head>**

**<body>**

**<div class="container-fluid mt-5">**

**<div class="card">**

**<div class="card-body">**

**<div class="row">**

**<div class="col-4">**

****

**</div>**

**<div class="col-4">**

****

**</div>**

**<div class="col-4">**

****

**</div>**

**</div>**

**</div>**

```
        <div class="card-footer">
            <div class="row">
                <div class="col-4">
                    <h2 class="card-title text-
center">Amber Heard1</h2>
                </div>
                <div class="col-4">
                    <h2 class="card-title text-
center">Amber Heard2</h2>
                </div>
                <div class="col-4">
                    <h2 class="card-title text-
center">Amber Heard3</h2>
                </div>
            </div>
        </div>
    </div>
</div>
</body>
</html>
```

## Bootstrap Collapse Plugin

- Collapsibles are useful when you want to hide and show large amount of content:
- A `data-bs-toggle="collapse"` attribute is used to show and hide the content.
- A `data-bs-target` attribute is used to connect a button with div tag.
- A `"collapse"` class inside `<div>` is used to hide/collapse the content for first time.

### ex:1

```
<!DOCTYPE html>
```

```
<html>
```

```
<head>
```

```
  <title>IHUB TALENT</title>
```

```
  <!-- add bootstrap 5 plugins -->
```

```
  <meta charset="utf-8">
```

```
  <meta name="viewport" content="width=device-width, initial-scale=1">
```

```
  <link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/css/bootstrap.min.css" rel="stylesheet" >
```

```
  <script src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/js/bootstrap.bundle.min.js" ></script>
```

```
  <!-- Bootstrap Font Icon CSS -->
```

```
<link rel="stylesheet" href="https://cdn.jsdelivr.net/npm/bootstrap-  
icons@1.5.0/font/bootstrap-icons.css">
```

```
</head>
```

```
<body>
```

```
    <div class="container mt-5">
```

```
        <button class="btn btn-primary" data-bs-  
toggle="collapse"
```

```
        data-bs-target="#myId"> Toggle </button>
```

```
        <h1 id="myId" class="collapse">This is heading  
tag</h1>
```

```
    </div>
```

```
</body>
```

```
</html>
```

ex:2

```
<!DOCTYPE html>
```

```
<html>
```

```
<head>
```

```
    <title>IHUB TALENT</title>
```

```
    <!-- add bootstrap 5 plugins -->
```

```
    <meta charset="utf-8">
```

```
<meta name="viewport" content="width=device-width, initial-scale=1">
```

```
<link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/css/bootstrap.min.css" rel="stylesheet" >
```

```
<script src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/js/bootstrap.bundle.min.js" ></script>
```

```
<!-- Bootstrap Font Icon CSS -->
```

```
<link rel="stylesheet" href="https://cdn.jsdelivr.net/npm/bootstrap-icons@1.5.0/font/bootstrap-icons.css">
```

```
</head>
```

```
<body>
```

```
  <div class="container mt-5">
```

```
    <a href="#myId" data-bs-toggle="collapse"> Toggle  
</a>
```

```
    <h1 id="myId" class="collapse">This is heading  
tag</h1>
```

```
  </div>
```

```
</body>
```

```
</html>
```

## Bootstrap collapse plugin with cards

```
<!DOCTYPE html>

<html>

<head>

    <title>IHUB TALENT</title>


    <!-- add bootstrap 5 plugins -->

    <meta charset="utf-8">


    <meta name="viewport" content="width=device-width, initial-
scale=1">


    <link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-
alpha3/dist/css/bootstrap.min.css" rel="stylesheet" >


    <script src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-
alpha3/dist/js/bootstrap.bundle.min.js" ></script>


    <!-- Bootstrap Font Icon CSS -->

    <link rel="stylesheet" href="https://cdn.jsdelivr.net/npm/bootstrap-
icons@1.5.0/font/bootstrap-icons.css">


</head>

<body>

    <div class="container mt-5">
```



```

<div class="card">

    <div class="card-header">

        <button class="btn btn-outline-primary"
            data-bs-toggle="collapse"
            data-bs-target="#myId"> Toggle

    </button>

    </div>

    <div class="card-body collapse" id="myId">

        <div class="row">

            <div class="col-4">

                

            </div>

            <div class="col-4">

                

            </div>

            <div class="col-4">

                

            </div>

        </div>

    </div>

</div>

```

```
</div>

</body>

</html>
```

### Bootstrap responsive navbar

- Navbars require a wrapping `.navbar` with `.navbar-expand{-sm|-md|-lg|-xl|-xxl}` for responsive collapsing and color scheme classes.
- Navbars and their contents are fluid by default.
- Change the container to limit their horizontal width in different ways.
- Use our spacing and flex utility classes for controlling spacing and alignment within navbars.
- Navbars are responsive by default, but you can easily modify them to change that.
- Responsive behavior depends on our Collapse JavaScript plugin.
- `.navbar-brand` for your company, product, or project name.
- `.navbar-nav` for a full-height and lightweight navigation (including support for dropdowns).
- `.navbar-toggler` for use with our collapse plugin and other navigation toggling behaviors.
- Flex and spacing utilities for any form controls and actions.
- `.navbar-text` for adding vertically centered strings of text.
- `.collapse.navbar-collapse` for grouping and hiding navbar contents by a parent breakpoint.
- Add an optional `.navbar-scroll` to set a max-height and scroll expanded navbar content.

#### ex:1

```
<!DOCTYPE html>

<html>

<head>
```

**<title>IHUB TALENT</title>**

**<!-- add bootstrap 5 plugins -->**

**<meta charset="utf-8">**

**<meta name="viewport" content="width=device-width, initial-scale=1">**

**<link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/css/bootstrap.min.css" rel="stylesheet" >**

**<script src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/js/bootstrap.bundle.min.js" ></script>**

**<!-- Bootstrap Font Icon CSS -->**

**<link rel="stylesheet" href="https://cdn.jsdelivr.net/npm/bootstrap-icons@1.5.0/font/bootstrap-icons.css">**

**</head>**

**<body>**

**<nav class="navbar navbar-expand-lg navbar-light bg-light">**

**<div class="container-fluid">**

**<a class="navbar-brand" href="#">IHUBTALENT</a>**

**<button class="navbar-toggler"**

```

        data-bs-toggle="collapse"
        data-bs-target="#navbarId">

        <span class="navbar-toggler-icon"></span>
    </button>
    <div class="collapse navbar-collapse"
id="navbarId">

        <ul class="navbar-nav ">
            <li class="nav-item">
                <a class="nav-link active"
href="#">Home</a>
            </li>
            <li class="nav-item">
                <a class="nav-link active"
href="#">About</a>
            </li>
            <li class="nav-item">
                <a class="nav-link active"
href="#">Service</a>
            </li>
            <li class="nav-item">
                <a class="nav-link active"
href="#">Portfolio</a>
            </li>
            <li class="nav-item">
                <a class="nav-link active"
href="#">Contact</a>

```

```
        </li>
    </ul>
</div>
</div>
</nav>
```

```
</body>
```

```
</html>
```

**ex:2**

```
<!DOCTYPE html>
```

```
<html>
```

```
<head>
```

```
    <title>IHUB TALENT</title>
```

```
    <!-- add bootstrap 5 plugins -->
```

```
    <meta charset="utf-8">
```

```
    <meta name="viewport" content="width=device-width, initial-
scale=1">
```

```
    <link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-
alpha3/dist/css/bootstrap.min.css" rel="stylesheet" >
```

```
    <script src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-
alpha3/dist/js/bootstrap.bundle.min.js" ></script>
```

```
    <!-- Bootstrap Font Icon CSS -->
```

```
<link rel="stylesheet" href="https://cdn.jsdelivr.net/npm/bootstrap-  
icons@1.5.0/font/bootstrap-icons.css">
```

```
</head>
```

```
<body>
```

```
<nav class="navbar navbar-expand-lg navbar-dark bg-dark">
```

```
<div class="container-fluid">
```

```
<a class="navbar-brand"  
href="#">IHUBTALENT</a>
```

```
<button class="navbar-toggler"  
data-bs-toggle="collapse"  
data-bs-target="#navbarId">
```

```
<span class="navbar-toggler-icon"></span>
```

```
</button>
```

```
<div class="collapse navbar-collapse"  
id="navbarId">
```

```
<ul class="navbar-nav ">
```

```
<li class="nav-item">
```

```
<a class="nav-link active"  
href="#">Home</a>
```

```
</li>
```

```
<li class="nav-item">
```

```
<a class="nav-link active"  
href="#">About</a>
```

```

        </li>
        <li class="nav-item">
            <a class="nav-link active"
href="#">Service</a>
        </li>
        <li class="nav-item">
            <a class="nav-link active"
href="#">Portfolio</a>
        </li>
        <li class="nav-item">
            <a class="nav-link active"
href="#">Contact</a>
        </li>
    </ul>
</div>
</div>
</nav>
</body>
</html>

```

### ex:3

```

<!DOCTYPE html>
<html>
<head>
    <title>IHUB TALENT</title>

    <!-- add bootstrap 5 plugins -->

```

**<meta charset="utf-8">**

**<meta name="viewport" content="width=device-width, initial-scale=1">**

**<link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/css/bootstrap.min.css" rel="stylesheet" >**

**<script src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/js/bootstrap.bundle.min.js" ></script>**

**<!-- Bootstrap Font Icon CSS -->**

**<link rel="stylesheet" href="https://cdn.jsdelivr.net/npm/bootstrap-icons@1.5.0/font/bootstrap-icons.css">**

**</head>**

**<body>**

**<nav class="navbar navbar-expand-lg navbar-dark bg-dark fixed-top">**

**<div class="container-fluid">**

**<a class="navbar-brand" href="#">IHUBTALENT</a>**

**<button class="navbar-toggler"**

**data-bs-toggle="collapse"**

**data-bs-target="#navbarId">**



```

        <span class="navbar-toggler-icon"></span>
    </button>
    <div class="collapse navbar-collapse"
id="navbarId">
        <ul class="navbar-nav ">
            <li class="nav-item">
                <a class="nav-link active"
href="#">Home</a>
            </li>
            <li class="nav-item">
                <a class="nav-link active"
href="#">About</a>
            </li>
            <li class="nav-item">
                <a class="nav-link active"
href="#">Service</a>
            </li>
            <li class="nav-item">
                <a class="nav-link active"
href="#">Portfolio</a>
            </li>
            <li class="nav-item">
                <a class="nav-link active"
href="#">Contact</a>
            </li>
        </ul>
    </div>

```

**</div>**

**</nav>**

**<h1>This is heading tag </h1>**

**<h1>This is heading tag </h1>**

**<h1>This is heading tag </h1>**

**<h1>This is heading tag </h1>**

**<h1>This is heading tag </h1>**

**<h1>This is heading tag </h1>**

**<h1>This is heading tag </h1>**

**<h1>This is heading tag </h1>**

**<h1>This is heading tag </h1>**

**<h1>This is heading tag </h1>**

**<h1>This is heading tag </h1>**

**<h1>This is heading tag </h1>**

**<h1>This is heading tag </h1>**

**<h1>This is heading tag </h1>**

**<h1>This is heading tag </h1>**

**</body>**

**</html>**

## Bootstrap Scrollspy

- The scrollspy plugin automatically highlights the navigation links based on the scroll position to indicate where the user is currently on the page.

```
<!DOCTYPE html>
```

```
<html>
```

```
<head>
```

```
  <title>IHUB TALENT</title>
```

```
  <!-- add bootstrap 5 plugins -->
```

```
  <meta charset="utf-8">
```

```
  <meta name="viewport" content="width=device-width, initial-  
scale=1">
```

```
  <link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-  
alpha3/dist/css/bootstrap.min.css" rel="stylesheet" >
```

```
  <script src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-  
alpha3/dist/js/bootstrap.bundle.min.js" ></script>
```

```
  <!-- Bootstrap Font Icon CSS -->
```

```
  <link rel="stylesheet" href="https://cdn.jsdelivr.net/npm/bootstrap-  
icons@1.5.0/font/bootstrap-icons.css">
```

```
  <style>
```

```
.section1  
{  
    width: 100%;  
    height: 560px;  
    background-color: #C4E538;  
}  
.section2  
{  
    width: 100%;  
    height: 560px;  
    background-color: #ED4C67;  
}  
.section3  
{  
    width: 100%;  
    height: 560px;  
    background-color: #9980FA;  
}  
.section4  
{  
    width: 100%;  
    height: 560px;  
    background-color: #12CBC4;  
}  
.section5
```

```
{  
    width: 100%;  
    height: 560px;  
    background-color: #833471;  
}
```

</style>

</head>

<body>

<nav class="navbar navbar-expand-lg navbar-dark bg-dark  
fixed-top">

<div class="container-fluid">

<a class="navbar-brand"  
href="#">IHUBTALENT</a>

<button class="navbar-toggler"

data-bs-toggle="collapse"

data-bs-target="#navbarId">

<span class="navbar-toggler-icon"></span>

</button>

<div class="collapse navbar-collapse"  
id="navbarId">

<ul class="navbar-nav ">

```

        <li class="nav-item">
            <a class="nav-link active"
href="#homeId">Home</a>
        </li>
        <li class="nav-item">
            <a class="nav-link active"
href="#aboutId">About</a>
        </li>
        <li class="nav-item">
            <a class="nav-link active"
href="#serviceId">Service</a>
        </li>
        <li class="nav-item">
            <a class="nav-link active"
href="#portfolioId">Portfolio</a>
        </li>
        <li class="nav-item">
            <a class="nav-link active"
href="#contactId">Contact</a>
        </li>
    </ul>
</div>
</div>
</nav>

<section class="section1" id="homeId">

```

```
<h1 class="pt-5 text-center">
```

Home Page

```
</h1>
```

```
</section>
```

```
<section class="section2" id="aboutId">
```

```
<h1 class="pt-5 text-center">
```

About Page

```
</h1>
```

```
</section>
```

```
<section class="section3" id="serviceId">
```

```
<h1 class="pt-5 text-center">
```

Service Page

```
</h1>
```

```
</section>
```

```
<section class="section4" id="portfolioId">
```

```
<h1 class="pt-5 text-center">
```

Portfolio Page

```
</h1>
```

```
</section>
```

```
<section class="section5" id="contactId">
```

```
<h1 class="pt-5 text-center">
```

Contact Page

```
</h1>
```

```
</section>
```

`</body>`

`</html>`

## Bootstrap5 forms

- Bootstrap 5 supports two types of form layouts.

### 1) Stacked Forms

### 2) Inline forms

#### 1) Stacked Forms

- All textual `<input>` and `<textarea>` elements with class `.form-control` get proper form styling.
- we add a `.form-label` class to each label element to ensure correct padding.
- Checkboxes have different markup. They are wrapped around a container element with `.form-check`, and labels have a class of `.form-check-label`, while checkboxes and radio buttons use `.form-check-input`.

#### ex:1

`<!DOCTYPE html>`

`<html>`

`<head>`

`<title>IHUB TALENT</title>`

`<!-- add bootstrap 5 plugins -->`

`<meta charset="utf-8">`

`<meta name="viewport" content="width=device-width, initial-scale=1">`



```
<link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/css/bootstrap.min.css" rel="stylesheet" >
```

```
<script src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/js/bootstrap.bundle.min.js" ></script>
```

```
<!-- Bootstrap Font Icon CSS -->
```

```
<link rel="stylesheet" href="https://cdn.jsdelivr.net/npm/bootstrap-icons@1.5.0/font/bootstrap-icons.css">
```

```
</head>
```

```
<body>
```

```
    <div class="container mt-5">
```

```
        <!-- stack form -->
```

```
        <form action="">
```

```
            <label class="my-3">UserName:</label>
```

```
            <input type="text" name="t1" class="form-control" placeholder="username" autocomplete="off" />
```

```
            <label class="my-3">Password:</label>
```

```
            <input type="password" name="t1" class="form-control" placeholder="password" />
```

```
            <input type="submit" value="submit" class="btn btn-primary my-5 w-100"/>
```

**</form>**

**</div>**

**</body>**

**</html>**

**ex:2**

**<!DOCTYPE html>**

**<html>**

**<head>**

**<title>IHUB TALENT</title>**

**<!-- add bootstrap 5 plugins -->**

**<meta charset="utf-8">**

**<meta name="viewport" content="width=device-width, initial-scale=1">**

**<link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/css/bootstrap.min.css" rel="stylesheet" >**

**<script src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/js/bootstrap.bundle.min.js" ></script>**

**<!-- Bootstrap Font Icon CSS -->**

**<link rel="stylesheet" href="https://cdn.jsdelivr.net/npm/bootstrap-icons@1.5.0/font/bootstrap-icons.css">**

**</head>**

```
<body>

  <div class="container mt-5">

    <div class="w-50">

      <!-- stack form -->

      <form action="">

        <label class="my-3">UserName:</label>

        <input type="text" name="t1" class="form-
control" placeholder="username" autocomplete="off" />

        <label class="my-3">Password:</label>

        <input type="password" name="t1" class="form-
control" placeholder="password" />

        <input type="submit" value="submit" class="btn
btn-primary my-5 w-100"/>

      </form>

    </div>

  </div>

</body>
</html>
```

**ex:3**

**<!DOCTYPE html>**

**<html>**

**<head>**

**<title>IHUB TALENT</title>**

**<!-- add bootstrap 5 plugins -->**

**<meta charset="utf-8">**

**<meta name="viewport" content="width=device-width, initial-scale=1">**

**<link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/css/bootstrap.min.css" rel="stylesheet" >**

**<script src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/js/bootstrap.bundle.min.js" ></script>**

**<!-- Bootstrap Font Icon CSS -->**

**<link rel="stylesheet" href="https://cdn.jsdelivr.net/npm/bootstrap-icons@1.5.0/font/bootstrap-icons.css">**

**</head>**

**<body>**

**<div class="container mt-5">**

```
        <form action="">
            <label>Address:</label>
            <textarea name="t1" rows="5" cols="10"
class="form-control"></textarea>
        </form>
```

```
    </div>
</body>
</html>
```

#### ex:4

```
<!DOCTYPE html>
<html>
<head>
    <title>IHUB TALENT</title>

    <!-- add bootstrap 5 plugins -->
    <meta charset="utf-8">

    <meta name="viewport" content="width=device-width, initial-
scale=1">

    <link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-
alpha3/dist/css/bootstrap.min.css" rel="stylesheet" >

    <script src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-
alpha3/dist/js/bootstrap.bundle.min.js" ></script>
```

```
<!-- Bootstrap Font Icon CSS -->

<link rel="stylesheet" href="https://cdn.jsdelivr.net/npm/bootstrap-
icons@1.5.0/font/bootstrap-icons.css">

</head>

<body>

    <div class="container mt-5">

        <form action="">

            <div class="form-check">

                <input type="radio" name="t1" value="male" class="form-
                check-input"/>

                <label class="form-check-label">MALE</label>

            </div>

            <div class="form-check">

                <input type="radio" name="t1" value="female"
                class="form-check-input"/>

                <label class="form-check-label">FEMALE</label>

            </div>

        </form>

    </div>
```

**</body>**

**</html>**

**ex:5**

**<!DOCTYPE html>**

**<html>**

**<head>**

**<title>IHUB TALENT</title>**

**<!-- add bootstrap 5 plugins -->**

**<meta charset="utf-8">**

**<meta name="viewport" content="width=device-width, initial-scale=1">**

**<link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/css/bootstrap.min.css" rel="stylesheet" >**

**<script src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/js/bootstrap.bundle.min.js" ></script>**

**<!-- Bootstrap Font Icon CSS -->**

**<link rel="stylesheet" href="https://cdn.jsdelivr.net/npm/bootstrap-icons@1.5.0/font/bootstrap-icons.css">**

**</head>**

**<body>**

**<div class="container mt-5">**

```
<form action="">

    <div class="form-check">

        <input type="checkbox" name="t1" value="married"
class="form-check-input"/>
        <label class="form-check-label">MARRIED</label>
    </div>

    <div class="form-check">

        <input type="checkbox" name="t1" value="single"
class="form-check-input"/>
        <label class="form-check-label">SINGLE</label>
    </div>

</form>

</div>

</body>
</html>
```



**ex:6**

```
<!DOCTYPE html>
```

```
<html>
```

```
<head>
```

```
    <title>IHUB TALENT</title>
```

```
    <!-- add bootstrap 5 plugins -->
```

```
    <meta charset="utf-8">
```

```
    <meta name="viewport" content="width=device-width, initial-  
scale=1">
```

```
    <link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-  
alpha3/dist/css/bootstrap.min.css" rel="stylesheet" >
```

```
    <script src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-  
alpha3/dist/js/bootstrap.bundle.min.js" ></script>
```

```
    <!-- Bootstrap Font Icon CSS -->
```

```
    <link rel="stylesheet" href="https://cdn.jsdelivr.net/npm/bootstrap-  
icons@1.5.0/font/bootstrap-icons.css">
```

```
</head>
```

```
<body>
```

```
    <div class="container mt-5">
```

```
<form action="">

    <label>Select Country:</label>
    <select name="t1" class="form-select">
        <option value="">none</option>
        <option value="india">India</option>
        <option
value="america">America</option>
        <option
value="australia">Australia</option>
        <option value="canada">Canada</option>
    </select>

</form>

</div>

</body>
</html>
```

### ex:7

```
<!DOCTYPE html>
<html>
<head>
    <title>IHUB TALENT</title>

    <!-- add bootstrap 5 plugins -->
```

```
<meta charset="utf-8">
```

```
<meta name="viewport" content="width=device-width, initial-  
scale=1">
```

```
<link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-  
alpha3/dist/css/bootstrap.min.css" rel="stylesheet" >
```

```
<script src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-  
alpha3/dist/js/bootstrap.bundle.min.js" ></script>
```

```
<!-- Bootstrap Font Icon CSS -->
```

```
<link rel="stylesheet" href="https://cdn.jsdelivr.net/npm/bootstrap-  
icons@1.5.0/font/bootstrap-icons.css">
```

```
</head>
```

```
<body>
```

```
<div class="container mt-5">
```

```
<form action="">
```

```
<label>Performance Rating :</label>
```

```
<input type="range" name="t1" class="form-  
range"/>
```

```
</form>
```

```
        </div>

</body>
</html>
```

### ex:8

```
<!DOCTYPE html>

<html>

<head>

    <title>IHUB TALENT</title>


    <!-- add bootstrap 5 plugins -->

    <meta charset="utf-8">


    <meta name="viewport" content="width=device-width, initial-
scale=1">


    <link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-
alpha3/dist/css/bootstrap.min.css" rel="stylesheet" >


    <script src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-
alpha3/dist/js/bootstrap.bundle.min.js" ></script>


    <!-- Bootstrap Font Icon CSS -->

    <link rel="stylesheet" href="https://cdn.jsdelivr.net/npm/bootstrap-
icons@1.5.0/font/bootstrap-icons.css">

</head>
```

```
<body>

  <div class="container mt-5">

    <form action="">

      <div class="input-group">

        <label class="input-group-
text">www.</label>

        <input type="text" name="t1"/>

        <label class="input-group-
text">.com</label>

      </div>

    </form>

  </div>

</body>
</html>
```

### Inline Forms

- If you want your form elements to appear side by side, use .row and .col.

ex:

```
<!DOCTYPE html>
```

```
<html>

<head>

    <title>IHUB TALENT</title>

    <!-- add bootstrap 5 plugins -->

    <meta charset="utf-8">

    <meta name="viewport" content="width=device-width, initial-
scale=1">

    <link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-
alpha3/dist/css/bootstrap.min.css" rel="stylesheet" >

    <script src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-
alpha3/dist/js/bootstrap.bundle.min.js" ></script>

    <!-- Bootstrap Font Icon CSS -->

    <link rel="stylesheet" href="https://cdn.jsdelivr.net/npm/bootstrap-
icons@1.5.0/font/bootstrap-icons.css">

</head>

<body>

    <div class="container mt-5">

        <form action="">
```

```
<div class="row">
```

```
    <div class="col-2">
```

```
        <label>UserName:</label>
```

```
    </div>
```

```
    <div class="col-3">
```

```
        <input type="text" name="t1"/>
```

```
    </div>
```

```
    <div class="col-2">
```

```
        <label>Password:</label>
```

```
    </div>
```

```
    <div class="col-3">
```

```
        <input type="password" name="t1"/>
```

```
    </div>
```

```
    <div class="col-2">
```

```
        <input type="submit" value="submit"/>
```

```
    </div>
```

```
</div>
```

```
</form>
```

```
</div>
```

```
</body>
```

```
</html>
```

## Bootstrap Carousel

- A `.carousel` class creates a carousel.
- A `.slide` class adds a CSS transition and animation effect when sliding from one item to the next. Remove this class if you do not want this effect.
- A `.carousel-inner` class adds slides to the carousel.
- A `.carousel-item` class specifies the content of each slide.
- Add elements inside `<div class="carousel-caption">` within each `<div class="carousel-item">` to create a caption for each slide.
- A `.carousel-indicators` class adds indicators for the carousel.
- These are the little dots at the bottom of each slide (which indicates how many slides there are in the carousel, and which slide the user are currently viewing).
- A `.carousel-control-prev` class adds a left (previous) button to the carousel, which allows the user to go back between the slides.
- A `.carousel-control-next` class adds a right (next) button to the carousel, which allows the user to go forward between the slides.
- A `.carousel-control-prev-icon` class used together with `.carousel-control-prev` to create a "previous" button.
- A `.carousel-control-next-icon` class used together with `.carousel-control-next` to create a "next" button.

```
<!DOCTYPE html>
```

```
<html>
```

```
<head>
```

```
  <title>IHUB TALENT</title>
```

```
  <!-- add bootstrap 5 plugins -->
```

```
  <meta charset="utf-8">
```



```
<meta name="viewport" content="width=device-width, initial-scale=1">
```

```
<link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/css/bootstrap.min.css" rel="stylesheet" >
```

```
<script src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha3/dist/js/bootstrap.bundle.min.js" ></script>
```

```
<!-- Bootstrap Font Icon CSS -->
```

```
<link rel="stylesheet" href="https://cdn.jsdelivr.net/npm/bootstrap-icons@1.5.0/font/bootstrap-icons.css">
```

```
</head>
```

```
<body>
```

```
<div class="container mt-5">
```

```
<div id="carouselId" class="carousel slide" data-bs-ride="carousel">
```

```
<div class="carousel-indicators">
```

```
<button type="button" data-bs-target="#carouselId" data-bs-slide-to="0" class="active"></button>
```

```
<button type="button" data-bs-target="#carouselId" data-  
bs-slide-to="1" ></button>
```

```
<button type="button" data-bs-target="#carouselId" data-  
bs-slide-to="2" ></button>
```

```
</div>
```

```
<div class="carousel-inner">
```

```
<div class="carousel-item active">
```

```

```

```
<div class="carousel-caption">
```

```
<h1>Washington DC</h1>
```

```
<p>Our Team Is Our
```

```
Strength</p>
```

```
</div>
```

```
</div>
```

```
<div class="carousel-item">
```

```

```

```

<div class="carousel-caption">
    <h1>Los Angeles</h1>
    <p>Our Work Is Our
Identity</p>
</div></div>
<div class="carousel-item">

<div class="carousel-caption"><h1>New Jersey</h1>
<p>Our Service are Best Practice</p>
    </div> </div></div>
<button class="carousel-control-prev" type="button" data-bs-
target="#carouselId" data-bs-slide="prev">
    <span class="carousel-control-prev-icon" aria-
hidden="true"></span>
    <span class="visually-hidden">Previous</span>
</button>

<button class="carousel-control-next" type="button" data-bs-
target="#carouselId" data-bs-slide="next">
    <span class="carousel-control-next-icon" aria-
hidden="true"></span>
    <span class="visually-hidden">Next</span>
</button></div>
</div></body></html>

```