



Department of Computer Science
Faculty of Computing
UNIVERSITI TEKNOLOGI MALAYSIA

SUBJECT NAME: COMPUTER ORGANIZATION AND ARCHITECTURE

SUBJECT CODE: SECR 1033

SEMESTER: 2 - 2023/24

LAB TITLE: **Programming 3: Interactive Usage of Link Libraries
and Comparison & Conditional Jumps**

PART 1: Interactive Usage of Link Libraries
PART 2: Comparison & Conditional Jumps

INSTRUCTION: Complete the lab activities in Part 1C and Part 2C and divide loads among group member equally

STUDENT INFO : Name : NG YU HIN
Metric No : A23CS0148
Section: 02
Email : nghin@graduate.utm.my

STUDENT INFO : Name : ELIJAH SHE YU SHENG
Metric No : A23CS0073
Section : 02
Email : elijahsheyu@graduate.utm.my

COMMENTS:

Computer Organization and Architecture SECR 2033

Programming 3: Interactive Usage of Link Libraries and Comparison & Conditional Jumps

PART 1: Interactive Usage of Link Libraries

Part 1A – Programming review


Link Library Overview

- A file containing procedures that have been compiled into machine code
- These procedures are ready to be used (via the CALL instruction) within your program. They have their own unique name.
- Most, if not all, of these procedures run on pre-selected registers which you MUST use.

Calling a Library Procedure


- Call a library procedure using the CALL instruction. Some procedures require input arguments.
- The INCLUDE directive copies in the procedure prototypes (declarations).
- The following example displays "1234" on the console (as shown in output):

```
INCLUDE Irvine32.inc
.code
    mov eax,1234h    ; input argument
    call WriteHex    ; show hex number
    call Crlf        ; end of line
```



- In the example above, register EAX must be used for it to work correctly. Try the command below and see what happens.

```
INCLUDE Irvine32.inc
.code
    mov ax,1234h     ; input argument
    call WriteHex    ; show hex number
    call Crlf        ; end of line
```



Library Procedures – Overview

Here are some of the procedures available to you. You can find more from the Internet and reference books (Kip Irvine, Assembly Language programming books are a good place to start).

- Clrscr - Clears the console and locates the cursor at the upper left corner.
- Crlf - Writes an end of line sequence to standard output.
- Delay - Pauses the program execution for a specified *n* millisecond interval.
- DumpMem - Writes a block of memory to standard output in hexadecimal.
- DumpRegs - Displays the EAX, EBX, ECX, EDX, ESI, EDI, EBP, ESP, EFLAGS, and EIP registers in hexadecimal. Also displays the Carry, Sign, Zero, and Overflow flags.
- GetCommandtail - Copies the program's command-line arguments (called the *command tail*) into an array of bytes.
- GetMseconds - Returns the number of milliseconds that have elapsed since midnight.
- Gotoxy - Locates cursor at row and column on the console.
- Random32 - Generates a 32-bit pseudorandom integer in the range 0 to FFFFFFFFh.
- Randomize - Seeds the random number generator.
- RandomRange - Generates a pseudorandom integer within a specified range.
- ReadChar - Reads a single character from standard input.
- ReadHex - Reads a 32-bit hexadecimal integer from standard input, terminated by the Enter key.
- ReadInt - Reads a 32-bit signed decimal integer from standard input, terminated by the Enter key.
- ReadString - Reads a string from standard input, terminated by the Enter key.
- SetTextColor - Sets the foreground and background colors of all subsequent text output to the console.
- WaitMsg - Displays message, waits for Enter key to be pressed.
- WriteBin - Writes an unsigned 32-bit integer to standard output in ASCII binary format.
- WriteChar - Writes a single character to standard output.
- WriteDec - Writes an unsigned 32-bit integer to standard output in decimal format.
- WriteHex - Writes an unsigned 32-bit integer to standard output in hexadecimal format.
- WriteInt - Writes a signed 32-bit integer to standard output in decimal format.
- WriteString - Writes a null-terminated string to standard output.

Reference:

<https://csc.csudh.edu/mmccullough/asm/help/>

 [Irvine Library](#)

Part 1B – Let's do a little programming by example

You are given a few examples here. Try them out.

Example 1


Clear the screen, delay the program for **500 milliseconds**, and dump the registers and flags.

```
.code
    call Clrscr
    mov eax,500
    call Delay
    call DumpRegs
```

Example 2

Display a null-terminated **string** and move the cursor to the beginning of the next screen line. Attach the output screen capture for this example.


```
.data
str1 BYTE "Assembly language is easy!",0
.code
    mov edx,OFFSET str1
    call WriteString
    call CrLf
```



Example 3

Display an unsigned integer in binary, decimal, and hexadecimal, each on a separate line. Attach the output screen capture for this example.


```
.data IntVal = 35
.code
    mov eax,IntVal
    call WriteBin ; display binary
    call CrLf
    call WriteDec ; display decimal
    call CrLf
    call WriteHex; display hexadecimal call
    CrLf
```



Example 4

Input a string from the user (*ReadString*). EDX points to the string. Attach the output screen capture for this example. (**Tips: It is always a good practice to have a string to ask for input)

```
.data
str2 BYTE "Give me your name: ",0
buffer2 BYTE 21 DUP(0) ; input buffer
.code
```



```

mov edx, OFFSET str2 ; display message1
call WriteString
call crlf
mov edx,OFFSET buffer2 ; point to the buffer
mov ecx,SIZEOF buffer2 ; specify max characters
call ReadString ; input the string
mov edx, OFFSET buffer2 ; point to the buffer
call WriteString
call crlf

```

Example 5

Input a decimal number from the user (*ReadDec*).. The procedure reads a 32- bit unsigned decimal integer from the keyboard and returns the value in EAX. **Output a number** to screen (*WriteDec*). The procedure writes a 32-bit unsigned integer to the console window in decimal format with no leading zeros. Pass the integer in EAX. Attach the output screen capture for this example. (**Tips: It is always a good practice to have a string to ask for input)

```

.data
str1 BYTE "Enter a decimal: ",0
decNum DWORD ?
promptBad BYTE "Invalid input, please enter again",0

.code
mov edx, offset str1
call writestring

read:  call ReadDec
      jnc goodInput
      mov  edx,OFFSET promptBad
      call WriteString
      jmp  read          ;go input again

goodInput:
      mov  decNum,eax    ;store good value
      call WriteDec

```



Example 6


Generate and display ten pseudorandom signed integers in the range 0 – 99. Pass each integer to WriteInt in EAX and display it on a separate line. Attach the output screen capture for this example.

```

.code
mov ecx,10 ; loop counter

L1:  mov  eax,100 ; ceiling value
      call RandomRange ; generate random int
      call WriteInt    ; display signed int
      call Crlf        ; goto next display line
      loop L1          ; repeat loop

```



Part 1C – Let's do a little programming on your own

Program 1: LOOP and ADD




Figure 1 : A hexagon

Figure 1 illustrates a hexagon figure with same length of side. To calculate the perimeter of the hexagon, the following formula is given.

$$\text{Perimeter_hexagon1} = \text{side1} + \text{side2} + \text{side3} + \text{side4} + \text{side5} + \text{side6}$$

$$\text{Perimeter_hexagon2} = \text{side1} + \text{side2} + \text{side3} + \text{side4} + \text{side5} + \text{side6}$$

$$\text{TotalPerimeter} = \text{Perimeter_hexagon1} + \text{Perimeter_hexagon2}$$

Write a complete program using assembly language to calculate the perimeter of TWO different hexagons with different sizes.

In the program, you should do these steps:

- i. Get two values from keyboard (32-bit unsigned integer) and save into the variable name **sideHex1** for the first hexagon and **sideHex2** for the second hexagon.
- ii. Calculate both of the perimeters (Example: $\text{Perimeter_hexagon1} = 18 \rightarrow 3+3+3+3+3+3$) by using LOOP and ADD instruction. Save the first result in **Perimeter_hexagon1** and the second result in **Perimeter_hexagon2** (as 32-bit unsigned integer).
- iii. Then, add the two perimeters and save in **TotalPerimeter** variable.
- iv. Display the output as shown in Figure 2.

```
C:\Drive D Old\Pengajaran COA\Sem 2 20232024\materials\Lab\Lab 3 new 2024\lab3new
Calculate Perimeter 2-Hexagon (LOOP and ADD instructions) :
Input Hexagon 1 (side length) : 21
Input Hexagon 2 (side length) : 32
Result of Perimeter Hexagon 1 and 2:
126
192
Total Perimeter Hexagon 1 and 2: 318
```

Figure 2: Sample Output

Program 2

Write a program that will **interactively** ask the **user to input the values of 6 integers** in DWORD and you have to put the values into an array name HELLO.

- Example of HELLO array after the user input the values:

1 st Value	2 nd Value	3 rd Value	4 th Value	5 th Value	6 th Value
HELLO[0]	HELLO[4]	HELLO[8]	HELLO[12]	HELLO[16]	HELLO[20]
32	65	77	89	14	54

- Your CountEVEN will count the value of HELLO[0], HELLO[8] and HELLO[16] and store it in variable name TotalEVEN
- Your CountODD will count the value of HELLO[4], HELLO[12] and HELLO[20] store it in variable name TotalODD
- Lastly, display the value of TotalEVEN and TotalODD
- Display the output as shown in Figure 3.
- **You must use LOOP instruction to do the addition process.**

```
C:\Drive D Old\Pengajaran COA\Sem 2 20232024\materials\Lab\Lab 3 new 2024\lab3new\Debug'
Calculate SUM (unsign INT) index (Odd or Even) in array Hello[6] :

Integer Input : 20
Integer Input : 25
Integer Input : 30
Integer Input : 37
Integer Input : 40
Integer Input : 43

Result Sum Hello[index]:

Sum Hello[even] index location : 90
Sum Hello[odd] index location : 105
```

Figure 3: Sample Output

PART 2: Comparison & Conditional Jumps

Part 2A – Programming review

A) BOOLEAN and COMPARISON INSTRUCTIONS

Logical Instructions

The processor instruction set provides the instructions AND, OR, XOR, TEST and NOT Boolean logic, which tests, sets and clears the bits according to the need of the program. These instructions set the CF, OF, PF, SF and ZF flags.

Conditional Instructions

Sometimes a program needs to do different things depending on the result of an operation. As shown in Figure 2.1, if the conditions are met then process A. Otherwise, proceed with process B. This is conditional branching. This is different from unconditional branching (the JMP instruction) previously studied.




Figure 2.1

Compare (CMP) instruction

First, let us look at the compare (CMP) instruction. This instruction is used in to test branching conditions.

- The CMP instruction compares two operands.
- This instruction basically subtracts one operand from the other for comparing whether the operands are equal or not.
- It does not disturb the destination or source operands (i.e. these does not change)
- The instruction format:
 - The destination operand can be either register or memory.
 - The source operand can be register, memory or immediate value.

CMP Destination, Source

<code>CMP BX, 00 ; Compare the value in BX with zero JE TARGET ; Jump to TARGET if Equal</code>

Sneak-peek: JE is Jump if Equal

B) CONDITIONAL JUMPS

Conditional Branching or Conditional Jump

This is performed by a set of jump instructions depending upon the condition. The conditional instructions transfer the control by breaking the sequential flow and they do it by changing the offset value in IP (Instruction Pointer). □ Written in the form J<condition>. Example: JE, JNZ, JL, JG

- There are different groups of conditional jump instructions:
 - Jumps based on specific flag values
 - Jumps based on equality between operands or the value of (E)CX
 - Jumps based on comparisons of unsigned operands
 - Jumps based on comparisons of signed operands
- The instruction format:

J<condition> TARGET

Examples:

JE TARGET
JNZ TARGET
JL TARGET

Table 1: Jumps based on specific flag values

Instruction	Description
JZ	Jump if zero; ZF = 1
JNZ	Jump if not zero; ZF = 0
JC	Jump if carry; CF = 1
JNC	Jump if not carry; CF = 0
JO	Jump if overflow; OF = 1
JNO	Jump if not overflow; OF = 0
JS	Jump if signed; SF = 1
JNS	Jump if not signed; SF = 0
JP	Jump if parity (even); PF = 1
JNP	Jump if not parity (odd); PF = 0

Table 2: Jumps based on equality between operands or the value of (E)CX

Instruction	Description	Instruction	Description
JE	Jump if equal	JCXZ	Jump if CX=0
JNE	Jump if not equal	JECXZ	Jump if ECX ≠ 0

Table 3: Jumps based on comparisons of unsigned operands

Instruction	Description	Instruction	Description
JA	Jump if above	JNBE	Jump if not below or equal
JAE	Jump if above or equal	JNB	Jump if not below
JB	Jump if below	JNAE	Jump if not above or equal
JBE	Jump if below or equal	JNA	Jump if not above

Note: These are only meaningful when comparing unsigned values

Table 4: Jumps based on comparisons of signed operands

Instruction	Description	Instruction	Description
JG	Jump if above	JNLE	Jump if not less or equal
JGE	Jump if above or equal	JNL	Jump if not less
JL	Jump if less	JNGE	Jump if not greater or equal
JLE	Jump if less or equal	JNG	Jump if not greater

Note: These are only meaningful when comparing signed values

Part 2B – Let's do a little programming by example

You are given a few examples here. Try them out.

Example 1

Increment AX by 1 until reaches the value of 10. This is essentially doing a loop using a CMP command.

<pre>;using CMP MOV EAX,0 L1: INC AX CMP AX, 10 JL L1 MOV TOTAL, AX</pre>	<pre>;using LOOP MOV EBX,0 MOV ECX,10 L2: INC BX LOOP L2 MOV TOTALS, BX</pre>
---	---

Note: the result of both TOTAL and TOTALS are the same.

Example 2

Some conditional jumps examples.

```
MOV AX,4
CMP AX,4      ; compare AX with 4
JE L1  ; if AX = 4 then jump to L1
MOV BX,0AAAAH ; do this if AX ≠ 4

JMP HERE      ; use this to guide the program sequence
L1:
MOV BX, 0BBBBH ; do this if AX = 4

HERE:
CALL DUMPREGS
```

```
MOV AX,TOTAL    ; say TOTAL can be 2 or 4
SUB AX,2
JZ L2           ; if ZF = 1, jump to L2
MOV BX,0AAAAH   ; this is done if TOTAL = 4
JMP HERE

L2:             ; this is done if TOTAL = 2
MOV BX,0BBBBH   ;

HERE:
CALL DUMPREGS
```

Example 3

A look into signed and unsigned comparisons. The same value compared as signed and unsigned will yield different results. JA is a jump based on unsigned comparison while JG is a jump based on signed comparison. In the example below, JA will not go to L3 (unsigned 7Fh is smaller than unsigned 80h) but JG will jump to L4 (signed 7Fh is larger than signed 80h).

```
        MOV AX,7FH
        MOV BX,80H
        CMP AX,BX
        JA L3                ; jump based on
unsigned comparison
        MOV CX,0AAAAH
        JMP HERE
L3:
        MOV CX, 0BBBBH

HERE:
        CALL DUMPREGS
        MOV AX,+127          ; signed version of 7FH
        MOV BX,-128          ; signed version of 80H
        CMP AX,BX
        JG L4                ; jump based on signed
comparison
        MOV DX,0DDDDH
        JMP SINI
L4:
        MOV DX,0EEEEH

SINI:
        CALL DUMPREGS

EXIT
```

Part 2C – Let's do a little programming on your own

Combine in Part 1- Program 1 and Program 2 and create a MENU OPTION:

Example:

Welcome to Simple Math Activities:

Select Your Option (Main Menu):

1. To calculate Perimeter Hexagon (Loop and ADD instructions)
2. To calculate SUM (unsign int) index (Odd or Even) in an Array Matrix

Continue – type (y) and Exit type (n): **y** or **n**

Thank you ... BYE !!!

Branch Condition:

```
If (select == 1)
    jmp_to periHex_loopAdd
```

```
If (select == 2)
    jum_to calSum_oddeven
```

```
If (char_in == y)
    clear screen & Main Menu
else
    Exit program
```


Operation Label:

```
periHex_loopAdd:
    do calculate Perimeter Hexagon (Loop and ADD instructions)
```

```
calSum_oddeven
    calculate SUM (unsign int) index (Odd or Even) in an Array Matrix
```

Sampel Output is shown in the following Figure 3.1 to 3.4.

Main Menu



```
C:\Drive D Old\Pengajaran COA\Sem 2 20232024\materials\Lab\Lab 3 new 2024\lab3new\Debug\templatelab1.exe
Welcome to Simple Math Activities :

Main Menu :


1. To calculate Perimeter Hexagon (Loop and ADD instructions)
2. To calculate SUM (unsign int) index [Odd or Even] in an Array Hello [6]

Select Your Input :
```

Figure 3.1. Main Menu

Select Option:

1. To calculate Perimeter Hexagon (Loop and ADD instructions)



```
Select C:\Drive D Old\Pengajaran COA\Sem 2 20232024\materials\Lab\Lab 3 new 2024\lab3new
Calculate Perimeter 2-Hexagon (LOOP and ADD instructions) :

Input Hexagon 1 (side length) : 21
Input Hexagon 2 (side length) : 32

Result of Perimeter Hexagon 1 and 2:
126
192

Total Perimeter Hexagon 1 and 2: 318

Press 'y' to Main Menu or 'n' to Exit the benchmark :
```

Figure 3.2. Perimeter Hexagon

2. To calculate SUM (unsign int) index (Odd or Even) in an Array Matrix

```
C:\Drive D Old\Pengajaran COA\Sem 2 20232024\materials\Lab\Lab 3 new 2024\lab3new\Debug\1
Calculate SUM (unsign INT) index (Odd or Even) in array Hello[6] :
Interger Input : 20
Interger Input : 25
Interger Input : 30
Interger Input : 37
Interger Input : 40
Interger Input : 43

Result Sum Hello[index]:
Sum Hello[even] index location : 90
Sum Hello[odd] index location : 105

Press 'y' to Main Menu or 'n' to Exit the benchmark :
```

Figure 3.3. Array Sum Index Even and Odd in Hello [6]

3. Exit

```
Press 'y' to Main Menu or 'n' to Exit the benchmark : n
Thank you ... BYE!!
```

Figure 3.4. Exit Program