

Actively Secure Half-Gates with Minimum Overhead under Duplex Networks

Hongrui Cui

Shanghai Jiao Tong University



Kang Yang

State Key Laboratory of Cryptology



Xiao Wang

Northwestern University



Yu Yu

Shanghai Jiao Tong University

Shanghai Qi Zhi Institute



上海期智研究院

SHANGHAI QI ZHI INSTITUTE

Background on Constant Round 2PC

■ Steady improvement in the semi-honest world

Textbook [Yao86]	P&P [BMR90]	GRR3 [NPS99]	GRR2 [PSSW90]	Free-XOR [KS08]	FleXOR [KMR14]	Half-Gates [ZRE15]	Three-Halves [RR21]
XOR: 8κ AND: 8κ	XOR: 4κ AND: 4κ	XOR: 3κ AND: 3κ	XOR: 2κ AND: 2κ	XOR: 0 AND: 3κ	$\{0, 1, 2\}_\kappa$	2κ	$1.5\kappa + 5$

Background on Constant Round 2PC

■ Steady improvement in the semi-honest world

Textbook [Yao86]	P&P [BMR90]	GRR3 [NPS99]	GRR2 [PSSW90]	Free-XOR [KS08]	FleXOR [KMR14]	Half-Gates [ZRE15]	Three-Halves [RR21]
XOR: 8κ AND: 8κ	XOR: 4κ AND: 4κ	XOR: 3κ AND: 3κ	XOR: 2κ AND: 2κ	XOR: 0 AND: 3κ	$\{0, 1, 2\}_\kappa$	2κ	$1.5\kappa + 5$

■ What about the malicious world?

Cut-and-Choose [LP07,NO09,HKE13,NST17,...]
$O(\rho\kappa)$ or $O(\frac{\rho\kappa}{\log C})$


Background on Constant Round 2PC

■ Steady improvement in the semi-honest world

Textbook [Yao86]	P&P [BMR90]	GRR3 [NPS99]	GRR2 [PSSW90]	Free-XOR [KS08]	FleXOR [KMR14]	Half-Gates [ZRE15]	Three-Halves [RR21]
XOR: 8κ AND: 8κ	XOR: 4κ AND: 4κ	XOR: 3κ AND: 3κ	XOR: 2κ AND: 2κ	XOR: 0 AND: 3κ	$\{0, 1, 2\}_\kappa$	2κ	$1.5\kappa + 5$

■ What about the malicious world?

Cut-and-Choose [LP07,NO09,HKE13,NST17,...]	Authenticated Garbling [WRK17,KRRW18]
$O(\rho\kappa)$ or $O(\frac{\rho\kappa}{\log C})$	$\Pi_{\text{pre}}: 13\kappa + 8\rho$ $\Pi_{\text{online}}: 2\kappa + 1$




Background on Constant Round 2PC

- Steady improvement in the semi-honest world

Textbook [Yao86]	P&P [BMR90]	GRR3 [NPS99]	GRR2 [PSSW90]	Free-XOR [KS08]	FleXOR [KMR14]	Half-Gates [ZRE15]	Three-Halves [RR21]
XOR: 8κ	XOR: 4κ	XOR: 3κ	XOR: 2κ	XOR: 0	$\{0, 1, 2\}_\kappa$	2κ	$1.5\kappa + 5$
AND: 8κ	AND: 4κ	AND: 3κ	AND: 2κ	AND: 3κ			

- What about the malicious world?

Cut-and-Choose [LP07,NO09,HKE13,NST17,...]	Authenticated Garbling [WRK17,KRRW18]	PCGs [BCG+19, YWL+20, CRR21,...]
$O(\rho\kappa)$ or $O(\frac{\rho\kappa}{\log C})$	$\Pi_{\text{pre}}: 13\kappa + 8\rho$ $\Pi_{\text{online}}: 2\kappa + 1$	




Background on Constant Round 2PC

- Steady improvement in the semi-honest world

Textbook	P&P	GRR3	GRR2	Free-XOR	FleXOR	Half-Gates	Three-Halves
[Yao86]	[BMR90]	[NPS99]	[PSSW90]	[KS08]	[KMR14]	[ZRE15]	[RR21]
XOR: 8κ	XOR: 4κ	XOR: 3κ	XOR: 2κ	XOR: 0	$\{0, 1, 2\}_\kappa$	2κ	$1.5\kappa + 5$
AND: 8κ	AND: 4κ	AND: 3κ	AND: 2κ	AND: 3κ			

■ What about the malicious world?

Cut-and-Choose [LP07,NO09,HKE13,NST17,...]	Authenticated Garbling [WRK17,KRRW18]	PCGs [BCG+19, YWL+20, CRR21,...]	AG from PCG [DILO22]
$O(\rho\kappa)$ or $O(\frac{\rho\kappa}{\log C})$	$\Pi_{\text{pre}}: 13\kappa + 8\rho$ $\Pi_{\text{online}}: 2\kappa + 1$		$\mathcal{F}_{\text{VOLE-hyb.}} 2\kappa + 8\rho$ $\mathcal{F}_{\text{DAMT-hyb.}} 2\kappa + 4\rho$




Can we close the gap?

Our Contributions

- Authenticated garbling with one-way comm. as small as semi-honest half-gates

2PC	Rounds		Communication per AND gate	
	Prep.	Online	one-way (bits)	two-way (bits)
Half-gates	1	2	2κ	2κ
HSS-PCG	8	2	$8\kappa + 11$ (4.04 \times)	$16\kappa + 22$ (8.09 \times)
KRRW-PCG	4	4	$5\kappa + 7$ (2.53 \times)	$8\kappa + 14$ (4.05 \times)
DILO	7	2	$2\kappa + 8\rho + 1$ (2.25 \times)	$2\kappa + 8\rho + 5$ (2.27 \times)
This work	8	3	$2\kappa + 5$ ($\approx 1\times$)	$4\kappa + 10$ (2.04 \times)
This work+DILO	8	2	$2\kappa + 3\rho + 2$ (1.48 \times)	$2\kappa + 3\rho + 4$ ($\approx 1.48\times$)



Authenticated Garbling = Distributed Garbling + Checking



controls garbling so it can

Λ_i	Λ_j	Masked L_{k,Λ_k}
0	0	$L_{k,0} \oplus (\lambda_i \cdot \lambda_j \oplus \lambda_k) \Delta_A$
0	1	$L_{k,0} \oplus (\lambda_i \cdot \bar{\lambda}_j \oplus \lambda_k) \Delta_A$
1	0	$L_{k,0} \oplus (\bar{\lambda}_i \cdot \lambda_j \oplus \lambda_k) \Delta_A$
1	1	$L_{k,0} \oplus (\bar{\lambda}_i \cdot \bar{\lambda}_j \oplus \lambda_k) \Delta_A$


- selective-failure on $\Lambda := z \oplus \lambda \Rightarrow$ Secret share $\lambda := a \oplus b$
- garble different logic \Rightarrow Add IT-MAC, equality check, etc.

Authenticated Garbling = Distributed Garbling + Checking


 controls garbling so it can

Λ_i	Λ_j	Masked L_{k,Λ_k}
0	0	$L_{k,0} \oplus (\lambda_i \cdot \lambda_j \oplus \lambda_k)\Delta_A$
0	1	$L_{k,0} \oplus (\lambda_i \cdot \bar{\lambda}_j \oplus \lambda_k)\Delta_A$
1	0	$L_{k,0} \oplus (\bar{\lambda}_i \cdot \lambda_j \oplus \lambda_k)\Delta_A$
1	1	$L_{k,0} \oplus (\bar{\lambda}_i \cdot \bar{\lambda}_j \oplus \lambda_k)\Delta_A$

- selective-failure on $\Lambda := z \oplus \lambda \Rightarrow$ Secret share $\lambda := a \oplus b$
- garble different logic \Rightarrow Add IT-MAC, equality check, etc.
- We need preprocessing information to complete garbling



$$a \oplus a = a \cdot \Delta_B$$



a, \hat{a}, Δ_A


$a \quad \hat{a} \quad b \quad \hat{b}$

samples

$\mathcal{F}_{\text{pre}} \quad [a], [\hat{a}], [b], [\hat{b}]$

Δ_A, Δ_B

$\hat{a}_k \oplus \hat{b}_k = \lambda_i \cdot \lambda_j \text{ for } (i, j, k, \wedge)$



b, \hat{b}, Δ_B


$a \quad \hat{a} \quad b \quad \hat{b}$

Authenticated Garbling = Distributed Garbling + Checking


 controls garbling so it can

Λ_i	Λ_j	Masked L_{k,Λ_k}
0	0	$L_{k,0} \oplus (\lambda_i \cdot \lambda_j \oplus \lambda_k)\Delta_A$
0	1	$L_{k,0} \oplus (\lambda_i \cdot \bar{\lambda}_j \oplus \lambda_k)\Delta_A$
1	0	$L_{k,0} \oplus (\bar{\lambda}_i \cdot \lambda_j \oplus \lambda_k)\Delta_A$
1	1	$L_{k,0} \oplus (\bar{\lambda}_i \cdot \bar{\lambda}_j \oplus \lambda_k)\Delta_A$

- selective-failure on $\Lambda := z \oplus \lambda \Rightarrow$ Secret share $\lambda := a \oplus b$
- garble different logic \Rightarrow Add IT-MAC, equality check, etc.
- We need preprocessing information to complete garbling




$$a \oplus a = a \cdot \Delta_B$$



 a, \hat{a}, Δ_A

\mathcal{F}_{pre}

samples
 $[a], [\hat{a}], [b], [\hat{b}]$
 Δ_A, Δ_B

$\hat{a}_k \oplus \hat{b}_k = \lambda_i \cdot \lambda_j \text{ for } (i, j, k, \wedge)$


 b, \hat{b}, Δ_B



Λ_i	Λ_j	Alice's GC	Bob's GC
0	0	$L_{k,0} \oplus K[\Lambda_{00}]$	$M[\Lambda_{00}]$
0	1	$L_{k,0} \oplus K[\Lambda_{01}]$	$M[\Lambda_{01}]$
1	0	$L_{k,0} \oplus K[\Lambda_{10}]$	$M[\Lambda_{10}]$
1	1	$L_{k,0} \oplus K[\Lambda_{11}]$	$M[\Lambda_{11}]$

$$\Lambda_k \cdot \Delta_A := \lambda_k \cdot \Delta_A \oplus (\Lambda_i \oplus \lambda_i) \cdot (\Lambda_j \oplus \lambda_j) \cdot \Delta_A$$

$$= \lambda_k \cdot \Delta_A \oplus \dots \oplus (\hat{a}_k \oplus \hat{b}_k) \cdot \Delta_A$$


Free-XOR GC \Rightarrow
 $|\Delta_A| = \kappa \approx 128$

Authenticated Garbling = Distributed Garbling + Checking

 controls garbling so it can

Λ_i	Λ_j	Masked L_{k,Λ_k}
0	0	$L_{k,0} \oplus (\lambda_i \cdot \lambda_j \oplus \lambda_k)\Delta_A$
0	1	$L_{k,0} \oplus (\lambda_i \cdot \bar{\lambda}_j \oplus \lambda_k)\Delta_A$
1	0	$L_{k,0} \oplus (\bar{\lambda}_i \cdot \lambda_j \oplus \lambda_k)\Delta_A$
1	1	$L_{k,0} \oplus (\bar{\lambda}_i \cdot \bar{\lambda}_j \oplus \lambda_k)\Delta_A$

- selective-failure on $\Lambda := z \oplus \lambda \Rightarrow$ Secret share $\lambda := a \oplus b$
- garble different logic \Rightarrow Add IT-MAC, equality check, etc.
- We need preprocessing information to complete garbling



Λ_i	Λ_j	Alice's GC	Bob's GC
0	0	$L_{k,0} \oplus K[\Lambda_{00}]$	$M[\Lambda_{00}]$
0	1	$L_{k,0} \oplus K[\Lambda_{01}]$	$M[\Lambda_{01}]$
1	0	$L_{k,0} \oplus K[\Lambda_{10}]$	$M[\Lambda_{10}]$
1	1	$L_{k,0} \oplus K[\Lambda_{11}]$	$M[\Lambda_{11}]$

Free-XOR GC \Rightarrow
 $|\Delta_A| = \kappa \approx 128$

$$\Lambda_k \cdot \Delta_A := \lambda_k \cdot \Delta_A \oplus (\Lambda_i \oplus \lambda_i) \cdot (\Lambda_j \oplus \lambda_j) \cdot \Delta_A$$

$$= \lambda_k \cdot \Delta_A \oplus \dots \oplus (\hat{a}_k \oplus \hat{b}_k) \cdot \Delta_A$$

$$\Lambda_k \cdot \Delta_B := \lambda_k \cdot \Delta_B \oplus (\Lambda_i \oplus \lambda_i) \cdot (\Lambda_j \oplus \lambda_j) \cdot \Delta_B$$


$$= \lambda_k \cdot \Delta_B \oplus \dots \oplus (\hat{a}_k \oplus \hat{b}_k) \cdot \Delta_B$$

Λ_i	Λ_j	Alice's AuthGC	Bob's AuthGC
0	0	$L_{k,0} \oplus M[\Lambda_{00}]$	$K[\Lambda_{00}]$
0	1	$L_{k,0} \oplus M[\Lambda_{01}]$	$K[\Lambda_{01}]$
1	0	$L_{k,0} \oplus M[\Lambda_{10}]$	$K[\Lambda_{10}]$
1	1	$L_{k,0} \oplus M[\Lambda_{11}]$	$K[\Lambda_{11}]$

IT-MAC Soundness \Rightarrow
 $|\Delta_B| = \rho \approx 40$

KRRW18: Distributed Half-Gates Garbling + Equality Checking

- Distributed half-gates garbling is fully compatible with \mathcal{F}_{pre}




$$\begin{aligned} \Lambda_k \cdot \Delta_A &:= \lambda_k \cdot \Delta_A \oplus (\Lambda_i \oplus \lambda_i) \cdot (\Lambda_j \oplus \lambda_j) \cdot \Delta_A \\ &= \underbrace{(\lambda_k \oplus \lambda_i \lambda_j) \cdot \Delta_A}_{\text{already shared}} \oplus \underbrace{\Lambda_i \lambda_j \cdot \Delta_A}_{G_{k,0}} \oplus \underbrace{\Lambda_j (\Lambda_i \oplus \lambda_i) \cdot \Delta_A}_{G_{k,1}} \end{aligned}$$

4κ bits/AND WRK17	\Rightarrow	$2\kappa + 1$ bits/AND KRRW18
-----------------------------	---------------	----------------------------------

KRRW18: Distributed Half-Gates Garbling + Equality Checking

- Distributed half-gates garbling is fully compatible with \mathcal{F}_{pre}



$$\begin{aligned} \Lambda_k \cdot \Delta_A &:= \lambda_k \cdot \Delta_A \oplus (\Lambda_i \oplus \lambda_i) \cdot (\Lambda_j \oplus \lambda_j) \cdot \Delta_A \\ &= \underbrace{(\lambda_k \oplus \lambda_i \lambda_j) \cdot \Delta_A}_{\text{already shared}} \oplus \underbrace{\Lambda_i \lambda_j \cdot \Delta_A}_{G_{k,0}} \oplus \underbrace{\Lambda_j (\Lambda_i \oplus \lambda_i) \cdot \Delta_A}_{G_{k,1}} \end{aligned}$$

4κ bits/AND
WRK17

⇒

2κ + 1 bits/AND
KRRW18

- b**-mask removes selective failure, now only need to check correct AND correlation

$\Lambda_k \oplus \lambda_k = (\Lambda_i \oplus \lambda_i) \cdot (\Lambda_j \oplus \lambda_j)$
 $\Leftrightarrow e_k := \Lambda_k \oplus \lambda_k \oplus \Lambda_i \Lambda_j \oplus \Lambda_i \lambda_j \oplus \lambda_i \Lambda_j \oplus \lambda_i \lambda_j = 0$


Check:

- Evaluator sends $\{\Lambda_w\}$ for all AND gates
- The checking equation reduces to equality check
- Use random linear combination to reduce comm.


4ρ bits/AND
WRK17

⇒

0 bits/AND
KRRW18




Efficient COT/sVOLE and Designated Verifier Zero Knowledge



- Efficient protocol for $\mathcal{F}_{\text{COT}}, \mathcal{F}_{\text{sVOLE}}$ with sublinear comm. and linear comp. from LPN [YWL+20, CRR21, ...]
- We refer the $\mathbb{F}_p = \mathbb{F}_2$ variant of $\mathcal{F}_{\text{sVOLE}}$ as \mathcal{F}_{COT}

Efficient COT/sVOLE and Designated Verifier Zero Knowledge



- Efficient protocol for $\mathcal{F}_{\text{COT}}, \mathcal{F}_{\text{sVOLE}}$ with sublinear comm. and linear comp. from LPN [YWL+20,CRR21,...]
- We refer the $\mathbb{F}_p = \mathbb{F}_2$ variant of $\mathcal{F}_{\text{sVOLE}}$ as \mathcal{F}_{COT}


Derandomization operation: Fix

$\delta := \mathbf{x} \oplus \mathbf{u}$


$\mathbf{x} := \mathbf{u}$

$\mathbf{x} := \mathbf{u} \oplus \delta \cdot \Delta$


Efficient COT/sVOLE and Designated Verifier Zero Knowledge




- Efficient protocol for $\mathcal{F}_{\text{COT}}, \mathcal{F}_{\text{sVOLE}}$ with sublinear comm. and linear comp. from LPN [YWL+20, CRR21, ...]
- We refer the $\mathbb{F}_p = \mathbb{F}_2$ variant of $\mathcal{F}_{\text{sVOLE}}$ as \mathcal{F}_{COT}



- Efficient proof for deg- d relations on \mathbf{u} [DIO21, YSWW21, ...]




Efficient COT/sVOLE and Designated Verifier Zero Knowledge




- Efficient protocol for $\mathcal{F}_{\text{COT}}, \mathcal{F}_{\text{sVOLE}}$ with sublinear comm. and linear comp. from LPN [YWL+20, CRR21, ...]
- We refer the $\mathbb{F}_p = \mathbb{F}_2$ variant of $\mathcal{F}_{\text{sVOLE}}$ as \mathcal{F}_{COT}

Derandomization operation: Fix




- Efficient proof for deg- d relations on u [DIO21, YSWW21, ...]




- In DILO, those PCG correlations are called “simple correlations”
- Unfortunately, we still don’t have an efficient direct \mathcal{F}_{pre} PCG construction
- The closest is the $\mathcal{F}_{\text{DAMT}}$ correlation generated from Ring-LPN, but with ρ -time overhead

Prior Art: DILO



- Garbler can only guess once
- If \mathbf{b} is uniformly random, then guessing leaks no information
- If #Guess is too large, then abort happens overwhelmingly, if #Guess is too little, then we don't require much entropy from \mathbf{b}

Prior Art: DILO




- Garbler can only guess once
- If \mathbf{b} is uniformly random, then guessing leaks no information
- If #Guess is too large, then abort happens overwhelmingly, if #Guess is too little, then we don't require much entropy from \mathbf{b}

DILO Observation 1

It suffices for \mathbf{b} to be ρ -wise independent

- #Guess $\leq \rho$: Abort is input-independent
- #Guess $> \rho$: Abort is overwhelming

Prior Art: DILO



- Garbler can only guess once
- If \mathbf{b} is uniformly random, then guessing leaks no information
- If #Guess is too large, then abort happens overwhelmingly, if #Guess is too little, then we don't require much entropy from \mathbf{b}

DILO Observation 1

It suffices for \mathbf{b} to be ρ -wise independent

- #Guess $\leq \rho$: Abort is input-independent
- #Guess $> \rho$: Abort is overwhelming


DILO Observation 2

We can construct ρ -wise independent \mathbf{b} by linear expansion


$$\mathbf{b} = \mathbf{M} \times \mathbf{b}^*$$

- For $L = O(\rho \cdot \log(\frac{n}{\rho}))$, a uniformly random \mathbf{M} suffices
- We can encode \mathbf{b}^* in \mathcal{F}_{COT} global keys


DILO Implementation of $\mathcal{F}_{\text{cpre}}$: Encoding \mathbf{b}^* as Global Keys




DILO Implementation of $\mathcal{F}_{\text{cpre}}$: Encoding \mathbf{b}^* as Global Keys




- COT can be extended to block COT, preserving PCG efficiency



DILO Implementation of $\mathcal{F}_{\text{cpre}}$: Computing \hat{b}_k




DILO Implementation of $\mathcal{F}_{\text{cpre}}$: Computing \hat{b}_k




- $[a]_{b_j^* \Delta_B} \equiv [ab_j^*]_{\Delta_B}$
- By linearity on IT-MAC, we can get $[a_i b_j]_{\Delta_B}$ for any i, j


DILO Implementation of $\mathcal{F}_{\text{cpre}}$: Computing \hat{b}_k




- $[\mathbf{a}]_{b_j^* \Delta_B} \equiv [\mathbf{a} b_j^*]_{\Delta_B}$
- By linearity on IT-MAC, we can get $[a_i b_j]_{\Delta_B}$ for any i, j



DILO Implementation of $\mathcal{F}_{\text{cpre}}$: Computing \hat{b}_k





- $[\mathbf{a}]_{b_j^* \Delta_B} \equiv [\mathbf{a} b_j^*]_{\Delta_B}$
- By linearity on IT-MAC, we can get $[a_i b_j]_{\Delta_B}$ for any i, j




Define $[\tilde{b}_k]_{\Delta_B} := [\hat{a}_k \oplus a_i a_j \oplus a_i b_j \oplus a_j b_i]_{\Delta_B}$

DILO Implementation of $\mathcal{F}_{\text{cpre}}$: Computing \hat{b}_k



DILO Implementation of $\mathcal{F}_{\text{cpre}}$: Authenticating \hat{b}_k (Under Δ_A)

- It suffices to compute \tilde{b}_k since $[\hat{b}_k]_{\Delta_A} = [\tilde{b}_k]_{\Delta_A} \oplus [b_i b_j]_{\Delta_A}$




- $\tilde{b}_k = \hat{a}_k \oplus a_i a_j \oplus a_i b_j \oplus a_j b_i$

- $\tilde{b}_k \oplus \tilde{b}_k = (\hat{a}_k \oplus a_i a_j \oplus a_i b_j \oplus a_j b_i) \cdot \Delta_A$


Verify mult. correlation $\mathcal{F}_{\text{DVZK}}$

DILO Implementation of $\mathcal{F}_{\text{cpre}}$: Authenticating \hat{b}_k (Under Δ_A)

- It suffices to compute \tilde{b}_k since $[\hat{b}_k]_{\Delta_A} = [\tilde{b}_k]_{\Delta_A} \oplus [b_i b_j]_{\Delta_A}$




- $\tilde{b}_k = \hat{a}_k \oplus a_i a_j \oplus a_i b_j \oplus a_j b_i$
- $\tilde{b}_k \oplus \tilde{b}_k = (\hat{a}_k \oplus a_i a_j \oplus a_i b_j \oplus a_j b_i) \cdot \Delta_A$




DILO Implementation of $\mathcal{F}_{\text{cpre}}$: Authenticating \hat{b}_k (Under Δ_A)

- It suffices to compute \tilde{b}_k since $[\hat{b}_k]_{\Delta_A} = [\tilde{b}_k]_{\Delta_A} \oplus [b_i b_j]_{\Delta_A}$



- $\tilde{b}_k = \hat{a}_k \oplus a_i a_j \oplus a_i b_j \oplus a_j b_i$
- $\tilde{b}_k \oplus \tilde{b}_k = (\hat{a}_k \oplus a_i a_j \oplus a_i b_j \oplus a_j b_i) \cdot \Delta_A$

Verify mult. correlation $\mathcal{F}_{\text{DVZK}}$




Locally compute $[v_k]_{\Delta_B} := [\tilde{b}_k \cdot \Delta_A \oplus \hat{a}_{k,2}]_{\Delta_B}$

- Diagram showing a protocol step where a party (represented by an icon) sends $m_{k,2} := \tilde{b}_k$ to another party (represented by an icon).
- $\tilde{b}_k := (\tilde{b}_k \oplus \tilde{b}_k) \cdot \Delta_B^{-1}$
 - $\hat{b}_k = \tilde{b}_k \oplus b_i b_j$

The Online Protocol

KRRW Check:

- Evaluator sends $\{\Lambda_w\}$ for all AND gates
- The checking equation reduces to equality check
- Use random linear combination to reduce comm.


$$\Lambda = a \oplus b \oplus z$$

The Online Protocol

KRRW Check:

- Evaluator sends $\{\Lambda_w\}$ for all AND gates
- The checking equation reduces to equality check
- Use random linear combination to reduce comm.

$$\Lambda = a \oplus b \oplus z \quad b = M \times b^*$$

The Online Protocol

KRRW Check:

- Evaluator sends $\{\Lambda_w\}$ for all AND gates
- The checking equation reduces to equality check
- Use random linear combination to reduce comm.



$$\Lambda = a \oplus b \oplus z \quad b = M \times b^*$$

DILO-WRK Check

$$\begin{aligned} \Lambda_k \cdot \Delta_B &:= \lambda_k \cdot \Delta_B \oplus (\Lambda_i \oplus \lambda_i) \cdot (\Lambda_j \oplus \lambda_j) \cdot \Delta_B \\ &= \lambda_k \cdot \Delta_B \oplus \Lambda_i \Lambda_j \cdot \Delta_B \oplus \Lambda_i \lambda_j \cdot \Delta_B \oplus \Lambda_j \lambda_i \cdot \Delta_B \oplus (\hat{a}_k \oplus \hat{b}_k) \cdot \Delta_B \end{aligned}$$

The Online Protocol

KRRW Check:

- Evaluator sends $\{\Lambda_w\}$ for all AND gates
- The checking equation reduces to equality check
- Use random linear combination to reduce comm.

$$\Lambda = a \oplus b \oplus z \quad b = M \times b^*$$

DILO-WRK Check

$$\Lambda_k \cdot \Delta_B := \lambda_k \cdot \Delta_B \oplus (\Lambda_i \oplus \lambda_i) \cdot (\Lambda_j \oplus \lambda_j) \cdot \Delta_B$$

$$\Lambda_i(a_j \oplus b_j)\Delta_B = \Lambda_i b_j \Delta_B \oplus \Lambda_i K[a_j] \oplus \Lambda_i M[a_j]$$

$$= \lambda_k \cdot \Delta_B \oplus \Lambda_i \Lambda_j \cdot \Delta_B \oplus \Lambda_i \lambda_j \cdot \Delta_B \oplus \Lambda_j \lambda_i \cdot \Delta_B \oplus (\hat{a}_k \oplus \hat{b}_k) \cdot \Delta_B$$

The Online Protocol

KRRW Check:

- Evaluator sends $\{\Lambda_w\}$ for all AND gates
- The checking equation reduces to equality check
- Use random linear combination to reduce comm.




$$\Lambda = a \oplus b \oplus z \quad b = M \times b^*$$

DILO-WRK Check

$$\Lambda_k \cdot \Delta_B := \lambda_k \cdot \Delta_B \oplus (\Lambda_i \oplus \lambda_i) \cdot (\Lambda_j \oplus \lambda_j) \cdot \Delta_B$$
$$= \lambda_k \cdot \Delta_B \oplus \Lambda_i \Lambda_j \cdot \Delta_B \oplus \Lambda_i \lambda_j \cdot \Delta_B \oplus \Lambda_j \lambda_i \cdot \Delta_B \oplus (\hat{a}_k \oplus \hat{b}_k) \cdot \Delta_B$$

$$\Lambda_i(a_j \oplus b_j)\Delta_B = \Lambda_i b_j \Delta_B \oplus \Lambda_i K[a_j] \oplus \Lambda_i M[a_j]$$

GC



2κ bits/AND

AuthGC

Λ_i	Λ_j	Alice's AuthGC	Bob's AuthGC
0	0	$L_{k,0} \oplus M[\Lambda_{00}]$	$K[\Lambda_{00}]$
0	1	$L_{k,0} \oplus M[\Lambda_{01}]$	$K[\Lambda_{01}]$
1	0	$L_{k,0} \oplus M[\Lambda_{10}]$	$K[\Lambda_{10}]$
1	1	$L_{k,0} \oplus M[\Lambda_{11}]$	$K[\Lambda_{11}]$




3ρ bits/AND

= 2κ + 3ρ bits/AND

Optimizing the Compressed Preprocessing Protocol


The overhead of DILO is
 $5\rho + 2$ bits per AND gate



Optimizing the Compressed Preprocessing Protocol


The overhead of DILO is
 $5\rho + 2$ bits per AND gate

- Why not call $\text{Fix}(\tilde{b}_k)$ directly?
- We need to detect against dishonest $\text{Fix}()$ input



Optimizing the Compressed Preprocessing Protocol

The overhead of DILO is
 $5\rho + 2$ bits per AND gate




- Why not call $\text{Fix}(\tilde{b}_k)$ directly?
- We need to detect against dishonest $\text{Fix}()$ input

- $[\mathbf{a} \Delta_A]_{\Delta_B} \equiv [\mathbf{a}]_{\Delta_A \cdot \Delta_B}$
- $M[\mathbf{a} \Delta_A] \oplus K[\mathbf{a} \Delta_A] = \mathbf{a} \Delta_A \Delta_B$
- We denote it as $\langle \mathbf{a} \rangle$

Dual Key Authentication

Optimizing the Compressed Preprocessing Protocol





The overhead of DILO is
 $5\rho + 2$ bits per AND gate



- Why not call $\text{Fix}(\tilde{b}_k)$ directly?
- We need to detect against dishonest $\text{Fix}()$ input


Dual Key Authentication

- $[\mathbf{a} \Delta_A]_{\Delta_B} \equiv [\mathbf{a}]_{\Delta_A \cdot \Delta_B}$
- $M[\mathbf{a} \Delta_A] \oplus K[\mathbf{a} \Delta_A] = \mathbf{a} \Delta_A \Delta_B$
- We denote it as $\langle \mathbf{a} \rangle$

- Suppose we generate $\langle \tilde{b}_k \rangle$ and $\langle r \rangle, [r]_B$ (mask for )
-  can open $y := \sum_k \chi^k \cdot \tilde{b}_k \oplus r$ and convince 
-  calls $\text{Fix}(\tilde{b}_k)$ and checks $\sum_k \chi^k [\tilde{b}_k] \oplus [r] \oplus y = 0$

Optimizing the Compressed Preprocessing Protocol





The overhead of DILO is
 $5\rho + 2$ bits per AND gate



- Why not call $\text{Fix}(\tilde{b}_k)$ directly?
- We need to detect against dishonest $\text{Fix}()$ input

- $[\mathbf{a} \Delta_A]_{\Delta_B} \equiv [\mathbf{a}]_{\Delta_A \cdot \Delta_B}$
- $M[\mathbf{a} \Delta_A] \oplus K[\mathbf{a} \Delta_A] = \mathbf{a} \Delta_A \Delta_B$
- We denote it as $\langle \mathbf{a} \rangle$

Dual Key Authentication

- Suppose we generate $\langle \tilde{b}_k \rangle$ and $\langle r \rangle, [r]_B$ (mask for )
-  can open $y := \sum_k \chi^k \cdot \tilde{b}_k \oplus r$ and convince 
-  calls $\text{Fix}(\tilde{b}_k)$ and checks $\sum_k \chi^k [\tilde{b}_k] \oplus [r] \oplus y = 0$

If so we can reduce 4ρ bits to 1 bit

Our goal is to generate $\langle \tilde{b}_k \rangle := \langle \hat{a}_k \rangle \oplus \langle a_i a_j \rangle \oplus \langle a_i b_j \rangle \oplus \langle a_j b_i \rangle$


Optimizing the Compressed Preprocessing Protocol, Continued

- $\langle \tilde{b}_k \rangle := \langle \hat{a}_k \rangle \oplus \langle a_i a_j \rangle \oplus \langle a_i b_j \rangle \oplus \langle a_j b_i \rangle$

- $D_A[\hat{a}_k] \oplus D_B[\hat{a}_k] = \hat{a}_k \Delta_A \Delta_B$

- $D_A[a_i b_j] \oplus D_B[a_i b_j] = a_i b_j \Delta_A \Delta_B$

The compression technique allows encoding \mathbf{b} in $\mathcal{F}_{\text{bCOT}}$ global keys




Optimizing the Compressed Preprocessing Protocol, Continued

- $\langle \tilde{b}_k \rangle := \langle \hat{a}_k \rangle \oplus \langle a_i a_j \rangle \oplus \langle a_i b_j \rangle \oplus \langle a_j b_i \rangle$

- $D_A[\hat{a}_k] \oplus D_B[\hat{a}_k] = \hat{a}_k \Delta_A \Delta_B$

- $D_A[a_i b_j] \oplus D_B[a_i b_j] = a_i b_j \Delta_A \Delta_B$

The compression technique allows encoding \mathbf{b} in $\mathcal{F}_{\text{bCOT}}$ global keys




Optimizing the Compressed Preprocessing Protocol, Continued


- $\langle \tilde{b}_k \rangle := \langle \hat{a}_k \rangle \oplus \langle a_i a_j \rangle \oplus \langle a_i b_j \rangle \oplus \langle a_j b_i \rangle$

- $D_A[\hat{a}_k] \oplus D_B[\hat{a}_k] = \hat{a}_k \Delta_A \Delta_B$

- $D_A[a_i b_j] \oplus D_B[a_i b_j] = a_i b_j \Delta_A \Delta_B$




$$\boxed{a} = \boxed{a} + \boxed{a} \times [\beta_1, \dots, \beta_L, \Delta_B]$$



$$\boxed{\hat{a}} = \boxed{\hat{a}} + \boxed{\hat{a}} \times [\beta_0, \Delta_B]$$

The compression technique allows encoding \mathbf{b} in $\mathcal{F}_{\text{bCOT}}$ global keys



$$\begin{array}{cc} \alpha_0 & \oplus & \beta_0 & = \Delta_A \Delta_B \\ \alpha_i & \oplus & \beta_i & = b_i^* \Delta_A \Delta_B \end{array}$$

Optimizing the Compressed Preprocessing Protocol, Continued

- $\langle \tilde{b}_k \rangle := \langle \hat{a}_k \rangle \oplus \langle a_i a_j \rangle \oplus \langle a_i b_j \rangle \oplus \langle a_j b_i \rangle$

- $D_A[\hat{a}_k] \oplus D_B[\hat{a}_k] = \hat{a}_k \Delta_A \Delta_B$

- $D_A[a_i b_j] \oplus D_B[a_i b_j] = a_i b_j \Delta_A \Delta_B$



$$\boxed{a} = \boxed{a} + \boxed{a} \times [\beta_1, \dots, \beta_L, \Delta_B]$$

$\mathcal{F}_{\text{bCOT}}^{L+1}$

$$\boxed{\hat{a}} = \boxed{\hat{a}} + \boxed{\hat{a}} \times [\beta_0, \Delta_B]$$

$\mathcal{F}_{\text{bCOT}}^2$

The compression technique allows encoding \mathbf{b} in $\mathcal{F}_{\text{bCOT}}$ global keys

\mathcal{F}_{COT}

$\text{Fix}(\{\Delta_B, \mathbf{b}^* \Delta_B\})$

α_0	\oplus	β_0		$=$	$\Delta_A \Delta_B$
α_i	\oplus	β_i		$=$	$b_i^* \Delta_A \Delta_B$

\Leftrightarrow

α_0	$\cdot \Delta_A^{-1}$	\oplus	β_0	$\cdot \Delta_A^{-1}$	$=$	Δ_B
α_i	$\cdot \Delta_A^{-1}$	\oplus	β_i	$\cdot \Delta_A^{-1}$	$=$	$b_i^* \Delta_B$

By $\text{Fix}(\Delta'_A)$


$K[\beta_0]$	\oplus	$\beta_0 \cdot \Delta'_A$	$=$	$M[\beta_0]$
$K[\beta_i]$	\oplus	$\beta_i \cdot \Delta'_A$	$=$	$M[\beta_i]$

[DIO21] gives a modular way of proving equality under independent keys


Optimizing the Compressed Preprocessing Protocol, Completed

$$\Pi_{\text{Samp}} \Delta_A, \Delta_B \leftarrow \$ \text{ s.t. } \text{lsb}(\Delta_A \Delta_B) = 1$$


Optimizing the Compressed Preprocessing Protocol, Completed




Optimizing the Compressed Preprocessing Protocol, Completed




Optimizing the Compressed Preprocessing Protocol, Completed







Optimizing the Compressed Preprocessing Protocol, Completed







Optimizing the Compressed Preprocessing Protocol, Completed




Optimizing the One-way Communication Via Dual Execution





- Optimized $\mathcal{F}_{\text{cpre}}$ + DILO-WRK =  \rightarrow : $2\kappa + 3\rho + 2$ bits,  \rightarrow : 2 bits
- How about optimizing one-way communication? Maybe dual execution?


Optimizing the One-way Communication Via Dual Execution

- Optimized $\mathcal{F}_{\text{cpre}}$ + DILO-WRK =  \rightarrow  : $2\kappa + 3\rho + 2$ bits,  \rightarrow  : 2 bits
- How about optimizing one-way communication? Maybe dual execution?




Optimizing the One-way Communication Via Dual Execution





- Optimized $\mathcal{F}_{\text{cpre}}$ + DILO-WRK =  \rightarrow  : $2\kappa + 3\rho + 2$ bits,  \rightarrow  : 2 bits
- How about optimizing one-way communication? Maybe dual execution?




- [HEK12, HsV20]: Check for equality in circuit outputs




Optimizing the One-way Communication Via Dual Execution

- Optimized $\mathcal{F}_{\text{cpre}}$ + DILO-WRK =  \rightarrow  : $2\kappa + 3\rho + 2$ bits,  \rightarrow  : 2 bits
- How about optimizing one-way communication? Maybe dual execution?



- [HEK12, HsV20]: Check for equality in circuit outputs



Optimizing the One-way Communication Via Dual Execution



$\mathcal{F}_{\text{cpre}}$

$$[\mathbf{a}], [\hat{\mathbf{a}}], [\mathbf{b}], [\hat{\mathbf{b}}], \Delta_A, \Delta_B \leftarrow \$$$

$$\text{s.t. } \hat{a}_k \oplus \hat{b}_k = (a_i \oplus b_i) \cdot (a_j \oplus b_j)$$

Π_{DG}

$$\{\lambda_k, L_{k,0}, L_{k,1}\} \quad \{\Lambda_k, L_{k,\Lambda_k}\} \text{ for } k \in \mathcal{W}$$



$\mathcal{F}_{\text{cpre}}$

$$[\mathbf{a}'], [\hat{\mathbf{a}}'], [\mathbf{b}'], [\hat{\mathbf{b}}'], \Delta_A, \Delta_B \leftarrow \$$$

$$\text{s.t. } \hat{a}'_k \oplus \hat{b}'_k = (a'_i \oplus b'_i) \cdot (a'_j \oplus b'_j)$$

Π_{DG}

$$\{\lambda'_k, L'_{k,0}, L'_{k,1}\} \quad \{\Lambda'_k, L'_{k,\Lambda'_k}\} \text{ for } k \in \mathcal{W}$$

Optimizing the One-way Communication Via Dual Execution



$\mathcal{F}_{\text{cpre}}$



$$[\mathbf{a}], [\hat{\mathbf{a}}], [\mathbf{b}], [\hat{\mathbf{b}}], \Delta_A, \Delta_B \leftarrow \$$$

$$\text{s.t. } \hat{a}_k \oplus \hat{b}_k = (a_i \oplus b_i) \cdot (a_j \oplus b_j)$$

Π_{DG}

$$\{\lambda_k, L_{k,0}, L_{k,1}\} \quad \{\Lambda_k, L_{k,\Lambda_k}\} \text{ for } k \in \mathcal{W}$$

$$L_{k,\Lambda_k} = L_{k,0} \oplus \Lambda_k \cdot \Delta_A$$



$\mathcal{F}_{\text{cpre}}$



$$[\mathbf{a}'], [\hat{\mathbf{a}}'], [\mathbf{b}'], [\hat{\mathbf{b}}'], \Delta_A, \Delta_B \leftarrow \$$$

$$\text{s.t. } \hat{a}'_k \oplus \hat{b}'_k = (a'_i \oplus b'_i) \cdot (a'_j \oplus b'_j)$$


Π_{DG}

$$\{\lambda'_k, L'_{k,0}, L'_{k,1}\} \quad \{\Lambda'_k, L'_{k,\Lambda'_k}\} \text{ for } k \in \mathcal{W}$$

$$L'_{k,\Lambda'_k} = L'_{k,0} \oplus \Lambda'_k \cdot \Delta_B$$

- Color bits and wire masks are authenticated for every wire
- This enables checking equality for every wire across two executions

[HK21] Garbled Sharing



Conclusion

- Further optimization on the compression technique of [DILO22]
- Dual-key authentication and efficient generation
- Dual execution upon distribution garbling eliminates 1-bit leakage
- Malicious 2PC with one-way comm. of $2\kappa + 5$ bits, two way comm. of $2\kappa + 3\rho + 4$ bits

2PC	Rounds		Communication per AND gate	
	Prep.	Online	one-way (bits)	two-way (bits)
Half-gates	1	2	2κ	2κ
HSS-PCG	8	2	$8\kappa + 11$ (4.04 \times)	$16\kappa + 22$ (8.09 \times)
KRRW-PCG	4	4	$5\kappa + 7$ (2.53 \times)	$8\kappa + 14$ (4.05 \times)
DILO	7	2	$2\kappa + 8\rho + 1$ (2.25 \times)	$2\kappa + 8\rho + 5$ (2.27 \times)
This work	8	3	$2\kappa + 5$ (≈ 1 \times)	$4\kappa + 10$ (2.04 \times)
This work+DILO	8	2	$2\kappa + 3\rho + 2$ (1.48 \times)	$2\kappa + 3\rho + 4$ (≈ 1.48 \times)

Thanks for your listening

Merci beaucoup