



Run Continuously with systemd

Keep the daemon running at boot and check logs quickly

Code: github.com/RickLee-kr/Stellar-Case-Alert-to-Sylog



1. Create the service file

/etc/systemd/system/stellar-alert-case.service

```
[Unit]
Description=Stellar Cyber Alert + Case Syslog daemon
After=network-online.target
Wants=network-online.target

[Service]
Type=simple
User=aella
Group=aella
WorkingDirectory=/home/aella/kt
ExecStart=/usr/bin/python3 /home/aella/kt/Stellar_Alert_Case_Syslog.py \
  --alert-interval 60 \
  --case-interval 3600 \
  --alert-syslog-ip 10.10.10.20 \
  --alert-syslog-port 5201 \
  --case-syslog-ip 10.10.10.20 \
  --case-syslog-port 5142 \
  --case-include-summary \
  --no-case-format-summary \
  --case-fetch-timeout 90
Restart=on-failure
RestartSec=10

[Install]
WantedBy=multi-user.target
```



Adjust paths, user, IPs, and ports for your environment.



2. Enable and start

```
sudo systemctl daemon-reload
sudo systemctl enable stellar-alert-case.service
sudo systemctl restart stellar-alert-case.service
sudo systemctl status stellar-alert-case.service
journalctl -u stellar-alert-case.service -f
```

- ✓ enable: start automatically at boot
- ✓ restart: start now or reload after changes
- ✓ journalctl -f: follow live service logs



3. Quick checks

Show unit file

```
systemctl cat stellar-alert-case.service
```

Check process

```
ps -ef | grep -i stellar
```

Follow service logs

```
journalctl -u stellar-alert-case.service -f
```

View send logs

```
tail -n 20 ~/.local/state/stellar_alert_case/
logs/stellar_cases_$(date +%Y%m%d_%H).log
```



Operational tips

- Use Restart=on-failure for automatic recovery
- Use --debug only when troubleshooting
- Case Kill Chain parsing needs --case-include-summary
- Output is newline-delimited JSON (NDJSON) over TCP

Page 3 of 3