Gramática LL(1)

```
S = DeclaID S
S = FunDecla S
S = ProcDecla S
S = epsilon
DeclaID = Type LId ';'
DeclaID = 'const' Type LId ';'
Type = 'int' | 'float' | 'bool' | 'char' | 'string'
LId = Id AtriOpt LIdr
LIdr = ',' AtriOpt LIdr
LIdr = epsilon
Id = 'ID' ArrayOpt
ArrayOpt = '[' Ea ']'
ArrayOpt = epsilon
AtriOpt = '=' Ec
AtriOpt = epsilon
FunDecla = 'fun' Type FunName '(' ParamDecla ')' Body
FunName = 'id' | 'main'
Param = Ec Paramr
Param = epsilon
Paramr = ',' Ec Paramr
Paramr = epsilon
ParamDecla = Type 'id' ArrayOpt ParamDeclar
ParamDecla = epsilon
ParamDeclar = ',' Type 'id' ArrayOpt ParamDeclar
ParamDeclar = epsilon
```

```
ProcDecla = 'proc' FunName '(' ParamDecla ')' Body
Body = '{' BodyPart '}'
BodyPart = DeclaId BodyPart
BodyPart = Command BodyPart
BodyPart = BodyPartr ';' BodyPart
BodyPart = 'return' Return ';'
BodyPart = epsilon
BodyPartr = 'id' ParamAtr
ParamAtr = '(' Param ')'
ParamAtr = '[' Ea ']' '=' Ec Atr
ParamAtr = '=' Ec Atr
Atr = ',' Id '=' Ec Atr
Atr = epsilon
Return = Ec// quando for função
Return = epsilon // quando for procedimento
Command = 'print' '(' CT STRING' PrintParam ')' ';'
Command = 'println' '(' 'CT STRING' PrintParam ')' ';'
Command = 'read' '(' ReadParam ')' ';'
Command = 'while' '(' Eb ')' Body
Command = 'for' ForParam
Command = 'if' '(' Eb ')' Body Ifr
PrintParam = ',' Ec PrintParam
PrintParam = epsilon
ReadParam = 'id' ArrayOpt ReadParamr
ReadParamr = ',' 'id' ArrayOpt ReadParamr
ReadParamr = epsilon
ForParams = '(' 'RW INT' 'ID' ':' Ea ',' Ea ForStep ')' Body
ForStep = ',' Ea
ForStep = epsilon
```

Ifr = 'else' Body

Ifr = epsilon

Ec = Eb Ecr

Ecr = 'OP_CONC' Eb Ecr

Ecr = epsilon

Eb = Tb Ebr

Ebr = 'OP OR' Tb Ebr

Ebr = epsilon

Tb = Fb Tbr

 $Tbr = 'OP_AND' Fb Tbr$

Tbr = epsilon

Fb = 'OP NOT' Fb

Fb = Ra Fbr

Fbr = 'OP GREATER' Ra Fbr

Fbr = 'OP LESS' Ra Fbr

Fbr = 'OP GRTEREQ' Ra Fbr

Fbr = 'OP_LESSEQ' Ra Fbr

Fbr = epsilon

Ra = Ea Rar

Rar = 'OP_REAL' Ea Rar

Rar = 'OP_REALNOT' Ea Rar

Rar = epsilon

Ea = Ta Ear

Ear = 'OP AD' Ta Ear

Ear = 'OP_SUB' Ta Ear

Ear = epsilon

Ta = Pa Tar

Tar = 'OP_MULT' Pa Tar

Tar = 'OP_DIV' Pa Tar

Tar = epsilon

Pa = Fa Par

Par = 'OP_MOD' Fa Par

Par = epsilon

Fa = '(' Ec ')'

 $Fa = 'OP_SUB' Fa$

Fa = IdOrFun | 'CT_INT' | 'CT_FLOAT' | 'CT_BOOL' | 'CT_STRING' | 'CT_CHAR'

IdOrFun = 'id' IdOrFunr

IdOrFunr = '(' Param ')' IdOrFunr = '[' Ea ']'