

GATTO: Can Topological Information Improve Node Classification via GAT?

Midterm Report for Learning from Network's project

Francesco Biscaccia Carrara (2120934), Riccardo Modolo (2123750),
Alessandro Viespoli (2120824)

Master Degree in Computer Engineering
University of Padova

I. INTRODUCTION

The scope of this document is to:

- **Clarify all points** not properly explained in the proposal paper
- Summarize all **work done**
- Define the **missing work**
- Estimate **time to finish the project**.

II. CLARIFICATION POINTS

One of the most important points of clarification concern the data: in the proposal paper, we did not provide an extensive explanation of how data are built and how we want to use them. The graphs chosen in SNAP^[1] are undirected and contain communities, no other features are present in the files. We want to use all communities as label, and a node can only belong to one community. For GAT tuning we want to compute the following feature for each node:

- betweenness centrality
- closeness centrality
- clustering coefficient
- *(other possible features)*

III. WORK DONE

We have already built the **precomputation module** (explained in the project proposal) and the code to automate the testing phase inside cluster.

IV. WORK IN PROGRESS

We need to build the **GAT module** and do the tests on **CAPRI**^[2]. We must also decide the hyperparameters in node2vec.

V. ESTIMATION

In our estimation, we can finish the paper five or six days before the deadline.

REFERENCES

- [1] Jure Leskovec and Andrej Krevl. *SNAP Datasets: Stanford Large Network Dataset Collection*. <http://snap.stanford.edu/data>. June 2014.
- [2] DEI University of Padova. *CAPRI: Calcolo ad Alte Prestazioni per la Ricerca e l'Innovazione*. 2017. URL: <https://capri.dei.unipd.it>.