
## Firewall and IDS/IPS

Antonio Lioy < lioy @ polito.it >

Politecnico di Torino Dip. Automatica e Informatica

#### What is a firewall?

- firewall = wall to protect against fire propagation
- controlled connection between networks at different security levels = boundary protection (network filter)



# Ingress vs. Egress firewall

#### ingress firewall

- incoming connections
- typically to select the (public) services offered
- sometimes as part of an application exchange initiated by my users

#### egress firewall

- outgoing connections
- typically to check the activity of my personnel (!)
- easy classification for channel-based services (e.g. TCP applications), but difficult for message-based stateless services (e.g. ICMP, UDP applications)

# THE THREE COMMANDMENTS OF FIREWALL

- I. the FW must be the only contact point of the internal network with the external one
- II. only the "authorized" traffic can traverse the FW
- III. the FW must be a highly secure system itself

D.Cheswick S.Bellovin

# **Authorization policies**

"All that is not explicitly permitted, is forbidden"

permittist, allowist

- higher security (gatekeeper)
- more difficult to manage


blocklist, denylist "All that is not explicitly forbidden, is permitted"

- lower security (open gates)
- more easy to manage

# FW: basic components

- packet filter / screening router / choke component that filters traffic at network level
- bastion host secure system, with auditing
- application gateway (proxy) service that works on behalf of an application, with access control
- dual-homed gateway system with two network cards and routing disabled

## A which level the controls are made?



# Firewall technologies

#### different controls at various network levels:

- (static) packet filter
- stateful (dynamic) packet filter
- cutoff proxy
- circuit-level gateway / proxy
- application-level gateway / proxy
- stateful inspection

#### differences in terms of:

- controls to be performed (= threats detected)
- performance
- protection of the firewall O.S.
- keeping or breaking the client-server model

## Packet filter

- historically available on routers
- packet inspection at network level
  - IP header
  - transport header
- rule example:
  - permit incoming connections to our web server "src any dst 10.1.2.3/0.0.0.0 tcp 80 allow"
  - only our internal DNS server can query DNS external servers "src 10.1.2.1/0.0.0.0 dst any udp 53 allow"
  - typically, there is an (implicit) "deny all" rule at the end
  - order is important (first match principle)

# Packet filter: pros and cons

- independent of applications
  - good scalability
  - approximate controls: easy to "fool" (e.g. IP spoofing, fragmented packets)
- good performance
- low cost (available on routers and in many OS)
- difficult to support services with dynamically allocated ports (e.g. FTP)
- complex to configure
- difficult to perform user authentication

# **Application-level gateway**

- composed by a set of proxies inspecting the packet payload at application level
- often requires modifications to the client application
- may optionally mask / renumber the internal IP addresses
- when used as part of a firewall, usually performs also peer authentication
- top security!! (e.g. against buffer overflow of the target application)
- difference between forward-proxy (egress) and reverse-proxy (ingress)
- rule example:
  - deny dangerous HTTP methods "PUT, DELETE deny"

# Application-level gateway (1)

- rules are more fine-grained and simple than those of a packet filter
- every application needs a specific proxy
  - delay in supporting new applications
  - heavy on resources (many processes)
  - low performance (user-mode processes)
- SMP may improve performance
- completely breaks the client/server model
  - more protection for the server
  - may authenticate the client
  - not transparent to the client

# Application-level gateway (2)

- the proxy OS may be exposed to attacks
- problems with application-level security techniques that do not permit traffic inspection (e.g. TLS)
- variants:
  - transparent proxy
    - less intrusive for the client
    - more work (packet rerouting + dst extraction)
  - strong application proxy (checking semantics, not just syntax)
    - only some commands/data are forwarded
    - this is the only correct configuration for a proxy

# Circuit-level gateway (1)

- a generic proxy (i.e. not "application-aware")
  - creates a transport-level circuit between client and server ...
  - but it doesn't understand or manipulate in any way the payload data
  - it just copies between its two interfaces the TCP segments or UDP datagrams (if they match the access control rules)
  - but, in doing this, it will re-assemble the IP packets and hence it will provide protection against some L3/L4 attacks

# Circuit-level gateway (2)

- breaks the TCP/UDP-level client/server model during the connection
  - more protection for the server
    - isolated from all attacks related to the TCP handshake
    - isolated from all attacks related to the IP fragmentation
  - may authenticate the client
    - but this requires modification to the application
- still exhibits many limitations of the packet filter
- SOCKS is the most famous one

# HTTP (forward) proxy


- a HTTP server acting just as a front-end and then passing requests to the real server (external)
- it's an egress control
- benefits (besides network ACL):
  - shared cache of external pages for all internal users
  - authentication + authorization of internal users
  - various controls (e.g. allowed sites, transfer direction, data types, ...)




# **HTTP** reverse proxy

- HTTP server acting just as a front-end for the real server(s) which the requests are passed to
- implements network ACL & content inspection
- ... plus additional benefits:
  - obfuscation (no info about the real server)
  - TLS accelerator (with unprotected back-end connections ...)
  - load balancer
  - web accelerator (=cache for static content)
  - compression
  - spoon feeding (gets from the server a whole dynamic page and feeds it to the client according to its speed, so unloading the application server)

# Reverse proxy: possible configurations






© A.Lioy (Politecnico di Torino, 2005-2023)

21

# WAF (Web Application Firewall)

- large use of web applications = many threats
- WAF = module installed at a proxy (forward and/or reverse) to filter the application traffic
  - HTTP commands
  - header of HTTP request/response
  - content of HTTP request/response
- ModSecurity
  - plugin for Apache and NGINX (50% and 30% of worldwide HTTP servers)
  - OWASP ModSecurity Core Rule Set (CRS)

## "Packet filter" architecture




© A.Lioy (Politecnico di Torino, 2005-2023)

24

## "Packet filter" architecture

- exploits the packet filter to screen the traffic both at IP and upper levels
  - if implemented with a router then it's a "screening router" and there's no need for extra dedicated hardware
- no need for a proxy and hence no need to modify the applications
- simple, easy, cheap and ... insecure!

# "Dual-homed gateway" architecture




© A.Lioy (Politecnico di Torino, 2005-2023)

26

# "Dual-homed gateway" architecture

- easy to implement
- small additional hardware requirements
- the internal network can be masqueraded
- unflexible
- large work overhead

## "Screened host" architecture




© A.Lioy (Politecnico di Torino, 2005-2023)

## "Screened-host" architecture

#### router:

- blocks traffic INT > EXT unless from the bastion
- blocks traffic EXT > INT unless goes to the bastion
- exception: directly enabled services
- bastion host runs circuit/application gateway to control the authorized services
- more expensive and complex to manage (two systems rather one)
- more flexible (skip control over some services / hosts)
- only the hosts/protocols passing through the bastion can be masked (unless the PF uses NAT)

## "Screened subnet" architecture




## "Screened subnet" architecture

- DMZ (De-Militarized Zone)
- the DMZ is home not only to the gateway but also to other hosts (tipically the public servers):
  - Web
  - remote access
  - **.** . . .
- the routing may be configured so that the internal network is unknown
- expensive

# "Screened subnet" architecture (version 2)

- to reduce costs and simplify management often the PFs are omitted (and their function incorporated into the gateway)
- AKA "three-legged firewall"



© A.Lioy (Politecnico di Torino, 2005-2023)


32

# Local / personal firewall

- firewall directly installed at the node to be protected
- typically, a packet filter
- w.r.t. a normal network firewall, it may limit the PROCESSES that are permitted:
  - to open network channels towards other nodes (i.e. act as a client)
  - to answer network requests (i.e. act as a server)
- important to limit the diffusion of malware and trojans, or to avoid configuration mistakes
- beware: in order to be effective, the firewall management MUST be separated from system management

# Protection offered by a firewall

- a firewall is 100% effective only for attacks over/against blocked channels
- the other channels require other protection techniques:
  - VPN
  - "semantic" firewall / IDS
  - application-level security



# **Intrusion Detection System (IDS)**

#### definition:

- system to identify actors using a computer or a network without authorization
- extendable to identify authorized actors violating their privileges

#### hypothesis:

the behavioural "pattern" of non-authorized users differs from that of the authorized ones

## **IDS:** functional features

#### passive IDS:

- cryptographic checksum (e.g. tripwire)
- pattern matching ("attack signature")

#### active IDS:

- "learning" = statistical analysis of the system behaviour
- "monitoring" = active statistical info collection of traffic, data, sequences, actions
- "reaction" = comparison against statistical parameters (reaction when a threshold is exceeded)

# **IDS:** topological features

- HIDS (host-based IDS)
  - log analysis (OS, service or application)
  - internal OS monitoring tools
- NIDS (network-based IDS)
  - network traffic monitoring tools

# NIDS components

#### sensor

- checks traffic and logs looking for suspect patterns
- generated the relevant security events
- interacts with the system (ACLs, TCP reset, ...)


#### director

- coordinates the sensors
- manages the security database

#### IDS message system

secure and reliable communication among the IDS components

## **NIDS** architecture



## **IPS**

- Intrusion Prevention System
- to speed-up and automate the reaction to intrusions = IDS + distributed dynamic firewall
- a technology, not a product, with large impact on many elements of the protection system
- dangerous! may take the wrong decision and block innocent traffic
- often integrated in a single product IDPS

# **Next-Generation Firewall (NGFW)**

- application identification
  - whatever network port is used
  - if possible, deciphering/re-ciphering the traffic
- user identification
  - integration with captive portal, 802.1x, or end-point authN (Kerberos, Active Directory, LDAP, ...)
- per-user and per-application policies
- filtering based also upon known vulnerabilities, threats, malware, ...

# **Unified Threat Management (UTM)**

- integration of several products in a single device
  - UTM- or security-appliance
- firewall, VPN, anti-malware, content-inspection, IDPS, ...
- the actual capabilities depend upon the manufacturer
- mainly targeted to reduce the number of different systems, hence the management complexity and the cost

