

```

<!DOCTYPE html><!-- -->
<html lang="en">
<head> <!-- Head of HTML linking ti stylesheet -->
    <meta charset="UTF-8">
    <title>Title</title>
    <link rel="stylesheet" type="text/css" href="style.css">
</head>
<body><!-- main wrapper for teh whole doc -->
<div id="Wrapper1">
    <header></header><!-- First of the windows, decided to make 8 of them in total it is a bit complicated but i wanted different IDs as i
id not want to mix code for all of them
    as the Quiz is slightly different and it was easier in the end for debugging -->
    <div id="DivButton0">
        <p>Hello user please enter your name below and hit start to begin your Quiz.
            I decided to leave the --- TEST --- function i used for myself as it might be helpful during testing on top of the comments.
            Press the button to use it if you decide, the test window is resizable as well.</p>
        <input type="text" id="userName" placeholder="Enter your name here" value="Gemma Deery" >
        <button id="StartQuiz" onclick="getUserName(0)">Start</button>
    </div><!-- The first window is a prime example i did not add sections as i felt this would have made the code even more bloated -->
    <div id="DivButton1"> <!-- first we hae the headers -->
        <div id="Head1">
            <h1 id="Quiz1">My Quiz</h1> <!-- then Quiz title -->
            <h2 id="Count1">Question 1 of 5</h2> <!-- Question numbers -->
            <p id="Question1"></p>
        </div><!-- Each radio button has its label with unique references -->
        <div id="Button1A">
            <input id="answer1A" type="radio" name="answer" value="answer A">
            <label id="label1A" for="answer1A">answer A</label>
        </div>
        <div id="Button1B">
            <input id="answer1B" type="radio" name="answer" value="answer B">
            <label id="label1B" for="answer1B">answer B</label>
        </div>
        <div id="Button1C">
            <input id="answer1C" type="radio" name="answer" value="answer C">
            <label id="label1C" for="answer1C">answer C</label>
        </div>
        <div id="Button1D">
            <input id="answer1D" type="radio" name="answer" value="answer D">
            <label id="label1D" for="answer1D">answer D</label>
        </div>
        <div id="Button1E">
            <button id="Next1" onclick="checked(1)">Next</button>
        </div>
    </div><!-- All below code is a copy of above, although very complicated in the beelining it was easy to add/remove windows and debug in
the end with unique IDs -->
    <div id="DivButton2">
        <div id="Head2">
            <h1 id="Quiz2">My Quiz</h1>
            <h2 id="Count2">Question 2 of 5</h2>
            <p id="Question2"></p>
        </div>
        <div id="Button2A">
            <input id="answer2A" type="radio" name="answer" value="answer A">
            <label id="label2A" for="answer2A">answer A</label>
        </div>
        <div id="Button2B">
            <input id="answer2B" type="radio" name="answer" value="answer B">
            <label id="label2B" for="answer2B">answer B</label>
        </div>
        <div id="Button2C">
            <input id="answer2C" type="radio" name="answer" value="answer C">
            <label id="label2C" for="answer2C">answer C</label>
        </div>
        <div id="Button2D">
            <input id="answer2D" type="radio" name="answer" value="answer D">
            <label id="label2D" for="answer2D">answer D</label>
        </div>
        <div id="Button2E">
            <button id="Previous2" onclick="previousNavigation (1)">Previous</button>
            <button id="Next2" onclick="checked(2)">Next</button>
        </div>
    </div>
    <div id="DivButton3">

```

```
<div id="Head3">
  <h1 id="Quiz3">My Quiz</h1>
  <h2 id="Count3">Question 3 of 5</h2>
  <p id="Question3"></p>
</div>
<div id="Button3A">
  <input id="answer3A" type="radio" name="answer" value="answer A">
  <label id="label3A" for="answer3A">answer A</label>
</div>
<div id="Button3B">
  <input id="answer3B" type="radio" name="answer" value="answer B">
  <label id="label3B" for="answer3B">answer B</label>
</div>
<div id="Button3C">
  <input id="answer3C" type="radio" name="answer" value="answer C">
  <label id="label3C" for="answer3C">answer C</label>
</div>
<div id="Button3D">
  <input id="answer3D" type="radio" name="answer" value="answer D">
  <label id="label3D" for="answer3D">answer D</label>
</div>
<div id="Button3E">
  <button id="Previous3" onclick="previousNavigation (2)">Previous</button>
  <button id="Next3" onclick="checked(3) ">Next</button>
</div>
</div>
<div id="DivButton4">
  <div id="Head4">
    <h1 id="Quiz4">My Quiz</h1>
    <h2 id="Count4">Question 4 of 5</h2>
    <p id="Question4"></p>
  </div>
  <div id="Grid">
    <div id="Button4A">
      <input id="answer4A" type="radio" name="answer" value="answer A">
      <label id="label4A" for="answer4A"></label>
    </div>
    <div id="Button4B">
      <input id="answer4B" type="radio" name="answer" value="answer B">
      <label id="label4B" for="answer4B"></label>
    </div>
    <div id="Button4C">
      <input id="answer4C" type="radio" name="answer" value="answer C">
      <label id="label4C" for="answer4C"></label>
    </div>
    <div id="Button4D">
      <input id="answer4D" type="radio" name="answer" value="answer D">
      <label id="label4D" for="answer4D"></label>
    </div>
  </div>
  <div id="Button4E">
    <button id="Previous4" onclick="previousNavigation (3)">Previous</button>
    <button id="Next4" onclick="checked(4) ">Next</button>
  </div>
</div>
<div id="DivButton5">
  <div id="Head5">
    <h1 id="Quiz5">My Quiz</h1>
    <h2 id="Count5">Question 5 of 5</h2>
    <p id="Question5">Math time !</p>
  </div>
  <div id="Math">
    <p id="equationIntro">Solve the following equation (use either words or numbers)</p>
    <p id="equation">place holder</p>
  </div>
  <div id="Button5A">
    <input id="answer5A" type="text" name="answer" placeholder="Enter your answer ..." required>
  </div>
  <div id="Button5E">
    <button id="Previous5" onclick="previousNavigation (4)">Previous</button>
    <button id="Next5" onclick="submit(5) ">Submit</button>
  </div>
</div>
<div id="DivButton6">
```

```

<div id="score">
<h1>SCORE</h1>
    <p id="scoreParagraph1">placeholder</p>
    <p id="scoreParagraph2">placeholder</p>
    <p id="scoreParagraph3">placeholder</p>
</div>
<p id="scoreParagraph4">placeholder</p>
<div id="Button6E">
    <button id="Previous6" onclick="previousNavigation (5)">Previous</button>
    <button id="Finish" onclick="nextNavigation(6)">Finish</button>
</div>
</div>
<div id="DivButton7">
<p id="goodGame"> GOOD GAME !!!</p>
</div>
<div id="test"><!-- This was for testing but i felt it might be helpful to leave out to read the code a bit easier -->
    <button id="TestButton" onclick="testMenu()">TEST MENU</button>
    <div id="testSub">
<h3>TESTING</h3>
        <p id="p1">1-test</p>
        <p id="p2">2-test</p>
        <p id="p3">3-test</p>
        <p id="p4">4-test</p>
        <p id="p5">5-test</p>
        <p id="p6">6-test</p>
        <p id="p7">7-test</p>
        <p id="p8">8-test</p>
        <p id="p9">9-test</p>
        <p id="p10">10-test</p>
        <p id="p11">11-test</p>
        <p id="p12">12-test</p>
        <p id="p13">13-test</p>
        <p id="p14">14-test</p>
        <p id="p15">15-test</p>
        <p id="p16">16-test</p>
        <p id="p17">17-test</p>
        <p id="p18">18-test</p>
        <p id="p19">19-test</p>
        <p id="P20">20-test</p>
        <p id="p21">21-test</p>
        <p id="p22">22-test</p>
        <p id="p23">23-test</p>
        <p id="p24">24-test</p>
        <p id="p25">25-test</p>
        <p id="p26">26-test</p>
        <p id="p27">27-test</p>
        <p id="p28">28-test</p>
        <p id="p29">29-test</p>
        <p id="P30">30-test</p>
    </div>
</div>
</div>
</div>
<script src="app.js"></script>
</body>
</html>
```