

# Blockchain and Cryptocurrencies

## Week 7 — Chapter 9: Bitcoin as a Platform

Prof. Dr. Peter Thiemann

Albert-Ludwigs-Universität Freiburg, Germany

SS 2020

## Non monetary uses

1 Bitcoin as a Log

2 Colored Coins

3 Lotteries

# Bitcoin as a Log

## Blockchain

- tamperproof ledger
- append-only
- history preserved

# Bitcoin as a Log

## Blockchain

- tamperproof ledger
- append-only
- history preserved

## Log File (wikipedia, excerpt)

[...] a **log file** is a file that records either events that occur in an operating system or other software runs, or messages between different users of a communication software.

A **transaction log** is a [...] data collection method that automatically captures the type, content, or time of transactions made [...] with that system.

# Secure Timestamping


## Goal

prove knowledge of value  $x$  at time  $T$

## Method

- choose random  $r$  with high min-entropy
- publish  $H(r||x)$  at time  $T$  on the blockchain
- (e.g., using OP\_RETURN or coin burn)
- if challenged later, we can produce  $r$  and  $x$  and point to the record on the blockchain

Mini transaction in which  
you can put an address



# Applications of Secure Timestamping

- Prior knowledge of ideas

# Applications of Secure Timestamping

- Prior knowledge of ideas
- Proof of submission

# Applications of Secure Timestamping

- Prior knowledge of ideas
- Proof of submission
- Digital signature schemes (Guy Fawkes signature scheme)



# Applications of Secure Timestamping

- Prior knowledge of ideas
- Proof of submission
- Digital signature schemes (Guy Fawkes signature scheme)

## Overlay Currency

- uses Bitcoin as the transport and consensus layer
- (standard) Bitcoin nodes and miners are not aware of the overlay's transactions
- special nodes verify the overlay transaction, e.g., from OP\_RETURN instructions
- example: counterparty

# Contents

1 Bitcoin as a Log

2 Colored Coins

3 Lotteries

# Fungibility

## Definition (wikipedia)

In economics, **fungibility** is the **property of a good or a commodity whose individual units are essentially interchangeable**, and each of its parts is indistinguishable from another part.

- Are bitcoins fungible?

# Colored Coins

- Bitcoins with additional metadata
- Implemented using special scripts
- Examples: tickets, shares, collectibles, subscriptions

# Contents

1 Bitcoin as a Log

2 Colored Coins

3 Lotteries

# Secure Multiparty Lotteries in Bitcoin

## The offline version: Coin Flip

- Alice and Bob want to bet on the outcome of a coin flip
- They agree on the amount and the method to determine the winner
- Bob throws the coin, Alice shouts “heads” or “tails” while the coin is in the air
- When the coin lands, Alice wins if she correctly predicted the coin top

# Secure Multiparty Lotteries in Bitcoin

## The offline version: Coin Flip

- Alice and Bob want to bet on the outcome of a coin flip
- They agree on the amount and the method to determine the winner
- Bob throws the coin, Alice shouts “heads” or “tails” while the coin is in the air
- When the coin lands, Alice wins if she correctly predicted the coin top

## Properties

- The outcome is random and cannot be influenced
- The winner is immediately known to Alice and Bob

# Secure Multiparty Lotteries in Bitcoin

## The offline version: Coin Flip

- Alice and Bob want to bet on the outcome of a coin flip
- They agree on the amount and the method to determine the winner
- Bob throws the coin, Alice shouts “heads” or “tails” while the coin is in the air
- When the coin lands, Alice wins if she correctly predicted the coin top

## Properties

- The outcome is random and cannot be influenced
- The winner is immediately known to Alice and Bob

## Drawbacks

- All participants have to be physically present
- They need to trust each other



# Issues of Bitcoin Lotteries

## Randomness?

- Can we get un-influenciable randomness on the blockchain?
- No random instruction in script

# Issues of Bitcoin Lotteries

## Randomness?

- Can we get un-influenciable randomness on the blockchain?
- No random instruction in script

## Mutual trust?

- Bettors are not (simultaneously / physically) present
- But want to guarantee payout

# Issues of Bitcoin Lotteries

## Randomness?

- Can we get un-influenciable randomness on the blockchain?
- No random instruction in script

## Mutual trust?

- Bidders are not (simultaneously / physically) present
- But want to guarantee payout

## Building block for other applications

- Sealed bid auctions without trusted auctioneer
- Randomization (e.g., to break ties)
- Transfer of the auctioned (digital) asset

# Coin Flipping (attempt)

Three party coin flip

# Coin Flipping (attempt)

## Three party coin flip

- Desired outcome: 0, 1, or 2

# Coin Flipping (attempt)

## Three party coin flip

- Desired outcome: 0, 1, or 2
- A, B, and C each pick a (large) random number  $a$ ,  $b$ , and  $c$

# Coin Flipping (attempt)

## Three party coin flip

- Desired outcome: 0, 1, or 2
- A, B, and C each pick a (large) random number  $a$ ,  $b$ , and  $c$
- Everyone publishes their number at the same time

# Coin Flipping (attempt)

## Three party coin flip

- Desired outcome: 0, 1, or 2
- A, B, and C each pick a (large) random number  $a$ ,  $b$ , and  $c$
- Everyone publishes their number at the same time
- Everyone calculates  $(a + b + c) \bmod 3$



# Coin Flipping (attempt)

## Three party coin flip

- Desired outcome: 0, 1, or 2
- A, B, and C each pick a (large) random number  $a$ ,  $b$ , and  $c$
- Everyone publishes their number at the same time
- Everyone calculates  $(a + b + c) \bmod 3$

## Simultaneity

- cannot be guaranteed on the Internet
- if A publishes last, she can affect the outcome ...

# Three Party Fair Coin Flip

## Round One

- A, B, and C each pick a (large) random number  $a$ ,  $b$ , and  $c$
- Everyone publishes the hashes  $H(a)$ ,  $H(b)$ ,  $H(c)$
- Abort the protocol if two of the hashes are equal

# Three Party Fair Coin Flip

## Round One

- A, B, and C each pick a (large) random number  $a$ ,  $b$ , and  $c$
- Everyone publishes the hashes  $H(a)$ ,  $H(b)$ ,  $H(c)$
- Abort the protocol if two of the hashes are equal

## Round Two

- Every party reveals their number  $a$ ,  $b$ , and  $c$
- Everyone can check consistency with the previously published hashes
- Everyone computes  $(a + b + c) \bmod 3$

# Three Party Fair Coin Flip

## Round One

- A, B, and C each pick a (large) random number  $a$ ,  $b$ , and  $c$
- Everyone publishes the hashes  $H(a)$ ,  $H(b)$ ,  $H(c)$
- Abort the protocol if two of the hashes are equal

## Round Two

- Every party reveals their number  $a$ ,  $b$ , and  $c$
- Everyone can check consistency with the previously published hashes
- Everyone computes  $(a + b + c) \bmod 3$

## Remark

It is sufficient that one participant picks a number at random!

## Drawback of the coin flip protocol

- Once  $C$  sees values  $a$  and  $b$  in round three, she can figure out whether she won
- She could choose to never reveal  $c$  and block the protocol indefinitely!

# Fairness and Commitment

## Drawback of the coin flip protocol

- Once  $C$  sees values  $a$  and  $b$  in round three, she can figure out whether she won
- She could choose to never reveal  $c$  and block the protocol indefinitely!

## What's needed

- a commitment to the stake
- automatic loss of the stake if  $c$  leaves the protocol (i.e., no reaction inside a time limit)

# Timed Commitment in Bitcoin

## Timed commitment between Alice and Bob

- Alice puts up a **bond** that vouches for value  $x$ :
- a bitcoin transaction with an output that can be spent in two ways
  - ① transaction signed by both Alice and Bob
  - ② transaction that includes the value  $x$ , but only needs Alice's signature

# Timed Commitment in Bitcoin

## Timed commitment between Alice and Bob

- Alice puts up a **bond** that vouches for value  $x$ :
- a bitcoin transaction with an output that can be spent in two ways
  - ① transaction signed by both Alice and Bob
  - ② transaction that includes the value  $x$ , but only needs Alice's signature

## Step 2

- Alice and Bob sign a transaction that transfers the bond to Bob
- This transaction comes with a **lock time**  $t$  in the future
- Alice intends to reveal  $x$  before  $t$ , so this transaction will never be accepted



# Timed Commitment in Bitcoin

## Timed commitment between Alice and Bob

- Alice puts up a **bond** that vouches for value  $x$ :
- a bitcoin transaction with an output that can be spent in two ways
  - ① transaction signed by both Alice and Bob
  - ② transaction that includes the value  $x$ , but only needs Alice's signature

## Step 2

- Alice and Bob sign a transaction that transfers the bond to Bob
- This transaction comes with a **lock time**  $t$  in the future
- Alice intends to reveal  $x$  before  $t$ , so this transaction will never be accepted

## Possible Outcomes

- Alice reveals  $x$  before time  $t$  and her bond is returned
- Alice fails to reveal  $x$  before  $t$  and her bonds falls to Bob

# Bitcoin script for timed commitment

## Locking script for the output

```
OP_IF
  <AlicePubKey> OP_CHECKSIGVERIFY <BobPubKey> OP_CHECKSIG
OP_ELSE
  <AlicePubKey> OP_CHECKSIGVERIFY OP_HASH <H(x)> OP_EQUAL
OP_ENDIF
```

# Bitcoin script for timed commitment

## Locking script for the output

```
OP_IF  
  <AlicePubKey> OP_CHECKSIGVERIFY <BobPubKey> OP_CHECKSIG  
OP_ELSE  
  <AlicePubKey> OP_CHECKSIGVERIFY OP_HASH <H(x)> OP_EQUAL  
OP_ENDIF
```

## Unlocking script; bond forfeited

```
<BobSignature> <AliceSignature> 1
```

# Bitcoin script for timed commitment

## Locking script for the output

```
OP_IF  
  <AlicePubKey> OP_CHECKSIGVERIFY <BobPubKey> OP_CHECKSIG  
OP_ELSE  
  <AlicePubKey> OP_CHECKSIGVERIFY OP_HASH <H(x)> OP_EQUAL  
OP_ENDIF
```

## Unlocking script; bond forfeited

```
<BobSignature> <AliceSignature> 1
```

## Unlocking script; bond returned

```
<x> <AliceSignature> 0
```

# Application to Secure Lottery

## $n$ -party lottery protocol

- **timed** hash commitments
- $n$  parties  $\rightarrow n^2 - n$  commitments required
- to be effective, players have to escrow more than they are betting

# Thanks!