

Our Clients



Our Own Brands



KSQUARE™

Corporate Office

B-403/404 Signature - 2, Sarkhej Sanand Road,
Sarkhej, Ahmedabad - 382210.

Factory Unit

No. 56, Mahagujarat Industrial Estate, Sarkhej-Bavla Road,
B/h Intas Pharma, Moraiya, Changodar-382213.

sales@ksquareenergy.com +91 72279 31916 | 19

www.ksquareenergy.com



KSQUARE™

Precision Engineering for Uninterrupted Power



- ✓ MAX 98.1% EFFICIENCY
- ✓ IP66 PROTECTION
- ✓ SAFE & RELIABLE
- ✓ HIGH YIELD
- ✓ EASY TO USE

Ksquare Solar Inverter
1 kW to 25 kW



www.ksquareenergy.com

sales@ksquareenergy.com



Model	KSQ-1K-SS	KSQ-1.5K-SS	KSQ-2K-SS	KSQ-2.5K-SS	KSQ-3K-SS	KSQ-3.3K-SS	KSQ-3.6K-SS	KSQ-4K-SS	KSQ-4.2K-SS	KSQ-4.6K-SS	KSQ-5K-SS	KSQ-6K-SS	KSQT-4K	KSQT-5K	KSQT-6K	KSQT-8K	KSQT-10K	KSQT-12K	KSQT-15K	KSQT-17K	KSQT-20K	KSQT-25K
INPUT																						
Max. Input Power (W)	1600	2400	3200	4000	4800	4800	5888	6400	6700	7360	8000	9600	6400	8000	9600	12800	16000	19200	24000	27200	32000	40000
Start-up Voltage (V)	60						80						180									
Max. DC Input Voltage (V)	500						600						1100									
Min. DC Voltage (V)	55						-						150									
Rated DC Input Voltage (V)	360						360						620									
MPPT Voltage Range (V)	80-450						100-500						160-1000									
Full power MPPT voltage range (V)	-						200-500	220-500	210-500	260-500	280-500	330-500	-									
No. of MPP Trackers	1						1						2									
No. of DC Inputs per MPPT	1						1						1						1/2	2		
Max. Input Current (A)	16						20						15/15						15/30	30/30		
Max. Short-circuit Current (A)	20						25						20/20						20/40	40/40		
Backfeed current to the array (A)	-						0						-									
Output																						
Rated Output Power (W)	1000	1500	2000	2500	3000	3300	3680	4000	4200	4600	5000	6000	4000	5000	6000	8000	10000	12000	15000	17000	20000	25000
Max. Output Power (W)	1100	1650	2200	2750	3300	300	3680	4400	4200	5060	5500	6600	4400	5500	6600	8800	11000	13200	16500	18700	22000	25000
Max. Apparent Power (VA)	1100	1650	2200	2750	3300	300	3680	4400	4200	5060	5500	6600	4400	5500	6600	8800	11000	13200	16500	18700	22000	25000
Rated Output Voltage (V)	220/230												3L/N/PE, 230/400V									
Rated AC Frequency (Hz)	50/60Hz 45-55Hz/55-65Hz						50/60						50/60Hz 45-55Hz/55-65Hz									
Max. Output Current (A)	4.8	7.2	9.6	12	14.4	14.4	16		19.1	23	25	30	6.7	8.4	10	13.3	16.5	20	25	28.4	31.9	39
Power Factor	0.8 leading...0.8 lagging																					
Max. Total Harmonic Distortion	<3% @Rated Output Power																					
DCI	<0.5%In																					
Efficiency																						
Max. Efficiency	97.3%		97.5%				98.1%						98.3%				98.6%					
European Efficiency	96.4%		97.0%				97.5%						97.9%				98.2%					
MPPT Efficiency	99.9%																					
Protection																						
DC Reverse Polarity Protection													Integrated									
Insulation Resistance Protection													Integrated									
AFCI													Optional									
DC Switch													Optional									
Surge Protection													Integrated									
Over-temperature Protection													Integrated									
Residual Current Protection													Integrated									
Islanding protection	Integrated												Frequency shift, Integrated									
Anti-islanding Protection													Integrated									
AC Short-circuit Protection													Integrated									
AC Over-voltage Protection													Integrated									
General Data																						
Dimensions (mm)	327W*297H*114D						410W*360H*120D						550W*410H*175D									
Weight (KG)	6.5						11.5						23						26	29		
Protection Degree	Ip65						Ip66						Ip65									
Self-consumption at Night (W)	<1																					
Topology	Transformer less																					
Operating Temperature Range (° C)	-30~60																					
Relative Humidity (%)	0~100																					
Operating Altitude (m)	4000 (derating@ > 3000)						3000 (derating@ > 2000)						4000 (derating@ > 3000)									
Cooling	Natural Convection																		Smart Fan Cooling			
Noise Level (dB)	< 25																		<40			
Display	OLED & LED						OLED(Optional)						OLED & LED									
Communication	RS485/WiFi/GPRS/LAN (Optional)																					

** Due to differences in voltage values in various countries, minor variations may occur. The final interpretation rights belong to Ksquare Energy Pvt Ltd.