



Product Service

Attestation of Conformity

No. N8A 110557 0014 Rev. 00

Holder of Certificate: **MINDRA GREEN ENERGY LLP**
102, Devraj Industrial Park, OFF, Pirana Piplaj Road
Piplaj
Ahmedabad, Gujarat 382405
INDIA

Product: **Converter**
(Photovoltaic grid-connected inverter)

This Attestation of Conformity is issued on a voluntary basis according to the Low Voltage Directive 2014/35/EU relating to electrical equipment designed for use within certain voltage limits. It confirms that the listed equipment complies with the principal protection requirements of the directive and is based on the technical specifications applicable at the time of issuance. It refers only to the particular sample submitted for testing and certification. For details see: www.tuvsud.com/ps-cert

Test report no.: 64290193056602A

Date, 2021-02-18

(Billy Qiu)

Page 1 of 3

After preparation of the necessary technical documentation as well as the EU declaration of conformity the required CE marking can be affixed on the product. The declaration of conformity is issued under the sole responsibility of the manufacturer. Other relevant EU-directives have to be observed.



Product Service

Attestation of Conformity

No. N8A 110557 0014 Rev. 00

Model(s): MIND 3300, MIND 4300, MIND 4700,
MIND 5300, MIND 6000, MIND 3400,
MIND 5400, MIND 5600, MIND 5900

Parameters:

Model Specifications	MIND 3300	MIND 4300	MIND 4700	MIND 5300	MIND 6000
Input (DC)					
Max. DC power	4050W	5670W	6210W	6750W	8100W
Max. DC voltage	600Vd.c.				
Normal DC voltage	380Vd.c.				
MPPT voltage range	80V-550Vd.c.				
MPPT voltage range (full load)	280Vd.c.-480Vd.c.	220Vd.c.-480Vd.c.	210Vd.c.-480Vd.c.	230Vd.c.-480Vd.c.	280Vd.c.-480Vd.c.
Number of MPP trackers	1	2	2	2	2
Strings per MPP tracker	1	1	1	1	1
Max. input current per MPPT tracker	12.5 Ad.c.	11 Ad.c.*2	12.5 Ad.c.*2	12.5 Ad.c.*2	12.5 Ad.c.*2
PV short circuit current	15.6 Ad.c.	13.2 Ad.c.*2	15.6 Ad.c.*2	15.6 Ad.c.*2	15.6 Ad.c.*2
Max. DC power	4050W	5670W	6210W	6750W	8100W
Output (AC)					
Normal AC output Power	3000W	4200W	4600W	5000W	6000W
Max. AC output Power	3300W	4620W	5060W	5500W	6600W
Max. AC apparent Power	3300VA	4620VA	5060VA	5500VA	6600VA
Normal AC voltage	230Va.c.				
Normal AC grid frequency	50 Hz				
Max. output current	14.5Aa.c.	20Aa.c.	22Aa.c.	24Aa.c.	28.5Aa.c.
Power Factor	0.8 leading to 0.8 lagging				
General					
Temperature range	-25 °C to +60 °C (> 45°C derating)				
Altitude	≤4000m				
Ingress protection rating	IP65				
Protection Class	Class I				

Page 2 of 3

After preparation of the necessary technical documentation as well as the EU declaration of conformity the required CE marking can be affixed on the product. The declaration of conformity is issued under the sole responsibility of the manufacturer. Other relevant EU-directives have to be observed.



Product Service

Attestation of Conformity

No. N8A 110557 0014 Rev. 00

Model Specifications	MIND 3400	MIND 5400	MIND 5600	MIND 5900
Input (DC)				
Max. DC power	4050W	5670W	6210W	6750W
Max. DC voltage	600Vd.c.			
Normal DC voltage	380Vd.c.			
MPPT voltage range	80V-550Vd.c.			
MPPT voltage range (full load)	250Vd.c.-480Vd.c.	200Vd.c.-480Vd.c.	195Vd.c.-480Vd.c.	210Vd.c.-480Vd.c.
Number of MPP trackers	1	2	2	2
Strings per MPP tracker	1	1	1	1
Max. input current per MPPT tracker	12.5 Ad.c.	11 Ad.c.*2	12.5 Ad.c.*2	12.5 Ad.c.*2
PV short circuit current	15.6 Ad.c.	13.2 Ad.c. *2	15.6 Ad.c. *2	15.6 Ad.c. *2
Max. DC power	4050W	5670W	6210W	6750W
Output (AC)				
Normal AC output Power	3000W	4200W	4600W	4999W
Max. AC output Power	3000W	4200W	4600W	4999W
Max. AC apparent Power	3000VA	4200VA	4600VA	4999VA
Normal AC voltage	230Va.c.			
Normal AC grid frequency	50 Hz			
Max. output current	13Aa.c.	18.5Aa.c.	20Aa.c.	21.7Aa.c.
Power Factor	0.8 leading to 0.8 lagging			
General				
Temperature range	-25 °C to +60 °C (> 45°C derating)			
Altitude	≤4000m			
Ingress protection rating	IP65			
Protection Class	Class I			

**Tested
according to:**

EN 62109-1:2010
EN 62109-2:2011

Page 3 of 3

After preparation of the necessary technical documentation as well as the EU declaration of conformity the required CE marking can be affixed on the product. The declaration of conformity is issued under the sole responsibility of the manufacturer. Other relevant EU-directives have to be observed.



Product Service

CERTIFICATE

No. Z2 110557 0013 Rev. 00

Holder of Certificate: **MINDRA GREEN ENERGY LLP**
102, Devraj Industrial Park, OFF, Pirana Piplaj Road
Piplaj
Ahmedabad, Gujarat 382405
INDIA

Certification Mark:



Product: **Converter**
(Photovoltaic grid-connected inverter)

The product was tested on a voluntary basis and complies with the essential requirements. The certification mark shown above can be affixed on the product. It is not permitted to alter the certification mark in any way. In addition, the certification holder must not transfer the certificate to third parties. This certificate is valid until the listed date, unless it is cancelled earlier. All applicable requirements of the testing and certification regulations of TÜV SÜD Group have to be complied. For details see: www.tuvsud.com/ps-cert

Test report no.: 64290193056602A

Valid until: 2025-09-24

Date, 2021-02-18

(Billy Qiu)

CERTIFICATE

No. Z2 110557 0013 Rev. 00

Model(s):

**MIND 3300, MIND 4300, MIND 4700,
MIND 5300, MIND 6000, MIND 3400,
MIND 5400, MIND 5600, MIND 5900**

Parameters:

Model Specifications	MIND 3300	MIND 4300	MIND 4700	MIND 5300	MIND 6000
Input (DC)					
Max. DC power	4050W	5670W	6210W	6750W	8100W
Max. DC voltage	600Vd.c.				
Normal DC voltage	380Vd.c.				
MPPT voltage range	80V-550Vd.c.				
MPPT voltage range (full load)	280Vd.c.-480Vd.c.	220Vd.c.-480Vd.c.	210Vd.c.-480Vd.c.	230Vd.c.-480Vd.c.	280Vd.c.-480Vd.c.
Number of MPP trackers	1	2	2	2	2
Strings per MPP tracker	1	1	1	1	1
Max. input current per MPPT tracker	12.5 Ad.c.	11 Ad.c.*2	12.5 Ad.c.*2	12.5 Ad.c.*2	12.5 Ad.c.*2
PV short circuit current	15.6 Ad.c.	13.2 Ad.c.*2	15.6 Ad.c.*2	15.6 Ad.c.*2	15.6 Ad.c.*2
Max. DC power	4050W	5670W	6210W	6750W	8100W
Output (AC)					
Normal AC output Power	3000W	4200W	4600W	5000W	6000W
Max. AC output Power	3300W	4620W	5060W	5500W	6600W
Max. AC apparent Power	3300VA	4620VA	5060VA	5500VA	6600VA
Normal AC voltage	230Va.c.				
Normal AC grid frequency	50 Hz				
Max. output current	14.5Aa.c.	20Aa.c.	22Aa.c.	24Aa.c.	28.5Aa.c.
Power Factor	0.8 leading to 0.8 lagging				
General					
Temperature range	-25 °C to +60 °C (> 45°C derating)				
Altitude	≤4000m				
Ingress protection rating	IP65				
Protection Class	Class I				

CERTIFICATE

No. Z2 110557 0013 Rev. 00

Model Specifications	MIND 3400	MIND 5400	MIND 5600	MIND 5900
Input (DC)				
Max. DC power	4050W	5670W	6210W	6750W
Max. DC voltage	600Vd.c.			
Normal DC voltage	380Vd.c.			
MPPT voltage range	80V-550Vd.c.			
MPPT voltage range (full load)	250Vd.c.-480Vd.c.	200Vd.c.-480Vd.c.	195Vd.c.-480Vd.c.	210Vd.c.-480Vd.c.
Number of MPP trackers	1	2	2	2
Strings per MPP tracker	1	1	1	1
Max. input current per MPPT tracker	12.5 Ad.c.	11 Ad.c.*2	12.5 Ad.c.*2	12.5 Ad.c.*2
PV short circuit current	15.6 Ad.c.	13.2 Ad.c. *2	15.6 Ad.c. *2	15.6 Ad.c. *2
Max. DC power	4050W	5670W	6210W	6750W
Output (AC)				
Normal AC output Power	3000W	4200W	4600W	4999W
Max. AC output Power	3000W	4200W	4600W	4999W
Max. AC apparent Power	3000VA	4200VA	4600VA	4999VA
Normal AC voltage	230Va.c.			
Normal AC grid frequency	50 Hz			
Max. output current	13Aa.c.	18.5Aa.c.	20Aa.c.	21.7Aa.c.
Power Factor	0.8 leading to 0.8 lagging			
General				
Temperature range	-25 °C to +60 °C (> 45°C derating)			
Altitude	≤4000m			
Ingress protection rating	IP65			
Protection Class	Class I			

**Tested
according to:**

IEC 62109-1:2010
EN 62109-1:2010
IEC 62109-2:2011
EN 62109-2:2011



Product Service

Attestation of Conformity

No. N8A 110557 0009 Rev. 00

Holder of Certificate: **MINDRA GREEN ENERGY LLP**
102, Devraj Industrial Park, OFF, Pirana Piplaj Road
Piplaj
Ahmedabad, Gujarat 382405
INDIA

Product: **Converter**
(PV grid-interactive inverter)

This Attestation of Conformity is issued on a voluntary basis according to the Low Voltage Directive 2014/35/EU relating to electrical equipment designed for use within certain voltage limits. It confirms that the listed equipment complies with the principal protection requirements of the directive and is based on the technical specifications applicable at the time of issuance. It refers only to the particular sample submitted for testing and certification. For details see: www.tuvsud.com/ps-cert

Test report no.: 64290160004105B

Date, 2020-12-21

(Billy Qiu)

Page 1 of 3

After preparation of the necessary technical documentation as well as the EU declaration of conformity the required CE marking can be affixed on the product. The declaration of conformity is issued under the sole responsibility of the manufacturer. Other relevant EU-directives have to be observed.



Product Service

Attestation of Conformity

No. N8A 110557 0009 Rev. 00

Model(s): MIND 3200D, MIND 3600, MIND 3900,
MIND 4000, MIND 4200, MIND 4600,
MIND 4900, MIND 5000, MIND 5200

Parameters:

Model	MIND 3200D	MIND 3600	MIND 3900	MIND 4000	MIND 4200
V _{max} PV	500 Vd.c.	500 Vd.c.	500 Vd.c.	500 Vd.c.	500 Vd.c.
MPPT range (full load)	150 ~ 400 Vd.c.	165 ~ 400 Vd.c.	156 ~ 400 Vd.c.	165 ~ 400 Vd.c.	168 ~ 400 Vd.c.
I _{sc} PV	2 x 13.2 Ad.c.	2 x 15.6 Ad.c.	2 x 15.6 Ad.c.	2 x 15.6 Ad.c.	2 x 15.6 Ad.c.
Max. continuous output current	14 Aa.c.	16 Aa.c.	17 Aa.c.	17.5 Aa.c.	18 Aa.c.
Nominal output power	3200 W	3680 W	3900 W	4000 W	4200 W
Nominal AC Frequency	50/60 Hz	50/60 Hz	50 Hz	50/60 Hz	50 Hz
Nominal AC voltage	230 Va.c.				
Power factor (full load)	>0.99				
Protective class	I				
Ingress protection	IP65				

Model	MIND 4600	MIND 4900	MIND 5000	MIND 5200
V _{max} PV	500 Vd.c.	500 Vd.c.	500 Vd.c.	500 Vd.c.
MPPT range (full load)	200 ~ 400 Vd.c.	196 ~ 400 Vd.c.	200 ~ 400 Vd.c.	208 ~ 400 Vd.c.
I _{sc} PV	2 x 15.6 Ad.c.	2 x 15.6 Ad.c.	2 x 15.6 Ad.c.	2 x 15.6 Ad.c.
Max. continuous output current	20 Aa.c.	21.5 Aa.c.	22 Aa.c.	22.5 Aa.c.
Nominal output power	4600 W	4900 W	5000 W	5200 W
Nominal AC Frequency	50/60 Hz	50 Hz	50/60 Hz	50 Hz
Nominal AC voltage	230 Va.c.			
Power factor (full load)	>0.99			
Protective class	I			
Ingress protection	IP65			

Page 2 of 3

After preparation of the necessary technical documentation as well as the EU declaration of conformity the required CE marking can be affixed on the product. The declaration of conformity is issued under the sole responsibility of the manufacturer. Other relevant EU-directives have to be observed.



Product Service

Attestation of Conformity

No. N8A 110557 0009 Rev. 00

**Tested
according to:**

EN 62109-1:2010
EN 62109-2:2011

Page 3 of 3

After preparation of the necessary technical documentation as well as the EU declaration of conformity the required CE marking can be affixed on the product. The declaration of conformity is issued under the sole responsibility of the manufacturer. Other relevant EU-directives have to be observed.

TÜV SÜD Product Service GmbH • Certification Body • Ridlerstraße 65 • 80339 Munich • Germany



Product Service

Test Verification

Dated: 2020-11-06

Applicant: MINDRA GREEN ENERGY LLP
102, Devraj Industrial Park, OFF, Pirana Piplaj Road,
Piplaj Ahmedabad, Gujarat 382405, INDIA

Product: PV Grid-interactive Inverter

Model: MIND 3200D, MIND 3600, MIND 3900, MIND 4000,
MIND 4200, MIND 4600, MIND 4900, MIND 5000,
MIND 5200

Tested according to: IEC 61683:1999;
IEC 60068-2-1:2007;
IEC 60068-2-2:2007;
IEC 60068-2-14:2009;
IEC 60068-2-30:2005;

Test report No.: 64.290.17.00166.03A

TÜV SÜD Certification and Testing (China) Co., Ltd. Guangzhou Branch

Section Manager
[Billy Qiu]

This Verification confirms that the test results of the presented product in the above listed test report are in compliance with the specified requirements. This Verification is part of the full test report(s) and should be read in conjunction with it.



Product Service

CERTIFICATE

No. Z2 110557 0006 Rev. 00

Holder of Certificate: **MINDRA GREEN ENERGY LLP**
102, Devraj Industrial Park, OFF, Pirana Piplaj Road
Piplaj
Ahmedabad, Gujarat 382405
INDIA

Certification Mark:



Product: **Converter**
(PV grid-interactive inverter)

The product was tested on a voluntary basis and complies with the essential requirements. The certification mark shown above can be affixed on the product. It is not permitted to alter the certification mark in any way. In addition, the certification holder must not transfer the certificate to third parties. This certificate is valid until the listed date, unless it is cancelled earlier. All applicable requirements of the testing and certification regulations of TÜV SÜD Group have to be complied. For details see: www.tuvsud.com/ps-cert

Test report no.: 64290170016402B

Valid until: 2025-01-02

Date, 2020-12-21

(Billy Qiu)

CERTIFICATE

No. Z2 110557 0006 Rev. 00

Model(s): MIND 3200D, MIND 3600, MIND 3900,
MIND 4000, MIND 4200, MIND 4600,
MIND 4900, MIND 5000, MIND 5200

Parameters:

Model	MIND 3200D	MIND 3600	MIND 3900	MIND 4000	MIND 4200
Vmax PV	500 Vd.c.	500 Vd.c.	500 Vd.c.	500 Vd.c.	500 Vd.c.
MPPT range (full load)	150 ~ 400 Vd.c.	165 ~ 400 Vd.c.	156 ~ 400 Vd.c.	165 ~ 400 Vd.c.	168 ~ 400 Vd.c.
Isc PV	2 x 13.2 Ad.c.	2 x 15.6 Ad.c.	2 x 15.6 Ad.c.	2 x 15.6 Ad.c.	2 x 15.6 Ad.c.
Max. continuous output current	14 Aa.c.	16 Aa.c.	17 Aa.c.	17.5 Aa.c.	18 Aa.c.
Nominal output power	3200 W	3680 W	3900 W	4000 W	4200 W
Nominal AC Frequency	50 Hz	50 Hz	50 Hz	50 Hz	50 Hz
Nominal AC voltage	230 Va.c.				
Power factor (full load)	>0.99				
Protective class	I				
Ingress protection	IP65				

Model	MIND 4600	MIND 4900	MIND 5000	MIND 5200
Vmax PV	500 Vd.c.	500 Vd.c.	500 Vd.c.	500 Vd.c.
MPPT range (full load)	200 ~ 400 Vd.c.	196 ~ 400 Vd.c.	200 ~ 400 Vd.c.	208 ~ 400 Vd.c.
Isc PV	2 x 15.6 Ad.c.	2 x 15.6 Ad.c.	2 x 15.6 Ad.c.	2 x 15.6 Ad.c.
Max. continuous output current	20 Aa.c.	21.5 Aa.c.	22 Aa.c.	22.5 Aa.c.
Nominal output power	4600 W	4900 W	5000 W	5200 W
Nominal AC Frequency	50 Hz	50 Hz	50 Hz	50 Hz
Nominal AC voltage	230 Va.c.			
Power factor (full load)	>0.99			
Protective class	I			
Ingress protection	IP65			

CERTIFICATE

No. Z2 110557 0006 Rev. 00

**Tested
according to:**

IEC 62109-1(ed.1)
EN 62109-1:2010
IEC 62109-2(ed.1)
EN 62109-2:2011
IEC 61727(ed.2)
IEC 62116(ed.2)

**Production
Facility(ies):**

076189



Product Service

CERTIFICATE

No. Z2 110557 0004 Rev. 00

Holder of Certificate: **MINDRA GREEN ENERGY LLP**
102, Devraj Industrial Park, OFF, Pirana Piplaj Road
Piplaj
Ahmedabad, Gujarat 382405
INDIA

Certification Mark:



Product: **Converter**
(PV grid-interactive inverter)

The product was tested on a voluntary basis and complies with the essential requirements. The certification mark shown above can be affixed on the product. It is not permitted to alter the certification mark in any way. In addition, the certification holder must not transfer the certificate to third parties. This certificate is valid until the listed date, unless it is cancelled earlier. All applicable requirements of the testing and certification regulations of TÜV SÜD Group have to be complied. For details see: www.tuvsud.com/ps-cert

Test report no.: 64290160004105B

Valid until: 2025-01-02

Date, 2020-12-21

(Billy Qiu)

CERTIFICATE

No. Z2 110557 0004 Rev. 00

Model(s): MIND 3200D, MIND 3600, MIND 3900,
MIND 4000, MIND 4200, MIND 4600,
MIND 4900, MIND 5000, MIND 5200

Parameters:

Model	MIND 3200D	MIND 3600	MIND 3900	MIND 4000	MIND 4200
Vmax PV	500 Vd.c.	500 Vd.c.	500 Vd.c.	500 Vd.c.	500 Vd.c.
MPPT range (full load)	150 ~ 400 Vd.c.	165 ~ 400 Vd.c.	156 ~ 400 Vd.c.	165 ~ 400 Vd.c.	168 ~ 400 Vd.c.
Isc PV	2 x 13.2 Ad.c.	2 x 15.6 Ad.c.	2 x 15.6 Ad.c.	2 x 15.6 Ad.c.	2 x 15.6 Ad.c.
Max. continuous output current	14 Aa.c.	16 Aa.c.	17 Aa.c.	17.5 Aa.c.	18 Aa.c.
Nominal output power	3200 W	3680 W	3900 W	4000 W	4200 W
Nominal AC Frequency	50/60 Hz	50/60 Hz	50 Hz	50/60 Hz	50 Hz
Nominal AC voltage	230 Va.c.				
Power factor (full load)	>0.99				
Protective class	I				
Ingress protection	IP65				

Model	MIND 4600	MIND 4900	MIND 5000	MIND 5200
Vmax PV	500 Vd.c.	500 Vd.c.	500 Vd.c.	500 Vd.c.
MPPT range (full load)	200 ~ 400 Vd.c.	196 ~ 400 Vd.c.	200 ~ 400 Vd.c.	208 ~ 400 Vd.c.
Isc PV	2 x 15.6 Ad.c.	2 x 15.6 Ad.c.	2 x 15.6 Ad.c.	2 x 15.6 Ad.c.
Max. continuous output current	20 Aa.c.	21.5 Aa.c.	22 Aa.c.	22.5 Aa.c.
Nominal output power	4600 W	4900 W	5000 W	5200 W
Nominal AC Frequency	50/60 Hz	50 Hz	50/60 Hz	50 Hz
Nominal AC voltage	230 Va.c.			
Power factor (full load)	>0.99			
Protective class	I			
Ingress protection	IP65			



Product Service

CERTIFICATE

No. Z2 110557 0004 Rev. 00

Tested according to: EN 62109-1:2010
EN 62109-2:2011

Production Facility(ies): 076189