



MELT BLOWN FILTER CARTRIDGES



Excellence in standards, excellence in filtration.

mmp proudly holds the distinction of being the first company in India to receive **NSF certification** for its filter cartridges. **Lagoon-branded Melt-blown filter cartridges** are recognized for their production in a meticulously controlled environment, guaranteeing superior filtration quality and an extended lifespan.

Lagoon Melt-blown filter cartridges are meticulously crafted through an expert manufacturing process. The process commences by heating Polypropylene resins, causing them to transform into a molten liquid state. Subsequently, these molten polymers are extruded through spinnerets onto a rotating spindle under controlled air pressure.

The resulting nonwoven fibers are meticulously arranged and bonded to create three distinct layers within a cylindrical shape. The innermost layer is tightly bonded to effectively filter minute particles, while the two outer layers provide a less restrictive filtration for capturing larger impurities.

mmp caters to a wide range of filtration needs without compromising on performance. Our cartridges feature nominal micron dimensions ranging from 27-35mm ID and 50-63mm OD, with lengths varying from 5" to 70".

Our innovative three-layer gradient construction sets us apart, progressing in the micron range from 1 μ to 100 μ . This distinctive design adeptly captures particles and impurities of all sizes, ensuring optimal cartridge utilization and delivering a purer liquid for consumption.

The gradient construction significantly improves the removal of contaminants at each level, ensuring superior filtration quality.

These cartridges exhibit a flow rate of 1m³ per hour per 10", withstanding a pressure of 2.5 kg/cm² and temperatures up to 60°C. This results in high-performance filtration and prolonged durability for extended periods.

Lagoon Melt-blown cartridges are ideally suited for domestic applications. Some of the most common applications are in reverse osmosis, water purifiers, air purifiers/compressors, and occasionally vacuum cleaners. Their lightweight and durable nature not only lightens the load on the system but also proves cost-effective for consumers.



MELT BLOWN FILTER CARTRIDGES



Technical Name	Melt Blown Filter Cartridges (Medium Density)
Raw Material	Virgin Polypropylene
ID	20-35mm±
OD	50-63mm± 1mm Jumbo 114± 2mm
Length	5"-50" 127mm to 1778mm
Microns	1-100μ
Construction	Polypropylene fibres are extruded through tiny perforations under pressure and high temperature on a rotating mandrel, forming three layers for gradient filtration
Flow	1m ³ per hour per 10" at pressure of 2.5Kg/cm ²
Temperature	Max. 60° C

Office Address:

C3-602 Anushruti Tower, SG Road, Thaltej,
Ahmedabad – 380059 Gujarat, India

Contact:

+91 70437 45709
+91 98300 30030

Email

ahmd-sales@mmpfilter.com
ntodi@mmpfilter.com