



MELT BLOWN FILTER CARTRIDGES



The higher the density, the higher the performance.

mmp has achieved the distinction of being the first company in India to attain **NSF certification** for its Oceanic-branded Melt-blown filter cartridges. Crafted by industry experts, these cartridges are tailored for controlled environments, employing cutting-edge machinery to ensure heightened effectiveness and superior filtration quality.

The production of Oceanic Melt-blown filter cartridges involves a specialized manufacturing process executed with precision. The process begins with the melting of polypropylene granules, which are then extruded through a machine. Utilizing air pressure, the molten polypropylene is subsequently passed through minuscule holes in spinnerets onto a rotating spindle.

Using these PP fibers, a cylindrical filter is created with three distinct layers tightly wound around a robust and denser inner core. The three-layered structure plays a pivotal role in efficiently filtering out minute particles from the liquid. Meeting stringent safety and efficacy standards, these filter cartridges have earned FDA approval.

This premium material ensures steadfast performance, surmounting challenges with ease. Catering to diverse needs, it features a broad range of Inner Diameters (ID) from 20 to 35mm and Outer Diameters (OD) from 40 to 114mm, accompanied by lengths ranging from 5" to 70". With Nominal microns spanning from 0.5-100µ, our cartridges provide a comprehensive filtration spectrum.

Crafted with a three-layered gradient design, it assures superior removal of contaminants at varying levels, ultimately enhancing both cartridge utilization and filtration proficiency.

With a flow rate of 1m³ per hour per 10", operating under a pressure of 3.5 kg/cm² and with standing temperatures of up to 60°C, our filter cartridges ensure high-performance filtration without compromising efficacy.

Oceanic Melt-blown filter cartridges find extensive applications in diverse industries such as desalination, petroleum, chemicals, and water treatment. Thanks to their higher-density design, these filter cartridges excel in effectively capturing minute particles from liquids.

USE OF PRODUCT IN VARIOUS INDUSTRIES



Desalination



Petroleum



Water Treatment



Chemical

MELT BLOWN FILTER CARTRIDGES



Technical Name	Melt Blown Filter Cartridges (High Density)
Raw Material	Virgin Polypropylene
ID	20-35mm±
OD	40-114mm±
Length	5"-70" 127mm to 1778mm
Microns	0.5-100μ
Construction	Polypropylene fibres are extruded through tiny Perforations under pressure and high temperature on a rotating mandrel, forming three layers for gradient filtration.
Flow	1m ³ per hour per 10" at pressure of 3.5Kg/cm ²
Temperature	Max. 60° C

Office Address:

C3-602 Anushruti Tower, SG Road, Thaltej,
Ahmedabad – 380059 Gujarat, India

Contact:

+91 70437 45709
+91 98300 30030

Email

ahmd-sales@mmpfilter.com
ntodi@mmpfilter.com