



PYOORITE® PP PLEATED FILTER CARTRIDGE



Advanced Polypropylene Filtration Excellence

mmp produces Polypropylene pleated filter cartridges under the brand name Pyoorite. Meticulously engineered, these cartridges enhance structural stability without compromising overall integrity. Expertly crafted, the cartridges are made from virgin polypropylene, a common and reliable material for their design.

Utilizing high-quality plastic, virgin polypropylene serves as the primary material. This PP undergoes a melting process and is then extruded. Using a molding machine, it takes on a cylindrical shape. Subsequently, the cylindrical filter cartridge is perforated, creating small holes that act as passages for water to pass through after filtration. In the subsequent step, a pleated membrane is introduced between the perforated core to optimize space utilization. The pleating enhances the surface area, thereby improving the efficiency of the filter.

The ends of these filter cartridges undergo heat sealing instead of using glue to attach the cap at the end. These caps or fittings can be changed or customized as per the customer's system requirements. This choice reflects mmp's commitment to ensuring a risk-free and smooth filtration process. It is safer to use these filters in the pharmaceuticals, food, and beverages industries, as there's no use of adhesive or any chemical to seal the caps and fittings at the end.

Customized to specific requirements, our filters are offered in Double Open-End (DOE) or Single Open-End (SOE) designs, each presenting distinctive applications and advantages.

mmp produces these filter cartridges in various lengths and diameters, ranging from 5", 10", 20", 30", 40", to 50". They feature an inner diameter (ID) of 27mm and an outer diameter (OD) of 65mm. These cartridges are available in various micron ratings, including 0.1, 0.2, 0.45, 1, 2, 5, and 10µ. The diverse micron ratings determine the size of particles the filter can efficiently capture. Engineered to withstand temperatures up to 60°C, the cartridges boast a flow rate of 1m³ per hour per 10" at a pressure of 2.5kg/cm². This ensures effective filtration without compromising performance.

These cartridges find wide-ranging applications in various industries, including chemical processing, water treatment plants, food and beverage, healthcare, pharmaceuticals, and more. Crafted with meticulous care and expertise, Pyoorite filter cartridges are safe and effective, ensuring the removal of impurities from liquids.



PYOORITE[®] PP PLEATED FILTER CARTRIDGE



Technical Name	PP Pleated Filter Cartridges
Raw Material	Virgin Polypropylene
ID	27 mm
OD	65 mm or as required by customer
Length	5" 10" 20" 30" 40" & 50"
Microns	0.1, 0.2, 0.45, 1, 2, 5 & 10μ
Construction	Inside and outside perforated core, In between pleated membrane filtration media.
Top & Bottom	DOE (Double open end) SOE (Single open end)
Flow	1m ³ per hour per 10" at pressure of 2.5kg/cm ²
Temperature	60° C

USE OF PRODUCT IN VARIOUS INDUSTRIES



PETROLEUM



CHEMICAL



PHARMACEUTICALS



FOOD & DAIRY



METALLURGY



CEMENT



ENERGY

Office Address:

C3-602 Anushruti Tower, SG Road, Thaltej,
Ahmedabad – 380059 Gujarat, India

Contact:

+91 70437 45709
+91 98300 30030

Email

ahmd-sales@mmpfilter.com
ntodi@mmpfilter.com