

PLEATED CARTRIDGES

mmp's advanced Pleated Cartridges are expertly crafted and designed for superior performance. These cartridges can be customized to meet your specific filtration needs.

Versatile Fabric Choice

Explore a range of fabric options for our Pleated Cartridges, including Spun bonded Polypropylene, Aramid (Nomex), PPS, PTFE, and Cellulose. These choices provide tailored filtration solutions for a diverse range of applications.

Customizable Coating Selection

Customize your filtration requirements with options such as PTFE membrane lamination, Oil and Water repellent, Antistatic, Oil and water repellent + antistatic, and PTFE coating. Adapt to specific environmental challenges to achieve optimal filtration performance.

Flexible Pleat Depths

Choose from standard pleat depths ranging from 16mm to 48mm, ensuring efficient filtration. Custom pleat depths are available to meet specific customer requirements, guaranteeing precision and effectiveness.

USE OF PRODUCT IN VARIOUS INDUSTRIES



PETROLEUM



CHEMICAL



PHARMACEUTICALS



FOOD & DAIRY



METALLURGY



CEMENT



ENERGY



Durable Top & Bottom Materials

Opt for top and bottom components made from Stainless Steel (SS), Aluminum, or Mild Steel (MS). This choice ensures durability and compatibility with various filtration systems, guaranteeing long-lasting performance.

Versatile Fitment Options

Available in 3 lugs/Din/PCD type fitment, with loading options from the top or bottom as required. This versatility allows seamless integration into diverse filtration setups, accommodating various system configurations.

Tailored Sizing Options

Choose from varied sizes, including 3 Lug sizes (150mm, 225mm, 325mm), Din Type (as required), and PCD Type (as required). This ensures a perfect fit for your system, enhancing overall efficiency and performance. The tailored sizing options cater to your specific filtration needs.

PLEATED CARTRIDGES



Technical Name	Pleated Filter Cartridge
Fabric	Spun bonded: Polyester, Polypropylene, Aramid, PPS, PTFE Non woven: Polyester, Aramid, PPS, PTFE Coating
Coating	PTFE membrane lamination, Oil and Water repellent, Antistatic, Oil and water repellent + antistatic, PTFE coating
Pleats	16mm & 18mm (standard pleat depth) As required by the customer
Top & Bottom	Mild Steel, Galvanized Iron, Stainless steel, Polyurethane
Fitment suitable for cell plate diameter	As required by the customer
Length	As required by the customer

Office Address:

C3-602 Anushruti Tower, SG Road, Thaltej,
Ahmedabad – 380059 Gujarat, India

Contact:

+91 70437 45709
+91 98300 30030

Email

ahmd-sales@mmpfilter.com
ntodi@mmpfilter.com