

Laboratory Report

OBJECT ORIENTED PROGRAMMING THROUGH JAVA (CSE2016L)

School of Engineering
Department of Computer Science and Engineering

Submitted By	
Student Name	Prashant Dagar
Roll Number	190020203031
Section/Group	A- T2 group
Department	Computer Science and Engineering
Session/Semester	2020-21/ Odd Semester
Submitted To	
Faculty Name	Ms. Neha Kapoor

GD GOENKA
SCHOOL OF
ENGINEERING



G D Goenka University
Gurgaon, Haryana

INDEX

S No	Date	Aim the Experiment	Signature	Grade
1	05 th August 2020	WAP to print your name		
2	05 th August 2020	WAP in java to accept two numbers (int) as command line arguments and prints their sum.		
3	19 th August 2020	WAP to find the sum of the digits of a number.		
4	19 th August 2020	WAP to convert an int value into its hexadecimal and binary equivalent.		
5	26 th August 2020	WAP to create a non- static function that prints the sum of two numbers.		
6	26 th August 2020	WAP to create a static function to find the sum of two numbers.		
7	2 nd September 2020	WAP to print factorial of a number using recursion.		
8	2 nd September 2020	WAP to implement constructor overloading by passing different number of parameters of different types.		
9	9 th September 2020	WAP to Create an abstract class Shape which has a field PI=3.14 as final and it has an abstract method Volume. Make two subclasses Cone and Sphere from this class and they print their volume.		

10	16 th September 2020	WAP in which class "A" extends class "B". Show the order of execution of the constructors if object of class B is created.		
11	21 st October 2020	WAP in which a class inherits two interfaces		


Experiment No. 1

AIM : Write a program to print your name.

Program:

```
public class Name {  
    public static void main(String[] args) { System.out.println("Hello, I  
    am Prashant");}  
  
}
```

Output



```
PS C:\Prashant\Programming\Java\Java> javac Name.java  
PS C:\Prashant\Programming\Java\Java> java Name  
Hello, I am Prashant
```


Experiment No. 2

AIM :WAP in java to accept two numbers (int) as command line arguments and print their sum.

Program:

```
public class Main {  
  
    public static void main(String ar[]) { int x,y,s;  
    x=Integer.parseInt(ar[0]); y=Integer.parseInt(ar[1]); s=x+y;  
    System.out.println("sum of " + x + " and " + y + " is " +s); }  
  
}
```

Output:



```
PS C:\Prashant\Programming\Java\Java> java Main 50 50  
sum of 50 and 50 is 100  
PS C:\Prashant\Programming\Java\Java> █
```

Experiment No. 3

AIM : WAP to find the sum of the digits of a number.

Program:

```
import java.util.Scanner;

public class Sumofdigit {

    public static void main(final String[] args) {
        int num, sum;
        final Scanner m = new Scanner(System.in);
        System.out.print("Enter a number: ");
        num = m.nextInt();

        sum = sum_of_digits(num);

        System.out.print("The sum is: " + sum + "\n");
        m.close();
    }

    public static int sum_of_digits(int a) {
        int s = 0;
        while (a > 0) {
            final int m = a % 10;
            s = s + m;
            a = a/10;
        }
        return s; }
}
```

Output:

```
PS C:\Prashant\Programming\Java\Java> javac Sumofdigit.java
PS C:\Prashant\Programming\Java\Java> java Sumofdigit
Enter a number: 67085
The sum is: 26
PS C:\Prashant\Programming\Java\Java>
```

Experiment No. 4

AIM : WAP to convert an int value into its hexadecimal and binary equivalent.

Program:

```
import java.util.Scanner;

public class Hexatodeci {

    public static void main(String[] args){
        int num;
        String i,j;
        Scanner m = new Scanner(System.in);
        System.out.print("Enter a number: ");
        num =m.nextInt();

        i = binary_equivalent(num);
        j = hexadecimal_equivalent(num);
        System.out.print("The binary equivalent of "+num+ " is " +i+
"\n");
        System.out.print("The hexadecimal equivalent of "+num+ " i
s " +j+ "\n");
        m.close();

    }

    public static String binary_equivalent(int a){
        String c = Integer.toBinaryString(a);
        return c;
    }

    public static String hexadecimal_equivalent(int b){
        String d = Integer.toHexString(b);
        return d;
    }
}
```



```
}  
}
```

Output:

```
PS C:\Prashant\Programming\Java\Java> java Hexatodeci  
Enter a number: 103738  
The binary equivalent of 103738 is 11001010100111010  
The hexadecimal equivalent of 103738 is 1953a  
PS C:\Prashant\Programming\Java\Java>
```

Experiment No. 5

AIM : WAP to create a non- static function that prints the sum of two numbers.

Program:

```
import java.util.Scanner;
public class Nonstat_sum {

    public static void main(String args[]){
        Scanner s = new Scanner(System.in);
        System.out.print("Enter 1st number: ");
        int n1 = s.nextInt();
        System.out.print("Enter 2nd number: ");
        int n2 = s.nextInt();
        sum m = new sum(n1,n2);
        m.display();
        s.close();
    }
}

class sum{
    int a,b,ans;
    sum(int i,int j){
        a=i;
        b=j;
        ans=i+j;
    }
    void display(){
        System.out.print("The sum of the two numbers is "+ans+"\n")
    }
};
```

}

Output:

```
PS S:\Programming\Java\Practice Questions> java Nonstat_sum
Enter 1st number: 34
Enter 2nd number: 78
The sum of the two numbers is 112
```

Experiment No. 6

AIM : WAP to create a static function to find the sum of two numbers.

Program:

```
import java.util.Scanner;
public class Stat_sum {

    static int a,b,sum;
    static Scanner s1 = new Scanner(System.in);
    public static void main(String[] args){
        Input1();
        Input2();
        sum = SumCal(a,b);
        Display(sum);
    }
    public static int Input1(){
        System.out.println("Enter 1st number: ");
        a = s1.nextInt();
        return a;
    }
    public static int Input2(){
        System.out.println("Enter 2nd number: ");
        b = s1.nextInt();
        return b;
    }
    public static int SumCal(int a, int b){
        return(a+b);
    }
    public static int Display(int sum){
        System.out.println("The sum of given numbers is : "+sum);
        return 0;
    }
}
```

}

Output:

```
PS S:\Programming\Java\Practice Questions> java Stat_sum
Enter 1st number:
67
Enter 2nd number:
45
The sum of given numbers is : 112
```

Experiment No. 7

AIM : WAP to print factorial of a number using recursion.

Program:

```
import java.util.Scanner;

public class Facto_recursion{

    public static void main(String args[]){
        System.out.println("\nEnter a number:- ");
        Scanner n = new Scanner(System.in);
        int num = n.nextInt();
        Facto_recursion r = new Facto_recursion();
        int fact = r.factorial(num);
        r.Display(num,fact);
        n.close();
    }

    int factorial(int n){
        if (n==0)
            return 1;
        else
            return(n*factorial(n-1));
    }

    void Display(int n, int fact){
        System.out.println("Factorial of "+n+" is:- "+fact);
    }

}
```

Output:

```
PS C:\Prashant\Programming\Java\Java> java Facto_recursion
```

```
Enter a number:-
```

```
12
```

```
Factorial of 12 is:- 479001600
```

Experiment No. 8

AIM : WAP to implement constructor overloading by passing different number of parameters of different types.

Program:

```
import java.util.Scanner;

public class Pass_parameter {
    public static void main(String args[]){
        System.out.println("\nEnter the dimensions of cuboid:");
        Scanner n = new Scanner(System.in);
        int c1 = n.nextInt();
        int c2 = n.nextInt();
        int c3 = n.nextInt();
        Volume v1 = new Volume (c1,c2,c3);
        v1.displayvolofcuboid();

        System.out.println("\nEnter the dimensions of cube:");
        int p1 = n.nextInt();
        Volume v2 = new Volume (p1);
        v2.displayvolofcube();

        System.out.println("\nEnter the dimensions of cylinder:");
        int y1 = n.nextInt();
        int y2 = n.nextInt();
        Volume v3 = new Volume (y1,y2);
        v3.displayvolofcylinder();

        n.close();
    }
}
```


\\ in another file in same folder

```
public class Volume {

    int l;    // length of the object
    int b;    // breadth of the object
    int h;    // height of the object
    int r;    // radius of the circle/object
    float vol; // voulume of object

    void volOfCuboid(int length, int breadth, int height){
        vol = length*breadth*height;
    }
    void volOfCube(int length){
        vol = length*length*length;
    }
    void volOfCylinder(int radius, int height){
        final float PI = (float) 3.14;
        vol =(PI*(radius*radius)*height);
    }

    Volume(int length, int breadth, int height){
        l = length;
        b = breadth;
        h = height;
        this.volOfCuboid(length, breadth, height);
    }
    Volume(int length){
        l = length;
        this.volOfCube(length);
    }
    Volume(int radius, int height){
        r = radius;
        h = height;
        this.volOfCylinder(radius, height);
    }
}
```

```
}

void displayvolofcuboid(){
    System.out.print("Volume of cuboid is "+vol+"\n");
}
void displayvolofcube(){
    System.out.print("Volume of cube is "+vol+"\n");
}
void displayvolofcylinder(){
    System.out.print("Volume of cylinder is "+vol+"\n");
}
}
```

Output:

```
PS C:\Prashant\Programming\Java\Java> java Pass_parameter
```

```
Enter the dimensions of cuboid:
```

```
34
```

```
54
```

```
32
```

```
Volume of cuboid is 58752.0
```

```
Enter the dimensions of cube:
```

```
45
```

```
Volume of cube is 91125.0
```

```
Enter the dimensions of cylinder:
```

```
56
```

```
78
```

```
Volume of cylinder is 768069.1
```

Experiment No. 9

AIM : WAP to Create an abstract class Shape which has a field $PI=3.14$ as final and it has an abstract method Volume. Make two subclasses Cone and Sphere from this class and they print their volume.

Program:

```
public abstract class Shape {

    final double pi = 3.14;
    abstract void volume();
}

// in same folder but in different file for volume of cone

import java.util.Scanner;
public class Cone extends Shape{

    void volume(){
        Scanner n=new Scanner(System.in);
        System.out.println("\nEnter radius of cone:- ");
        double radius= n.nextDouble();
        System.out.println("\nEnter height of cone:- ");
        double height=n.nextDouble();
        double v=0.33333*pi*radius*height;
        System.out.println("\nVolume of cone is:- "+ v);
        n.close();
    }
}
```

```
}
```

// again for volume of sphere creating a class file in same folder but in different file

```
import java.util.Scanner;
```

```
public class Sphere extends Shape{
```

```
    void volume(){
```

```
        Scanner n=new Scanner(System.in);
```

```
        System.out.println("\nEnter radius of Sphere:- ");
```

```
        double radius=n.nextDouble();
```

```
        double v= 1.3333333*pi*radius*radius*radius;
```

```
        System.out.println("\nThe volume of sphere is :- "+ v);
```

```
        n.close();
```

```
    }
```

```
}
```

// to display the results

```
import java.util.Scanner;
```

```
public class Display {
```

```
    public static void main(String args[]){
```

```
        Scanner n=new Scanner(System.in);
```


```
        System.out.println("\nPlease enter a choice:-\n1. Cone\n2. Sphere");
```

```
        int op= n.nextInt();
```

```
switch(op){
    case 1:{
        Cone c = new Cone();
        c.volume();
        break;

    }
    case 2:{
        Sphere s = new Sphere();
        s.volume();
        break;
    }
    default: System.out.println("Invalid choice entered");
}
n.close();
}
```

Output:



```
PS C:\Prashant\Programming\Java\Java> java Display

Please enter a choice:-
1. Cone
2. Sphere
1

Enter radius of cone:-
23

Enter height of cone:-
43

Volume of cone is:- 1035.1429818000001
```

```
PS C:\Prashant\Programming\Java\Java> java Display
```

```
Please enter a choice:-
```

```
1. Cone
```

```
2. Sphere
```

```
2
```

```
Enter radius of Sphere:-
```

```
34
```

```
The volume of sphere is :- 164552.742552848
```

```
PS C:\Prashant\Programming\Java\Java> java Display
```

```
Please enter a choice:-
```

```
1. Cone
```

```
2. Sphere
```

```
4
```

```
Invalid choice entered
```

Experiment No. 10

AIM : WAP in which class “A” extends class “B”. Show the order of execution of the constructors if object of class B is created.

Program:

```
class College {  
  
    College(){  
  
        System.out.println("It's the constructor class of college");  
    }  
}  
  
class Student extends College {  
  
    Student(){  
        System.out.println("It's the extended class of student");  
    }  
}  
  
public class Lab10 {  
  
    public static void main (String args[]){  
  
        Student obj = new Student();  
  
    }  
}
```

Output:

```
PS C:\Prashant\Programming\Java\Java> java Lab10
```

```
It's the constructor class of college
```

```
It's the extended class of student
```


Experiment No. 11

AIM : WAP in which a class inherits two interfaces

Program:

```
import java.util.Scanner;

interface area{
    public void ar(int s);
}
interface volume{
    public void vol(int s);
}

class Shape implements area, volume {
    Scanner sc = new Scanner(System.in);
    public void ar(int s){

        System.out.println("\nArea of cube is: "+ 6*s*s);

    }
    public void vol(int s){
        System.out.println("\nVolume of cube is: "+ s*s*s);
    }
}
```

```
public class Lab11 {  
    public static void main(String args[]){  
        Scanner sc = new Scanner(System.in);  
        System.out.println("\nEnter the side of the cube");  
        int side= sc.nextInt();  
        Shape sp = new Shape();  
        sp.ar(side);  
        sp.vol(side);  
        sc.close();  
    }  
}
```

Output:

```
PS C:\Prashant\Programming\Java\Java> javac Lab11.java
```

```
PS C:\Prashant\Programming\Java\Java> java Lab11
```

```
Enter the side of the cube
```

```
674
```

```
Area of cube is: 2725656
```

```
Volume of cube is: 306182024
```