30/11/2022, 05:42 QA Community

COURSEWARE

Professional Skills Agile Fundamentals Jira Git **DevOps** Cloud Fundamentals **Databases Introduction** Java Beginner Maven Testing (Foundation) Java Intermediate HTML **CSS** Introduction to CSS3 Fonts Transform Selectors Selectors - Pseudo-Class / Pseudo-Elements Spatial Attributes Alignment Overflow Display and Positioning Background and Borders **Bootstrap Introduction** Bootstrap Nav **Bootstrap Collapse Bootstrap Grid** Bootstrap Forms & Inputs Bootstrap Modal **Bootstrap Cards** Javascript

Bootstrap Collapse

Contents

- Overview
- <u>Tutorial</u>
- Exercises

Overview

As well as providing all the tools to easily create a great looking navigation bar, bootstrap also provides a feature called **collapse**, which allows us to create a collapsable navigation bar.

Tutorial

We already have a simple implementation of a navigation bar using bootstrap.

```
<body>
  <nav class="navbar navbar-light bg-light">
     <a href="link/to/page" class="navbar-brand">My Company</a>
     <a href="link/to/login" class="nav-link">Login</a>
        <a href="link/to/home" class="nav-link">Home</a>
        <a href="link/to/memes" class="nav-link">Memes</a>
        </nav>
</body>
```

In order for collapse to grab only the items we want, we need to surround the in a <div class="collapse navbar-collapse">

Like so:

```
<nav class="navbar navbar-light bg-light">
      <a href="link/to/page" class="navbar-brand">My Company</a>
      <div class="collapse navbar-collapse">
         class="nav-item">
               <a href="link/to/login" class="nav-link">Login</a>
            <a href="link/to/home" class="nav-link">Home</a>
            <a href="link/to/memes" class="nav-link">Memes</a>
            </div>
   </nav>
</body>
```

Now, if you test out this code, you'll see that our navigation bar is gone! The problem is that we've made a collapsible navigation bar, but with no way to expand it.

Spring Boot

Selenium

Markdown

IDE Cheatsheet

So, let's add a button that will do this for us.

Sonarqube Advanced Testing (Theory) Cucumber MongoDB **Express NodeJS** React **Express-Testing** Pre-Project Assessment

<button class="navbar-toggler" data-bs-toggle="collapse"> </button>

The buttons to do this in HTML would look out of place - Bootstrap's version is

Let's implement this into our code:

rather nicer:

```
<body>
   <nav class="navbar navbar-light bg-light">
      <a href="link/to/page" class="navbar-brand">My Company</a>
      <button class="navbar-toggler" data-bs-toggle="collapse">
         <span class="navbar-toggler-icon"></span>
      </button>
      <div class="collapse navbar-collapse">
         <a href="link/to/login" class="nav-link">Login</a>
            <a href="link/to/home" class="nav-link">Home</a>
            <a href="link/to/memes" class="nav-link">Memes</a>
            </div>
   </nav>
</body>
```

We now need to assign a target for the button - we do this with the data-bstarget tag, and by assigning the same id to our <div>:

```
<body>
   <nav class="navbar navbar-light bg-light">
      <a href="link/to/page" class="navbar-brand">My Company</a>
      <button class="navbar-toggler" data-bs-toggle="collapse" data-bs-</pre>
target="#hasToMatch">
          <span class="navbar-toggler-icon"></span>
      </button>
      <div class="collapse navbar-collapse" id="hasToMatch">
          <a href="link/to/login" class="nav-link">Login</a>
             <a href="link/to/home" class="nav-link">Home</a>
             <a href="link/to/memes" class="nav-link">Memes</a>
             </div>
   </nav>
</body>
```

Brilliant! We have now implemented our collapsible navigation bar. The final step is to import our JavaScript packages.

The specific import you need will be dependent on the Bootstrap template you are using, so please check the relevant documentation for that template (they're easily-Googleable).

For the purposes of this tutorial, we'll use Bootstrap's bog-standard Getting Started scripts, which can be found here.

Remember: CSS gets imported in the <head> tag! JavaScript gets imported at the end of the <body> tag!

30/11/2022, 05:42

QA Community

Pulling everything together, this should look something like the following:

```
<!DOCTYPE html>
<html lang="en">
<head>
   <meta charset="UTF-8">
   <title>Bootstrap Tutorial</title>
   <link href="https://cdn.jsdelivr.net/npm/bootstrap@5.0.0-</pre>
beta1/dist/css/bootstrap.min.css" rel="stylesheet"
       integrity="sha384-
giJF6kkoqNQ00vy+HMDP7azOuL0xtbfIcaT9wjKHr8RbDVddVHyTfAAsrekwKmP1"
crossorigin="anonymous">
</head>
<body>
   <nav class="navbar navbar-light bg-light">
       <a href="link/to/page" class="navbar-brand">My Company</a>
       <button class="navbar-toggler" data-bs-toggle="collapse" data-bs-</pre>
target="#hasToMatch">
           <span class="navbar-toggler-icon"></span>
       </button>
       <div class="collapse navbar-collapse" id="hasToMatch">
           <a href="link/to/login" class="nav-link">Login</a>
              <a href="link/to/home" class="nav-link">Home</a>
              <a href="link/to/memes" class="nav-link">Memes</a>
              </div>
    <script src="https://cdn.jsdelivr.net/npm/bootstrap@5.0.0-</pre>
beta1/dist/js/bootstrap.bundle.min.js"
       integrity="sha384-
ygbV9kiqUc6oa4msXn9868pTtWMgiQaeYH7/t7LECLbyPA2x65Kgf800JFdroafW"
       crossorigin="anonymous"></script>
</body>
</html>
```

Exercises

There are no exercises for this module.