AMERICAN INTERNATIONAL UNIVERSITY-BANGLADESH

Faculty of Engineering Laboratory Report Cover Sheet

Students must complete all details except the faculty use part.

PRAESIDIUM	AL.
A ()	MINERSIT
20/0 1994 S	
	PARESIDIUM PRAESIDIUM

Group Submission

Please submit all reports to your subject supervisor or the office of the concerned faculty.		
Experiment Title: Implementation of a motor control system using Arduino: Digital input, outputs and PWM		
Experiment Number: 09 Due Date: 02-05-2024 Semester: Spring 23-24 Subject Code: EEE 4103 Subject Name: Microprocessor and Embedded Systems Section: E Course Instructor: Protik Parvez Sheikh Degree Program: BSc CSE		

Declaration and Statement of Authorship:

Group Number (if applicable):

- 1. I/we hold a copy of this report, which can be produced if the original is lost/damaged.
- 2. This report is my/our original work and no part of it has been copied from any other student's work or fromany other source except where due acknowledgement is made.
- 3. No part of this report has been written for me/us by any other person except where such collaboration hasbeen authorized by the lecturer/teacher concerned and is clearly acknowledged in the report.
- 4. I/we have not previously submitted or currently submitting this work for any other course/unit.
- 5. This work may be reproduced, communicated, compared and archived for the purpose of detectingplagiarism.
- 6. I/we give permission for a copy of my/our marked work to be retained by the School for review and comparison, including review by external examiners.

I/we understand that

Faculty comments

7. Plagiarism is the presentation of the work, idea or creation of another person as though it is your own. It is a form of cheating and is a very serious academic offence that may lead to expulsion from the University. Plagiarized material can be drawn from, and presented in, written, graphic and visual form, including electronic data, and oral presentations. Plagiarism occurs when the origin of the material used is not appropriately cited.

Individual Submission

8. Enabling plagiarism is the act of assisting or allowing another person to plagiarize or to copy your work

	Student	Student Date
Name	Number	Signature
omitted by:		
RIFAH SANZIDA	22-47154-1	
oup Members:		
MD. JOBAER HOSSAIN	22-47116-1	
SAMIA SHARMIN DOLA	22-47126-1	
MD. SAMIN YEASAR	22-47139-1	
SHAYAN ABRAR	22-47156-1	
faculty use only:	Total Marks:	Marks Obtained:
	oup Members: MD. JOBAER HOSSAIN SAMIA SHARMIN DOLA MD. SAMIN YEASAR	Name Mumber mitted by: RIFAH SANZIDA 22-47154-1 oup Members: MD. JOBAER HOSSAIN SAMIA SHARMIN DOLA 22-47126-1 MD. SAMIN YEASAR 22-47139-1 SHAYAN ABRAR 22-47156-1

Title:

Implementation of a motor control system using Arduino: Digital input, outputs, and PWM.

Objectives:

The objectives of this experiment are to-

- Introduce students to the pulse-width modulation (PWM) signals produced by the Arduinoboard.
- Adjust the velocity of a DC motor by manipulating the Arduino-generated PWM signals.
- Alter the DC motor's rotation by utilizing the input push switch.

Overview of the board:




Figure 1: Circuit Diagram of Motor Control using Arduino and L298N [3]

Apparatus:

- L298N Driver
- 12 V High Torque DC Motor
- Arduino Board
- Potentiometer
- A DC power supply
- Breadboard and Jumper Wires

CODE:

```
int in 1 = 8; //Declaring where our module is wired
int in 2 = 9:
int ConA = 10;// Don't forget this is a PWM DI/DO
int speed1;
void setup() {
Serial.begin(9600);
pinMode(2, INPUT);
pinMode(8, OUTPUT);
pinMode(9, OUTPUT);
pinMode(10, OUTPUT);
void TurnMotorA(){ //A function to control the direction and speed
if (digitalRead(2) == LOW)
digitalWrite(in1, LOW); //Switch between these HIGH and LOW states to change direction
digitalWrite(in2, HIGH);
float analogvalue = analogRead(A0); // declaring and reading an analog voltage value
from the pin
int PWMvalue = map(analog value, 0, 1023, 0, 255); // mapping the analog readings to
change
                 // range from 0-1023 to 0-255 to divide the value by 4 to get a PWM
                  value
analogWrite(ConA, PWMvalue);// To activate the DC motor
else if (digitalRead(2) == HIGH){
digitalWrite(in1, HIGH); //Switch between these HIGH and LOW states to change direction
digitalWrite(in2, LOW);
float analogvalue = analogRead(A0); // declaring and reading an analog voltage value
from the pin
int PWMvalue = map(analogvalue, 0, 1023, 0, 255); // mapping the analog readings to
change
                 // range from 0-1023 to 0-255 to divide the value by 4 to get a PWM
                  value
analogWrite(ConA, PWMvalue);// To activate the DC motor
}
```

```
void loop() {
float analogvalue = analogRead(A0); // declaring and reading an analog voltage value
from the pin
int PWMvalue = map(analogvalue, 0, 1023, 0, 255); // mapping the analog readings to
change
                  // range from 0-1023 to 0-255 to divide the value by 4 to get a PWM
                  value
Serial.print("Digital Value = ");
Serial.print(PWMvalue);
                             //print digital value on serial monitor
                        //convert digital value to analog voltage
float analogVoltage = (PWMvalue *5.00)/255.00;
Serial.print(" Analog Voltage = ");
Serial.println(analogvalue);
TurnMotorA();
                  // function that keeps looping to run the motor continuously
                  //you can add another one with a different direction or stop
}
```

Simulation:




Figure 2: Speed control using potentiometer simulation.

Report writing:

1. Include all codes and scripts in the lab report following the writing template. Answer: All codes and scripts are attached above

DISCUSSION:

In this experiment, we connected a DC motor to an Arduino UNO to regulate its speed and direction via PWM (Pulse Width Modulation). The motor was linked to an L298N motor driving module, which we extensively discussed to understand its workings. Our project aimed to control the motor, utilizing a written code uploaded to the Arduino. Using a potentiometer, we managed the speed through PWM, and the module facilitated changing the motor's direction. Additionally, we monitored the motor speed (ranging from 0 to 255) through theserial monitor. Overall, our observations confirmed the successful functionality of the system, validating the achievement of our experiment's objectives.

Conclusion:

In this experiment, we connected a DC motor to an Arduino UNO to regulate its speed and direction via PWM (Pulse Width Modulation). The motor was linked to an L298N motor driving module, which we extensively discussed to understand its workings. Our project aimed to control the motor, utilizing a written code uploaded to the Arduino. Using a potentiometer, we managed the speed through PWM, and the module facilitated changing themotor's direction. Additionally, we monitored the motor speed (ranging from 0 to 255) through the serial monitor. Overall, our observations confirmed the successful functionality of the system, validating the achievement of our experiment's objectives.

References:

[1] Circuit Digest [Online : June 7, 2015] [Cited

:December 23, 2023]

Available : https://circuitdigest.com/microcontroller-projects/dc-motor-control-with-arduino-uno-pwm

[2] L298N Motor Driver Module. (n.d.). Components101. [Online] [Cited: December 23, 2023]

Available: https://components101.com/modules/l293n-motor-driver-module

[3] H-bridge DC Motor Control Using Complementary PWM, Shoot-

through, and Dead-time. (2022, August,29). Available:

https://www.allaboutcircuits.com/technical-articles/h- bridge-dc-motor-control- complementary-pulse-width-modulation-pwm-shoot-through-dead-time-pwm/