

PRISM API & Integration Documentation

1. Requirements Extraction Service (Python API)

A. Async Extraction (Main Flow)

Initializes the extraction process in the background. Returns a task_id.

Endpoint: POST /extract-async

Payload:

```
{
  "project_id": "healthcare_portal_101",
  "file_urls": [
    "s3://my-bucket/docs/policy.pdf",
    "s3://my-bucket/docs/ui_specs.pptx"
  ]
}
```

B. Status Polling

Used to check the status of the Celery task.

Endpoint: GET /status/{task_id}

Response Example:

```
{
  "task_id": "8b9cad0e-...",
  "status": "PROGRESS",
  "result": { "total_requirements": 38 }
}
```

2. Status Updates (Calls to Java Backend)

Base URL: POST http://localhost:8080/api/document-statuses/projects/{project_id}

Updates sent by the Python service:

- PENDING (Batch): Initial list of files.
- IN_PROGRESS: Sent when a specific file starts processing.
- COMPLETED: Sent when a file is successfully extracted.
- FAILED: Sent if an error occurs for a file.

Example Payload (IN_PROGRESS):

```
[
  { "documentUrl": "s3://file_A.pdf", "status": "IN_PROGRESS" }
]
```

3. Final Storage (Sync to Postgres)

Endpoint: POST /api/requirements/project/{project_id}

Payload:

```
[
  {
    "requirement_id": "HC-001",
  }
]
```

PRISM API & Integration Documentation

```
"title": "Dual-Factor Authentication",  
"description": "System must require MFA...",  
"type": "Technical",  
"priority": "High"  
}  
]
```

4. AWS Integration Details

The service requires the following .env variables:

1. AWS_ACCESS_KEY_ID: Standard access key.
2. AWS_SECRET_ACCESS_KEY: Standard secret key.
3. AWS_SESSION_TOKEN: Optional (required for SSO/Temp tokens).
4. S3_BUCKET_NAME: The target bucket for all operations.