

MoMagic Truecaller Bundle APIs(Robi)

API Version: 1.0.0

Created: 22 August 2024

Updated: 22 August 2024

Developed by MoMagic Bangladesh Ltd.
Dhaka, Bangladesh

Confidentiality: Distribution of this document is restricted. Holders of this document must ensure the confidentiality of the content and under no circumstances is this document to be shown or released to anyone without the prior consent of MoMagic.

Copyright: This document and its contents belongs to MoMagic it may not be copied, photocopied, scanned or redistributed without written consent from MoMagic Bangladesh Ltd.

Revision History

1. Subscription Activation API Documentation

This API endpoint facilitates the activation of a Truecaller bundle for a specific partner. It processes the incoming request, validates the provided data, and subsequently activates the subscription if the data is accurate.

Workflow:

1. Obtain the Partner's Public Key:

- Ensure you have the partner's public key available in PEM format. This key is essential for encrypting the data.

2. Prepare the Data:

- Format the data you want to encrypt. Typically, this will be a JSON object that you need to convert to a string.
- Use appropriate padding (e.g., RSA_PKCS1_OAEP_PADDING) for encryption.
- Base64 encode the encrypted data to ensure it can be safely transmitted over text-based protocols.

3. Send the encrypted Data:

- Transmit the encrypted data along with the relevant partnerId in a POST request. Refer to the example provided below for guidance.

4. Request Outcome:

- **Success:**
 - If the request is processed successfully, the subscription will be activated for the specified MSISDN.
- **Failure:**
 - If the request fails, the response will include a detailed reason for the failure.

Base URL

The base URL for all API requests is:

`https://api.hullor.io`

Endpoints

POST: `/api/v2/truecaller-bundle/activate``

Request

Returns a JSON object with the following properties:

- **partnerId** (integer, required): Unique identifier for the partner provided by MoMagic Bangladesh Limited.
- **data** (object, required): An object with the following properties:
 - **days** (integer, required): Subscription validity in days.
 - **msisdn** (string, required): Mobile number (11 digits) for charging..
 - **trxId** (string, required): Unique identifier for each request for further tracking(must be 16 to 32 characters).

Encrypt the data following the process described in section 1.2.

Example Request:

```
{
  "data":
  "CmZl9mIuZw/cGIxphxyfeojC0Fib1DMVHSXhdx7JSJNogLH++NDR3geEs01fj/Q9cKe3pbLW6gWVvIxsQLqtX00r+GaoHW
m5Ltun2MxCfySWH37X5axIRk02ZJJzIr1CQ5o2F6EpYOs+nWNLucb0eVlqEdzajSFrieXTvpko+O88LMgkTUX6u/gygHe7Q
0KG/SYXNYkyAr00HYHxJVG/eqXL/HUXI8P2o8wLqN3eANX61rY+jQzMmxTUflJQhX5R2ePoeK1L+Qef/X1pR72xlJLNpBB7
aFA4poQsqhpCqSmkPN4E97XMyqCPEL0HvXiU8G4kNimrIuvjMBPKbFcSKA==" ,
  "partnerId": 1001
}
```

Response

Returns a JSON object with the following properties:

- **success** (boolean): Boolean value indicating success (true) or failure (false).
- **message** (string): Additional information about the response.
- **status_code** (string): HTTP status code for the response.

