


Tuple

Python Tuples

- **Tuples** are very similar to lists, except that they are immutable (they cannot be changed).
- They are created using **parentheses**, rather than square brackets.



- We generally use tuple for heterogeneous (different) datatypes and list for homogeneous (similar) datatypes.
- Since tuple are immutable, iterating through tuple is faster than with list. So there is a slight performance boost.
- Tuples that contain immutable elements can be used as key for a dictionary. With list, this is not possible.
- If you have data that doesn't change, implementing it as tuple will guarantee that it remains write-protected.

Creating a Tuple

- A tuple is created by placing all the items (elements) inside a parentheses (), separated by comma.
- The parentheses are optional but is a good practice to write it.
- A tuple can have any number of items and they may be of different types (integer, float, list, string etc.).

```
# empty tuple  
my_tuple = ()  
print(my_tuple)
```

```
# tuple having integers  
my_tuple = (1, 2, 3)  
print(my_tuple)
```

```
# tuple with mixed datatypes  
my_tuple = (1, "Hello", 3.4)  
print(my_tuple)
```

```
# nested tuple  
my_tuple = ("mouse", [8, 4, 6], (1, 2, 3))  
print(my_tuple)
```

```
# tuple can be created without parentheses  
# also called tuple packing  
my_tuple = 3, 4.6, "dog"  
print(my_tuple)
```

```
()  
(1, 2, 3)  
(1, 'Hello', 3.4)  
( 'mouse', [8, 4, 6], (1, 2, 3))  
(3, 4.6, 'dog')
```

- Creating a tuple with one element is a bit tricky.
- Having one element within parentheses is not enough. We will need a trailing comma to indicate that it is in fact a tuple.

```
# only parentheses is not enough  
my_tuple = ("hello")  
print(type(my_tuple))
```

```
# need a comma at the end  
my_tuple = ("hello",)  
print(type(my_tuple))
```

```
# parentheses is optional  
my_tuple = "hello",  
print(type(my_tuple))
```

```
<class 'str'>  
<class 'tuple'>  
<class 'tuple'>
```

Accessing Elements in a Tuple

You can access the values in the tuple with their index, just as you did with lists:

- Nested tuple are accessed using nested indexing
- Negative indexing can be applied to tuples similar to lists.
- We can access a range of items in a tuple by using the slicing operator
- Trying to reassign a value in a tuple causes a `TypeError`.

```
marks = (23,45,32)
print(marks[0])
print(marks[2])
```

23

32

```
# nested tuple
n_tuple = ("SIKANDER", [8, 4, 6], (1, 2, 3))

print(n_tuple[0])
print(n_tuple[1])

print(n_tuple[0][0])
print(n_tuple[1][0])
```

```
SIKANDER
[8, 4, 6]
S
8
```

Changing a Tuple

- Unlike lists, tuples are immutable.
- This means that elements of a tuple cannot be changed once it has been assigned. But, if the element is itself a mutable datatype like list, its nested items can be changed.

```
n_tuple = ("SIKANDER", [8, 4, 6], (1, 2, 3))  
print(n_tuple)
```

```
n_tuple[1][1] = 23  
print(n_tuple)
```

```
('SIKANDER', [8, 4, 6], (1, 2, 3))  
('SIKANDER', [8, 23, 6], (1, 2, 3))
```

Similar to List,

- We can use + operator to combine two tuples. This is also called **concatenation**.
- We can also **repeat** the elements in a tuple for a given number of times using the * operator.
- Both + and * operations result into a new tuple.

```
# Concatenation  
print((1, 2, 3) + (4, 5, 6))
```

```
# Repeat  
print(("Repeat",) * 3)
```

```
(1, 2, 3, 4, 5, 6)
```

```
('Repeat', 'Repeat', 'Repeat')
```


Deleting a Tuple

- We cannot change the elements in a tuple. That also means we cannot delete or remove items from a tuple.
- But deleting a tuple entirely is possible using the keyword `del`.

```
my_tuple = ('p','r','o','g','r','a','m','i','z')

del my_tuple[3]
# TypeError: 'tuple' object doesn't support item deletion

# can delete entire tuple
del my_tuple

# NameError: name 'my_tuple' is not defined
my_tuple
```

Python Tuple Methods

- Methods that add items or remove items are not available with tuple.

Only the following two methods are available.

Method	Description
<u>count(x)</u>	Return the number of items that is equal to x
<u>index(x)</u>	Return index of first item that is equal to x

```
my_tuple = ('a','p','p','l','e',)

print('Total count of element p is ', my_tuple.count('p'))

print('Index of l is ', my_tuple.index('l'))
```

```
Total count of element p is  2
Index of l is 3
```

Tuple Membership Test


- We can test if an item exists in a tuple or not, using the keyword `in`.

```
my_tuple = ('a','p','p','l','e',)  
print('a' in my_tuple)  
print('b' in my_tuple)  
print('g' not in my_tuple)
```


```
True  
False  
True
```

Iterating Through a Tuple

Using a for loop we can iterate through each item in a tuple.



```
names = ('Sikander', 'Sharath', 'John', 'Kate')  
for name in names:  
    print('Hello ', name)
```



```
Hello Sikander  
Hello Sharath  
Hello John  
Hello Kate
```

Built-in Functions with Tuple

Function	Description
<u>len()</u>	Return the length (the number of items) in the tuple.
<u>max()</u>	Return the largest item in the tuple.
<u>min()</u>	Return the smallest item in the tuple
<u>sorted()</u>	Take elements in the tuple and return a new sorted list (does not sort the tuple itself).
<u>sum()</u>	Return the sum of all elements in the tuple.
<u>tuple()</u>	Convert an iterable (list, string, set, dictionary) to a tuple.

Thank You!

