

Computer Networks 2021 Exercises - Unit 2

FAN: scha0174

NOTE: Each student's work unit is unique. You must use the work that has been generated for your FAN. If you do not, then you will fail this work unit.

NOTE: You must record your answers in the answer file EXACTLY as required, and commit and make sure your changes have been pushed to the github server, as they will otherwise not be counted.

NOTE: The topic coordinator will periodically run the automatic marking script, which will cause a file called unit2-results.pdf to be updated in your repository. You should check this file to make sure that your answers have been correctly counted. That file will contain the time and date that the marking script was last run, so that you can work out if it has been run since you last changed your answers. You are free to update your answers as often as you wish, until the deadline for the particular work unit.

1 Socket Programming General Knowledge

For each question, you must record your answer in the unit2-answers.txt file in your git repository. Each statement is either true or false. You must record 't' if you think the statement is true, or 'f', if you think that the statement is false. Your answer must be lower case. Uppercase answers will be marked incorrect. For example, if you believed that the answer to the following question was potato, you would put the word potato at the end of the rj= line in the file unit2-answers.txt.

| Question# | Description |
|-----------|--|
| rj | The potato is a white-flesh starchy vegetables from which hot chips are made |

The entry in unit2-answers.txt would thus look like:

```
# Question 'rj': The potato is a white-flesh starchy vegetables from which hot chips are made
```

Templates for each answer are provided in `unit2-answers.txt` for your convenience.

Are the following statements true or false?

| Question# | Statement |
|-----------|---|
| ab | The <code>accept()</code> function for the C programming language accepts all waiting network sockets each time it is called. |

| Question# | Statement |
|-----------|--|
| ac | The <code>close()</code> function for the C programming language can be called by either the initiator or receiver of a socket connection. |

| Question# | Statement |
|-----------|---|
| ad | The <code>close()</code> function for the C programming language cannot be called on connection-less sockets. |

| Question# | Statement |
|-----------|---|
| ae | The <code>write()</code> function for the C programming language can result in a 'broken pipe' condition. |

| Question# | Statement |
|-----------|---|
| af | The <code>write()</code> function for the C programming language can be used to write data to a socket. |

| Question# | Statement |
|-----------|--|
| ag | The <code>socket()</code> function for the C programming language sets the address of a network socket |

| Question# | Statement |
|-----------|--|
| ah | The <code>write()</code> function for the C programming language is used to write the address information into a socket. |

| Question# | Statement |
|-----------|---|
| ai | The connect() function for the C programming language normally requires the network address, but not any layer 4 address of the target. |

| Question# | Statement |
|-----------|---|
| aj | The close() function for the C programming language closes a server's socket and all open connections created by that socket. |

| Question# | Statement |
|-----------|--|
| ak | A network socket usually contains addressing information for layer 3 and layer 4 |

| Question# | Statement |
|-----------|---|
| al | The send() function for the C programming language can be used to write data to a connection-oriented socket. |

| Question# | Statement |
|-----------|---|
| am | The bind() function for the C programming language connects a socket to a network address |

| Question# | Statement |
|-----------|--|
| an | The connect() function for the C programming language is used by a client to connect to a server |

| Question# | Statement |
|-----------|---|
| ao | The recv() function for the C programming language normally waits for data to arrive, if none is waiting. |

| Question# | Statement |
|-----------|---|
| ap | The write() function for the C programming language is used to reply to a read() request from a server. |

2 Socket Program Design

For each question, you must record your answer in the `unit2-answers.txt` file in your git repository. You will be presented with several short socket-based programmes written using various programming languages. These programmes have been scrambled, and you must unscramble them, by placing the statements in the correct order. Your answers will be the numbers of the lines, once they have been ordered correctly.

(Note that leading white space and comments are removed from the lines of the programmes. The programmes will be written in either Python, C or JavaScript.)

For example, you would answer the following question:

| Line# | Text |
|-------|-------------------------------|
| 1 | Remove cake from the oven. |
| 2 | Collect the ingredients. |
| 3 | Put cake mix into the oven. |
| 4 | Mix the ingredients together. |

| Question# | Text |
|-----------|--------------|
| gh | First line. |
| gi | Second line. |
| gj | Third line. |
| gk | Fourth line. |

By entering the following into your `unit2-answers.txt` file:

```
# Question 'gh': Place the lines of the supplied programme in the correct order.  
  
gh=2  
  
gi=4  
  
gj=3  
  
gk=1
```

Templates for each answer are provided in `unit2-answers.txt` for your convenience.

Correct the order of the lines in the following simple network programme

| Line# | Text |
|-------|---|
| 1 | <code>with socket.socket(socket.AF_INET, socket.SOCK_STREAM) as s:</code> |
| 2 | <code>s.sendall(b'Hello, world')</code> |
| 3 | <code>data = s.recv(1024)</code> |
| 4 | <code>s.connect((HOST, PORT))</code> |
| 5 | <code>print('Received', repr(data))</code> |
| 6 | <code>import socket</code> |

| Question# | Text |
|-----------|---------------------|
| aq | <i>First line.</i> |
| ar | <i>Second line.</i> |
| as | <i>Third line.</i> |
| at | <i>Fourth line.</i> |
| au | <i>Fifth line.</i> |
| av | <i>Sixth line.</i> |

Correct the order of the lines in the following simple network programme

| Line# | Text |
|-------|---|
| 1 | <code>if not data:</code> |
| 2 | <code>with socket.socket(socket.AF_INET, socket.SOCK_STREAM) as s:</code> |
| 3 | <code>while True:</code> |
| 4 | <code>conn, addr = s.accept()</code> |
| 5 | <code>s.listen()</code> |
| 6 | <code>import socket</code> |
| 7 | <code>with conn:</code> |
| 8 | <code>conn.sendall(data)</code> |
| 9 | <code>data = conn.recv(1024)</code> |
| 10 | <code>print('Connected by', addr)</code> |
| 11 | <code>s.bind((HOST, PORT))</code> |
| 12 | <code>break</code> |

| Question# | Text |
|-----------|---------------|
| aw | First line. |
| ax | Second line. |
| ay | Third line. |
| az | Fourth line. |
| ba | Fifth line. |
| bb | Sixth line. |
| bc | Seventh line. |
| bd | Eighth line. |
| be | Ninth line. |
| bf | Tenth line. |
| bg | 11th line. |
| bh | 12th line. |

3 Socket Program Implementation

This question forms part of the DN/HD vs lower grade diagnosis. The pedagogical diagnosis is made based on the guidance from: <https://www.flinders.edu.au/content/dam/documents/staff/policies/academic-students/grading-scheme.pdf>. Specifically, in this item, the DN gate will be:

- iii. produced work which shows a developing capacity for original, critical and creative thinking over and above the essential requirements of the learning outcomes

and the HD gate will be:

- iii. consistently demonstrated knowledge skills and application at the highest level expected of a student at a given topic level

If you are running Windows, you will need to first install ncat from <https://nmap.org/ncat/>, and also NodeJS from nodejs.org

Write a simple network programme in JavaScript that listens on port 54321 and implements a simple game:

Maze Walker. On receiving a connection, your server programme should send back the a simple

maze display, prompting the user to move through the maze using w,a,s and d to move, where w is forwards, s is backwards and a and d are left and right, respectively. To make your life easier, the maze should always be the following, with the starting position of the player indicated by the X:

```
### #  
#  #  
# ###  
#  #  
#X###
```

It should read input from the client, and based on that input, move the X through the maze. The X may not be moved onto a # symbol, or moved outside of the maze. When the X is placed in the space in the top line of the maze, the connection should be closed.

The game does not need to implement any other logic.

For example, if the client were to send w, a, and then d, the server would send the following:

```
### #  
#  #  
# ###  
#X  #  
# ###
```

then,

```
### #  
#  #  
# ###  
#X  #  
# ###
```

and then,

```
### #  
#  #  
# ###
```



```
# X #
```

```
# ###
```

Your solution should be placed in a single file, `unit2-maze.js` in your git repository, and should be runnable using a command line line:

```
node unit2-maze.js
```

And you should be able to test it with a command like:

```
nc 127.0.0.1 54321
```