



nassli
LED LIGHTS

LED DOWN LIGHT BIZZA

Application:

It can be widely used for shopping malls, Palaces, Trade shows, Supermarkets, Conference Halls, Hotels, Schools, Hospitals, Meeting room Factories, Theater, Cinemas, Kitchens and Corridor etc...

Feature:

The product used as pure light source , using LED technology human and environment friendly, no PB, Hg nor UV.
High power saving fixture, no decay and color temperature shift.
Can be dimmable (through direct control or via network).



SPECIFICATIONS

ITEM	DESCRIPTION
Input Voltage	220 - 240 VAC
Frequency	50 / 60 Hz
Power factor	>98%
CCT	3000K, 4000K, 6000K
CRI	>80%
LED Efficiency	130-150Lm/W
Power supply	Tridonic / Nassli / GL
LED Type	Citizen
Materials	Aluminum, PC, & Friendly material
Beam Angle	65°
Life Time	>50,000 Hour
Operating Temp	-20°C to +55°C
Storage Temp	-40°C to +85°C
Certifications	CE, SELV and ISO
Mounting	Recessed
IP Rating	IP20
Dimmable	On Request
Emergency	On Request
Warranty	5 Years

Order code	Dimensions(mm)	Power(Watt)	Lumen
NSL-DLT-200-30W-XXK-COB-TD-XX-IP20	W230 H83 Ø200	30	3000
NSL-DLT-200-30W-XXK-COB-NS-IP20	W230 H83 Ø200	30	3000
NSL-DLT-200-35W-XXK-COB-TD-XX-IP20	W230 H83 Ø200	35	3500
NSL-DLT-200-35W-XXK-COB-NS-IP20	W230 H83 Ø200	35	3500
NSL-DLT-200-40W-XXK-COB-TD-XX-IP20	W230 H83 Ø200	40	4200
NSL-DLT-200-40W-XXK-COB-NS-IP20	W230 H83 Ø200	40	4200