



NASSLI
LED LIGHTS

LED CYLINDER LIGHT

Application:

It can be widely used for decoration, shopping malls, Palaces, Trade shows, Supermarkets, Conference Halls, Hotels, Schools, Hospitals, Meeting room Factories, Theater, Cinemas and Corridor etc.

Feature:

High cooling aluminum, 500 cm², make it good even for hot areas.

High lumen Output

Power saving: as it replace the halogen, CFL, metal halide so it save between 50% to 90% of the consumed power.

We Have diffrent option(diffuser, Wide lens, Narrow lens)

Frame colores: Thermal coated (Black / Gray / White / Gold)

TYPE L2



SPECIFICATIONS

ITEM	DESCRIPTION
Input Voltage	220 - 240 V A C
Frequency	50 / 60 H z
Power factor	>90%
CCT	3000K, 4000k, 6000k
CRI	>80%
LED Efficiency	110-120Lm/W
Power supply	Tridonic / Nassli / GL
LED Type	Citizen,Osram/Philips/Tridonic
Materials	Aluminum, PC, & Friendly material
Beam Angle	60°
Life Time	>50,000 Hour
Operating Temp	-20°C to +55°C
Storage Temp	-40°C to +85°C
Certifications	CE, SELV and ISO
Mounting	Suspended/Surface Mounted
IP Rating	IP20
Dimmable	DALI On Request
Emergency	On Request
Warranty	5 Years

Order code	Dimensions(mm)	Power(Watt)	Lumen
NSL-PENDANT LIGHT-7W-XXK-SMD-TD-XX-IP20	D60 H600	7	850
NSL-PENDANT LIGHT-7W-XXK-SMD-NS-IP20	D60 H600	7	850