



nassli
LED LIGHTS

LED DOWN LIGHT WA

Application:

It can be widely used for decoration, shopping malls, Palaces, Trade shows, Supermarkets, Conference Halls, Hotels, Schools, Hospitals, Meeting room Factories, Theater, Cinemas, Kitchens and Corridor etc...

Feature:

The product used as pure light source, using LED technology human and environment friendly, no PB, Hg nor UV.
High power saving fixture, no decay and color temperature shift.
Can be dimmable (through direct control or via network).



SPECIFICATIONS

ITEM	DESCRIPTION
Input Voltage	220 - 240 VAC
Frequency	50 / 60Hz
Power factor	>98%
CCT	2700K, 4000K, 5000K, 6000K
CRI	>80%
LED Efficiency	130-140Lm/W
Power supply	Tridonic / Nassli / Philips
LED Type	COB Citizen
Materials	Aluminum, PC, & Friendly material
HoneyComb	UGR
Beam Angle	24°, 38°
Life Time	>50,000 Hour
Operating Temp	-20°C to +55°C
Storage Temp	-40°C to +85°C
Certifications	CE, SELV and ISO
Mounting	Recessed
IP Rating	IP23
Dimmable	On Request
Emergency	On Request
Warranty	5 Years

Order code	Dimensions(mm)	Power(Watt)	Lumen
NSL-DAJ-WA-55-7W-XXK-COB-NS-IP23	W66 H85 Ø55	7	910
NSL-DAJ-WA-55-7W-XXK-COB-TD-XX-IP23	W66 H85 Ø55	7	910
NSL-DAJ-WA-55-7W-XXK-COB-PH-XX-IP23	W66 H85 Ø55	7	910
NSL-DAJ-WA-75-10W-XXK-COB-NS-IP23	W90 H115 Ø75	10	1300
NSL-DAJ-WA-75-10W-XXK-COB-TD-XX-IP23	W90 H115 Ø75	10	1300
NSL-DAJ-WA-75-10W-XXK-COB-PH-XX-IP23	W90 H115 Ø75	10	1300



nassli
LED LIGHTS

LED DOWN LIGHT GS

Application:

It can be widely used for decoration, shopping malls, Palaces, Trade shows, Supermarkets, Conference Halls, Hotels, Schools, Hospitals, Meeting room Factories, Theater, Cinemas, Kitchens and Corridor etc...

Feature:

The product used as pure light source, using LED technology human and environment friendly, no PB, Hg nor UV.
High power saving fixture, no decay and color temperature shift.
Can be dimmable (through direct control or via network).



SPECIFICATIONS

ITEM	DESCRIPTION
Input Voltage	220 - 240 VAC
Frequency	50 / 60Hz
Power factor	>98%
CCT	2700K, 4000K, 5000K, 6000K
CRI	>80%
LED Efficiency	130-140Lm/W
Power supply	Tridonic / Nassli / Philips
LED Type	COB Citizen
Materials	Aluminum, PC, & Friendly material
HoneyComb	UGR
Beam Angle	24°, 38°
Life Time	>50,000 Hour
Operating Temp	-20°C to +55°C
Storage Temp	-40°C to +85°C
Certifications	CE, SELV and ISO
Mounting	Recessed
IP Rating	IP43
Dimmable	On Request
Emergency	On Request
Warranty	5 Years



nassli
LED LIGHTS

LED DOWN LIGHT GS

Order code	Dimensions(mm)	Power(Watt)	Lumen
NSL-DAJ-GS-55-7W-XXK-COB-NS-IP43	W66 H85 Ø55	7	910
NSL-DAJ-GS-55-7W-XXK-COB-TD-XX-IP43	W66 H85 Ø55	7	910
NSL-DAJ-GS-55-7W-XXK-COB-PH-XX-IP43	W66 H85 Ø55	7	910
NSL-DAJ-GS-75-10W-XXK-COB-NS-IP43	W90 H115 Ø75	10	1300
NSL-DAJ-GS-75-10W-XXK-COB-TD-XX-IP43	W90 H115 Ø75	10	1300
NSL-DAJ-GS-75-10W-XXK-COB-PH-XX-IP43	W90 H115 Ø75	10	1300
NSL-DAJ-GS-95-15W-XXK-COB-NS-IP43	W110 H131.4 Ø95	15	1950
NSL-DAJ-GS-95-15W-XXK-COB-TD-XX-IP43	W110 H131.4 Ø95	15	1950
NSL-DAJ-GS-95-15W-XXK-COB-PH-XX-IP43	W110 H131.4 Ø95	15	1950
NSL-DAJ-GS-125-18W-XXK-COB-NS-IP43	W142 H153 Ø125	18	2340
NSL-DAJ-GS-125-25W-XXK-COB-NS-IP43	W142 H153 Ø125	25	3250
NSL-DAJ-GS-125-25W-XXK-COB-TD-XX-IP43	W142 H153 Ø125	25	3250
NSL-DAJ-GS-125-25W-XXK-COB-PH-XX-IP43	W142 H153 Ø125	25	3250
NSL-DAJ-GS-150-18W-XXK-COB-NS-IP43	W142 H153 Ø125	18	2340
NSL-DAJ-GS-150-25W-XXK-COB-NS-IP43	W142 H153 Ø125	25	3250
NSL-DAJ-GS-150-30W-XXK-COB-TD-XX-IP43	W165 H178 Ø150	30	3900
NSL-DAJ-GS-150-30W-XXK-COB-PH-XX-IP43	W165 H178 Ø150	30	3900