



nassli
LED LIGHTS

LED DOWN LIGHT GS ADJUSTABLE

Application:

It can be widely used for decoration, shopping malls, Palaces, Trade shows, Supermarkets, Conference Halls, Hotels, Schools, Hospitals, Meeting room Factories, Theater, Cinemas, Kitchens and Corridor etc...

Feature:

The product used as pure light source , using LED technology human and environment friendly, no PB, Hg nor UV.
High power saving fixture, no decay and color temperature shift.
Can be dimmable (through direct control or via network).

SPECIFICATIONS

ITEM	DESCRIPTION
Input Voltage	220 - 240 VAC
Frequency	50 / 60Hz
Power factor	>98%
CCT	3000K, 4000K, 5000K, 6000K
CRI	>80%, >90%
LED Efficiency	130-140Lm/W
Power supply	Tridonic / Nassli / Philips/ GL
LED Type	Citizen
Materials	Aluminum, PC, & Friendly material
HoneyComb	UGR
Beam Angle	24°, 38°
Life Time	>50,000 Hour
Operating Temp	-20°C to +55°C
Storage Temp	-40°C to +85°C
Certifications	CE, SELV and ISO
Mounting	Recessed
IP Rating	IP23
Dimmable	ON/OFF, DALI, 0-10V
Emergency	On Request
Warranty	5 Years



FRAME CUT OUT: 150X150MM





nassli
LED LIGHTS

LED DOWN LIGHT GS ADJUSTABLE

Order code	Dimensions(mm)	Power(Watt)	Lumen
NSL-DAJ-GS-95-15W-XXK-COB-NS-IP23-SQ	W110 H131.4 Ø95	15	1950
NSL-DAJ-GS-95-15W-XXK-COB-TD-XX-IP23-SQ	W110 H131.4 Ø95	15	1950
NSL-DAJ-WA-75-10W-XXK-COB-NS-IP23-SQ	W90 H115 Ø75	10	1300
NSL-DAJ-WA-75-10W-XXK-COB-TD-XX-IP23-SQ	W90 H115 Ø75	10	1300