



nassli
LED LIGHTS

LED DOWN LIGHT YN-MTR

Application:

It can be widely used for decoration, shopping malls, Palaces, Trade shows, Supermarkets, Conference Halls, Hotels, Schools, Hospitals, Meeting room Factories, Theater, Cinemas, Kitchens and Corridor etc...

Feature:

The product used as pure light source , using LED technology human and environment friendly, no PB, Hg nor UV.
High power saving fixture, no decay and color temperature shift.
Can be dimmable (through direct control or via network).



Dimensions:
Cut Out: 100*190mm
Outer Size: 110*200mm

SPECIFICATIONS

ITEM	DESCRIPTION
Input Voltage	220 - 240 VAC
Frequency	50 / 60Hz
Power factor	>98%
CCT	2700K, 3000K, 4000K, 5000K, 6000K
CRI	>80%, >90%
LED Efficiency	110-130lm/W
Power supply	Tridonic / Nassli / LF / Ph / GL / QP
LED Type	Citizen, Osram, Bridgelux
Materials	Aluminum, PC, & Friendly material
HoneyComb	-
Beam Angle	15°, 24°, 36°, 60°
Life Time	>50,000 Hour
Operating Temp	-20°C to +55°C
Storage Temp	-40°C to +85°C
Certifications	CE, SELV and ISO
Mounting	Recessed
IP Rating	IP44
Dimmable	On Request
Emergency	On Request
Warranty	5 Years

Order code	Dimensions(mm)	Power(Watt)	Lumen
NSL-DLYN-MTR-2.5-2X12W-XXK-COB-NS-IP44-REC	W85 H50 Ø75	2X12	2X1320
NSL-DLYN-MTR-3.5-15W-XXK-COB-NS-IP44	W108 H64 Ø95	15	1700
NSL-DLYN-MTR-4-20/25/30W-XXK-COB-NS-IP44	W130 H77 Ø115	20/25/30	2200/2875/3450