



nassli
LED LIGHTS

LED DOWN LIGHT CRX28-3

Application:

It can be widely used for decoration, shopping malls, Palaces, Trade shows, Supermarkets, Conference Halls, Hotels, Schools, Hospitals, Meeting room Factories, Theater, Cinemas, Kitchens and Corridor etc...

Feature:

The product used as pure light source, using LED technology human and environment friendly, no PB, Hg nor UV.
High power saving fixture, no decay and color temperature shift.
Can be dimmable (through direct control or via network).



SPECIFICATIONS

ITEM	DESCRIPTION
Input Voltage	220 - 240 V A C
Frequency	50 / 60 H z
Power factor	>98%
CCT	2700K, 3000K, 4000K, 6000K
CRI	>83%
LED Efficiency	120-130Lm/W
Power supply	Tridonic / Nassli / GL
LED Type	Osram / Epistar
Materials	Aluminum, PC, & Friendly material
Beam Angle	110°
Life Time	>50,000 Hour
Operating Temp	-20°C to +55°C
Storage Temp	-40°C to +65°C
Certifications	CE, SELV and ISO
Mounting	Recessed
IP Rating	IP20 / IP44
Dimmable	On Request
Emergency	On Request
Warranty	5 Years

Order code	Dimensions(mm)	Power(Watt)	Lumen
NSL-CRX28-3-N200-30W-XXK-SMD-NS-IP20	W42 H218 Ø200	30	3000
NSL-CRX28-3-N200-30W-XXK-SMD-TD-XX-IP20	W42 H218 Ø200	30	3000
NSL-CRX28-3-N200-35W-XXK-SMD-NS-IP20	W42 H218 Ø200	35	3500
NSL-CRX28-3-N200-35W-XXK-SMD-TD-XX-IP20	W42 H218 Ø200	35	3500