



nassli
LED LIGHTS

LED DOWN LIGHT T18

Application:

It can be widely used for decoration, shopping malls, Palaces, Trade shows, Supermarkets, Conference Halls, Hotels, Schools, Hospitals, Meeting room Factories, Theater, Cinemas, Kitchens and Corridor etc...

Feature:

The product used as pure light source, using LED technology human and environment friendly, no PB, Hg nor UV.
High power saving fixture, no decay and color temperature shift.
Can be dimmable (through direct control or via network).



SPECIFICATIONS

ITEM	DESCRIPTION
Input Voltage	220 - 240 V A C
Frequency	50 / 60 H z
Power factor	>98%
CCT	2700K, 3000K, 4000K, 6000K
CRI	>83%
LED Efficiency	110-120Lm/W
Power supply	Tridonic / Nassli
LED Type	Osram / Epistar
Materials	Aluminum, PC, & Friendly material
Beam Angle	160°
Life Time	>50,000 Hour
Operating Temp	-20°C to +55°C
Storage Temp	-40°C to +65°C
Certifications	CE, SELV and ISO
Mounting	Recessed
IP Rating	IP20
Dimmable	On Request
Emergency	On Request
Warranty	5 Years

Order code	Dimensions(mm)	Power(Watt)	Lumen
NSL-DLT18-5-15W-XXK-SMD-NS-XX-IP20	W160 H65 Ø140	15	1650
NSL-DLT18-5-15W-XXK-SMD-NS-XX-IP44	W160 H65 Ø140	15	1650
NSL-DLT18-5-15W-XXK-SMD-TD-XX-IP20	W160 H65 Ø140	15	1650
NSL-DLT18-5-15W-XXK-SMD-TD-XX-IP44	W160 H65 Ø140	15	1650



nassli
LED LIGHTS

LED DOWN LIGHT T18

Application:

It can be widely used for decoration, shopping malls, Palaces, Trade shows, Supermarkets, Conference Halls, Hotels, Schools, Hospitals, Meeting room Factories, Theater, Cinemas, Kitchens and Corridor etc...

Feature:

The product used as pure light source, using LED technology human and environment friendly, no PB, Hg nor UV.
High power saving fixture, no decay and color temperature shift.
Can be dimmable (through direct control or via network).



SPECIFICATIONS

ITEM	DESCRIPTION
Input Voltage	220 - 240 V A C
Frequency	50 / 60 H z
Power factor	>98%
CCT	2700K, 3000K, 4000K, 6000K
CRI	>83%
LED Efficiency	110-120Lm/W
Power supply	Tridonic / Nassli
LED Type	Osram / Epistar
Materials	Aluminum, PC, & Friendly material
Beam Angle	160°
Life Time	>50,000 Hour
Operating Temp	-20°C to +55°C
Storage Temp	-40°C to +65°C
Certifications	CE, SELV and ISO
Mounting	Recessed
IP Rating	IP20
Dimmable	On Request
Emergency	On Request
Warranty	5 Years

Order code	Dimensions(mm)	Power(Watt)	Lumen
NSL-DLT18-5-20W-XXK-SMD-NS-XX-IP20	W160 H65 Ø140	20	2200
NSL-DLT18-5-20W-XXK-SMD-NS-XX-IP44	W160 H65 Ø140	20	2200
NSL-DLT18-5-20W-XXK-SMD-TD-XX-IP20	W160 H65 Ø140	20	2200
NSL-DLT18-5-20W-XXK-SMD-TD-XX-IP44	W160 H65 Ø140	20	2200